

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 14.01.97
Test oil : ISO 4113

Combination No. : 0 402 996 309

Injection pump
Pump designation : PES6P130A720RS8521
EP type number : 0 412 936 200

Governor
Governor design. : RE30
Governor no. : 0 421 890 032

Cust. part No. : 309 4436

Customer-spec. information
Customer : CDC
Motor : V30
Power KW : 1007.0

TEST BENCH REQUIREMENTS

Inlet line : 4.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 084

Inlet press. bar : 3.0
Tolerance bar : ± 0.1

Test nozzle holder
assembly : 1 688 901 105

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 089

Outside diameter : 8.0

A01

x inside diameter : 3.0
x length mm : 600

REMARKS

Pump-specific values
in Section (B)
must be observed!

(A) INJECTION PUMP SETTINGS

No basic setting.
Setting of constant delivery
under Section C.

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0

Prestroke mm : 4.30
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 12.00
Tolerance mm : ± 0.20

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.75

Start of delivery blocking

Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Barrel no. : 1

Beginning of delivery difference

and maximum rack
travel : 10.00
Tolerance mm : ± 1.50
Difference °CS : 6.00

(B) POSITIONER TESTING

Warm-up time: 3 minutes at
n=600 min⁻¹, Uact = 2.5 V

TESTING & SETTING RACK TRAVEL SENSOR
POSITION

Engine speed min⁻¹: 0

Setting point
(P, R and H pump)

Uact V : 3.100
CRT mm : 13.00
Tolerance mm : +/- 0.05
Check
tolerance mm : +/- 0.10

Check value
(P, R and H pump)

Uact V : 1.700
CRT mm : 6.15
Tolerance mm : +/- 0.25
Check
tolerance mm : +/- 0.30

Setting point
(M pump)

Uact V : 3.100
CRT mm : 12.50
Tolerance mm : +/- 0.05
Check
tolerance mm : +/- 0.10

Check value
(M pump)

Uact V : 1.700
CRT mm : 5.50
Tolerance mm : +/- 0.25
Check
tolerance mm : +/- 0.30

Stop position

Uact V : Value with
deenergised adjusting magnet
and control rod in
stop position.

CRT mm : 0.75
Tolerance mm : +/- 0.25

A02

Check
tolerance mm : +/- 0.35

ENGINE-SPEED SENSOR
(All P and R pumps not
H and M pumps)

Test with control rod
in stop position

Engine speed min⁻¹: 60
Amplitude V : 1.4
Tolerance V : +/- 0.6
Check
tolerance V : +/- 1.20

Engine speed min⁻¹: 600
Difference
Amplitude to
Amplitude V : max.1.4

(C) INJECTION PUMP WITH POSITIONER

TEST POINT V1

Rated speed rpm : 900
Uact V : 3.050
Del. quantity
cm³/1000 strokes : 425.5
Tolerance
cm³/1000 strokes : +/- 1.0
Check tolerance
cm³/1000S. : +/- 5.0
Speed
Tolerance
cm³/1000 strokes : 10.0
Check tolerance
cm³/1000S. : 14.0

FUEL DELIVERY CHARACTERISTICS

Rated speed rpm : 750
Uact V : 3.000
Del. quantity
cm³/1000 strokes : 434.0
Tolerance
cm³/1000 strokes : +/- 10.0
Check tolerance
cm³/1000S. : +/- 12.0
Speed
Tolerance
cm³/1000 strokes : 16.0
Check tolerance
cm³/1000S. : 18.0

TEST POINT L1

Rated speed rpm : 400
Uact V : 1.280
Tolerance Volt : + 0.060
Check tolerance
Volt : + 0.070
Del. quantity
cm³/1000 strokes : 49.0
Tolerance
cm³/1000 strokes : + 3.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 14.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
Uact V : 4.700
Del. quantity
cm³/1000 strokes : 260.0
Tolerance
cm³/1000 strokes : + 19.0
Check tolerance
cm³/1000S. : + 22.0
Spreed
Tolerance
cm³/1000 strokes : 40.0
Check tolerance
cm³/1000S. : 50.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 13.01.97
Test oil : ISO 4113

Combination No. : 9 400 030 730

Injection pump
Pump designation : PES6A95D320/3RS2881
EP type number : 9 410 037 215

Governor
Governor design. : RSV475...1100A0C844R
Governor no. : 9 420 034 710

Cust. part No. : 3928599

Customer-spec. information
Customer : CDC
Motor : 6BTA
Power KW : 111.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 047

Inlet press. bar : 2.0
Tolerance bar : ± 0.1

Test nozzle holder
assembly : 1 688 901 101

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test Lines : 1 680 750 014

Outside diameter : 6.0

A04

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0

Prestroke mm : 2.85
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Start of delivery blocking

*NW after s.o.d. : 8.50
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1100

Rack travel in mm : 12.00
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 102.5

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 3.0

Spreed

Tolerance
cm³/1000 strokes : 3.5

Check tolerance
cm³/1000S. : 6.0

Rated speed rpm : 500

Rack travel in mm : 5.35
Tolerance mm : ± 0.10

Del. quantity
cm³/1000 strokes : 22.0
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 4.5

Spreed
Tolerance
cm³/1000 strokes : 3.5
Check tolerance
cm³/1000S. : 5.5

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : - 3
Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : ± 0.20

governor spring
pre-tension
click setting x : 2.50

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1100

Aneroid pressure
hPa : 1200

Del. quantity
cm³/1000 strokes : 102.5
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 3.0

Spreed
Tolerance
cm³/1000 strokes : 3.5
Check tolerance
cm³/1000S. : 6.0

CONTROL LEVER

control lever
position degree : 104.0
tolerance degree : ± 4.0

RATED SPEED

rack travel mm : 11.00
Rated speed rpm : 1165
Tolerance 1/min : ± 5

rack travel mm : 6.00
Rated speed rpm : 1225
Tolerance 1/min : ± 5

rack travel mm : 0.85
Tolerance mm : ± 0.55
Rated speed rpm : 1300

rack travel mm : 6.00
Rated speed rpm : 1225

LOW IDLE

control lever
position degree : 83.0
tolerance degree : ± 4.0

Control lever difference
Grad : 21.0
tolerance degree : ± 6.0

Setting point w/out bumper spring

Rated speed rpm : 500
rack travel mm : 4.85
Tolerance mm : ± 0.10

Testing:

Rated speed rpm : 500
rack travel mm : 5.35
Tolerance mm : +- 0.10

Rated speed rpm : 100

CRT mm min. : > 19.00

TORQUE CONTROL

Rated speed rpm : 1100
rack travel mm : 12.00
Tolerance mm : +- 0.05

Rated speed rpm : 750
rack travel mm : 13.35
Tolerance mm : +- 0.20

Rated speed rpm : 1000
rack travel mm : 12.90
Tolerance mm : +- 0.20

Rated speed rpm : 900
rack travel mm : 13.30
Tolerance mm : +- 0.20

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1200

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : 10.20
Tolerance mm : +- 0.10

MEASUREMENT

Rated speed rpm : 500

Pressure hPa : 865
rack travel mm : 12.60
Tolerance mm : +- 0.20

Pressure hPa : 500
rack travel mm : 11.00
Tolerance mm : +- 0.20

Start interlock

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1200
Rated speed rpm : 900
Del. quantity
cm³/1000 strokes : 120.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000s. : +- 4.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 84.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000s. : +- 3.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : +- 0.50
Del. quantity
cm³/1000 strokes : 120.5
Tolerance
cm³/1000 strokes : +- 10.0
Check tolerance
cm³/1000s. : +- 15.0

LOW IDLE

Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 22.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000s. : +- 4.5
Speed
Tolerance
cm³/1000 strokes : 3.5
Check tolerance
cm³/1000s. : 5.5

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 18.12.96
Test oil : ISO 4113

Combination No. : O 402 046 874

Injection pump
Pump designation : PES6P120A72ORS3360
EP type number : O 412 026 785

Governor
Governor design. : RQV300...1100PA1254K
Governor no. : O 421 815 485

Cust. part No. :

Customer-spec. information
Customer : IVECO-FIAT
Motor : 8360.46.4107
Power KW : 198.0

TEST BENCH REQUIREMENTS

Inlet line : 4.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 034

Inlet press. bar : 2.5

Overflow quantity
min. l/h : 175
Tolerance l/h : ± 20.0

Test nozzle holder
assembly : 1 688 901 105

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 089

Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 4.15
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 14.00
Tolerance mm : ± 0.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50

Start of delivery mark

Check
tolerance °NW : ± 0.40

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1100

Rack travel in mm : 14.05
 Tolerance mm : + 0.05

Del. quantity
 cm³/1000 strokes : 184.0

Tolerance
 cm³/1000 strokes : + 1.0

Check tolerance
 cm³/1000S. : + 4.0

Spread

Tolerance
 cm³/1000 strokes : 5.0

Check tolerance
 cm³/1000S. : 9.0

Rated speed rpm : 300

Rack travel in mm : 6.60
 Tolerance mm : + 0.10
 Del. quantity
 cm³/1000 strokes : 25.0
 Tolerance
 cm³/1000 strokes : + 3.0
 Check tolerance
 cm³/1000S. : + 6.0
 Spread
 Tolerance
 cm³/1000 strokes : 8.0
 Check tolerance
 cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
 WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 1156
 guide sleeve
 travel mm : 9.00
 Tolerance mm : + 0.15

Rated speed rpm : 300
 guide sleeve
 travel mm : 2.68
 Tolerance mm : + 0.20

Rated speed rpm : 380
 guide sleeve
 travel mm : 3.01
 Tolerance mm : + 0.25

Rated speed rpm : 1450
 guide sleeve
 travel mm : 13.50
 Tolerance mm : + 0.50

GUIDE SLEEVE POSITION

control lever
 position degree : - 1
 Rated speed rpm : 1325

Rack travel in mm : 10.00
 Tolerance mm : + 2.70

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1100
 Aneroid pressure
 hPa : 1200
 Del. quantity
 cm³/1000 strokes : 184.0
 Tolerance
 cm³/1000 strokes : + 1.0
 Check tolerance
 cm³/1000S. : + 4.0
 Spread
 Tolerance
 cm³/1000 strokes : 5.0
 Check tolerance
 cm³/1000S. : 9.0

CONTROL LEVER

control lever
 position degree : 116.0
 tolerance degree : + 4.0

RATED SPEED

rack travel mm : 13.00
 Rated speed rpm : 1145
 Tolerance 1/min : + 5
 Check
 speed 1/min : + 10

rack travel mm : 4.00
 Rated speed rpm : 1260
 Tolerance 1/min : + 15
 Check
 speed 1/min : + 20

rack travel mm : 0.50
 Tolerance mm : + 0.50
 Rated speed rpm : 1400

LOW IDLE

control lever
position degree : 80.0
tolerance degree : ± 4.0

Testing:

Rated speed rpm : 300
rack travel mm : 6.60
Tolerance mm : ± 0.10

Rated speed rpm : 225

CRT mm min. : > 8.10

Rated speed rpm : 330

TORQUE CONTROL

Rated speed rpm : 1100
rack travel mm : 14.05
Tolerance mm : ± 0.05

Rated speed rpm : 700
rack travel mm : 13.60
Tolerance mm : ± 0.15

Rated speed rpm : 850
rack travel mm : 14.25
Tolerance mm : ± 0.15

Rated speed rpm : 500
rack travel mm : 13.30
Tolerance mm : ± 0.20

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 850
Pressure hPa : 1200
rack travel mm : 14.20
Tolerance mm : ± 0.15

Pressure hPa : -
Rated speed rpm : 850
rack travel mm : 10.80
Tolerance mm : ± 0.20

MEASUREMENT

Rated speed rpm : 850
Pressure hPa : 640
rack travel mm : 12.80
Tolerance mm : ± 0.20

Pressure hPa : 380
rack travel mm : 11.60
Tolerance mm : ± 0.05

Start interlock

Rated speed rpm : > 190
Rated speed rpm : < 220

Check
speed 1/min : > 170

Check
speed 1/min : < 240

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1200
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 182.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0

Aneroid pressure
hPa : 1200
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 160.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 88.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 12.50
Tolerance mm : ± 0.30

Del. quantity
cm³/1000 strokes : 90.0
Tolerance
cm³/1000 strokes : ± 15.0
Check tolerance
cm³/1000S. : ± 19.0

LOW IDLE

Rated speed rpm : 300
Del. quantity
cm³/1000 strokes : 25.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0
Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 10.12.96
Test oil : ISO 4113

Combination No. : 0 402 066 708

Injection pump
Pump designation : PES6P120A120RS3358
EP type number : 0 412 026 784

Governor
Governor design. : RSV475...1150P2A619
Governor no. : 0 421 833 522

Cust. part No. : 3283019

Customer-spec. information
Customer : CDC
Motor : 6BTA-590 ELITE
Power KW : 136.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 093

Inlet press. bar : 1.5

Overflow quantity
min. l/h : 100
Tolerance l/h : ± 20.0

Test nozzle holde
assembly : 1 688 901 103

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 089

Outside diameter : 8.0

x inside diameter : 3.0

x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 2.85
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50

Start of delivery blocking

*NW after s.o.d. : 6.75
Tolerance : ± 0.10
Check
tolerance °NW : ± 0.75

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1150

Rack travel in mm : 12.90
 Tolerance mm : + 0.05

Del. quantity
 cm³/1000 strokes : 179.0

Tolerance
 cm³/1000 strokes : + 1.0

Check tolerance
 cm³/1000S. : + 3.0

Spread

Tolerance
 cm³/1000 strokes : 4.0

Check tolerance
 cm³/1000S. : 7.5

Rated speed rpm : 475

Rack travel in mm : 7.20
 Tolerance mm : + 0.10
 Del. quantity
 cm³/1000 strokes : 60.0
 Tolerance
 cm³/1000 strokes : + 2.0
 Check tolerance
 cm³/1000S. : + 4.5
 Spread
 Tolerance
 cm³/1000 strokes : 6.0
 Check tolerance
 cm³/1000S. : 9.0

(B) SETTING OF INJECTION PUMP
 WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
 position degree : - 3
 Rated speed rpm : 800

Rack travel in mm : 0.50
 Tolerance mm : + 0.20

governor spring
 pre-tension
 click setting x : 4.75

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1150
 Aneroid pressure
 hPa : 1500
 Del. quantity
 cm³/1000 strokes : 179.0
 Tolerance
 cm³/1000 strokes : + 1.0
 Check tolerance
 cm³/1000S. : + 3.0
 Spread
 Tolerance
 cm³/1000 strokes : 4.0
 Check tolerance
 cm³/1000S. : 7.5

CONTROL LEVER

control lever
 position degree : 112.0
 tolerance degree : + 4.0

RATED SPEED

rack travel mm : 11.90
 Rated speed rpm : 1195
 Tolerance 1/min : + 5

rack travel mm : 4.00
 Rated speed rpm : 1330
 Tolerance 1/min : + 15

rack travel mm : 0.85
 Tolerance mm : + 0.55
 Rated speed rpm : 1400

rack travel mm : 4.00
 Rated speed rpm : 1345

LOW IDLE

control lever
 position degree : 90.0
 tolerance degree : + 4.0

Setting point w/out bumper spring

Rated speed rpm : 475
 rack travel mm : 6.70
 Tolerance mm : + 0.10

Testing:

Rated speed rpm : 475
rack travel mm : 7.20
Tolerance mm : \pm 0.10

rack travel mm : 2.00
Rated speed rpm : 675
Tolerance 1/min : \pm 30

TORQUE CONTROL

Rated speed rpm : 1150
rack travel mm : 12.90
Tolerance mm : \pm 0.05

Rated speed rpm : 750
rack travel mm : 12.95
Tolerance mm : \pm 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1500
rack travel mm : 12.90
Tolerance mm : \pm 0.05

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : 8.60
Tolerance mm : \pm 0.20

MEASUREMENT

Rated speed rpm : 500

Pressure hPa : 900
rack travel mm : 11.10
Tolerance mm : \pm 0.20

Pressure hPa : 560
rack travel mm : 9.60
Tolerance mm : \pm 0.05

Start interlock

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1500
Rated speed rpm : 750
Del. quantity
cm³/1000 strokes : 193.0

Tolerance
cm³/1000 strokes : \pm 3.0
Check tolerance
cm³/1000S. : \pm 6.0
Spreed
Tolerance
cm³/1000 strokes : 12.0
Check tolerance
cm³/1000S. : 16.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 90.0
Tolerance
cm³/1000 strokes : \pm 2.0
Check tolerance
cm³/1000S. : \pm 4.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.25
Tolerance mm : \pm 0.75
Del. quantity
cm³/1000 strokes : 165.0
Tolerance
cm³/1000 strokes : \pm 20.0
Check tolerance
cm³/1000S. : \pm 25.0

LOW IDLE

Rated speed rpm : 475
Del. quantity
cm³/1000 strokes : 60.0
Tolerance
cm³/1000 strokes : \pm 2.0
Check tolerance
cm³/1000S. : \pm 4.5
Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 9.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 17.01.97
Test oil : ISO 4113

Combination No. : 0 402 074 700

Injection pump
Pump designation : PES4P110B720RS3383
EP type number : 0 412 014 701

Governor
Governor design. : RSV300...1100P1A667
Governor no. : 0 421 833 582

Cust. part No. : 9279831

Customer-spec. information
Customer : LIEBHERR
Motor : D 924 TI-E A2
Power KW : 147.0

TEST BENCH REQUIREMENTS

Inlet line : 4.1

Test oil inlet temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 049

Inlet press. bar : 1.5
Tolerance bar : ± 0.1

Tolerance l/h : ± 10.0

Test nozzle holder assembly : 1 688 901 101

Opening pressure bar : 207.0
Tolerance bar : ± 1.5

Test lines : 1 680 750 008

Outside diameter : 6.0
x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 3.20
Tolerance mm : ± 0.05
Check tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 4- 2- 1- 3

Phasing : 0-90-180-270
Tolerance : ± 0.30
Check tolerance °NW : ± 0.50

Start of delivery mark
Tolerance : ± 0.10
Check tolerance °NW : ± 0.75

Barrel no. : 4

BASIC SETTING

Rated speed rpm : 1000

Rack travel in mm : 13.00
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 189.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 3.5

Spread

Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 7.5

Rated speed rpm : 400

Rack travel in mm : 4.20
Tolerance mm : ± 0.10

Del. quantity
cm³/1000 strokes : 20.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 5.5

Spread
Tolerance
cm³/1000 strokes : 4.5
Check tolerance
cm³/1000S. : 7.5

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : - 3
Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : ± 0.20

governor spring
pre-tension
click setting x : 4.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1000

Aneroid pressure
hPa : 1420

Del. quantity
cm³/1000 strokes : 189.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 3.5

Spread
Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 7.5

CONTROL LEVER

control lever
position degree : 106.0
tolerance degree : ± 4.0

RATED SPEED

rack travel mm : 12.00
Rated speed rpm : 1040
Tolerance 1/min : ± 5

rack travel mm : 4.00
Rated speed rpm : 1090
Tolerance 1/min : ± 15

rack travel mm : 0.85
Tolerance mm : ± 0.55
Rated speed rpm : 1200

rack travel mm : 4.00
Rated speed rpm : 1095

LOW IDLE

control lever
position degree : 74.0
tolerance degree : ± 4.0

Setting point w/out bumper spring

Rated speed rpm : 400
rack travel mm : 3.70
Tolerance mm : ± 0.10

Testing:

Rated speed rpm : 400
rack travel mm : 4.20
Tolerance mm : ± 0.10

rack travel mm : 2.00
Rated speed rpm : 490
Tolerance 1/min : ± 30

TORQUE CONTROL

Rated speed rpm : 1000
rack travel mm : 13.00
Tolerance mm : ± 0.05

Rated speed rpm : 500
rack travel mm : 13.00
Tolerance mm : ± 0.10

Rated speed rpm : 700
rack travel mm : 13.00
Tolerance mm : ± 0.10

ANEROID/ALTITUDE COMPENSATOR TEST

SETTING

Rated speed rpm : 550
Pressure hPa : 1420
rack travel mm : 13.00
Tolerance mm : ± 0.10

Pressure hPa : -
Rated speed rpm : 550
rack travel mm : 11.20
Tolerance mm : ± 0.20

MEASUREMENT

Rated speed rpm : 550
Pressure hPa : 910
rack travel mm : 12.70
Tolerance mm : ± 0.05

Pressure hPa : 780
rack travel mm : 11.60
Tolerance mm : ± 0.10

Start interlock

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1420
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 214.0

Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0

Aneroid pressure
hPa : 1420
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 205.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0

Aneroid pressure
hPa : -
Rated speed rpm : 550
Del. quantity
cm³/1000 strokes : 177.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 3.5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : ± 0.50
Del. quantity
cm³/1000 strokes : 150.0
Tolerance
cm³/1000 strokes : ± 15.0
Check tolerance
cm³/1000S. : ± 19.0

LOW IDLE

Rated speed rpm : 400
Del. quantity
cm³/1000 strokes : 20.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 5.5
Speed
Tolerance
cm³/1000 strokes : 4.5
Check tolerance
cm³/1000S. : 7.5

End of test specification sheet



BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 21.01.97
Test oil : ISO 4113

Combination No. : 0 402 074 700A

Injection pump
Pump designation : PES4P110B720RS3383
EP type number : 0 412 014 701

Governor
Governor design. : RSV300...1100P1A667
Governor no. : 0 421 833 582

Cust. part No. : 9279831

Customer-spec. information
Customer : LIEBHERR
Motor : D 924 TI-E A2
Power KW : 149.0

TEST BENCH REQUIREMENTS

Inlet line : 4.1

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 049

Inlet press. bar : 1.5
Tolerance bar : ± 0.1

Tolerance l/h : ± 10.0

Test nozzle holder
assembly : 1 688 901 101

Opening pressure
bar : 207.0
Tolerance bar : ± 1.5

Test lines : 1 680 750 008

Outside diameter : 6.0
x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 3.20
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 4- 2- 1- 3

Phasing : 0-90-180-270
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50

Start of delivery mark
Tolerance : ± 0.10
Check
tolerance °NW : ± 0.75

Barrel no. : 4

BASIC SETTING

Rated speed rpm : 890

Rack travel in mm : 13.85
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 203.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 3.5

Spreed

Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 7.5

Rated speed rpm : 500

Rack travel in mm : 4.20
Tolerance mm : ± 0.10

Del. quantity
cm³/1000 strokes : 24.0

Tolerance
cm³/1000 strokes : ± 3.0

Check tolerance
cm³/1000S. : ± 5.5

Spreed

Tolerance
cm³/1000 strokes : 4.5

Check tolerance
cm³/1000S. : 7.5

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : - 3

governor spring
pre-tension
click setting x : 4.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 890

Aneroid pressure
hPa : 1410

Del. quantity
cm³/1000 strokes : 203.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 3.5

Spreed

Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 7.5

CONTROL LEVER

control lever
position degree : 100.0

tolerance degree : ± 4.0

RATED SPEED

rack travel mm : 12.85

Rated speed rpm : 910

Tolerance 1/min : ± 5

rack travel mm : 4.00

Rated speed rpm : 990

Tolerance 1/min : ± 15

rack travel mm : 0.85

Tolerance mm : ± 0.55

Rated speed rpm : 1200

rack travel mm : 4.00

Rated speed rpm : 995

LOW IDLE

control lever
position degree : 80.0

tolerance degree : ± 4.0

Setting point w/out bumper spring

Rated speed rpm : 500

rack travel mm : 2.40

Tolerance mm : ± 0.10

Testing:

Rated speed rpm : 500

rack travel mm : 4.20

Tolerance mm : ± 0.10

TORQUE CONTROL

Rated speed rpm : 890

rack travel mm : 13.85
Tolerance mm : ± 0.05

Rated speed rpm : 500
rack travel mm : 13.85
Tolerance mm : ± 0.10

Rated speed rpm : 700
rack travel mm : 13.85
Tolerance mm : ± 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1410
rack travel mm : 13.85
Tolerance mm : ± 0.10

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : 11.40
Tolerance mm : ± 0.20

MEASUREMENT

Rated speed rpm : 500

Pressure hPa : 870
rack travel mm : 13.00
Tolerance mm : ± 0.05

Pressure hPa : 775
rack travel mm : 12.00
Tolerance mm : ± 0.10

Start interlock

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1410
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 230.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0

Aneroid pressure
hPa : 1410
Rated speed rpm : 700

Del. quantity
cm³/1000 strokes : 216.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 177.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 3.5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : ± 0.50
Del. quantity
cm³/1000 strokes : 150.0
Tolerance
cm³/1000 strokes : ± 15.0
Check tolerance
cm³/1000S. : ± 19.0

LOW IDLE

Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 24.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 5.5
Spreed
Tolerance
cm³/1000 strokes : 4.5
Check tolerance
cm³/1000S. : 7.5

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 21.01.97
Test oil : ISO 4113

Combination No. : 0 402 076 748A

Injection pump
Pump designation : PES6P110A72ORS3305
EP type number : 0 412 016 742

Governor
Governor design. : RSV300...1100P1A555
Governor no. : 0 421 833 379

Cust. part No. : 9271058

Customer-spec. information
Customer : LIEBHERR
Motor : D 926 TI
Power KW : 210.0

TEST BENCH REQUIREMENTS

Inlet line : 4.1

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 049

Inlet press. bar : 1.5
Tolerance bar : ± 0.1

Overflow quantity
min. L/h : 130
Tolerance L/h : ± 10.0

Test nozzle holde
assembly : 1 688 901 101

Opening pressure
bar : 207.0
Tolerance bar : ± 1.5

Test lines : 1 680 750 008
Outside diameter : 6.0
x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 3.20
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50

Start of delivery mark

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1000

Rack travel in mm : 11.25
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 165.0

Tolerance
 cm³/1000 strokes : + 1.0

Check tolerance
 cm³/1000S. : + 3.5

Speed

Tolerance
 cm³/1000 strokes : 4.0

Check tolerance
 cm³/1000S. : 7.5

Rated speed rpm : 400

Rack travel in mm : 4.40
 Tolerance mm : + 0.10
 Del. quantity
 cm³/1000 strokes : 36.0
 Tolerance
 cm³/1000 strokes : + 3.0
 Check tolerance
 cm³/1000S. : + 5.5

Speed

Tolerance
 cm³/1000 strokes : 4.5
 Check tolerance
 cm³/1000S. : 7.5

(B) SETTING OF INJECTION PUMP
 WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
 position degree : - 3
 Rated speed rpm : 800

Rack travel in mm : 0.50
 Tolerance mm : + 0.20

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1000
 Aneroid pressure
 hPa : 1100
 Del. quantity
 cm³/1000 strokes : 165.0
 Tolerance
 cm³/1000 strokes : + 1.0
 Check tolerance
 cm³/1000S. : + 3.5

Speed
 Tolerance
 cm³/1000 strokes : 4.0
 Check tolerance
 cm³/1000S. : 7.5

CONTROL LEVER

control lever
 position degree : 108.0
 tolerance degree : + 4.0

RATED SPEED

rack travel mm : 10.25
 Rated speed rpm : 1025
 Tolerance 1/min : + 5

rack travel mm : 4.00
 Rated speed rpm : 1095
 Tolerance 1/min : + 15

rack travel mm : 0.85
 Tolerance mm : + 0.55
 Rated speed rpm : 1260

rack travel mm : 4.00
 Rated speed rpm : 1100

LOW IDLE

control lever
 position degree : 78.0
 tolerance degree : + 4.0

Setting point w/out bumper spring

Rated speed rpm : 400
 rack travel mm : 3.90
 Tolerance mm : + 0.10

Testing:

Rated speed rpm : 400
 rack travel mm : 4.40
 Tolerance mm : + 0.10

rack travel mm : 2.00
 Rated speed rpm : 450
 Tolerance 1/min : + 30

TORQUE CONTROL

Rated speed rpm : 1000

rack travel mm : 11.25
 Tolerance mm : + 0.05

 Rated speed rpm : 600
 rack travel mm : 11.25
 Tolerance mm : + 0.10

 Rated speed rpm : 500
 rack travel mm : 11.30
 Tolerance mm : + 0.10

 Rated speed rpm : 450
 rack travel mm : 12.20
 Tolerance mm : + 0.10

 Rated speed rpm : 400
 rack travel mm : 12.20
 Tolerance mm : + 0.15

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 550
 Pressure hPa : 1100
 rack travel mm : 11.25
 Tolerance mm : + 0.05

 Pressure hPa : -
 Rated speed rpm : 550
 rack travel mm : 9.75
 Tolerance mm : + 0.10

MEASUREMENT

Rated speed rpm : 550

 Pressure hPa : 650
 rack travel mm : 11.00
 Tolerance mm : + 0.05

 Pressure hPa : 550
 rack travel mm : 10.25
 Tolerance mm : + 0.10

Start interlock

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
 hPa : 1100
 Rated speed rpm : 600
 Del. quantity
 cm³/1000 strokes : 186.0

Tolerance
 cm³/1000 strokes : + 2.0
 Check tolerance
 cm³/1000S. : + 5.0

 Aneroid pressure
 hPa : -
 Rated speed rpm : 550
 Del. quantity
 cm³/1000 strokes : 152.5
 Tolerance
 cm³/1000 strokes : + 1.0
 Check tolerance
 cm³/1000S. : + 3.5

STARTING FUEL DELIVERY

Rated speed rpm : 100
 rack travel mm : 20.50
 Tolerance mm : + 0.50
 Del. quantity
 cm³/1000 strokes : 145.0
 Tolerance
 cm³/1000 strokes : + 10.0
 Check tolerance
 cm³/1000S. : + 14.0

LOW IDLE

Rated speed rpm : 400
 Del. quantity
 cm³/1000 strokes : 36.0
 Tolerance
 cm³/1000 strokes : + 3.0
 Check tolerance
 cm³/1000S. : + 5.5
 Speed
 Tolerance
 cm³/1000 strokes : 4.5
 Check tolerance
 cm³/1000S. : 7.5

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 25.11.96
Test oil : ISO 4113

Combination No. : 0 402 076 7486

Injection pump
Pump designation : PES6P110A72ORS3305
EP type number : 0 412 016 742

Governor
Governor design. : RSV300...1100P1A555
Governor no. : 0 421 833 379

Cust. part No. : 9271056

Customer-spec. information
Customer : LIEBHERR
Motor : D 926 TI
Power KW : 218.0

TEST BENCH REQUIREMENTS

Inlet line : 4.1

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 049

Inlet press. bar : 1.5
Tolerance bar : ± 0.1

Overflow quantity
min. l/h : 130
Tolerance l/h : ± 10.0

Test nozzle holder
assembly : 1 688 901 101

Opening pressure
bar : 207.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 008

Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 3.20
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50

Start of delivery mark

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 900

Rack travel in mm : 12.30
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 181.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 3.5

Spread

Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 7.5

Rated speed rpm : 400

Rack travel in mm : 4.40
Tolerance mm : ± 0.10

Del. quantity
cm³/1000 strokes : 30.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 5.5

Spread
Tolerance
cm³/1000 strokes : 4.5
Check tolerance
cm³/1000S. : 7.5

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : - 3

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 900
Aneroid pressure
hPa : 1150
Del. quantity
cm³/1000 strokes : 181.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 3.5
Spread

Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 7.5

CONTROL LEVER

control lever
position degree : 100.0
tolerance degree : ± 4.0

RATED SPEED
rack travel mm : 10.85
Rated speed rpm : 925
Tolerance 1/min : ± 5

rack travel mm : 4.00
Rated speed rpm : 980
Tolerance 1/min : ± 15

rack travel mm : 4.00
Rated speed rpm : 995

LOW IDLE

control lever
position degree : 75.0
tolerance degree : ± 4.0

Setting point w/out bumper spring

Rated speed rpm : 500
rack travel mm : 3.90
Tolerance mm : ± 0.10

Testing:

Rated speed rpm : 500
rack travel mm : 4.40
Tolerance mm : ± 0.10

TORQUE CONTROL

Rated speed rpm : 900
rack travel mm : 12.30
Tolerance mm : ± 0.05

Rated speed rpm : 500
rack travel mm : 12.30
Tolerance mm : ± 0.10

Rated speed rpm : 700
rack travel mm : 12.30

Tolerance mm : + 0.10
Rated speed rpm : 450
rack travel mm : 13.70
Tolerance mm : + 0.10

ANEROID/ALTITUDE COMPENSATOR TEST

SETTING

Rated speed rpm : 550
Pressure hPa : 1150
rack travel mm : 12.30
Tolerance mm : + 0.05

Pressure hPa : -
Rated speed rpm : 550
rack travel mm : 9.45
Tolerance mm : + 0.10

MEASUREMENT

Rated speed rpm : 550
Pressure hPa : 800
rack travel mm : 11.80
Tolerance mm : + 0.05

Pressure hPa : 670
rack travel mm : 10.35
Tolerance mm : + 0.10

Start interlock

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1150
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 203.0
Tolerance
cm³/1000 strokes : + 2.0
Check tolerance
cm³/1000S. : + 5.0

Aneroid pressure
hPa : 1150
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 196.0
Tolerance
cm³/1000 strokes : + 2.0
Check tolerance
cm³/1000S. : + 5.0

Aneroid pressure
hPa : -
Rated speed rpm : 550
Del. quantity
cm³/1000 strokes : 143.0
Tolerance
cm³/1000 strokes : + 1.0
Check tolerance
cm³/1000S. : + 3.5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : + 0.50
Del. quantity
cm³/1000 strokes : 145.0
Tolerance
cm³/1000 strokes : + 10.0
Check tolerance
cm³/1000S. : + 14.0

LOW IDLE

Rated speed rpm : 400
Del. quantity
cm³/1000 strokes : 30.0
Tolerance
cm³/1000 strokes : + 3.0
Check tolerance
cm³/1000S. : + 5.5
Spread
Tolerance
cm³/1000 strokes : 4.5
Check tolerance
cm³/1000S. : 7.5

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 21.01.97
Test oil : ISO 4113

Combination No. : 0 402 076 748H

Injection pump
Pump designation : PES6P110A720RS3305
EP type number : 0 412 016 742

Governor
Governor design. : RSV300...1100P1A555
Governor no. : 0 421 833 379

Cust. part No. : 9271056

Customer-spec. information
Customer : LIEBHERR
Motor : D 926 TI-E A2
Power KW : 172.0

TEST BENCH REQUIREMENTS

Inlet line : 4.1

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 049

Inlet press. bar : 1.5
Tolerance bar : ± 0.1

Overflow quantity
min. l/h : 130
Tolerance l/h : ± 10.0

Test nozzle holder
assembly : 1 688 901 101

Opening pressure
bar : 207.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 008
Outside diameter : 6.0
x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 3.20
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50

Start of delivery mark

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 900

Rack travel in mm : 10.95
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 161.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 3.5

Speed

Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 7.5

Rated speed rpm : 400

Rack travel in mm : 4.90
Tolerance mm : ± 0.10

Del. quantity
cm³/1000 strokes : 36.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 5.5

Speed
Tolerance
cm³/1000 strokes : 4.5
Check tolerance
cm³/1000S. : 7.5

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : - 3

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 900
Aneroid pressure
hPa : 1050

Del. quantity
cm³/1000 strokes : 161.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 3.5

Speed

Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 7.5

CONTROL LEVER

control lever
position degree : 98.0
tolerance degree : ± 4.0

RATED SPEED

rack travel mm : 9.95
Rated speed rpm : 935
Tolerance 1/min : ± 5

rack travel mm : 4.00
Rated speed rpm : 975
Tolerance 1/min : ± 15

rack travel mm : 4.00
Rated speed rpm : 985

LOW IDLE

control lever
position degree : 74.0
tolerance degree : ± 4.0

Setting point w/out bumper spring

Rated speed rpm : 400
rack travel mm : 4.40
Tolerance mm : ± 0.10

Testing:

Rated speed rpm : 400
rack travel mm : 4.90
Tolerance mm : ± 0.10

TORQUE CONTROL

Rated speed rpm : 900
rack travel mm : 10.95
Tolerance mm : ± 0.05

Rated speed rpm : 500
rack travel mm : 10.95
Tolerance mm : ± 0.10

Rated speed rpm : 700
rack travel mm : 10.95

Tolerance mm : + 0.30

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 550
Pressure hPa : 1050
rack travel mm : 10.95
Tolerance mm : + 0.05

Pressure hPa : -
Rated speed rpm : 550
rack travel mm : 9.90
Tolerance mm : + 0.10

MEASUREMENT

Rated speed rpm : 550

Pressure hPa : 640
rack travel mm : 10.70
Tolerance mm : + 0.05

Pressure hPa : 590
rack travel mm : 10.20
Tolerance mm : + 0.10

Start interlock

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1080
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 181.0
Tolerance
cm³/1000 strokes : + 2.0
Check tolerance
cm³/1000S. : + 5.0

Aneroid pressure
hPa : 1080
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 175.0
Tolerance
cm³/1000 strokes : + 2.0
Check tolerance
cm³/1000S. : + 5.0

Aneroid pressure
hPa : -
Rated speed rpm : 500

Del. quantity
cm³/1000 strokes : 159.0
Tolerance
cm³/1000 strokes : + 1.0
Check tolerance
cm³/1000S. : + 3.5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : + 0.50
Del. quantity
cm³/1000 strokes : 155.0
Tolerance
cm³/1000 strokes : + 10.0
Check tolerance
cm³/1000S. : + 14.0

LOW IDLE

Rated speed rpm : 400
Del. quantity
cm³/1000 strokes : 36.0
Tolerance
cm³/1000 strokes : + 3.0
Check tolerance
cm³/1000S. : + 5.5
Speed
Tolerance
cm³/1000 strokes : 4.5
Check tolerance
cm³/1000S. : 7.5

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 21.01.97
Test oil : ISO 4113

Combination No. : 0 402 076 748I

Injection pump
Pump designation : PES6P110A720RS3305
EP type number : 0 412 016 742

Governor
Governor design. : RSV300...1100P1A555
Governor no. : 0 421 833 379

Cust. part No. : 9271056

Customer-spec. information

Customer : LIEBHERR
Motor : D 926 TI-E A2
Power KW : 210.0

TEST BENCH REQUIREMENTS

Inlet line : 4.1

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 049

Inlet press. bar : 1.5
Tolerance bar : ± 0.1

Overflow quantity
min. l/h : 130
Tolerance l/h : ± 10.0

Test nozzle holder
assembly : 1 688 901 101

Opening pressure
bar : 207.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 008

Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 3.20
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50

Start of delivery mark

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1000

Rack travel in mm : 13.00
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 183.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 3.5

Spread

Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 7.5

Rated speed rpm : 400

Rack travel in mm : 4.90
Tolerance mm : ± 0.10

Del. quantity
cm³/1000 strokes : 36.0

Tolerance
cm³/1000 strokes : ± 3.0

Check tolerance
cm³/1000S. : ± 5.5

Spread

Tolerance
cm³/1000 strokes : 4.5

Check tolerance
cm³/1000S. : 7.5

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : - 3

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1000
Aneroid pressure
hPa : 1080

Del. quantity
cm³/1000 strokes : 183.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 3.5

Spread

Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 7.5

CONTROL LEVER

control lever
position degree : 108.0
tolerance degree : ± 4.0

RATED SPEED

rack travel mm : 12.00
Rated speed rpm : 1030
Tolerance 1/min : ± 5

rack travel mm : 4.00
Rated speed rpm : 1100
Tolerance 1/min : ± 15

rack travel mm : 4.00
Rated speed rpm : 1100

LOW IDLE

control lever
position degree : 79.0
tolerance degree : ± 4.0

Setting point w/out bumper spring

Rated speed rpm : 400
rack travel mm : 4.40
Tolerance mm : ± 0.10

Testing:

Rated speed rpm : 400
rack travel mm : 4.90
Tolerance mm : ± 0.10

TORQUE CONTROL

Rated speed rpm : 1000
rack travel mm : 13.00
Tolerance mm : ± 0.05

Rated speed rpm : 500
rack travel mm : 13.00
Tolerance mm : ± 0.10

Rated speed rpm : 700
rack travel mm : 13.00

Tolerance mm : ± 0.30

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 550
Pressure hPa : 1080
rack travel mm : 13.00
Tolerance mm : ± 0.05

Pressure hPa : -
Rated speed rpm : 550
rack travel mm : 11.50
Tolerance mm : ± 0.10

MEASUREMENT

Rated speed rpm : 550
Pressure hPa : 775
rack travel mm : 12.60
Tolerance mm : ± 0.05

Pressure hPa : 705
rack travel mm : 11.80
Tolerance mm : ± 0.10

Start interlock

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1080
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 203.0
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 5.0

Aneroid pressure
hPa : 1080
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 194.0
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 5.0

Aneroid pressure
hPa : -
Rated speed rpm : 500

Del. quantity
cm³/1000 strokes : 175.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 3.5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : ± 0.50
Del. quantity
cm³/1000 strokes : 155.0
Tolerance
cm³/1000 strokes : ± 10.0
Check tolerance
cm³/1000S. : ± 14.0

LOW IDLE

Rated speed rpm : 400
Del. quantity
cm³/1000 strokes : 36.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 5.5
Spread
Tolerance
cm³/1000 strokes : 4.5
Check tolerance
cm³/1000S. : 7.5

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 21.01.97
Test oil : ISO 4113

Combination No. : 0 402 076 748K

Injection pump
Pump designation : PES6P110A720RS3305
EP type number : 0 412 016 742

Governor
Governor design. : RSV300...1100P1A555
Governor no. : 0 421 833 379

Cust. part No. : 9271056

Customer-spec. information
Customer : LIEBHERR
Motor : D 926 TI-E A2
Power KW : 195.0

TEST BENCH REQUIREMENTS

Inlet line : 4.1

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 049

Inlet press. bar : 1.5
Tolerance bar : ± 0.1

Overflow quantity
min. l/h : 130
Tolerance l/h : ± 10.0

Test nozzle holder
assembly : 1 688 901 101

Opening pressure
bar : 207.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 008

Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 3.20
Tolerance mm : ± 0.05
Check
Tolerance mm : ± 0.10

k travel in mm : 10.50
Tolerance mm : ± 1.50

Filling order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance *NW : ± 0.50

Start of delivery mark

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1000

Rack travel in mm : 11.00
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 163.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 3.5

Speed

Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 7.5

Rated speed rpm : 400

Rack travel in mm : 4.90
Tolerance mm : ± 0.10

Del. quantity
cm³/1000 strokes : 36.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 5.5

Speed
Tolerance
cm³/1000 strokes : 4.5
Check tolerance
cm³/1000S. : 7.5

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : - 3

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1000
Aneroid pressure
hPa : 1080

Del. quantity
cm³/1000 strokes : 163.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 3.5

Speed

Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 7.5

CONTROL LEVER

control lever
position degree : 108.0
tolerance degree : ± 4.0

RATED SPEED

rack travel mm : 10.00
Rated speed rpm : 1025
Tolerance 1/min : ± 5

rack travel mm : 4.00
Rated speed rpm : 1090
Tolerance 1/min : ± 15

rack travel mm : 4.00
Rated speed rpm : 1100

LOW IDLE

control lever
position degree : 79.0
tolerance degree : ± 4.0

Setting point w/out bumper spring

Rated speed rpm : 400
rack travel mm : 4.40
Tolerance mm : ± 0.10

Testing:

Rated speed rpm : 400
rack travel mm : 4.90
Tolerance mm : ± 0.10

TORQUE CONTROL

Rated speed rpm : 1000
rack travel mm : 11.00
Tolerance mm : ± 0.05

Rated speed rpm : 500
rack travel mm : 11.00
Tolerance mm : ± 0.10

Rated speed rpm : 700
rack travel mm : 11.00

Tolerance mm : ± 0.30

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1080
rack travel mm : 11.00
Tolerance mm : ± 0.05

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : 10.00
Tolerance mm : ± 0.10

MEASUREMENT

Rated speed rpm : 500
Pressure hPa : 630
rack travel mm : 10.80
Tolerance mm : ± 0.05

Pressure hPa : 590
rack travel mm : 10.30
Tolerance mm : ± 0.10

Start interlock

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1080
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 188.0
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 5.0

Aneroid pressure
hPa : 1080
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 178.0
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 5.0

Aneroid pressure
hPa : -
Rated speed rpm : 500

Del. quantity
cm³/1000 strokes : 167.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 3.5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : ± 0.50
Del. quantity
cm³/1000 strokes : 145.0
Tolerance
cm³/1000 strokes : ± 10.0
Check tolerance
cm³/1000S. : ± 14.0

LOW IDLE

Rated speed rpm : 400
Del. quantity
cm³/1000 strokes : 36.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 5.5
Speed
Tolerance
cm³/1000 strokes : 4.5
Check tolerance
cm³/1000S. : 7.5

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 17.01.97
 Test oil : ISO 4113
 Combination No. : 0 402 646 665
 Injection pump
 Pump designation : PE6P130A720RS7354
 EP type number : 0 412 636 835
 Governor
 Governor design. : RGV300...950PA1002
 : K
 Governor no. : 0 421 815 491
 Cust. part No. :

Customer-spec. information
 Customer : IVECO-FRANCE
 Motor : 8210.42K.3000

TEST BENCH REQUIREMENTS

Inlet line : 4.2
 Test oil inlet
 temp. °C : 40
 Tolerance °C : ± 2.0
 Overflow valve : 2 417 413 076
 Inlet press. bar : 2.5
 Tolerance bar : ± 0.1
 Test nozzle holde
 assembly : 1 688 901 105
 Opening pressure
 bar : 208.5
 Tolerance bar : ± 1.5
 Test lines : 1 680 750 075
 Outside diameter : 8.0

x inside diameter : 3.0
 x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
 Set equal delivery quant.
 per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
 Tolerance bar : ± 1.0
 Prestroke mm : 5.05
 Tolerance mm : ± 0.05
 Check
 tolerance mm : ± 0.10
 Rack travel in mm : 12.00
 Tolerance mm : ± 0.50
 Firing order : 1- 5- 3- 6- 2-
 : 4
 Phasing : 0-60-120-180-240
 Tolerance : ± 0.30
 Check
 tolerance °NW : ± 0.50
 Start of delivery mark
 Check
 tolerance °NW : ± 0.40
 Barrel no. : 1

BASIC SETTING

Rated speed rpm : 950
 Rack travel in mm : 11.95
 Tolerance mm : ± 0.05
 Del. quantity
 cm³/1000 strokes : 242.0
 Tolerance
 cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 4.0

Spread

Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 275

Rack travel in mm : 5.30

Tolerance mm : ± 0.10

Del. quantity
cm³/1000 strokes : 32.0

Tolerance
cm³/1000 strokes : ± 3.0

Check tolerance
cm³/1000S. : ± 6.0

Spread

Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 1025
guide sleeve
travel mm : 9.00
Tolerance mm : ± 0.15

Rated speed rpm : 300
guide sleeve
travel mm : 1.64
Tolerance mm : ± 0.20

Rated speed rpm : 764
guide sleeve
travel mm : 6.22
Tolerance mm : ± 0.25

Rated speed rpm : 500
guide sleeve
travel mm : 3.78
Tolerance mm : ± 0.25

Rated speed rpm : 1330
guide sleeve
travel mm : 13.50

Tolerance mm : ± 0.50

GUIDE SLEEVE POSITION

control lever
position degree : - 1
Rated speed rpm : 1190

Rack travel in mm : 11.00
Tolerance mm : ± 2.70

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 950
Aneroid pressure
hPa : 1000

Del. quantity
cm³/1000 strokes : 242.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 4.0

Spread

Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 114.0
tolerance degree : ± 4.0

RATED SPEED

rack travel mm : 10.90
Rated speed rpm : 1010
Tolerance 1/min : ± 5

Check
speed 1/min : ± 10

rack travel mm : 4.00
Rated speed rpm : 1110
Tolerance 1/min : ± 15

Check
speed 1/min : ± 20

rack travel mm : 0.50
Tolerance mm : ± 0.50
Rated speed rpm : 1250

LOW IDLE

control lever
position degree : 69.0
tolerance degree : ± 4.0

Testing:

Rated speed rpm : 275
rack travel mm : 5.30
Tolerance mm : ± 0.10

Rated speed rpm : 200

CRT mm min. : > 6.20

Rated speed rpm : 355

TORQUE CONTROL

Rated speed rpm : 950
rack travel mm : 11.95
Tolerance mm : ± 0.05

Rated speed rpm : 700
rack travel mm : 11.75
Tolerance mm : ± 0.10

Rated speed rpm : 550
rack travel mm : 11.30
Tolerance mm : ± 0.10

Rated speed rpm : 300
rack travel mm : 10.80
Tolerance mm : ± 0.30

ANEROID/ALTITUDE COMPENSATOR TEST

SETTING

Rated speed rpm : 950
Pressure hPa : 1000
rack travel mm : 11.95
Tolerance mm : ± 0.05

Pressure hPa : -
Rated speed rpm : 950
rack travel mm : 8.40
Tolerance mm : ± 0.40

MEASUREMENT

Rated speed rpm : 950

Pressure hPa : 290
rack travel mm : 9.35

Tolerance mm : ± 0.20

Pressure hPa : 500
rack travel mm : 11.10
Tolerance mm : ± 0.05

Start interlock

Rated speed rpm : > 130
Rated speed rpm : < 220

Check
speed 1/min : > 160
Check
speed 1/min : < 240

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1000
Rated speed rpm : 550
Del. quantity
cm³/1000 strokes : 262.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0

Aneroid pressure
hPa : -
Rated speed rpm : 550
Del. quantity
cm³/1000 strokes : 173.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.25
Tolerance mm : ± 0.75
Del. quantity
cm³/1000 strokes : 160.0
Tolerance
cm³/1000 strokes : ± 15.0
Check tolerance
cm³/1000S. : ± 19.0

LOW IDLE

Rated speed rpm : 275

Del. quantity
cm³/1000 strokes : 32.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000s. : ± 6.0
Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000s. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 16.01.97
Test oil : ISO 4113

Combination No. : 0 402 646 742

Injection pump
Pump designation : PE6P120A320LS7837-2
EP type number : 0 412 626 943

Governor
Governor design. : RQ300/1100PA1272
Governor no. : 0 421 801 804

Cust. part No. : 0270743002

Customer-spec. information

Customer : MB-NFZ
Motor : OM441 LA
Power KW : 228.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1

Test oil inlet temp. °C : 40
Tolerance °C : + 2.0

Overflow valve : 1 417 413 047

Inlet press. bar : 1.5
Tolerance bar : + 0.1

Overflow quantity min. l/h : 120
Tolerance l/h : + 20.0

Test nozzle holder assembly : 1 688 901 105

Opening pressure bar : 208.5
Tolerance bar : + 1.5

Test lines : 1 680 750 075

Outside diameter : 8.0

x inside diameter : 3.0

x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : + 1.0

Prestroke mm : 5.25
Tolerance mm : + 0.05
Check tolerance mm : + 0.10

Rack travel in mm : 20.50
Tolerance mm : + 0.50

Firing order : 6- 3- 5- 2- 4-
: 1

Phasing : 0-60-120-180-240
Tolerance : + 0.30
Check tolerance °NW : + 0.50

Start of delivery mark

Tolerance : + 0.10
Check tolerance °NW : + 0.75

Barrel no. : 6

CRT ZERO POSITION

Rack travel in mm : 12.60
Tolerance mm : + 0.05

BASIC SETTING

Rated speed rpm : 600

Rack travel in mm : 12.60
Tolerance mm : \pm 0.05

Del. quantity
cm³/1000 strokes : 191.0

Tolerance
cm³/1000 strokes : \pm 1.0

Check tolerance
cm³/1000S. : \pm 4.0

Speed

Tolerance
cm³/1000 strokes : 6.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 300

Rack travel in mm : 5.60
Tolerance mm : \pm 0.10

Del. quantity
cm³/1000 strokes : 16.0

Tolerance
cm³/1000 strokes : \pm 3.0

Check tolerance
cm³/1000S. : \pm 6.0

Speed

Tolerance
cm³/1000 strokes : 6.0

Check tolerance
cm³/1000S. : 10.0

**(B) SETTING OF INJECTION PUMP
WITH GOVERNOR**

GUIDE SLEEVE TRAVEL

Rated speed rpm : 1146
guide sleeve
travel mm : 6.54
Tolerance mm : \pm 0.15

Rated speed rpm : 300
guide sleeve
travel mm : 2.24

Tolerance mm : \pm 0.20

Rated speed rpm : 1100
guide sleeve
travel mm : 6.00
Tolerance mm : \pm 0.10

Rated speed rpm : 429
guide sleeve
travel mm : 4.97
Tolerance mm : \pm 0.10

Rated speed rpm : 550
guide sleeve
travel mm : 6.00
Tolerance mm : \pm 0.10

Rated speed rpm : 1340
guide sleeve
travel mm : 11.50
Tolerance mm : \pm 0.50

GUIDE SLEEVE POSITION

control lever
position degree : 109
Rated speed rpm : 650

Rack travel in mm : 20.00
Tolerance mm : \pm 0.80

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 600
Aneroid pressure
hPa : 600

Del. quantity
cm³/1000 strokes : 191.0

Tolerance
cm³/1000 strokes : \pm 1.0

Check tolerance
cm³/1000S. : \pm 4.0

Speed

Tolerance
cm³/1000 strokes : 6.0

Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 94.0
tolerance degree : \pm 4.0

RATED SPEED

rack travel mm : 12.70
Rated speed rpm : 1150
Tolerance 1/min : + 5
Check
speed 1/min : + 13

rack travel mm : 4.00
Rated speed rpm : 1260
Tolerance 1/min : + 15
Check
speed 1/min : + 20

rack travel mm : 0.75
Tolerance mm : + 0.75
Rated speed rpm : 1350

LOW IDLE

control lever
position degree : 72.0
tolerance degree : + 4.0

Testing:

Rated speed rpm : 300
rack travel mm : 5.60
Tolerance mm : + 0.10

rack travel mm : 2.00
Rated speed rpm : 400
Tolerance 1/min : + 20

Rated speed rpm : 200

CRT mm min. : > 9.00

TORQUE CONTROL

Rated speed rpm : 600
rack travel mm : 12.60
Tolerance mm : + 0.05

Rated speed rpm : 1100
rack travel mm : 13.70
Tolerance mm : + 0.10

Rated speed rpm : 700
rack travel mm : 13.70
Tolerance mm : + 0.10

ANEROID/ALTITUDE COMPENSATOR TEST

2-stage LDA setting

Rated speed rpm : 400
Pressure hPa : 600

MEASUREMENT

Pressure hPa : 350
rack travel mm : -0.80
Tolerance mm : + 0.15

Pressure hPa : 200
rack travel mm : -2.00
Tolerance mm : + 0.20

Pressure hPa : 975
rack travel mm : 0.50
Tolerance mm : + 0.05

Start interlock

Rated speed rpm : > 100
Rated speed rpm : < 220

Check
speed 1/min : > 80
Check
speed 1/min : < 240

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1500
Rated speed rpm : 1100
Del. quantity
cm³/1000 strokes : 214.0
Tolerance
cm³/1000 strokes : + 1.5
Check tolerance
cm³/1000S. : + 4.5
Spread
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

Aneroid pressure
hPa : 1500
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 216.0
Tolerance
cm³/1000 strokes : + 3.0
Check tolerance
cm³/1000S. : + 6.0

Aneroid pressure
hPa : 350

Rated speed rpm : 400
Del. quantity
cm³/1000 strokes : 158.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 145.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 205.0
Tolerance
cm³/1000 strokes : ± 15.0
Check tolerance
cm³/1000S. : ± 19.0

LOW IDLE

Rated speed rpm : 300
Del. quantity
cm³/1000 strokes : 16.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0
Speed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 10.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 16.01.97
Test oil : ISO 4113

Combination No. : 0 402 646 742T3

Injection pump
Pump designation : PE6P120A320LS7837-2
EP type number : 0 412 626 943

Governor
Governor design. : RQ300/1100PA1272
Governor no. : 0 421 801 804

Cust. part No. : 0270743002

Customer-spec. information

Customer : MB-NFZ
Motor : OM441 LA
Power KW : 228.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 047

Inlet press. bar : 1.5
Tolerance bar : ± 0.1

Overflow quantity
min. l/h : 120
Tolerance l/h : ± 20.0

Test nozzle holder
assembly : 1 688 901 019

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 075

Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 5.25
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 20.50
Tolerance mm : ± 0.50

Firing order : 6- 3- 5- 2- 4-
: 1

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50

Start of delivery mark

Tolerance : ± 0.10
Check
tolerance °NW : ± 0.75

Barrel no. : 6

CRT ZERO POSITION

Rack travel in mm : 12.60
Tolerance mm : ± 0.05

BASIC SETTING

Rated speed rpm : 600

Rack travel in mm : 12.60
Tolerance mm : + 0.05

Del. quantity
cm³/1000 strokes : 193.5

Tolerance
cm³/1000 strokes : + 1.0

Check tolerance
cm³/1000S. : + 4.0

Speed

Tolerance
cm³/1000 strokes : 6.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 300

Rack travel in mm : 5.60
Tolerance mm : + 0.10

Del. quantity
cm³/1000 strokes : 19.0

Tolerance
cm³/1000 strokes : + 3.0

Check tolerance
cm³/1000S. : + 6.0

Speed

Tolerance
cm³/1000 strokes : 6.0

Check tolerance
cm³/1000S. : 10.0

**(B) SETTING OF INJECTION PUMP
WITH GOVERNOR**

GUIDE SLEEVE TRAVEL

Rated speed rpm : 1146
guide sleeve
travel mm : 6.54
Tolerance mm : + 0.15

Rated speed rpm : 300
guide sleeve
travel mm : 2.24

Tolerance mm : + 0.20

Rated speed rpm : 1100
guide sleeve
travel mm : 6.00
Tolerance mm : + 0.10

Rated speed rpm : 429
guide sleeve
travel mm : 4.97
Tolerance mm : + 0.10

Rated speed rpm : 550
guide sleeve
travel mm : 6.00
Tolerance mm : + 0.10

Rated speed rpm : 1340
guide sleeve
travel mm : 11.50
Tolerance mm : + 0.50

GUIDE SLEEVE POSITION

control lever
position degree : 109
Rated speed rpm : 650

Rack travel in mm : 20.00
Tolerance mm : + 0.80

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 600
Aneroid pressure
hPa : 600

Del. quantity
cm³/1000 strokes : 193.5
Tolerance
cm³/1000 strokes : + 1.0

Check tolerance
cm³/1000S. : + 4.0

Speed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 95.0
tolerance degree : + 4.0

RATED SPEED

rack travel mm : 12.70
Rated speed rpm : 1150
Tolerance 1/min : + 5
Check
speed 1/min : + 13

rack travel mm : 4.00
Rated speed rpm : 1240
Tolerance 1/min : + 15
Check
speed 1/min : + 20

rack travel mm : 0.75
Tolerance mm : + 0.75
Rated speed rpm : 1350

LOW IDLE

control lever
position degree : 75.0
tolerance degree : + 4.0

Testing:

Rated speed rpm : 300
rack travel mm : 5.60
Tolerance mm : + 0.10

rack travel mm : 2.00
Rated speed rpm : 419
Tolerance 1/min : + 20

Rated speed rpm : 220
CRT mm min. : > 8.27

TORQUE CONTROL

Rated speed rpm : 600
rack travel mm : 12.60
Tolerance mm : + 0.05

Rated speed rpm : 1100
rack travel mm : 13.70
Tolerance mm : + 0.10

Rated speed rpm : 700
rack travel mm : 13.70
Tolerance mm : + 0.10

ANEROID/ALTITUDE COMPENSATOR TEST

2-stage LDA setting

Rated speed rpm : 400
Pressure hPa : 600

MEASUREMENT

Pressure hPa : 350
rack travel mm : -0.80
Tolerance mm : + 0.15

Pressure hPa : 200
rack travel mm : -2.00
Tolerance mm : + 0.20

Pressure hPa : 975
rack travel mm : 0.50
Tolerance mm : + 0.05

Start interlock

Rated speed rpm : > 100
Rated speed rpm : < 220

Check
speed 1/min : > 80
Check
speed 1/min : < 240

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1500
Rated speed rpm : 1100
Del. quantity
cm³/1000 strokes : 219.0
Tolerance
cm³/1000 strokes : + 1.5
Check tolerance
cm³/1000S. : + 4.5

Spread
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

Aneroid pressure
hPa : 1500
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 214.0
Tolerance
cm³/1000 strokes : + 3.0
Check tolerance
cm³/1000S. : + 6.0

Aneroid pressure
hPa : 350

Rated speed rpm : 400
Del. quantity
cm³/1000 strokes : 160.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 151.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 205.0
Tolerance
cm³/1000 strokes : ± 15.0
Check tolerance
cm³/1000S. : ± 19.0

LOW IDLE

Rated speed rpm : 300
Del. quantity
cm³/1000 strokes : 19.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0
Speed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 10.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Infoc for test and adjustment instructions.
See microcard(s) W400/...

Edition : 16.01.97
Test oil : ISC 4113

Combination No. : 0 402 646 743

Injection pump
Pump designation : PE6P120A320LS7837-2
EP type number : 0 412 626 943

Governor
Governor design. : RQ300/1100PA1271
Governor no. : 0 421 801 803

Cust. part No. : 0270743102

Customer-spec. information

Customer : MB-NFZ
Motor : OM441 LA
Power KW : 260.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 047

Inlet press. bar : 1.5
Tolerance bar : ± 0.1

Overflow quantity
min. l/h : 120
Tolerance l/h : ± 20.0

Test nozzle holde
assembly : 1 688 901 105

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 075

Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 5.25
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 20.50
Tolerance mm : ± 0.50

Firing order : 6- 3- 5- 2- 4-
: 1

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50

Start of delivery mark

Tolerance : ± 0.10
Check
tolerance °NW : ± 0.75

Barrel no. : 6

CRT ZERO POSITION

Rack travel in mm : 14.50
Tolerance mm : ± 0.10

BASIC SETTING

Rated speed rpm : 600

Rack travel in mm : 14.50
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 233.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 4.0

SpeedTolerance
cm³/1000 strokes : 6.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 300Rack travel in mm : 5.60
Tolerance mm : ± 0.10Del. quantity
cm³/1000 strokes : 18.0Tolerance
cm³/1000 strokes : ± 3.0Check tolerance
cm³/1000S. : ± 6.0**Speed**Tolerance
cm³/1000 strokes : 6.0Check tolerance
cm³/1000S. : 10.0

**(B) SETTING OF INJECTION PUMP
WITH GOVERNOR**

GUIDE SLEEVE TRAVELRated speed rpm : 1146
guide sleeve
travel mm : 6.50
Tolerance mm : ± 0.15Rated speed rpm : 300
guide sleeve
travel mm : 2.13

B21

Tolerance mm : ± 0.20

Rated speed rpm : 1100
guide sleeve
travel mm : 6.00
Tolerance mm : ± 0.10Rated speed rpm : 425
guide sleeve
travel mm : 4.89
Tolerance mm : ± 0.10Rated speed rpm : 550
guide sleeve
travel mm : 6.00
Tolerance mm : ± 0.10Rated speed rpm : 1340
guide sleeve
travel mm : 11.50
Tolerance mm : ± 0.50

GUIDE SLEEVE POSITIONcontrol lever
position degree : 109
Rated speed rpm : 650Rack travel in mm : 20.00
Tolerance mm : ± 0.80

FULL LOAD DELIVERY AT FULL LOAD STOPRated speed rpm : 600
Aneroid pressure
hPa : 850Del. quantity
cm³/1000 strokes : 233.0Tolerance
cm³/1000 strokes : ± 1.0Check tolerance
cm³/1000S. : ± 4.0**Speed**Tolerance
cm³/1000 strokes : 6.0Check tolerance
cm³/1000S. : 9.0

CONTROL LEVERcontrol lever
position degree : 100.0
tolerance degree : ± 4.0

RATED SPEED

rack travel mm : 14.60
Rated speed rpm : 1150
Tolerance 1/min : + 5
Check
speed 1/min : + 13

rack travel mm : 4.00
Rated speed rpm : 1265
Tolerance 1/min : + 15
Check
speed 1/min : + 20

rack travel mm : 0.75
Tolerance mm : + 0.75
Rated speed rpm : 1350

LOW IDLE

control lever
position degree : 74.0
tolerance degree : + 4.0

Testing:

Rated speed rpm : 300
rack travel mm : 5.60
Tolerance mm : + 0.10

rack travel mm : 2.00
Rated speed rpm : 400
Tolerance 1/min : + 20

Rated speed rpm : 200

CRT mm min. : > 9.00

TORQUE CONTROL

Rated speed rpm : 600
rack travel mm : 14.50
Tolerance mm : + 0.05

Rated speed rpm : 1100
rack travel mm : 15.60
Tolerance mm : + 0.10

Rated speed rpm : 700
rack travel mm : 15.60
Tolerance mm : + 0.10

ANEROID/ALTITUDE COMPENSATOR TEST

2-stage LDA setting

Rated speed rpm : 400
Pressure hPa : 850

MEASUREMENT

Pressure hPa : 500
rack travel mm : -1.60
Tolerance mm : + 0.15

Pressure hPa : 200
rack travel mm : -4.00
Tolerance mm : + 0.20

Pressure hPa : 1240
rack travel mm : 0.45
Tolerance mm : + 0.05

Start interlock

Rated speed rpm : > 100
Rated speed rpm : < 220

Check
speed 1/min : > 80
Check
speed 1/min : < 240

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1500
Rated speed rpm : 1100
Del. quantity
cm³/1000 strokes : 252.0
Tolerance
cm³/1000 strokes : + 1.5
Check tolerance
cm³/1000S. : + 4.5
Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

Aneroid pressure
hPa : 1500
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 258.0
Tolerance
cm³/1000 strokes : + 3.0
Check tolerance
cm³/1000S. : + 6.0

Aneroid pressure
hPa : 500

Rated speed rpm : 400
Del. quantity
cm³/1000 strokes : 185.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 145.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 240.0
Tolerance
cm³/1000 strokes : ± 10.0
Check tolerance
cm³/1000S. : ± 14.0

LOW IDLE

Rated speed rpm : 300
Del. quantity
cm³/1000 strokes : 18.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0
Speed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 10.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 22.01.97
Test oil : ISO 4113
Combination No. : 0 402 648 780
Injection pump
Pump designation : PE8P120A320LS7871
EP type number : 0 412 628 877
Governor
Governor design. : RQV300...1050PA1078
: 2K
Governor no. : 0 421 815 548
Cust. part No. : 988 04 47

Customer-spec. information
Customer : LIEBHERR
Motor : D 9408 TI-EA3
Power KW : 420.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1
Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 1 417 413 047
Inlet press. bar : 2.0
Tolerance bar : ± 0.1
Overflow quantity
min. l/h : 230
Tolerance l/h : ± 20.0
Test nozzle holde
assembly : 1 688 901 105
Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 075
Outside diameter : 8.0
x inside diameter : 3.0
x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0
Prestroke mm : 3.65
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10
Rack travel in mm : 10.50
Tolerance mm : ± 0.50
Firing order : 1- 8- 7- 2- 6
: - 5- 4
Phasing : 0-45-90-135-180
: -270-315
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50

BASIC SETTING

Rated speed rpm : 1050
Rack travel in mm : 12.65
Tolerance mm : ± 0.05
Del. quantity
cm³/1000 strokes : 295.0
Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : + 4.0

Spread

Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 350

Rack travel in mm : 4.50
Tolerance mm : + 0.10

Del. quantity
cm³/1000 strokes : 15.0
Tolerance
cm³/1000 strokes : + 3.0

Check tolerance
cm³/1000S. : + 6.0

Spread
Tolerance
cm³/1000 strokes : 6.0

Check tolerance
cm³/1000S. : 10.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 1117
guide sleeve
travel mm : 10.27
Tolerance mm : + 0.15

Rated speed rpm : 300
guide sleeve
travel mm : 1.11
Tolerance mm : + 0.20

Rated speed rpm : 755
guide sleeve
travel mm : 6.17
Tolerance mm : + 0.25

Rated speed rpm : 480
guide sleeve
travel mm : 3.75
Tolerance mm : + 0.25

Rated speed rpm : 1330
guide sleeve
travel mm : 13.50
Tolerance mm : + 0.50

GUIDE SLEEVE POSITION

control lever
position degree : - 1
Rated speed rpm : 1180

Rack travel in mm : 12.50
Tolerance mm : + 2.70

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1050
Aneroid pressure
hPa : 1600

Del. quantity
cm³/1000 strokes : 295.0
Tolerance
cm³/1000 strokes : + 1.0

Check tolerance
cm³/1000S. : + 4.0

Spread
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 121.0
tolerance degree : + 4.0

RATED SPEED
rack travel mm : 11.65
Rated speed rpm : 1120
Tolerance 1/min : + 5

rack travel mm : 4.00
Rated speed rpm : 1210
Tolerance 1/min : + 15

rack travel mm : 0.50
Tolerance mm : + 0.50
Rated speed rpm : 1300

LOW IDLE

control lever
position degree : 71.0
tolerance degree : + 4.0

Testing:

Rated speed rpm : 350
rack travel mm : 4.50
Tolerance mm : ± 0.10

Rated speed rpm : 300

CRT mm min. : > 5.50

Rated speed rpm : 400

TORQUE CONTROL

Rated speed rpm : 1050
rack travel mm : 12.65
Tolerance mm : ± 0.05

Rated speed rpm : 500
rack travel mm : 10.00
Tolerance mm : ± 0.10

Rated speed rpm : 800
rack travel mm : 11.80
Tolerance mm : ± 0.10

Rated speed rpm : 950
rack travel mm : 12.20
Tolerance mm : ± 0.10

Rated speed rpm : 600
rack travel mm : 10.80
Tolerance mm : ± 0.20

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 1050
Pressure hPa : 1600
rack travel mm : 12.65
Tolerance mm : ± 0.05

Pressure hPa : -
Rated speed rpm : 1050
rack travel mm : 8.30
Tolerance mm : ± 0.20

MEASUREMENT

Rated speed rpm : 1050

Pressure hPa : 1050
rack travel mm : 11.80
Tolerance mm : ± 0.05

Pressure hPa : 700
rack travel mm : 9.50
Tolerance mm : ± 0.20

Start interlock

Rated speed rpm : > 100
Rated speed rpm : < 270

Check speed 1/min : > 80
Check speed 1/min : < 290

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure hPa : 1600
Rated speed rpm : 500
Del. quantity cm³/1000 strokes : 276.0
Tolerance cm³/1000 strokes : ± 3.0
Check tolerance cm³/1000S. : ± 6.0

Aneroid pressure hPa : 1600
Rated speed rpm : 800
Del. quantity cm³/1000 strokes : 299.0
Tolerance cm³/1000 strokes : ± 3.0
Check tolerance cm³/1000S. : ± 6.0

Aneroid pressure hPa : -
Rated speed rpm : 550
Del. quantity cm³/1000 strokes : 209.0
Tolerance cm³/1000 strokes : ± 1.0
Check tolerance cm³/1000S. : ± 4.0
Speed Tolerance cm³/1000 strokes : 8.0
Check tolerance cm³/1000S. : 12.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 9.20
Tolerance mm : ± 0.30

Del. quantity
cm³/1000 strokes : 140.0
Tolerance
cm³/1000 strokes : ± 15.0
Check tolerance
cm³/1000s. : ± 19.0

LOW IDLE

Rated speed rpm : 350
Del. quantity
cm³/1000 strokes : 15.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000s. : ± 6.0
Speed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000s. : 10.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 17.01.97
Test oil : ISO 4113

Combination No. : 0 402 648 785

Injection pump
Pump designation : PE8P120A320LS7844
EP type number : 0 412 628 860

Governor
Governor design. : RQV350...1050PA1318
Governor no. : 0 421 814 185

Cust. part No. : 0270746302

Customer-spec. information
Customer : MB-NFZ
Motor : OM442 LA
Power KW : 370.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 047

Inlet press. bar : 2.0
Tolerance bar : ± 0.1

Overflow quantity
min. L/h : 130
Tolerance L/h : ± 20.0

Test nozzle holde
assembly : 1 688 901 105

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 075

Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 5.05
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 20.50
Tolerance mm : ± 0.50

Firing order : 8-7-2-6-3
 : -4-1

Phasing : 0-45-90-135-180
 : -270-315
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50

Start of delivery mark

Tolerance : ± 0.10
Check
tolerance °NW : ± 0.75

Barrel no. : 8

BASIC SETTING

Rated speed rpm : 1050

Rack travel in mm : 15.30
Tolerance mm : ± 0.05

<hr/>	
Del. quantity	
cm ³ /1000 strokes :	272.0
<hr/>	
Tolerance	
cm ³ /1000 strokes :	+ 1.0
<hr/>	
Check tolerance	
cm ³ /1000S.	: + 4.0
<hr/>	
Spreed	
<hr/>	
Tolerance	
cm ³ /1000 strokes :	5.0
<hr/>	
Check tolerance	
cm ³ /1000S.	: 9.0
<hr/>	

Rated speed rpm :	350
<hr/>	
Rack travel in mm :	5.00
Tolerance mm :	+ 0.10
Del. quantity	
cm ³ /1000 strokes :	19.0
Tolerance	
cm ³ /1000 strokes :	+ 3.0
Check tolerance	
cm ³ /1000S.	: + 6.0
<hr/>	
Spreed	
<hr/>	
Tolerance	
cm ³ /1000 strokes :	6.0
Check tolerance	
cm ³ /1000S.	: 10.0

(B) SETTING OF INJECTION PUMP WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm :	1106
guide sleeve	
travel mm :	8.02
Tolerance mm :	+ 0.15
<hr/>	
Rated speed rpm :	350
guide sleeve	
travel mm :	1.48
Tolerance mm :	+ 0.20
<hr/>	
Rated speed rpm :	900
guide sleeve	
travel mm :	5.69
Tolerance mm :	+ 0.25
<hr/>	
Rated speed rpm :	580

guide sleeve	
travel mm :	3.62
Tolerance mm :	+ 0.25
<hr/>	
Rated speed rpm :	1204
guide sleeve	
travel mm :	10.00
Tolerance mm :	+ 0.25
<hr/>	
Rated speed rpm :	1300
guide sleeve	
travel mm :	11.50
Tolerance mm :	+ 0.50

GUIDE SLEEVE POSITION

control lever	
position degree :	- 1
Rated speed rpm :	1174
<hr/>	
Rack travel in mm :	11.00
Tolerance mm :	+ 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm :	1050
Aneroid pressure	
hFa :	1300
Del. quantity	
cm ³ /1000 strokes :	272.0
Tolerance	
cm ³ /1000 strokes :	+ 1.0
Check tolerance	
cm ³ /1000S.	: + 4.0
<hr/>	
Spreed	
<hr/>	
Tolerance	
cm ³ /1000 strokes :	5.0
Check tolerance	
cm ³ /1000S.	: 9.0

CONTROL LEVER

control lever	
position degree :	120.0
tolerance degree :	+ 4.0

RATED SPEED

rack travel mm :	14.30
Rated speed rpm :	1095
Tolerance 1/min :	+ 5
<hr/>	
rack travel mm :	4.00
Rated speed rpm :	1190
Tolerance 1/min :	+ 15

rack travel mm : 0.50
Tolerance mm : ± 0.50
Rated speed rpm : 1300

LOW IDLE

control lever
position degree : 64.0
tolerance degree : ± 4.0

Testing:

Rated speed rpm : 350
rack travel mm : 5.00
Tolerance mm : ± 0.10

Rated speed rpm : 250

CRT mm min. : > 7.00

Rated speed rpm : 450

TORQUE CONTROL

Rated speed rpm : 1050
rack travel mm : 15.30
Tolerance mm : ± 0.05

Rated speed rpm : 800
rack travel mm : 15.30
Tolerance mm : ± 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Pressure hPa : -
Rated speed rpm : 500

MEASUREMENT

Pressure hPa : 700
rack travel mm : 4.60
Tolerance mm : ± 0.20

Pressure hPa : 180
rack travel mm : 0.20
Tolerance mm : ± 0.05

Start interlock

Rated speed rpm : > 100

CO2

Rated speed rpm : < 270

Check
speed 1/min : > 80

Check
speed 1/min : < 290

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1800

Rated speed rpm : 800

Del. quantity
cm³/1000 strokes : 274.0

Tolerance
cm³/1000 strokes : ± 3.0

Check tolerance
cm³/1000S. : ± 6.0

Aneroid pressure

hPa : -

Rated speed rpm : 500

Del. quantity
cm³/1000 strokes : 130.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 4.0

STARTING FUEL DELIVERY

Rated speed rpm : 100

Del. quantity
cm³/1000 strokes : 270.0

Tolerance
cm³/1000 strokes : ± 10.0

Check tolerance
cm³/1000S. : ± 14.0

LOW IDLE

Rated speed rpm : 350

Del. quantity
cm³/1000 strokes : 19.0

Tolerance
cm³/1000 strokes : ± 3.0

Check tolerance
cm³/1000S. : ± 6.0

Speed

Tolerance
cm³/1000 strokes : 6.0

Check tolerance
cm³/1000S. : 10.0

End of test specification sheet



BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 21.01.97
Test oil : ISO 4113

Combination No. : 0 402 676 823

Injection pump
Pump designation : PE6P120A320LS7885-1
EP type number : 0 412 626 948

Governor
Governor design. : RSV400...1000F1A589
Governor no. : 0 421 833 449

Cust. part No. : 9277732

Customer-spec. information

Customer : LIEBHERR
Motor : D 9406 TI
Power KW : 255.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 047

Inlet press. bar : 1.5
Tolerance bar : ± 0.1

Overflow quantity
min. l/h : 125
Tolerance l/h : ± 20.0

Test nozzle holder
assembly : 1 688 901 105

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 075

Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 4.55
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 6- 3- 5- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50

BASIC SETTING

Rated speed rpm : 900

Rack travel in mm : 13.50
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 263.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : + 4.0

Speed

Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 400

Rack travel in mm : 4.90

Tolerance mm : + 0.10

Del. quantity
cm³/1000 strokes : 23.0

Tolerance
cm³/1000 strokes : + 3.0

Check tolerance
cm³/1000S. : + 6.0

Speed

Tolerance
cm³/1000 strokes : 6.0

Check tolerance
cm³/1000S. : 10.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : - 3

Rated speed rpm : 800

Rack travel in mm : 0.50

Tolerance mm : + 0.20

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 900

Aneroid pressure
hPa : 1500

Del. quantity
cm³/1000 strokes : 263.0

Tolerance
cm³/1000 strokes : + 1.0

Check tolerance
cm³/1000S. : + 4.0

Speed

Tolerance
cm³/1000 strokes : 5.0

C05

Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 105.0
tolerance degree : + 4.0

RATED SPEED

rack travel mm : 12.50
Rated speed rpm : 935
Tolerance 1/min : + 5

rack travel mm : 4.00
Rated speed rpm : 1005
Tolerance 1/min : + 15

rack travel mm : 0.85
Tolerance mm : + 0.55
Rated speed rpm : 1200

rack travel mm : 4.00
Rated speed rpm : 1015

LOW IDLE

control lever
position degree : 80.0
tolerance degree : + 4.0

Setting point w/out bumper spring

Rated speed rpm : 400
rack travel mm : 4.40
Tolerance mm : + 0.10

Testing:

Rated speed rpm : 400
rack travel mm : 4.90
Tolerance mm : + 0.10

rack travel mm : 2.00
Rated speed rpm : 515
Tolerance 1/min : + 30

TORQUE CONTROL

Rated speed rpm : 900
rack travel mm : 13.50
Tolerance mm : + 0.05

Rated speed rpm : 700
rack travel mm : 13.50
Tolerance mm : ± 0.10

Rated speed rpm : 500
rack travel mm : 13.50
Tolerance mm : ± 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1500
rack travel mm : 13.50
Tolerance mm : ± 0.10

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : 12.35
Tolerance mm : ± 0.20

MEASUREMENT

Rated speed rpm : 500

Pressure hPa : 1020
rack travel mm : 13.20
Tolerance mm : ± 0.05

Pressure hPa : 935
rack travel mm : 12.80
Tolerance mm : ± 0.10

Start interlock

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1500
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 267.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0

Aneroid pressure
hPa : 1500
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 276.0
Tolerance
cm³/1000 strokes : ± 3.0

Check tolerance
cm³/1000S. : ± 6.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 243.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0
Spread
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : ± 0.50
Del. quantity
cm³/1000 strokes : 220.0
Tolerance
cm³/1000 strokes : ± 15.0
Check tolerance
cm³/1000S. : ± 19.0

LOW IDLE

Rated speed rpm : 400
Del. quantity
cm³/1000 strokes : 23.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0
Spread
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 10.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 21.01.97
Test oil : ISO 4113
Combination No. : 0 402 676 823A
Injection pump
Pump designation : PE6P120A32OLS7885-1
EP type number : 0 412 626 948
Governor
Governor design. : RSV400...1000P1A589
Governor no. : 0 421 833 449
Cust. part No. : 9277732

Customer-spec. information
Customer : LIEBHERR
Motor : D 9406 TI
Power KW : 255.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1
Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 1 417 413 047
Inlet press. bar : 1.5
Tolerance bar : ± 0.1
Tolerance l/h : ± 10.0
Test nozzle holder
assembly : 1 688 901 105
Opening pressure
bar : 208.5
Tolerance bar : ± 1.5
Test lines : 1 680 750 075

C07

Outside diameter : 8.0
x inside diameter : 3.0
x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0
Prestroke mm : 4.55
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10
Rack travel in mm : 10.50
Tolerance mm : ± 1.50
Firing order : 1- 6- 3- 5- 2-
: 4
Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50

BASIC SETTING

Rated speed rpm : 950
Rack travel in mm : 15.90
Tolerance mm : ± 0.05
Del. quantity
cm³/1000 strokes : 270.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0

Spreed

Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 400

Rack travel in mm : 4.70
Tolerance mm : + 0.10

Del. quantity
cm³/1000 strokes : 23.0

Tolerance
cm³/1000 strokes : + 3.0

Check tolerance
cm³/1000S. : + 6.0

Spreed

Tolerance
cm³/1000 strokes : 6.0

Check tolerance
cm³/1000S. : 10.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : - 3
Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : + 0.20

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 950
Aneroid pressure
hPa : 1500

Del. quantity
cm³/1000 strokes : 270.0

Tolerance
cm³/1000 strokes : + 1.0

Check tolerance
cm³/1000S. : + 4.0

Spreed

Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

C08

CONTROL LEVER

control lever
position degree : 104.0
tolerance degree : + 4.0

RATED SPEED

rack travel mm : 14.90
Rated speed rpm : 980
Tolerance 1/min : + 5

rack travel mm : 4.00
Rated speed rpm : 1080
Tolerance 1/min : + 15

rack travel mm : 0.85
Tolerance mm : + 0.55
Rated speed rpm : 1200

rack travel mm : 4.00
Rated speed rpm : 1090

LOW IDLE

control lever
position degree : 78.0
tolerance degree : + 4.0

Setting point w/out bumper spring

Rated speed rpm : 400
rack travel mm : 3.40
Tolerance mm : + 0.10

Testing:

Rated speed rpm : 400
rack travel mm : 4.70
Tolerance mm : + 0.10

rack travel mm : 2.00
Rated speed rpm : 460
Tolerance 1/min : + 30

TORQUE CONTROL

Rated speed rpm : 950
rack travel mm : 15.90
Tolerance mm : + 0.05

Rated speed rpm : 500
rack travel mm : 15.90

Tolerance mm : ± 0.10
Rated speed rpm : 700
rack travel mm : 15.90
Tolerance mm : ± 0.30

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 550
Pressure hPa : 1500
rack travel mm : 15.90
Tolerance mm : ± 0.05

Pressure hPa : -
Rated speed rpm : 550
rack travel mm : 12.90
Tolerance mm : ± 0.10

MEASUREMENT

Rated speed rpm : 550
Pressure hPa : 1050
rack travel mm : 15.20
Tolerance mm : ± 0.05

Pressure hPa : 850
rack travel mm : 13.60
Tolerance mm : ± 0.10

Start interlock

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1500
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 281.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0

Aneroid pressure
hPa : 1500
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 277.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0

C09

Aneroid pressure
hPa : -
Rated speed rpm : 550
Del. quantity
cm³/1000 strokes : 227.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0
Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : ± 0.50
Del. quantity
cm³/1000 strokes : 160.0
Tolerance
cm³/1000 strokes : ± 10.0
Check tolerance
cm³/1000S. : ± 14.0

LOW IDLE

Rated speed rpm : 400
Del. quantity
cm³/1000 strokes : 23.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0
Speed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 10.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 21.01.97
Test oil : ISO 4113

Combination No. : 0 402 676 823B

Injection pump
Pump designation : PE6P120A320LS7885-1
EP type number : 0 412 626 948

Governor
Governor design. : RSV400...1000P1A589
Governor no. : 0 421 833 449

Cust. part No. : 9277732

Customer-spec. information
Customer : LIEBHERR
Motor : D 9406 TI-E A3
Power kW : 250.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 047

Inlet press. bar : 1.5
Tolerance bar : ± 0.1

Tolerance l/h : ± 10.0

Test nozzle holder
assembly : 1 688 901 105

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 075

C10

Outside diameter : 8.0
x inside diameter : 3.0
x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 4.55
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 6- 3- 5- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50

BASIC SETTING

Rated speed rpm : 900

Rack travel in mm : 15.50
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 263.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 4.0

Spread

 Tolerance
 cm³/1000 strokes : 5.0

 Check tolerance
 cm³/1000s. : 9.0

 Rated speed rpm : 400

 Rack travel in mm : 4.70
 Tolerance mm : ± 0.10
 Del. quantity
 cm³/1000 strokes : 23.0
 Tolerance
 cm³/1000 strokes : ± 3.0
 Check tolerance
 cm³/1000s. : ± 6.0
 Spread
 Tolerance
 cm³/1000 strokes : 6.0
 Check tolerance
 cm³/1000s. : 10.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
 position degree : - 3

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 900
 Aneroid pressure
 hPa : 1500
 Del. quantity
 cm³/1000 strokes : 263.0
 Tolerance
 cm³/1000 strokes : ± 1.0
 Check tolerance
 cm³/1000s. : ± 4.0
 Spread
 Tolerance
 cm³/1000 strokes : 5.0
 Check tolerance
 cm³/1000s. : 9.0

CONTROL LEVER

control lever
 position degree : 99.0
 tolerance degree : ± 4.0

RATED SPEED

rack travel mm : 14.50
 Rated speed rpm : 935
 Tolerance 1/min : ± 5

rack travel mm : 4.00
 Rated speed rpm : 1005
 Tolerance 1/min : ± 15

rack travel mm : 0.85
 Tolerance mm : ± 0.55
 Rated speed rpm : 1200

rack travel mm : 4.00
 Rated speed rpm : 1010

LOW IDLE

control lever
 position degree : 76.0
 tolerance degree : ± 4.0

Setting point w/out bumper spring

Rated speed rpm : 400
 rack travel mm : 3.40
 Tolerance mm : ± 0.10

Testing:

Rated speed rpm : 400
 rack travel mm : 4.70
 Tolerance mm : ± 0.10

TORQUE CONTROL

Rated speed rpm : 900
 rack travel mm : 15.50
 Tolerance mm : ± 0.05

Rated speed rpm : 500
 rack travel mm : 15.50
 Tolerance mm : ± 0.10

Rated speed rpm : 700
 rack travel mm : 15.50
 Tolerance mm : ± 0.30

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1500
rack travel mm : 15.50
Tolerance mm : + 0.05

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : 13.70
Tolerance mm : + 0.10

MEASUREMENT

Rated speed rpm : 500
Pressure hPa : 950
rack travel mm : 14.90
Tolerance mm : + 0.05

Pressure hPa : 840
rack travel mm : 13.90
Tolerance mm : + 0.10

Start interlock

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1500
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 275.0
Tolerance
cm³/1000 strokes : + 3.0
Check tolerance
cm³/1000S. : + 6.0

Aneroid pressure
hPa : 1500
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 269.0
Tolerance
cm³/1000 strokes : + 3.0
Check tolerance
cm³/1000S. : + 6.0

Aneroid pressure
hPa : -
Rated speed rpm : 500

Del. quantity
cm³/1000 strokes : 243.0
Tolerance
cm³/1000 strokes : + 1.0
Check tolerance
cm³/1000S. : + 4.0
Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : + 0.50
Del. quantity
cm³/1000 strokes : 160.0
Tolerance
cm³/1000 strokes : + 10.0
Check tolerance
cm³/1000S. : + 14.0

LOW IDLE

Rated speed rpm : 400
Del. quantity
cm³/1000 strokes : 23.0
Tolerance
cm³/1000 strokes : + 3.0
Check tolerance
cm³/1000S. : + 6.0
Speed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 10.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 21.01.97
Test oil : ISO 4113

Combination No. : 0 402 676 823C

Injection pump
Pump designation : PE6P120A320LS7885-1
EP type number : C 412 626 948

Governor
Governor design. : RSV400...1000P1A589
Governor no. : 0 421 833 449

Cust. part No. : 9277732

Customer-spec. information

Customer : LIEBHERR
Motor : D 9406 TI-E
Power KW : 255.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 047

Inlet press. bar : 1.5
Tolerance bar : ± 0.1

Tolerance l/h : ± 10.0

Test nozzle holde
assembly : 1 688 901 105

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test Lines : 1 680 750 075

Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 4.55
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 6- 3- 5- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50

BASIC SETTING

Rated speed rpm : 900

Rack travel in mm : 15.50
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 263.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 4.0

Spread

 Tolerance
 cm³/1000 strokes : 5.0

 Check tolerance
 cm³/1000S. : 9.0

 Rated speed rpm : 400

 Rack travel in mm : 4.70
 Tolerance mm : + 0.10
 Del. quantity
 cm³/1000 strokes : 23.0
 Tolerance
 cm³/1000 strokes : + 3.0
 Check tolerance
 cm³/1000S. : + 6.0
 Spread
 Tolerance
 cm³/1000 strokes : 6.0
 Check tolerance
 cm³/1000S. : 10.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
 position degree : - 3

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 500
 Aneroid pressure
 hPa : 1500
 Del. quantity
 cm³/1000 strokes : 263.0
 Tolerance
 cm³/1000 strokes : + 1.0
 Check tolerance
 cm³/1000S. : + 4.0
 Spread
 Tolerance
 cm³/1000 strokes : 5.0
 Check tolerance
 cm³/1000S. : 9.0

CONTROL LEVER

control lever
 position degree : 99.0
 tolerance degree : + 4.0

RATED SPEED

rack travel mm : 14.50
 Rated speed rpm : 935
 Tolerance 1/min : + 5

rack travel mm : 4.00
 Rated speed rpm : 1005
 Tolerance 1/min : + 15

rack travel mm : 0.85
 Tolerance mm : + 0.55
 Rated speed rpm : 1200

rack travel mm : 4.00
 Rated speed rpm : 1010

LOW IDLE

control lever
 position degree : 76.0
 tolerance degree : + 4.0

Setting point w/out bumper spring

Rated speed rpm : 400
 rack travel mm : 3.40
 Tolerance mm : + 0.10

Testing:

Rated speed rpm : 400
 rack travel mm : 4.70
 Tolerance mm : + 0.10

TORQUE CONTROL

Rated speed rpm : 900
 rack travel mm : 15.50
 Tolerance mm : + 0.05

Rated speed rpm : 500
 rack travel mm : 15.50
 Tolerance mm : + 0.10

Rated speed rpm : 700
 rack travel mm : 15.50
 Tolerance mm : + 0.30

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1500
rack travel mm : 15.50
Tolerance mm : ± 0.05

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : 13.70
Tolerance mm : ± 0.10

MEASUREMENT

Rated speed rpm : 500
Pressure hPa : 950
rack travel mm : 14.90
Tolerance mm : ± 0.05

Pressure hPa : 840
rack travel mm : 13.90
Tolerance mm : ± 0.10

Start interlock

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1500
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 275.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0

Aneroid pressure
hPa : 1500
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 269.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0

Aneroid pressure
hPa : -
Rated speed rpm : 500

Del. quantity
cm³/1000 strokes : 243.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : ± 0.50
Del. quantity
cm³/1000 strokes : 160.0
Tolerance
cm³/1000 strokes : ± 10.0
Check tolerance
cm³/1000S. : ± 14.0

LOW IDLE

Rated speed rpm : 400
Del. quantity
cm³/1000 strokes : 23.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0
Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 10.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 17.01.97
Test oil : ISO 4113

Combination No. : 0 402 676 836

Injection pump
Pump designation : PE6P120A320LS7898
EP type number : 0 412 626 957

Governor
Governor design. : RSV350...1050P0A668
Governor no. : 0 421 833 587

Cust. part No. : 0280740302

Customer-spec. information
Customer : MB-NFZ
Motor : OM441 A euromot
Power KW : 190.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 047

Inlet press. bar : 1.5
Tolerance bar : ± 0.1

Overflow quantity
min. l/h : 130
Tolerance l/h : ± 20.0

Test nozzle holder
assembly : 1 688 901 105

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 075

Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 5.25
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 20.50
Tolerance mm : ± 0.50

Firing order : 6- 3- 5- 2- 4-
: 1

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50

Start of delivery mark

Tolerance : ± 0.10
Check
tolerance °NW : ± 0.75

Barrel no. : 6

BASIC SETTING

Rated speed rpm : 1030

Rack travel in mm : 13.30
Tolerance mm : ± 0.05

<hr/>	
Del. quantity	
cm ³ /1000 strokes :	206.0
<hr/>	
Tolerance	
cm ³ /1000 strokes :	+ 1.0
<hr/>	
Check tolerance	
cm ³ /1000S. :	+ 4.0
<hr/>	
Spreed	
<hr/>	
Tolerance	
cm ³ /1000 strokes :	5.0
<hr/>	
Check tolerance	
cm ³ /1000S. :	9.0
<hr/>	

Rated speed rpm :	350
<hr/>	
Rack travel in mm :	5.40
Tolerance mm :	+ 0.10
Del. quantity	
cm ³ /1000 strokes :	19.0
Tolerance	
cm ³ /1000 strokes :	+ 3.0
Check tolerance	
cm ³ /1000S. :	+ 6.0
<hr/>	
Spreed	
Tolerance	
cm ³ /1000 strokes :	6.0
Check tolerance	
cm ³ /1000S. :	10.0

(B) SETTING OF INJECTION PUMP WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever	
position degree :	- 3
Rated speed rpm :	800
<hr/>	
Rack travel in mm :	0.50
Tolerance mm :	+ 0.20
<hr/>	
governor spring	
pre-tension	
click setting x :	4.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm :	1030
-------------------	------

Aneroid pressure	
hPa :	1000
Del. quantity	
cm ³ /1000 strokes :	206.0
Tolerance	
cm ³ /1000 strokes :	+ 1.0
Check tolerance	
cm ³ /1000S. :	+ 4.0
<hr/>	
Spreed	
Tolerance	
cm ³ /1000 strokes :	5.0
Check tolerance	
cm ³ /1000S. :	9.0

CONTROL LEVER

control lever	
position degree :	93.0

ASSEMBLY GOVERNOR SETTING

Rated speed rpm :	1070
rack travel mm :	12.30
<hr/>	
Rated speed rpm :	1152
Tolerance 1/min :	+ 4
rack travel mm :	4.00
<hr/>	
rack travel mm :	0.85
Tolerance mm :	+ 0.55
Rated speed rpm :	1300

Rated speed rpm :	1071
rack travel mm :	12.30

Rated speed rpm :	1153
Tolerance 1/min :	+ 4
rack travel mm :	4.00

rack travel mm :	0.85
Tolerance mm :	+ 0.55
Rated speed rpm :	1300

Rated speed rpm :	1072
rack travel mm :	12.30

Rated speed rpm :	1154
Tolerance 1/min :	+ 4
rack travel mm :	4.00

rack travel mm :	0.85
Tolerance mm :	+ 0.55
Rated speed rpm :	1300

Rated speed rpm : 1073
rack travel mm : 12.30

Rated speed rpm : 1155
Tolerance 1/min : ± 4
rack travel mm : 4.00

rack travel mm : 0.85
Tolerance mm : ± 0.55
Rated speed rpm : 1300

Rated speed rpm : 1074
rack travel mm : 12.30

Rated speed rpm : 1156
Tolerance 1/min : ± 4
rack travel mm : 4.00

rack travel mm : 0.85
Tolerance mm : ± 0.55
Rated speed rpm : 1300

Rated speed rpm : 1075
rack travel mm : 12.30

Rated speed rpm : 1157
Tolerance 1/min : ± 4
rack travel mm : 4.00

rack travel mm : 0.85
Tolerance mm : ± 0.55
Rated speed rpm : 1300

LOW IDLE

control lever
position degree : 71.0

Testing:

Rated speed rpm : 350
rack travel mm : 5.40
Tolerance mm : ± 0.10

rack travel mm : 2.00
Rated speed rpm : 415

SET IDLE AUXILIARY SPRING

rack travel mm : 2.00

TORQUE CONTROL

Rated speed rpm : 1030
rack travel mm : 13.30

Tolerance mm : ± 0.05

Rated speed rpm : 800
rack travel mm : 13.30
Tolerance mm : ± 0.10

Rated speed rpm : 400
rack travel mm : 12.05
Tolerance mm : ± 0.15

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 400
Pressure hPa : 1000
rack travel mm : 13.30
Tolerance mm : ± 0.05

Pressure hPa : -
Rated speed rpm : 400
rack travel mm : 10.40
Tolerance mm : ± 0.15

MEASUREMENT

Rated speed rpm : 400

Pressure hPa : 500
rack travel mm : 12.05
Tolerance mm : ± 0.15

Pressure hPa : 350
rack travel mm : 10.80
Tolerance mm : ± 0.15

Start interlock

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1000
Rated speed rpm : 800
Del. quantity
cm³/1000 strokes : 207.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0
Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

Aneroid pressure
hPa : 500
Rated speed rpm : 400
Del. quantity
cm³/1000 strokes : 154.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 135.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 200.0
Tolerance
cm³/1000 strokes : ± 10.0
Check tolerance
cm³/1000S. : ± 14.0

LOW IDLE

Rated speed rpm : 350
Del. quantity
cm³/1000 strokes : 19.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0
Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 10.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 22.01.97
Test oil : ISO 4113

Combination No. : 0 402 698 033F1

Injection pump
Pump designation : PE8H120/320LS3-2
EP type number :

Governor
Governor design. : RE36 (FD 57102 - FD : 57108)
Governor no. :

Cust. part No. : 0250745602

Customer-spec. information
Customer : MB-NFZ
Motor : OM 442 LA

TEST BENCH REQUIREMENTS

Inlet line : 3.2 ELAB

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 032

Inlet press. bar : 3.5
Tolerance bar : ± 0.1

Test nozzle holder
assembly : 1 688 901 105

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 089

Outside diameter : 8.0

C20

x inside diameter : 3.0
x length mm : 600

REMARKS

Pump-specific values
in Section (B)
must be observed!

(A) INJECTION PUMP SETTINGS
No basic setting.
Setting of constant delivery
under Section C.

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 7.00
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 0.50

Firing order : 8-7-2-6-3
 : -4-1

Phasing : 0-45-90-135-180
 : -270-315
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Start of delivery mark
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Barrel no. : 8

(B) POSITIONER TESTING
Warm-up time: 3 minutes at
n=600 min⁻¹, Uact = 2.5 V

TESTING & SETTING RACK TRAVEL SENSOR POSITION

Engine speed min-1: 0

Setting point
(P, R and H pump)

Uact V : 3.100
 CRT mm : 13.00
 Tolerance mm : +/- 0.05
 Check tolerance mm : +/- 0.10

Check value
(P, R and H pump)

Uact V : 1.700
 CRT mm : 6.15
 Tolerance mm : +/- 0.25
 Check tolerance mm : +/- 0.30

Setting point
(M pump)

Uact V : 3.100
 CRT mm : 12.50
 Tolerance mm : +/- 0.05
 Check tolerance mm : +/- 0.10

Check value
(M pump)

Uact V : 1.700
 CRT mm : 5.50
 Tolerance mm : +/- 0.25
 Check tolerance mm : +/- 0.30

Stop position

Uact V : Value with
 deenergised adjusting magnet
 and control rod in
 stop position.

CRT mm : 0.75
 Tolerance mm : +/- 0.25
 Check tolerance mm : +/- 0.35

ENGINE-SPEED SENSOR
(All P and R pumps not
H and M pumps)

C21

Test with control rod
in stop position

Engine speed min-1: 60
 Amplitude V : 1.4
 Tolerance V : +/- 0.6
 Check tolerance V : +/- 1.20

Engine speed min-1: 600
 Difference
 Amplitude to
 Amplitude V : max.1.4

(C) INJECTION PUMP WITH POSITIONER

TEST POINT V1

Rated speed rpm : 750
 Uact V : 2.800
 Prestroke solenoid
 Stroke mm : 7.40
 Del. quantity
 cm³/1000 strokes : 347.0
 Tolerance
 cm³/1000 strokes : +/- 1.0
 Check tolerance
 cm³/1000S. : +/- 4.0
 Spreed
 Tolerance
 cm³/1000 strokes : 5.0
 Check tolerance
 cm³/1000S. : 9.0

FUEL DELIVERY CHARACTERISTICS

Rated speed rpm : 950
 Uact V : 2.900
 Prestroke solenoid
 Stroke mm : 8.00
 Del. quantity
 cm³/1000 strokes : 334.0
 Tolerance
 cm³/1000 strokes : +/- 4.0
 Check tolerance
 cm³/1000S. : +/- 8.0

Rated speed rpm : 550
 Uact V : 2.700
 Prestroke solenoid
 Stroke mm : 9.50
 Del. quantity
 cm³/1000 strokes : 354.0
 Tolerance
 cm³/1000 strokes : +/- 4.0
 Check tolerance
 cm³/1000S. : +/- 8.0

TEST POINT L1

Rated speed rpm : 300
Uact V : 1.500
Tolerance Volt : \pm 0.060
Check tolerance
Volt : \pm 0.060
Prestroke solenoid
Stroke mm : 8.00
Del. quantity
cm³/1000 strokes : 37.0
Tolerance
cm³/1000 strokes : \pm 3.0
Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 9.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
Uact V : 1.900
Prestroke solenoid
Stroke mm : 10.00
Del. quantity
cm³/1000 strokes : 114.0
Tolerance
cm³/1000 strokes : \pm 10.0
Check tolerance
cm³/1000S. : \pm 20.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 22.01.97
Test oil : ISO 4113
Combination No. : 0 402 698 033F2
Injection pump
Pump designation : PE8H120/320LS3-2
EP type number :
Governor
Governor design. : RE36 (FD 57109 - FD
: 66213)
Governor no. :
Cust. part No. : 0250745602

Customer-spec. information
Customer : MB-NFZ
Motor : OM 442 LA

TEST BENCH REQUIREMENTS

Inlet line : 3.2 ELAE
Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 2 417 413 082
Inlet press. bar : 3.5
Tolerance bar : ± 0.1
Test nozzle holder
assembly : 1 688 901 105
Opening pressure
bar : 208.5
Tolerance bar : ± 1.5
Test lines : 1 680 750 089
Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 600

REMARKS

Pump-specific values
in Section (B)
must be observed!

(A) INJECTION PUMP SETTINGS
No basic setting.
Setting of constant delivery
under Section C.

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 7.00
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 0.50

Firing order : 8- 7- 2- 6- 3
: - 4- 1

Phasing : 0-45-90-135-180
: -270-315
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Start of delivery mark

Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Barrel no. : 8

(B) POSITIONER TESTING

Warm-up time: 3 minutes at
n=600 min⁻¹, Uact = 2.5 V

TESTING & SETTING RACK TRAVEL SENSOR POSITION

Engine speed min-1: 0

Setting point
(P, R and H pump)

Uact V : 3.100
 CRT mm : 13.00
 Tolerance mm : +/- 0.05
 Check tolerance mm : +/- 0.10

Check value
(P, R and H pump)

Uact V : 1.700
 CRT mm : 6.15
 Tolerance mm : +/- 0.25
 Check tolerance mm : +/- 0.30

Setting point
(M pump)

Uact V : 3.100
 CRT mm : 12.50
 Tolerance mm : +/- 0.05
 Check tolerance mm : +/- 0.10

Check value
(M pump)

Uact V : 1.700
 CRT mm : 5.50
 Tolerance mm : +/- 0.25
 Check tolerance mm : +/- 0.30

Stop position

Uact V : Value with
 deenergised adjusting magnet
 and control rod in
 stop position.

CRT mm : 0.75
 Tolerance mm : +/- 0.25
 Check tolerance mm : +/- 0.35

ENGINE-SPEED SENSOR
(All P and R pumps not
 H and M pumps)

Test with control rod
 in stop position

Engine speed min-1: 60
 Amplitude V : 1.4
 Tolerance V : +/- 0.6
 Check tolerance V : +/- 1.20

Engine speed min-1: 600
 Difference
 Amplitude to
 Amplitude V : max.1.4

(C) INJECTION PUMP WITH POSITIONER

TEST POINT V1

Rated speed rpm : 750
 Uact V : 2.800
 Prestroke solenoid
 Stroke mm : 7.40
 Del. quantity
 cm³/1000 strokes : 350.0
 Tolerance
 cm³/1000 strokes : +/- 1.0
 Check tolerance
 cm³/1000S. : +/- 4.0
 Spreed
 Tolerance
 cm³/1000 strokes : 5.0
 Check tolerance
 cm³/1000S. : 9.0

FUEL DELIVERY CHARACTERISTICS

Rated speed rpm : 950
 Uact V : 2.900
 Prestroke solenoid
 Stroke mm : 8.00
 Del. quantity
 cm³/1000 strokes : 336.0
 Tolerance
 cm³/1000 strokes : +/- 4.0
 Check tolerance
 cm³/1000S. : +/- 8.0

Rated speed rpm : 550
 Uact V : 2.700
 Prestroke solenoid
 Stroke mm : 9.50
 Del. quantity
 cm³/1000 strokes : 357.0
 Tolerance
 cm³/1000 strokes : +/- 4.0
 Check tolerance
 cm³/1000S. : +/- 8.0

TEST POINT L1

Rated speed rpm : 300
Uact V : 1.500
Tolerance Volt : ± 0.060
Check tolerance
Volt : ± 0.060
Prestroke solenoid
Stroke mm : 8.00
Del. quantity
cm³/1000 strokes : 40.0
Tolerance
cm³/1000 strokes : ± 3.0
Speed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 9.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
Uact V : 1.900
Prestroke solenoid
Stroke mm : 10.00
Del. quantity
cm³/1000 strokes : 117.0
Tolerance
cm³/1000 strokes : ± 10.0
Check tolerance
cm³/1000S. : ± 20.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 22.01.97
Test oil : ISO 4113
Combination No. : 0 402 698 033F3
Injection pump
Pump designation : PE8H120/320LS3-2
EP type number :
Governor
Governor design. : RE36 (FD 66214 - FD
: 66231)
Governor no. :
Cust. part No. : 0250745602

Customer-spec. information
Customer : MB-NFZ
Motor : OM 442 LA

TEST BENCH REQUIREMENTS

Inlet line : 3.2 ELAB
Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 2 417 413 082
Inlet press. bar : 3.5
Tolerance bar : ± 0.1
Test nozzle holder
assembly : 1 688 901 105
Opening pressure
bar : 208.5
Tolerance bar : ± 1.5
Test lines : 1 680 750 089
Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 600

REMARKS

Pump-specific values
in Section (B)
must be observed!

(A) INJECTION PUMP SETTINGS
No basic setting.
Setting of constant delivery
under Section C.

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0
Prestroke mm : 7.00
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10
Rack travel in mm : 10.50
Tolerance mm : ± 0.50
Firing order : 8- 7- 2- 6- 3
: - 4- 1
Phasing : 0-45-90-135-180
: -270-315
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75
Start of delivery mark
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75
Barrel no. : 8

(B) POSITIONER TESTING
Warm-up time: 3 minutes at
n=600 min⁻¹, Uact = 2.5 V

TESTING & SETTING RACK TRAVEL SENSOR POSITION

Engine speed min-1: 0

Setting point
(P, R and H pump)

Uact V : 3.100
CRT mm : 13.00
Tolerance mm : +/- 0.05
Check tolerance mm : +/- 0.10

Check value
(P, R and H pump)

Uact V : 1.700
CRT mm : 6.15
Tolerance mm : +/- 0.25
Check tolerance mm : +/- 0.30

Setting point
(M pump)

Uact V : 3.100
CRT mm : 12.50
Tolerance mm : +/- 0.05
Check tolerance mm : +/- 0.10

Check value
(M pump)

Uact V : 1.700
CRT mm : 5.50
Tolerance mm : +/- 0.25
Check tolerance mm : +/- 0.30

Stop position

Uact V : Value with
deenergised adjusting magnet
and control rod in
stop position.

CRT mm : 0.75
Tolerance mm : +/- 0.25
Check tolerance mm : +/- 0.35

ENGINE-SPEED SENSOR
(All P and R pumps not
H and M pumps)

Test with control rod
in stop position

Engine speed min-1: 60
Amplitude V : 1.4
Tolerance V : +/- 0.6
Check tolerance V : +/- 1.20

Engine speed min-1: 600
Difference
Amplitude to
Amplitude V : max.1.4

(C) INJECTION PUMP WITH POSITIONER

TEST POINT V1

Rated speed rpm : 750
Uact V : 2.800
Prestroke solenoid
Stroke mm : 7.40
Del. quantity
cm3/1000 strokes : 344.0
Tolerance
cm3/1000 strokes : +/- 1.0
Check tolerance
cm3/1000S. : +/- 4.0
Spreed
Tolerance
cm3/1000 strokes : 5.0
Check tolerance
cm3/1000S. : 9.0

FUEL DELIVERY CHARACTERISTICS

Rated speed rpm : 950
Uact V : 2.900
Prestroke solenoid
Stroke mm : 8.00
Del. quantity
cm3/1000 strokes : 331.0
Tolerance
cm3/1000 strokes : +/- 4.0
Check tolerance
cm3/1000S. : +/- 8.0

Rated speed rpm : 550
Uact V : 2.700
Prestroke solenoid
Stroke mm : 9.50
Del. quantity
cm3/1000 strokes : 351.0
Tolerance
cm3/1000 strokes : +/- 4.0
Check tolerance
cm3/1000S. : +/- 8.0

TEST POINT 1.1

Rated speed rpm : 300
Uact V : 1.500
Tolerance Volt : +- 0.060
Check tolerance
Volt : +- 0.060
Prestroke solenoid
Stroke mm : 8.00
Del. quantity
cm³/1000 strokes : 34.0
Tolerance
cm³/1000 strokes : +- 3.0
Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 9.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
Uact V : 1.900
Prestroke solenoid
Stroke mm : 10.00
Del. quantity
cm³/1000 strokes : 111.0
Tolerance
cm³/1000 strokes : +- 10.0
Check tolerance
cm³/1000S. : +- 20.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 17.01.97
Test oil : ISO 4113

Combination No. : 0 402 698 804

Injection pump
Pump designation : PE8P120A720LS7205
EP type number : 0 412 628 895

Governor
Governor design. : RE30
Governor no. : 0 421 890 007

Cust. part No. : 1328039

Customer-spec. information
Customer : SCANIA
Motor : DSC1409,DSC1416

TEST BENCH REQUIREMENTS

Inlet line : 4.1

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 025

Inlet press. bar : 2.5
Tolerance bar : ± 0.1

Test nozzle holder
assembly : 1 688 901 104

Opening pressure
bar : 251.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 008

Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

Pump-specific values
in Section (B)
must be observed!

(A) INJECTION PUMP SETTINGS
No basic setting.
Setting of constant delivery
under Section C.

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 5.05
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 2- 7- 3- 4
 : - 6- 8

Phasing : 0-45-90-135-180
 : -270-315

Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Start of delivery mark

Tolerance : ± 0.10
Check
tolerance °NW : ± 0.75

Barrel no. : 1

Vibration
damper
(RoBo diaphragm) : 3.2

(B) POSITIONER TESTING

Warm-up time: 3 minutes at
n=600 min⁻¹, Uact = 2.5 V

TESTING & SETTING RACK TRAVEL SENSOR
POSITION

Engine speed min⁻¹: 0

Setting point
(P, R and H pump)

Uact V : 3.100
CRT mm : 13.00
Tolerance mm : +/- 0.05
Check
tolerance mm : +/- 0.10

Check value
(P, R and H pump)

Uact V : 1.700
CRT mm : 6.15
Tolerance mm : +/- 0.25
Check
tolerance mm : +/- 0.30

Setting point
(M pump)

Uact V : 3.100
CRT mm : 12.50
Tolerance mm : +/- 0.05
Check
tolerance mm : +/- 0.10

Check value
(M pump)

Uact V : 1.700
CRT mm : 5.50
Tolerance mm : +/- 0.25
Check
tolerance mm : +/- 0.30

Stop position

Uact V : Value with
deenergised adjusting magnet
and control rod in
stop position.

CRT mm : 0.75
Tolerance mm : +/- 0.25
Check
tolerance mm : +/- 0.35

ENGINE-SPEED SENSOR
(ALL P and R pumps not
H and M pumps)

Test with control rod
in stop position

Engine speed min⁻¹: 60
Amplitude V : 1.4
Tolerance V : +/- 0.6
Check
tolerance V : +/- 1.20

Engine speed min⁻¹: 600
Difference
Amplitude to
Amplitude V : max.1.4

(C) INJECTION PUMP WITH POSITIONER

TEST POINT V1

Rated speed rpm : 700
Uact V : 3.000
Del. quantity
cm³/1000 strokes : 248.0
Tolerance
cm³/1000 strokes : +/- 1.0
Check tolerance
cm³/1000S. : +/- 4.0
Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

FUEL DELIVERY CHARACTERISTICS

Rated speed rpm : 950
Uact V : 3.000
Del. quantity
cm³/1000 strokes : 224.0
Tolerance
cm³/1000 strokes : +/- 4.0
Check tolerance
cm³/1000S. : +/- 6.0

TEST POINT L1

Rated speed rpm : 250
Uact V : 1.410
Tolerance Volt : +/- 0.060
Check tolerance
Volt : +/- 0.060
Del. quantity
cm³/1000 strokes : 16.0

Tolerance
cm³/1000 strokes : ± 3.0
Speed
Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 8.0

End of test specification sheet



BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 21.01.97
Test oil : ISO 4113
Combination No. : 0 402 746 606C
Injection pump
Pump designation : PES6P110A72ORS7406
EP type number : 0 412 716 810
Governor
Governor design. : RQV300...1050PA1090
: 1K
Governor no. : 0 421 815 497
Cust. part No. : 9279607

Customer-spec. information
Customer : LIEBHERR
Motor : D 926 TI-E
Power kW : 230.0

TEST BENCH REQUIREMENTS

Inlet line : 4.1
Test oil inlet temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 1 417 413 025
Inlet press. bar : 1.5
Tolerance bar : ± 0.1
Overflow quantity min. l/h : 125
Tolerance l/h : ± 20.0
Test nozzle holder assembly : 1 688 901 101
Opening pressure bar : 208.5
Tolerance bar : ± 1.5

D04

Test lines : 1 680 750 008
Outside diameter : 6.0
x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0
Prestroke mm : 3.65
Tolerance mm : ± 0.05
Check tolerance mm : ± 0.10
Rack travel in mm : 10.50
Tolerance mm : ± 1.50
Firing order : 1- 5- 3- 6- 2-
: 4
Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check tolerance *NW : ± 0.50

BASIC SETTING

Rated speed rpm : 900
Rack travel in mm : 13.85
Tolerance mm : ± 0.05
Del. quantity cm³/1000 strokes : 212.0
Tolerance cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : + 4.0

Spreed

Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 500

Rack travel in mm : 5.30
Tolerance mm : + 0.10

Del. quantity
cm³/1000 strokes : 30.0

Tolerance
cm³/1000 strokes : + 3.0

Check tolerance
cm³/1000S. : + 6.0

Spreed
Tolerance
cm³/1000 strokes : 6.0

Check tolerance
cm³/1000S. : 10.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 1102
guide sleeve
travel mm : 10.05
Tolerance mm : + 0.15

Rated speed rpm : 350
guide sleeve
travel mm : 1.86
Tolerance mm : + 0.20

Rated speed rpm : 749
guide sleeve
travel mm : 6.11
Tolerance mm : + 0.25

Rated speed rpm : 480
guide sleeve
travel mm : 3.75
Tolerance mm : + 0.25

Rated speed rpm : 1330
guide sleeve
travel mm : 13.50
Tolerance mm : + 0.50

D05

GUIDE SLEEVE POSITION

control lever
position degree : - 1
Rated speed rpm : 1179

Rack travel in mm : 12.80
Tolerance mm : + 2.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 900
Aneroid pressure
hPa : 1400

Del. quantity
cm³/1000 strokes : 212.0

Tolerance
cm³/1000 strokes : + 1.0

Check tolerance
cm³/1000S. : + 4.0

Spreed
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 113.0
tolerance degree : + 4.0

RATED SPEED
rack travel mm : 12.85
Rated speed rpm : 935
Tolerance 1/min : + 5

rack travel mm : 4.00
Rated speed rpm : 1085
Tolerance 1/min : + 15

rack travel mm : 0.50
Rated speed rpm : 1145
Tolerance 1/min : + 0.50

LOW IDLE

control lever
position degree : 85.0
tolerance degree : + 4.0

Testing:

Rated speed rpm : 500
rack travel mm : 5.30
Tolerance mm : ± 0.10

Rated speed rpm : 350

CRT mm min. : > 8.50

TORQUE CONTROL

Rated speed rpm : 900
rack travel mm : 13.85
Tolerance mm : ± 0.05

Rated speed rpm : 500
rack travel mm : 13.00
Tolerance mm : ± 0.15

Rated speed rpm : 800
rack travel mm : 13.80
Tolerance mm : ± 0.15

Rated speed rpm : 700
rack travel mm : 13.85
Tolerance mm : ± 0.15

Rated speed rpm : 600
rack travel mm : 13.50
Tolerance mm : ± 0.15

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 1050
Pressure hPa : 1400
rack travel mm : 13.85
Tolerance mm : ± 0.05

Pressure hPa : -
Rated speed rpm : 1050
rack travel mm : 12.30
Tolerance mm : ± 0.15

MEASUREMENT

Rated speed rpm : 1050

Pressure hPa : 1050
rack travel mm : 13.30
Tolerance mm : ± 0.05

Pressure hPa : 910

rack travel mm : 12.75
Tolerance mm : ± 0.10

Start interlock

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1400
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 250.0
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 6.0

Aneroid pressure
hPa : 1400
Rated speed rpm : 800
Del. quantity
cm³/1000 strokes : 225.0
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 6.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 228.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 10.55
Tolerance mm : ± 0.20
Del. quantity
cm³/1000 strokes : 195.0
Tolerance
cm³/1000 strokes : ± 10.0
Check tolerance
cm³/1000S. : ± 14.0

LOW IDLE

Rated speed rpm : 500

Del. quantity
cm³/1000 strokes : 30.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0
Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 10.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 17.01.97
Test oil : ISO 4113

Combination No. : 0 402 746 627

Injection pump
Pump designation : PES6P120A720LS7262
EP type number : 0 412 726 918

Governor
Governor design. : RQV350...925PA1331
Governor no. : 0 421 814 190

Cust. part No. : 0240746202

Customer-spec. information
Customer : MTU
Motor : 6R183-02

TEST BENCH REQUIREMENTS

Inlet line : 4.1

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 047

Inlet press. bar : 1.5
Tolerance bar : ± 0.1

Overflow quantity
min. l/h : 110
Tolerance l/h : ± 20.0

Test nozzle holder
assembly : 1 688 901 019

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 075

Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 4.02
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 20.50
Tolerance mm : ± 0.50

Firing order : 6- 2- 4- 1- 5-
: 3

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50

Start of delivery mark

Tolerance : ± 0.10
Check
tolerance °NW : ± 0.75

Barrel no. : 6

BASIC SETTING

Rated speed rpm : 925

Rack travel in mm : 12.30
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 261.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 4.0

Spread

Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 350

Rack travel in mm : 5.30

Tolerance mm : ± 0.10

Del. quantity
cm³/1000 strokes : 21.0

Tolerance
cm³/1000 strokes : ± 3.0

Check tolerance
cm³/1000S. : ± 6.0

Spread

Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 988
guide sleeve

travel mm : 8.65

Tolerance mm : ± 0.15

Rated speed rpm : 350

guide sleeve

travel mm : 1.48

Tolerance mm : ± 0.20

Rated speed rpm : 485

guide sleeve

travel mm : 3.02

Tolerance mm : ± 0.25

Rated speed rpm : 1160

guide sleeve

travel mm : 11.50

Tolerance mm : ± 0.50

GUIDE SLEEVE POSITION

control lever

position degree : - 1

Rated speed rpm : 1055

Rack travel in mm : 11.30

Tolerance mm : ± 2.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 925

Aneroid pressure

hPa : 1200

Del. quantity

cm³/1000 strokes : 261.0

Tolerance

cm³/1000 strokes : ± 1.0

Check tolerance

cm³/1000S. : ± 4.0

Spread

Tolerance

cm³/1000 strokes : 5.0

Check tolerance

cm³/1000S. : 9.0

CONTROL LEVER

control lever

position degree : 118.0

tolerance degree : ± 4.0

RATED SPEED

rack travel mm : 11.30

Rated speed rpm : 975

Tolerance 1/min : ± 5

rack travel mm : 4.00

Rated speed rpm : 1055

Tolerance 1/min : ± 15

rack travel mm : 0.50

Tolerance mm : ± 0.50

Rated speed rpm : 1250

LOW IDLE

control lever

position degree : 65.0

tolerance degree : + 4.0

Testing:

Rated speed rpm : 350
rack travel mm : 5.30
Tolerance mm : +- 0.10

Rated speed rpm : 250
CRT mm min. : > 7.50

Rated speed rpm : 450

TORQUE CONTROL

Rated speed rpm : 925
rack travel mm : 12.30
Tolerance mm : + 0.05

Rated speed rpm : 750
rack travel mm : 12.30
Tolerance mm : + 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 600
Pressure hPa : 1200
rack travel mm : 12.30
Tolerance mm : + 0.05

Pressure hPa : -
Rated speed rpm : 600
rack travel mm : 8.05
Tolerance mm : + 0.15

MEASUREMENT

Rated speed rpm : 600
Pressure hPa : 300
rack travel mm : 8.90
Tolerance mm : + 0.05

Pressure hPa : 800
rack travel mm : 11.65
Tolerance mm : + 0.15

Start interlock

Rated speed rpm : > 100
Rated speed rpm : < 270

Check speed 1/min : > 80
Check speed 1/min : < 290

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure hPa : 1200
Rated speed rpm : 750
Del. quantity cm³/1000 strokes : 257.0
Tolerance cm³/1000 strokes : +- 2.0
Check tolerance cm³/1000S. : +- 5.0
Speed Tolerance cm³/1000 strokes : 10.0
Check tolerance cm³/1000S. : 14.0

Aneroid pressure hPa : -
Rated speed rpm : 500
Del. quantity cm³/1000 strokes : 132.5
Tolerance cm³/1000 strokes : +- 1.0
Check tolerance cm³/1000S. : +- 4.0
Speed Tolerance cm³/1000 strokes : 10.0
Check tolerance cm³/1000S. : 14.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 16.50
Tolerance mm : +- 0.20
Del. quantity cm³/1000 strokes : 390.0
Tolerance cm³/1000 strokes : +- 18.0
Check tolerance cm³/1000S. : +- 24.0

LOW IDLE

Rated speed rpm : 350
Del. quantity cm³/1000 strokes : 21.0

Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 22.01.97
Test oil : ISO 4113

Combination No. : 0 402 746 996

Injection pump
Pump designation : PES6P120A720LS7262
EP type number : 0 412 726 918

Governor
Governor design. : RQV350...1050PA1040
Governor no. : 0 421 814 007

Cust. part No. : 0250746002

Customer-spec. information

Customer : MTJ
Motor : 6R183-02
Power KW : 370.0

TEST BENCH REQUIREMENTS

Inlet line : 4.1

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 047

Inlet press. bar : 1.5
Tolerance bar : ± 0.1

Overflow quantity
min. l/h : 100
Tolerance l/h : ± 20.0

Test nozzle holder
assembly : 1 688 901 019

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 075

Outside diameter : 8.0

x inside diameter : 3.0

x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 4.05
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 20.50
Tolerance mm : ± 0.50

Firing order : 6- 2- 4- 1- 5-
: 3

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50

Start of delivery mark

Tolerance : ± 0.10
Check
tolerance °NW : ± 0.50

Barrel no. : 6

BASIC SETTING

Rated speed rpm : 1050

Rack travel in mm : 13.95
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 331.0

Tolerance
cm³/1000 strokes : + 1.0

Check tolerance
cm³/1000S. : + 4.0

Speed

Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 350

Rack travel in mm : 4.90
Tolerance mm : + 0.10

Del. quantity
cm³/1000 strokes : 20.0

Tolerance
cm³/1000 strokes : + 3.0

Check tolerance
cm³/1000S. : + 6.0

Speed

Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 1107
guide sleeve
travel mm : 8.03
Tolerance mm : + 0.20

Rated speed rpm : 350
guide sleeve
travel mm : 1.53
Tolerance mm : + 0.15

Rated speed rpm : 900
guide sleeve
travel mm : 5.69
Tolerance mm : + 0.25

Rated speed rpm : 404
guide sleeve
travel mm : 2.50

Tolerance mm : + 0.25

Rated speed rpm : 454
guide sleeve
travel mm : 3.08
Tolerance mm : + 0.25

Rated speed rpm : 570
guide sleeve
travel mm : 3.57
Tolerance mm : + 0.25

Rated speed rpm : 1204
guide sleeve
travel mm : 10.00
Tolerance mm : + 0.25

Rated speed rpm : 1300
guide sleeve
travel mm : 11.50
Tolerance mm : + 0.50

GUIDE SLEEVE POSITION

control lever
position degree : - 1
Rated speed rpm : 1170

Rack travel in mm : 13.00
Tolerance mm : + 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1050
Aneroid pressure
hPa : 1600

Del. quantity
cm³/1000 strokes : 331.0

Tolerance
cm³/1000 strokes : + 1.0

Check tolerance
cm³/1000S. : + 4.0

Speed

Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 118.0
tolerance degree : + 4.0

RATED SPEED

rack travel mm : 13.00
 Rated speed rpm : 1095
 Tolerance 1/min : + 5

 rack travel mm : 4.00
 Rated speed rpm : 1180
 Tolerance 1/min : + 15

 rack travel mm : 0.50
 Tolerance mm : + 0.50
 Rated speed rpm : 1250

LOW IDLE

control lever
 position degree : 64.0
 tolerance degree : + 4.0

Testing:

Rated speed rpm : 350
 rack travel mm : 4.90
 Tolerance mm : + 0.10

Rated speed rpm : 250

CRT mm min. : > 7.20

Rated speed rpm : 450

TORQUE CONTROL

Rated speed rpm : 1050
 rack travel mm : 13.95
 Tolerance mm : + 0.05

Rated speed rpm : 750
 rack travel mm : 13.95
 Tolerance mm : + 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
 Pressure hPa : 1600
 rack travel mm : 13.95
 Tolerance mm : + 0.10

Pressure hPa : -
 Rated speed rpm : 500
 rack travel mm : 7.60

Tolerance mm : + 0.20

MEASUREMENT

Rated speed rpm : 500

Pressure hPa : 1200
 rack travel mm : 13.65
 Tolerance mm : + 0.05

Pressure hPa : 400
 rack travel mm : 9.35
 Tolerance mm : + 0.15

Start interlock

Rated speed rpm : > 230
 Rated speed rpm : < 290

Check
 speed 1/min : > 210
 Check
 speed 1/min : < 310

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
 hPa : 1600
 Rated speed rpm : 750
 Del. quantity
 cm³/1000 strokes : 335.0
 Tolerance
 cm³/1000 strokes : + 3.0
 Check tolerance
 cm³/1000S. : + 6.0

Speed
 Tolerance
 cm³/1000 strokes : 3.0
 Check tolerance
 cm³/1000S. : 12.0

Aneroid pressure
 hPa : -
 Rated speed rpm : 500
 Del. quantity
 cm³/1000 strokes : 132.0
 Tolerance
 cm³/1000 strokes : + 1.0
 Check tolerance
 cm³/1000S. : + 4.0

Speed
 Tolerance
 cm³/1000 strokes : 8.0
 Check tolerance
 cm³/1000S. : 12.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 400.0
Tolerance
cm³/1000 strokes : ± 15.0
Check tolerance
cm³/1000S. : ± 19.0

LOW IDLE

Rated speed rpm : 350
Del. quantity
cm³/1000 strokes : 20.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 24.04.96
Test oil : ISO 4113

Combination No. : 0 403 446 249

Injection pump
Pump designation : PES6MW100/72ORS1197
EP type number : 0 413 406 185

Governor
Governor design. : RQV325...1350MW109K
Governor no. : 0 420 083 997

Cust. part No. :

Customer-spec. information
Customer : IVECO-FIAT
Motor : 8060.45.6000
Power KW : 169.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 457 413 010

Inlet press. bar : 1.5

Test nozzle holder
assembly : 1 688 901 101

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 014

Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 31.0
Tolerance bar : ± 1.0

Prestroke mm : 4.05
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

BASIC SETTING

Rated speed rpm : 1350

Rack travel in mm : 14.05
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 102.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 3.0

Speed

Tolerance
 cm3/1000 strokes : 3.5

Check tolerance
 cm3/1000S. : 6.0

Rated speed rpm : 330

Rack travel in mm : 8.20
 Tolerance mm : + 0.10

Del. quantity
 cm3/1000 strokes : 27.0
 Tolerance
 cm3/1000 strokes : + 2.0
 Check tolerance
 cm3/1000S. : + 4.5

Speed
 Tolerance
 cm3/1000 strokes : 3.5
 Check tolerance
 cm3/1000S. : 5.5

(B) SETTING OF INJECTION PUMP
 WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 1411
 guide sleeve
 travel mm : 10.31
 Tolerance mm : + 0.25

Rated speed rpm : 325
 guide sleeve
 travel mm : 1.90
 Tolerance mm : + 0.25

Rated speed rpm : 832
 guide sleeve
 travel mm : 5.05
 Tolerance mm : + 0.25

Rated speed rpm : 346
 guide sleeve
 travel mm : 2.27
 Tolerance mm : + 0.25

Rated speed rpm : 396
 guide sleeve
 travel mm : 3.13
 Tolerance mm : + 0.25

Rated speed rpm : 380
 guide sleeve
 travel mm : 3.01
 Tolerance mm : + 0.25

Rated speed rpm : 1640
 guide sleeve
 travel mm : 13.50
 Tolerance mm : + 0.50

GUIDE SLEEVE POSITION

control lever
 position degree : - 1
 Rated speed rpm : 1475

Rack travel in mm : 13.00
 Tolerance mm : + 2.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1350
 Aneroid pressure
 hPa : 850
 Del. quantity
 cm3/1000 strokes : 102.0
 Tolerance
 cm3/1000 strokes : + 1.0
 Check tolerance
 cm3/1000S. : + 3.0

Speed
 Tolerance
 cm3/1000 strokes : 3.5
 Check tolerance
 cm3/1000S. : 6.0

CONTROL LEVER

control lever
 position degree : 120.0
 tolerance degree : + 4.0

RATED SPEED

rack travel mm : 13.00
 Rated speed rpm : 1440
 Tolerance 1/min : + 5

rack travel mm : 4.00
 Rated speed rpm : 1550
 Tolerance 1/min : + 15

rack travel mm : 0.50
 Tolerance mm : + 0.50
 Rated speed rpm : 1650

LOW IDLE

control lever
 position degree : 82.0
 tolerance degree : ± 4.0

Testing:

Rated speed rpm : 330
 rack travel mm : 8.20
 Tolerance mm : ± 0.10

Rated speed rpm : 200

CRF mm min. : > 10.00

TORQUE CONTROL

Rated speed rpm : 1350
 rack travel mm : 14.05
 Tolerance mm : ± 0.05

Rated speed rpm : 1200
 rack travel mm : 13.70
 Tolerance mm : ± 0.10

Rated speed rpm : 1000
 rack travel mm : 13.35
 Tolerance mm : ± 0.15

Rated speed rpm : 700
 rack travel mm : 13.40
 Tolerance mm : ± 0.10

ANEROID/ALTITUDE
 COMPENSATOR TEST

SETTING

Rated speed rpm : 500
 Pressure hPa : 850
 rack travel mm : 13.50
 Tolerance mm : ± 0.10

Pressure hPa : -
 Rated speed rpm : 500
 rack travel mm : 11.40
 Tolerance mm : ± 0.05

MEASUREMENT

Rated speed rpm : 500

Pressure hPa : 550
 rack travel mm : 13.45
 Tolerance mm : ± 0.15

Pressure hPa : 350
 rack travel mm : 12.35
 Tolerance mm : ± 0.05

Start interlock

Rated speed rpm : > 265

Check
 speed 1/min : > 275

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
 hPa : 850
 Rated speed rpm : 1200
 Del. quantity
 cm³/1000 strokes : 102.0
 Tolerance
 cm³/1000 strokes : ± 1.5
 Check tolerance
 cm³/1000S. : ± 4.0

Speed
 Tolerance
 cm³/1000 strokes : 5.0
 Check tolerance
 cm³/1000S. : 7.0

Aneroid pressure
 hPa : 850
 Rated speed rpm : 1000
 Del. quantity
 cm³/1000 strokes : 102.0
 Tolerance
 cm³/1000 strokes : ± 1.5
 Check tolerance
 cm³/1000S. : ± 4.0

Aneroid pressure
 hPa : 850
 Rated speed rpm : 700
 Del. quantity
 cm³/1000 strokes : 106.0
 Tolerance
 cm³/1000 strokes : ± 1.5
 Check tolerance
 cm³/1000S. : ± 4.0

Aneroid pressure
 hPa : -
 Rated speed rpm : 500
 Del. quantity
 cm³/1000 strokes : 76.5
 Tolerance
 cm³/1000 strokes : ± 1.0
 Check tolerance
 cm³/1000S. : ± 3.0

STARTING FUEL DELIVERY

Rated speed rpm : 100

WARM-START DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 65.0
Tolerance
cm³/1000 strokes : +- 10.0
Check tolerance
cm³/1000S. : +- 13.0

COLD-START DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 105.0
Tolerance
cm³/1000 strokes : +- 8.0
Check tolerance
cm³/1000S. : +- 10.0

LOW IDLE

Rated speed rpm : 330
Del. quantity
cm³/1000 strokes : 27.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 4.5
Speed
Tolerance
cm³/1000 strokes : 3.5
Check tolerance
cm³/1000S. : 5.5

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 27.01.97
Test oil : ISO 4113

Combination No. : 0 400 464 119

Injection pump
Pump designation : PES4A75D410/3RS1255
EP type number : 0 410 474 966

Governor
Governor design. : RSV325...1400A80495L
Governor no. : 0 420 232 302

Cust. part No. :

Customer-spec. information
Customer : KHD
Motor : F4L912

TEST BENCH REQUIREMENTS

Inlet line : 1.3

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 419 992 198

Inlet press. bar : 1.5

Test nozzle holder
assembly : 0 681 343 009

Opening pressure
bar : 173.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 014

Outside diameter : 6.0

x inside diameter : 2.0

D20

x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 1.95
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 3- 4- 2

Phasing : 0-90-180-270
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

BASIC SETTING

Rated speed rpm : 1400

Rack travel in mm : 10.20
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 44.0

Tolerance
cm³/1000 strokes : ± 1.5

Check tolerance
cm³/1000S. : ± 3.0

Speed

Tolerance
cm³/1000 strokes : 3.5

Check tolerance
cm³/1000S. : 7.0

Rated speed rpm : 325

Rack travel in mm : 9.00

Tolerance mm : ± 0.10

Del. quantity
cm³/1000 strokes : 11.0

Tolerance
cm³/1000 strokes : ± 1.5

Check tolerance
cm³/1000S. : ± 3.5

Spread
Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 6.0

(B) SETTING OF INJECTION PUMP WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : - 3
Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : ± 0.20

governor spring
pre-tension
click setting x : 5.50

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1400

Aneroid pressure
hPa : -

Del. quantity
cm³/1000 strokes : 44.0

Tolerance
cm³/1000 strokes : ± 1.5

Check tolerance
cm³/1000S. : ± 3.0

Spread
Tolerance
cm³/1000 strokes : 3.5

Check tolerance
cm³/1000S. : 7.0

CONTROL LEVER

control lever
position degree : 119.0
tolerance degree : ± 4.0

RATED SPEED
rack travel mm : 9.20
Rated speed rpm : 1445
Tolerance 1/min : ± 5

rack travel mm : 4.00
Rated speed rpm : 1485
Tolerance 1/min : ± 15

rack travel mm : 0.85
Tolerance mm : ± 0.55
Rated speed rpm : 1700

rack travel mm : 4.00
Rated speed rpm : 1495

LOW IDLE

control lever
position degree : 70.0
tolerance degree : ± 4.0

Setting point w/out bumper spring

Rated speed rpm : 325
rack travel mm : 8.50
Tolerance mm : ± 0.10

Testing:

Rated speed rpm : 325
rack travel mm : 9.00
Tolerance mm : ± 0.10

rack travel mm : 2.00
Rated speed rpm : 700
Tolerance 1/min : ± 30

TORQUE CONTROL

Rated speed rpm : 1400
rack travel mm : 10.20
Tolerance mm : ± 0.05

Rated speed rpm : 500
rack travel mm : 11.55
Tolerance mm : ± 0.05

Rated speed rpm : 955
rack travel mm : 10.90
Tolerance mm : \pm 0.10

Start interlock

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.25
Tolerance mm : \pm 0.75
Del. quantity
cm³/1000 strokes : 110.0
Tolerance
cm³/1000 strokes : \pm 7.5
Check tolerance
cm³/1000S. : \pm 10.0

LOW IDLE

Rated speed rpm : 325
Del. quantity
cm³/1000 strokes : 11.0
Tolerance
cm³/1000 strokes : \pm 1.5
Check tolerance
cm³/1000S. : \pm 3.5
Speed
Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 6.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 27.01.97
Test oil : ISO 4113

Combination No. : 0 400 836 018

Injection pump
Pump designation : PES6A80D410/3RS2527
EP type number : 0 410 886 059

Governor
Governor design. : RQ275/1400AB798DL
Governor no. : 0 420 202 239

Cust. part No. :

Customer-spec. information
Customer : KHD
Motor : F6L912
Power KW : 88.3

TEST BENCH REQUIREMENTS

Inlet line : 3.1

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 419 992 198

Inlet press. bar : 1.5

Test nozzle holder
assembly : 0 681 343 009

Opening pressure
bar : 173.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 014

Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 1.95
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

BASIC SETTING

Rated speed rpm : 1400

Rack travel in mm : 11.65
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 65.5

Tolerance
cm³/1000 strokes : ± 1.5

Check tolerance
cm³/1000s. : ± 3.0

Speed

Tolerance
 cm³/1000 strokes : 3.5

Check tolerance
 cm³/1000S. : 7.0

Rated speed rpm : 275

Rack travel in mm : 8.70
 Tolerance mm : + 0.05

Del. quantity
 cm³/1000 strokes : 12.0
 Tolerance
 cm³/1000 strokes : + 1.5
 Check tolerance
 cm³/1000S. : + 3.5

Spreed
 Tolerance
 cm³/1000 strokes : 4.0
 Check tolerance
 cm³/1000S. : 6.0

(B) SETTING OF INJECTION PUMP
 WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Dimension a mm : 0.65

GUIDE SLEEVE POSITION

control lever
 position degree : - 1
 Rated speed rpm : 650

Rack travel in mm : 16.00
 Tolerance mm : + 0.40

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1400
 Aneroid pressure
 hPa : -

Del. quantity
 cm³/1000 strokes : 65.5
 Tolerance
 cm³/1000 strokes : + 1.5
 Check tolerance
 cm³/1000S. : + 3.0

Spreed
 Tolerance
 cm³/1000 strokes : 3.5

Check tolerance
 cm³/1000S. : 7.0

RATED SPEED
 rack travel mm : 10.60
 Rated speed rpm : 1453
 Tolerance 1/min : + 8

rack travel mm : 4.00
 Rated speed rpm : 1550
 Tolerance 1/min : + 15

rack travel mm : 9.50
 Tolerance mm : + 0.50
 Rated speed rpm : 1650

LOW IDLE

Testing:

Rated speed rpm : 275
 rack travel mm : 8.70
 Tolerance mm : + 0.05

rack travel mm : 2.00
 Rated speed rpm : 450
 Tolerance 1/min : + 20

Rated speed rpm : 100

CRT mm min. : > 7.00

Rated speed rpm : 600

CRT mm max. : < 1.00

TORQUE CONTROL

Rated speed rpm : 1400
 rack travel mm : 11.65
 Tolerance mm : + 0.05

Rated speed rpm : 650
 rack travel mm : 13.10
 Tolerance mm : + 0.10

Rated speed rpm : 810
 rack travel mm : 12.70
 Tolerance mm : + 0.10

Rated speed rpm : 1015
 rack travel mm : 12.05
 Tolerance mm : + 0.15

Start interlock

STARTING FUEL DELIVERY

Rated speed rpm : 1000
rack travel mm : 17.70
Tolerance mm : \pm 0.30
Del. quantity
cm³/1000 strokes : 100.0
Tolerance
cm³/1000 strokes : \pm 7.5
Check tolerance
cm³/1000S. : \pm 10.0

LOW IDLE

Rated speed rpm : 275
Del. quantity
cm³/1000 strokes : 12.0
Tolerance
cm³/1000 strokes : \pm 1.5
Check tolerance
cm³/1000S. : \pm 3.5
Spread
Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 6.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 25.01.97
Test oil : ISO 4113
Combination No. : 0 400 865 017
Injection pump
Pump designation : PES5A80D410/3RS2526
EP type number : 0 410 885 004
Governor
Governor design. : RSV325...1400A8C540L
Governor no. : 0 420 232 311

Cust. part No. :

Customer-spec. information
Customer : KHD
Motor : F5L912
Power kW : 62.5

TEST BENCH REQUIREMENTS

Inlet line : 3.1
Test oil inlet temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 1 419 992 198
Inlet press. bar : 1.5
Test nozzle holder assembly : 0 681 343 009
Opening pressure bar : 173.5
Tolerance bar : ± 1.5
Test lines : 1 680 750 014
Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0
Prestroke mm : 1.95
Tolerance mm : ± 0.05
Check tolerance mm : ± 0.10
Rack travel in mm : 10.50
Tolerance mm : ± 1.50
Firing order : 1- 3- 5- 4- 2
Phasing : 0-72-144-216-288
Tolerance : ± 0.50
Check tolerance °NW : ± 0.75

BASIC SETTING

Rated speed rpm : 1380
Rack travel in mm : 11.55
Tolerance mm : ± 0.05
Del. quantity cm³/1000 strokes : 65.5
Tolerance cm³/1000 strokes : ± 0.5
Check tolerance cm³/1000S. : ± 2.0
Speed
Tolerance cm³/1000 strokes : 2.0

Check tolerance
cm³/1000S. : 3.5

Rated speed rpm : 325

Rack travel in mm : 7.60

Tolerance mm : ± 0.10

Del. quantity

cm³/1000 strokes : 9.0

Tolerance

cm³/1000 strokes : ± 3.0

Check tolerance

cm³/1000S. : ± 4.5

Spread

Tolerance

cm³/1000 strokes : 2.0

Check tolerance

cm³/1000S. : 3.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever

position degree : - 3

Rated speed rpm : 800

Rack travel in mm : 0.65

Tolerance mm : ± 0.35

governor spring

pre-tension

click setting x : 5.50

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1380

Aneroid pressure

hPa : -

Del. quantity

cm³/1000 strokes : 65.5

Tolerance

cm³/1000 strokes : ± 0.5

Check tolerance

cm³/1000S. : ± 2.0

Spread

Tolerance

cm³/1000 strokes : 2.0

Check tolerance

cm³/1000S. : 3.5

CONTROL LEVER

control lever

position degree : 116.0

tolerance degree : ± 4.0

RATED SPEED

rack travel mm : 10.50

Rated speed rpm : 1425

Tolerance 1/min : ± 5

rack travel mm : 4.00

Rated speed rpm : 1470

Tolerance 1/min : ± 15

rack travel mm : 1.00

Tolerance mm : ± 0.70

Rated speed rpm : 1650

rack travel mm : 4.00

Rated speed rpm : 1520

LOW IDLE

control lever

position degree : 69.0

tolerance degree : ± 4.0

Setting point w/out bumper spring

Rated speed rpm : 325

rack travel mm : 8.10

Tolerance mm : ± 0.10

Testing:

Rated speed rpm : 325

rack travel mm : 7.60

Tolerance mm : ± 0.10

rack travel mm : 2.00

Rated speed rpm : 655

Tolerance 1/min : ± 30

TORQUE CONTROL

Rated speed rpm : 1380

rack travel mm : 11.55

Tolerance mm : ± 0.05

Rated speed rpm : 500

rack travel mm : 12.75

Tolerance mm : ± 0.05

Rated speed rpm : 900
rack travel mm : 12.25
Tolerance mm : ± 0.15

Start interlock

LOW IDLE

Rated speed rpm : 325
Del. quantity
cm³/1000 strokes : 9.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 4.5
Speed
Tolerance
cm³/1000 strokes : 2.0
Check tolerance
cm³/1000S. : 3.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 25.01.97
Test oil : ISO 4113

Combination No. : 0 400 866 092

Injection pump
Pump designation : PES6A80D410/3RS2527
EP type number : 0 410 886 059

Governor
Governor design. : RSV325...1400A8C540L
Governor no. : 0 420 232 311

Cust. part No. :

Customer-spec. information
Customer : KHD

TEST BENCH REQUIREMENTS

Inlet line : 1.3

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 419 992 198

Inlet press. bar : 1.5

Test nozzle holde
assembly : 0 681 343 009

Opening pressure
bar : 173.5
Tolerance bar : ± 1.5

Test Lines : 1 680 750 014

Outside diameter : 6.0
x inside diameter : 2.0
x length mm : 600

E01

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 1.95
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.50
Check
tolerance *NW : ± 0.75

BASIC SETTING

Rated speed rpm : 1380

Rack travel in mm : 11.50
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 65.5

Tolerance
cm³/1000 strokes : ± 0.5

Check tolerance
cm³/1000S. : ± 2.0

Spread

Tolerance
cm³/1000 strokes : 2.5

Check tolerance
cm³/1000S. : 4.0

Rated speed rpm : 325
Rack travel in mm : 8.50
Tolerance mm : ± 0.10
Del. quantity
cm³/1000 strokes : 10.0
Tolerance
cm³/1000 strokes : ± 1.5
Check tolerance
cm³/1000S. : ± 3.5
Speed
Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 6.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : - 3
Rated speed rpm : 800
Rack travel in mm : 0.50
Tolerance mm : ± 0.20
governor spring
pre-tension
click setting x : 4.80

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1380
Aneroid pressure
hPa : -
Del. quantity
cm³/1000 strokes : 65.5
Tolerance
cm³/1000 strokes : ± 0.5
Check tolerance
cm³/1000S. : ± 2.0
Speed
Tolerance
cm³/1000 strokes : 2.5
Check tolerance
cm³/1000S. : 4.0

CONTROL LEVER

control lever
position degree : 117.0
tolerance degree : ± 4.0

RATED SPEED

rack travel mm : 10.50
Rated speed rpm : 1425
Tolerance 1/min : ± 5

rack travel mm : 4.00
Rated speed rpm : 1460
Tolerance 1/min : ± 15

rack travel mm : 0.85
Tolerance mm : ± 0.55
Rated speed rpm : 1680

rack travel mm : 4.00
Rated speed rpm : 1525

LOW IDLE

control lever
position degree : 71.0
tolerance degree : ± 4.0

Setting point w/out bumper spring

Rated speed rpm : 325
rack travel mm : 8.00
Tolerance mm : ± 0.10

Testing:

Rated speed rpm : 325
rack travel mm : 8.50
Tolerance mm : ± 0.10

rack travel mm : 2.00
Rated speed rpm : 670
Tolerance 1/min : ± 30

TORQUE CONTROL

Rated speed rpm : 1380
rack travel mm : 11.50
Tolerance mm : ± 0.05

Rated speed rpm : 900
rack travel mm : 12.25
Tolerance mm : ± 0.15

Rated speed rpm : 400
rack travel mm : 12.75
Tolerance mm : ± 0.05

Start interlock

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.25
Tolerance mm : ± 0.75
Del. quantity
cm³/1000 strokes : 120.0
Tolerance
cm³/1000 strokes : ± 7.5
Check tolerance
cm³/1000S. : ± 10.0

LOW IDLE

Rated speed rpm : 325
Del. quantity
cm³/1000 strokes : 10.0
Tolerance
cm³/1000 strokes : ± 1.5
Check tolerance
cm³/1000S. : ± 3.5
Speed
Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 6.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 17.01.97
Test oil : ISO 4113
Combination No. : 0 400 266 143AA

Injection pump
Pump designation :
EP type number :

Governor
Governor design. :
Governor no. :

Cust. part No. : 32719459

Customer-spec. information
Customer : CUMMINS
Motor : 6BT-145PS/2600

TEST BENCH REQUIREMENTS

Inlet line : 3.1
Test oil inlet temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 1 419 992 198
Inlet press. bar : 1.5
Test nozzle holder assembly : 1 688 901 101
Opening pressure bar : 208.5
Tolerance bar : ± 1.5
Test lines : 1 680 750 014
Outside diameter : 6.0
x inside diameter : 2.0

E04

x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 2.15
Tolerance mm : ± 0.05
Check tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.50
Check tolerance *NW : ± 0.75

Start of delivery blocking

*NW after s.o.d. : 11.50

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1300

Rack travel in mm : 8.10
Tolerance mm : ± 0.05

Del. quantity cm³/1000 strokes : 76.0

Tolerance cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : +- 3.5

Speed

Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 6.5

Rated speed rpm : 350

Rack travel in mm : 6.00
Tolerance mm : +- 0.10

Del. quantity
cm³/1000 strokes : 13.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 4.5

Speed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 8.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : FREE
Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : +- 0.20

governor spring
pre-tension
click setting x : 4.25

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1300
Aneroid pressure
hPa : -
Del. quantity
cm³/1000 strokes : 76.0
Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 3.5

Speed
Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 6.5

CONTROL LEVER

control lever
position degree : 99.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 7.10
Rated speed rpm : 1345
Tolerance 1/min : +- 5

rack travel mm : 4.00
Rated speed rpm : 1415
Tolerance 1/min : +- 15

rack travel mm : 0.85
Tolerance mm : +- 0.55
Rated speed rpm : 1570

rack travel mm : 4.00
Rated speed rpm : 1420

LOW IDLE

control lever
position degree : 80.0
tolerance degree : +- 4.0

Setting point w/out bumper spring

Rated speed rpm : 350
rack travel mm : 5.50
Tolerance mm : +- 0.10

Testing:

Rated speed rpm : 350
rack travel mm : 6.00
Tolerance mm : +- 0.10

rack travel mm : 2.00
Rated speed rpm : 555
Tolerance 1/min : +- 30

TORQUE CONTROL

Rated speed rpm : 1300
rack travel mm : 8.10
Tolerance mm : \pm 0.05

Rated speed rpm : 500
rack travel mm : 8.55
Tolerance mm : \pm 0.05

Start interlock

End of test specification sheet

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : --
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 57.5
Tolerance
cm³/1000 strokes : \pm 1.5
Check tolerance
cm³/1000S. : \pm 3.5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 13.10
Tolerance mm : \pm 0.10
Del. quantity
cm³/1000 strokes : 105.0
Tolerance
cm³/1000 strokes : \pm 5.0
Check tolerance
cm³/1000S. : \pm 7.5

LOW IDLE

Rated speed rpm : 350
Del. quantity
cm³/1000 strokes : 13.0
Tolerance
cm³/1000 strokes : \pm 2.0
Check tolerance
cm³/1000S. : \pm 4.5
Spread
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 8.0

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 20.01.97
Test oil : ISO 4113
Combination No. : 0 400 866 188AA

Injection pump
Pump designation :
EP type number :

Governor
Governor design. :
Governor no. :

Cust. part No. : 3921160

Customer-spec. information

Customer : CDC
Motor : 6 CT/207Ps/1800

TEST BENCH REQUIREMENTS

Inlet line : 2.0

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 419 992 198

Inlet press. bar : 1.5

Test nozzle holder
assembly : 1 688 901 101

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 014

Outside diameter : 6.0

x inside diameter : 2.0

E07

x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 28.0
Tolerance bar : ± 1.0

Prestroke mm : 2.85
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Start of delivery mark

*NW after s.o.d. : 10.00

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 830

Rack travel in mm : 13.45
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 139.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : + 3.5

Spreed

Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 6.5

Rated speed rpm : 425

Rack travel in mm : 5.20
Tolerance mm : + 0.10

Del. quantity
cm³/1000 strokes : 11.5
Tolerance
cm³/1000 strokes : + 2.0

Check tolerance
cm³/1000S. : + 4.5

Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 8.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : FREE
Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : + 0.20

governor spring
pre-tension
click setting x : 4.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 830
Aneroid pressure
hPa : -
Del. quantity
cm³/1000 strokes : 139.0
Tolerance
cm³/1000 strokes : + 1.0

Check tolerance
cm³/1000S. : + 3.5

Spreed
Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 6.5

CONTROL LEVER

control lever
position degree : 102.0
tolerance degree : + 4.0

RATED SPEED

rack travel mm : 12.40
Rated speed rpm : 930
Tolerance 1/min : + 5

rack travel mm : 4.00
Rated speed rpm : 970
Tolerance 1/min : + 15

rack travel mm : 0.85
Tolerance mm : + 0.55
Rated speed rpm : 1100

rack travel mm : 4.00
Rated speed rpm : 975

LOW IDLE

control lever
position degree : 76.0
tolerance degree : + 4.0

Setting point w/out bumper spring

Rated speed rpm : 425
rack travel mm : 4.70
Tolerance mm : + 0.10

Testing:

Rated speed rpm : 425
rack travel mm : 5.20
Tolerance mm : + 0.10

rack travel mm : 2.00
Rated speed rpm : 460
Tolerance 1/min : + 30

TORQUE CONTROL

Rated speed rpm : 830
rack travel mm : 13.45
Tolerance mm : ± 0.05

Start interlock

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : ± 1.00
Del. quantity
cm³/1000 strokes : 143.0
Tolerance
cm³/1000 strokes : ± 10.0
Check tolerance
cm³/1000S. : ± 13.0

LOW IDLE

Rated speed rpm : 425
Del. quantity
cm³/1000 strokes : 11.5
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 4.5
Speed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 8.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 20.01.97
Test oil : ISO 4113
Combination No. : 0 400 866 197AA

Injection pump
Pump designation :
EP type number :

Governor
Governor design. :
Governor no. :

Cust. part No. : 3921120

Customer-spec. information
Customer : CDC
Motor : 6 CT/180Ps/2200

TEST BENCH REQUIREMENTS

Inlet line : 2.

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 419 992 198

Inlet press. bar : 1.5

Test nozzle holder
assembly : 1 688 901 101

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 014

Outside diameter : 6.0

x inside diameter : 2.0

E10

x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 28.0
Tolerance bar : ± 1.0

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-50-120-180-240
Tolerance : ± 0.50
Check
tolerance *NW : ± 0.75

BASIC SETTING

Rated speed rpm : 1100

Rack travel in mm : 11.25
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 104.5

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 3.5

Speed
Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 6.5

Rated speed rpm : 450

Rack travel in mm : 5.80
Tolerance mm : ± 0.10

Del. quantity
 cm³/1000 strokes : 18.0
 Tolerance
 cm³/1000 strokes : ± 2.0
 Check tolerance
 cm³/1000S. : ± 4.5
 Spreed
 Tolerance
 cm³/1000 strokes : 6.0
 Check tolerance
 cm³/1000S. : 8.0

(B) SETTING OF INJECTION PUMP
 WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
 position degree : FREE
 Rated speed rpm : 800
 Rack travel in mm : 0.50
 Tolerance mm : ± 0.20
 governor spring
 pre-tension
 click setting x : 4.75

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1100
 Aneroid pressure
 hPa : 900
 Del. quantity
 cm³/1000 strokes : 104.5
 Tolerance
 cm³/1000 strokes : ± 1.0
 Check tolerance
 cm³/1000S. : ± 3.5
 Spreed
 Tolerance
 cm³/1000 strokes : 4.0
 Check tolerance
 cm³/1000S. : 6.5

CONTROL LEVER

control lever
 position degree : 53.0
 tolerance degree : ± 4.0

RATED SPEED

rack travel mm : 10.20

Rated speed rpm : 1145
 Tolerance 1/min : ± 5
 rack travel mm : 4.00
 Rated speed rpm : 1235
 Tolerance 1/min : ± 15
 rack travel mm : 0.85
 Tolerance mm : ± 0.55
 Rated speed rpm : 1390
 rack travel mm : 4.00
 Rated speed rpm : 1240

LOW IDLE

control lever
 position degree : 33.0
 tolerance degree : ± 4.0

Setting point w/out bumper spring

Rated speed rpm : 450
 rack travel mm : 5.30
 Tolerance mm : ± 0.10

Testing:

Rated speed rpm : 450
 rack travel mm : 5.80
 Tolerance mm : ± 0.10

rack travel mm : 2.00
 Rated speed rpm : 570
 Tolerance 1/min : ± 30

TORQUE CONTROL

Rated speed rpm : 1100
 rack travel mm : 11.25
 Tolerance mm : ± 0.05

Rated speed rpm : 750
 rack travel mm : 12.10
 Tolerance mm : ± 0.10

Rated speed rpm : 1100
 rack travel mm : 10.25
 Tolerance mm : ± 0.05

ANEROID/ALTITUDE
 COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 900
rack travel mm : 12.10
Tolerance mm : \pm 0.10

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : 10.45
Tolerance mm : \pm 0.10

MEASUREMENT

Rated speed rpm : 500
Pressure hPa : 425
rack travel mm : 11.70
Tolerance mm : \pm 0.20

Pressure hPa : 305
rack travel mm : 11.15
Tolerance mm : \pm 0.05

Start interlock

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 900
Rated speed rpm : 750
Del. quantity
cm³/1000 strokes : 114.5
Tolerance
cm³/1000 strokes : \pm 2.0
Check tolerance
cm³/1000S. : \pm 4.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 81.0
Tolerance
cm³/1000 strokes : \pm 1.0
Check tolerance
cm³/1000S. : \pm 3.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : \pm 1.00
Del. quantity
cm³/1000 strokes : 145.0

Tolerance
cm³/1000 strokes : \pm 10.0
Check tolerance
cm³/1000S. : \pm 13.0

LOW IDLE

Rated speed rpm : 450
Del. quantity
cm³/1000 strokes : 18.0
Tolerance
cm³/1000 strokes : \pm 2.0
Check tolerance
cm³/1000S. : \pm 4.5
Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 8.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 21.01.97
Test oil : ISO 4113
Combination No. : 0 400 866 197AB

Injection pump
Pump designation :
EP type number :

Governor
Governor design. :
Governor no. :

Cust. part No. : 3915996

Customer-spec. information
Customer : CDC
Motor : 6 CT/202Ps/220G

TEST BENCH REQUIREMENTS

Inlet line : 2.

Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0

Overflow valve : 1 419 992 198

Inlet press. bar : 1.5

Test nozzle holde
assembly : 1 688 901 017

Opening pressure
bar : 208.5
Tolerance bar : +- 1.5

Test lines : 1 680 750 014

Outside diameter : 6.0

x inside diameter : 2.0

E13

x Length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 28.0
Tolerance bar : +- 1.0

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : +- 0.50
Check
tolerance *NW : +- 0.75

Start of delivery mark

*NW after s.o.d. : 11.00

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1100

Rack travel in mm : 12.15
Tolerance mm : +- 0.05

Del. quantity
cm³/1000 strokes : 119.5

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 3.5

Spread

Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 6.5

Rated speed rpm : 450

Rack travel in mm : 5.50
Tolerance mm : + 0.10

Del. quantity
cm³/1000 strokes : 18.0
Tolerance
cm³/1000 strokes : + 2.0
Check tolerance
cm³/1000S. : + 4.5

Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 8.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : FREE
Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : + 0.20

governor spring
pre-tension
click setting x : 2.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1100
Aneroid pressure
hPa : 900

Del. quantity
cm³/1000 strokes : 119.5
Tolerance
cm³/1000 strokes : + 1.0
Check tolerance
cm³/1000S. : + 3.5

Spreed
Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 6.5

CONTROL LEVER

control lever
position degree : 46.0
tolerance degree : + 4.0

RATED SPEED
rack travel mm : 11.10
Rated speed rpm : 1145
Tolerance 1/min : + 5

rack travel mm : 4.00
Rated speed rpm : 1200
Tolerance 1/min : + 15

rack travel mm : 0.85
Tolerance mm : + 0.55
Rated speed rpm : 1355

rack travel mm : 4.00
Rated speed rpm : 1205

LOW IDLE

control lever
position degree : 26.0
tolerance degree : + 4.0

Setting point w/out bumper spring

Rated speed rpm : 450
rack travel mm : 5.00
Tolerance mm : + 0.10

Testing:

Rated speed rpm : 450
rack travel mm : 5.50
Tolerance mm : + 0.10

rack travel mm : 2.00
Rated speed rpm : 510
Tolerance 1/min : + 30

TORQUE CONTROL

Rated speed rpm : 1100
rack travel mm : 12.15
Tolerance mm : + 0.05

Rated speed rpm : 750
rack travel mm : 13.30
Tolerance mm : + 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 900
rack travel mm : 13.30
Tolerance mm : ± 0.10

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : 10.45
Tolerance mm : ± 0.10

MEASUREMENT

Rated speed rpm : 500

Pressure hPa : 560
rack travel mm : 12.80
Tolerance mm : ± 0.20

Pressure hPa : 385
rack travel mm : 11.45
Tolerance mm : ± 0.05

Start interlock.

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 900
Rated speed rpm : 750
Del. quantity
cm³/1000 strokes : 135.0
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000s. : ± 4.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 79.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000s. : ± 3.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : ± 1.00
Del. quantity
cm³/1000 strokes : 145.0
Tolerance
cm³/1000 strokes : ± 10.0
Check tolerance
cm³/1000s. : ± 13.0

LOW IDLE

Rated speed rpm : 450
Del. quantity
cm³/1000 strokes : 18.0
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000s. : ± 4.5
Speed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000s. : 8.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 21.01.97
Test oil : ISO 4113
Combination No. : 0 400 866 204AA

Injection pump
Pump designation :
EP type number :

Governor
Governor design. :
Governor no. :

Cust. part No. : 3921107

Customer-spec. information
Customer : CDC
Motor : 6 CT/177Ps/2500

TEST BENCH REQUIREMENTS

Inlet line : 3.2
Test oil inlet temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 047

Inlet press. bar : 1.5
Tolerance bar : ± 0.1

Test nozzle holder assembly : 1 688 901 017

Opening pressure bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 014

Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0

Prestroke mm : 2.85
Tolerance mm : ± 0.05
Check tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.50
Check tolerance °NW : ± 0.75

Start of delivery mark

*NW after s.o.d. : 11.00

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1250

Rack travel in mm : 10.85
Tolerance mm : ± 0.05

Del. quantity cm³/1000 strokes : 100.5

Tolerance cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : + 3.0

Spreed

Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 6.5

Rated speed rpm : 400

Rack travel in mm : 5.30

Tolerance mm : + 0.10

Del. quantity
cm³/1000 strokes : 14.5

Tolerance
cm³/1000 strokes : + 2.0

Check tolerance
cm³/1000S. : + 4.5

Spreed

Tolerance
cm³/1000 strokes : 6.0

Check tolerance
cm³/1000S. : 8.0

(B) SETTING OF INJECTION PUMP WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : FREE
Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : + 0.20

governor spring
pre-tension
click setting x : 5.50

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1250
Aneroid pressure
hPa : -
Del. quantity
cm³/1000 strokes : 100.5
Tolerance
cm³/1000 strokes : + 1.0

E17

Check tolerance
cm³/1000S. : + 3.0

Spreed
Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 6.5

CONTROL LEVER

control lever
position degree : 105.0
tolerance degree : + 4.0

RATED SPEED

rack travel mm : 9.80
Rated speed rpm : 1330
Tolerance 1/min : + 5

rack travel mm : 4.00
Rated speed rpm : 1405
Tolerance 1/min : + 15

rack travel mm : 0.85
Tolerance mm : + 0.55
Rated speed rpm : 1565

rack travel mm : 4.00
Rated speed rpm : 1415

LOW IDLE

control lever
position degree : 80.0
tolerance degree : + 4.0

Setting point w/out bumper spring

Rated speed rpm : 400
rack travel mm : 4.80
Tolerance mm : + 0.10

Testing:

Rated speed rpm : 400
rack travel mm : 5.30
Tolerance mm : + 0.10

rack travel mm : 2.00
Rated speed rpm : 525
Tolerance 1/min : + 30

TORQUE CONTROL

Rated speed rpm : 1250
rack travel mm : 10.85
Tolerance mm : ± 0.05

Start interlock

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.00
Tolerance mm : ± 1.00
Del. quantity
cm³/1000 strokes : 155.0
Tolerance
cm³/1000 strokes : ± 10.0
Check tolerance
cm³/1000S. : ± 15.0

LOW IDLE

Rated speed rpm : 400
Del. quantity
cm³/1000 strokes : 14.5
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 4.5
Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 8.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 21.01.97
Test oil : ISO 4113
Combination No. : 0 400 866 204AB

Injection pump
Pump designation :
EP type number :

Governor
Governor design :
Governor no. :

Cust. part No. : 3921116

Customer-spec. information
Customer : CDC
Motor : 6 CT/123Ps/2100

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 047

Inlet press. bar : 1.5
Tolerance bar : ± 0.1

Test nozzle holder assembly : 1 688 901 101

Opening pressure bar : 208.5
Tolerance bar : ± 1.5

Test Lines : 1 680 750 014

Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0

Prestroke mm : 2.85
Tolerance mm : ± 0.05
Check tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.50
Check tolerance °NW : ± 0.75

Start of delivery blocking

*NW after s.o.d. : 11.00
Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1050

Rack travel in mm : 10.75
Tolerance mm : ± 0.05

Del. quantity cm³/1000 strokes : 100.0

Tolerance cm³/1000 strokes : ± 1.0

Check tolerance	
cm ³ /1000S.	: + 3.0
Speed	
Tolerance	
cm ³ /1000 strokes	: 4.0
Check tolerance	
cm ³ /1000S.	: 6.5

Rated speed rpm	: 500
Rack travel in mm	: 5.70
Tolerance mm	: + 0.10
Del. quantity	
cm ³ /1000 strokes	: 13.0
Tolerance	
cm ³ /1000 strokes	: + 2.0
Check tolerance	
cm ³ /1000S.	: + 4.5
Speed	
Tolerance	
cm ³ /1000 strokes	: 6.0
Check tolerance	
cm ³ /1000S.	: 8.0

(B) SETTING OF INJECTION PUMP WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever	
position degree	: FREE
Rated speed rpm	: 800
Rack travel in mm	: 0.50
Tolerance mm	: + 0.20
governor spring	
pre-tension	
click setting x	: 5.50

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm	: 1050
Aneroid pressure	
hPa	: -
Del. quantity	
cm ³ /1000 strokes	: 100.0
Tolerance	
cm ³ /1000 strokes	: + 1.0

E20

Check tolerance	
cm ³ /1000S.	: + 3.0
Speed	
Tolerance	
cm ³ /1000 strokes	: 4.0
Check tolerance	
cm ³ /1000S.	: 6.5

CONTROL LEVER

control lever	
position degree	: 54.0
tolerance degree	: + 4.0

RATED SPEED

rack travel mm	: 9.70
Rated speed rpm	: 1100
Tolerance 1/min	: + 5

rack travel mm	: 4.00
Rated speed rpm	: 1195
Tolerance 1/min	: + 15

rack travel mm	: 0.85
Tolerance mm	: + 0.55
Rated speed rpm	: 1350

rack travel mm	: 4.00
Rated speed rpm	: 1200

LOW IDLE

control lever	
position degree	: 35.0
tolerance degree	: + 4.0

Setting point w/out bumper spring

Rated speed rpm	: 500
rack travel mm	: 5.20
Tolerance mm	: + 0.10

Testing:

Rated speed rpm	: 500
rack travel mm	: 5.70
Tolerance mm	: + 0.10

rack travel mm	: 2.00
Rated speed rpm	: 615
Tolerance 1/min	: + 30

TORQUE CONTROL

Rated speed rpm : 1050
rack travel mm : 10.75
Tolerance mm : \pm 0.05

Rated speed rpm : 750
rack travel mm : 12.20

Start interlock

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 750
Del. quantity
cm³/1000 strokes : 122.0
Tolerance
cm³/1000 strokes : \pm 2.0
Check tolerance
cm³/1000S. : \pm 4.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.00
Tolerance mm : \pm 1.00
Del. quantity
cm³/1000 strokes : 145.0
Tolerance
cm³/1000 strokes : \pm 10.0
Check tolerance
cm³/1000S. : \pm 15.0

LOW IDLE

Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 18.0
Tolerance
cm³/1000 strokes : \pm 2.0
Check tolerance
cm³/1000S. : \pm 4.5
Speed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 8.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 21.01.97
Test oil : ISO 4113
Combination No. : 0 400 866 208AA

Injection pump
Pump designation :
EP type number :

Governor
Governor design. :
Governor no. :

Cust. part No. : 3921143

Customer-spec. information
Customer : CDC
Motor : 6 CT/173Ps/2200

TEST BENCH REQUIREMENTS

Inlet line : 2.

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 047

Inlet press. bar : 1.5

Test nozzle holder
assembly : 1 688 901 101

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 014

Outside diameter : 6.0

x inside diameter : 2.0

E22

x Length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 28.0
Tolerance bar : ± 1.0

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.50
Check
tolerance °Nw : ± 0.75

Start of delivery mark

*Nw after s.o.d. : 10.00

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1100

Rack travel in mm : 10.60
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 124.5

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 3.5

Spread

Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 6.5

Rated speed rpm : 400

Rack travel in mm : 5.60
Tolerance mm : + 0.10

Del. quantity
cm³/1000 strokes : 18.0
Tolerance
cm³/1000 strokes : + 2.0
Check tolerance
cm³/1000S. : + 4.5

Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 8.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : FREE
Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : + 0.20

governor spring
pre-tension
click setting x : 3.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1100
Aneroid pressure
hPa : -

Del. quantity
cm³/1000 strokes : 124.5
Tolerance
cm³/1000 strokes : + 1.0
Check tolerance
cm³/1000S. : + 3.5

Spreed
Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 6.5

CONTROL LEVER

E23

control lever
position degree : 99.0
tolerance degree : + 4.0

RATED SPEED
rack travel mm : 9.65
Rated speed rpm : 1145
Tolerance 1/min : + 5

rack travel mm : 4.00
Rated speed rpm : 1200
Tolerance 1/min : + 15

rack travel mm : 0.85
Tolerance mm : + 0.55
Rated speed rpm : 1355

rack travel mm : 4.00
Rated speed rpm : 1205

LOW IDLE

control lever
position degree : 78.0
tolerance degree : + 4.0

Setting point w/out bumper spring

Rated speed rpm : 400
rack travel mm : 5.10
Tolerance mm : + 0.10

Testing:

Rated speed rpm : 400
rack travel mm : 5.60
Tolerance mm : + 0.10

rack travel mm : 2.00
Rated speed rpm : 490
Tolerance 1/min : + 30

TORQUE CONTROL

Rated speed rpm : 1100
rack travel mm : 10.60
Tolerance mm : + 0.05

Start interlock

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.00
Tolerance mm : \pm 1.00
Del. quantity
cm³/1000 strokes : 147.5
Tolerance
cm³/1000 strokes : \pm 10.0
Check tolerance
cm³/1000S. : \pm 13.0

LOW IDLE

Rated speed rpm : 400
Del. quantity
cm³/1000 strokes : 18.0
Tolerance
cm³/1000 strokes : \pm 2.0
Check tolerance
cm³/1000S. : \pm 4.5
Speed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 8.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 21.01.97
Test oil : ISO 4113
Combination No. : 0 400 866 208AB

Injection pump
Pump designation :
EP type number :

Governor
Governor design. :
Governor no. :

Cust. part No. : 3921099

Customer-spec. information

Customer : CDC
Motor : 6 CT/210Ps/2200

TEST BENCH REQUIREMENTS

Inlet line : 2.

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 047

Inlet press. bar : 1.5

Test nozzle holder
assembly : 1 688 901 101

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 014

Outside diameter : 6.0

x inside diameter : 2.0

E25

x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 28.0
Tolerance bar : ± 1.0

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.50
Check
tolerance *NW : ± 0.75

Start of delivery mark

*NW after s.o.d. : 10.00

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1100

Rack travel in mm : 12.35
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 123.5

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 3.5

Speed

Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 6.5

Rated speed rpm : 400

Rack travel in mm : 5.70
Tolerance mm : + 0.10

Del. quantity
cm³/1000 strokes : 18.0
Tolerance
cm³/1000 strokes : + 2.0
Check tolerance
cm³/1000S. : + 4.5

Speed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 8.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : FREE
Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : + 0.20

governor spring
pre-tension
click setting x : 4.75

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1100
Aneroid pressure
hPa : -

Del. quantity
cm³/1000 strokes : 123.5
Tolerance
cm³/1000 strokes : + 1.0
Check tolerance
cm³/1000S. : + 3.5

Speed
Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 6.5

CONTROL LEVER

control lever
position degree : 54.0
tolerance degree : + 4.0

RATED SPEED
rack travel mm : 11.30
Rated speed rpm : 1150
Tolerance 1/min : + 5

rack travel mm : 4.00
Rated speed rpm : 1255
Tolerance 1/min : + 15

rack travel mm : 0.85
Tolerance mm : + 0.55
Rated speed rpm : 1410

rack travel mm : 4.00
Rated speed rpm : 1260

LOW IDLE

control lever
position degree : 32.0
tolerance degree : + 4.0

Setting point w/out bumper spring

Rated speed rpm : 400
rack travel mm : 5.20
Tolerance mm : + 0.10

Testing:

Rated speed rpm : 400
rack travel mm : 5.70
Tolerance mm : + 0.10

rack travel mm : 2.00
Rated speed rpm : 525
Tolerance 1/min : + 30

TORQUE CONTROL

Rated speed rpm : 1100
rack travel mm : 12.35
Tolerance mm : + 0.05

Start interlock

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.00
Tolerance mm : \pm 1.00
Del. quantity
cm³/1000 strokes : 145.0
Tolerance
cm³/1000 strokes : \pm 10.0
Check tolerance
cm³/1000S. : \pm 13.0

LOW IDLE

Rated speed rpm : 400
Del. quantity
cm³/1000 strokes : 18.0
Tolerance
cm³/1000 strokes : \pm 2.0
Check tolerance
cm³/1000S. : \pm 4.5
Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 8.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 24.01.97
Test oil : ISO 4113
Combination No. : 0 400 866 208AC

Injection pump
Pump designation :
EP type number :

Governor
Governor design. :
Governor no. :

Cust. part No. : 3921089

Customer spec. information

Customer : CDC
Motor : 6 C /155Ps/2500

TEST BENCH REQUIREMENTS

Inlet line : 2.

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 047

Inlet press. bar : 1.5

Test nozzle holder
assembly : 1 688 901 101

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test Lines : 1 680 750 014

Outside diameter : 6.0

x inside diameter : 2.0

x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 28.0
Tolerance bar : ± 1.0
Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.50
Check
tolerance *NW : ± 0.75

Start of delivery mark

*NW after s.o.d. : 11.00

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1050

Rack travel in mm : 9.65
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 80.5

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 3.5

Spread

Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 6.5

Rated speed rpm : 400

Rack travel in mm : 5.70
Tolerance mm : ± 0.10

Del. quantity
cm³/1000 strokes : 16.5
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 4.5

Speed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 8.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : FREE
Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : ± 0.20

governor spring
pre-tension
click setting x : 2.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1050
Aneroid pressure
hPa : -

Del. quantity
cm³/1000 strokes : 80.5
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 3.5

Speed
Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 6.5

CONTROL LEVER

F01

control lever
position degree : 95.0
tolerance degree : ± 4.0

RATED SPEED

rack travel mm : 8.60
Rated speed rpm : 1100
Tolerance 1/min : ± 5

rack travel mm : 4.00
Rated speed rpm : 1135
Tolerance 1/min : ± 15

rack travel mm : 0.85
Tolerance mm : ± 0.55
Rated speed rpm : 1290

rack travel mm : 4.00
Rated speed rpm : 1140

LOW IDLE

control lever
position degree : 77.0
tolerance degree : ± 4.0

Setting point w/out bumper spring

Rated speed rpm : 400
rack travel mm : 5.20
Tolerance mm : ± 0.10

Testing:

Rated speed rpm : 400
rack travel mm : 5.70
Tolerance mm : ± 0.10

rack travel mm : 2.00
Rated speed rpm : 470
Tolerance 1/min : ± 30

TORQUE CONTROL

Rated speed rpm : 1050
rack travel mm : 9.65
Tolerance mm : ± 0.05

Rated speed rpm : 750
rack travel mm : 10.50
Tolerance mm : ± 0.10

Start interlock

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 750
Del. quantity
cm³/1000 strokes : 88.5
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 4.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.00
Tolerance mm : ± 1.00
Del. quantity
cm³/1000 strokes : 155.0
Tolerance
cm³/1000 strokes : ± 10.0
Check tolerance
cm³/1000S. : ± 13.0

LOW IDLE

Rated speed rpm : 400
Del. quantity
cm³/1000 strokes : 16.5
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 4.5
Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 8.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 24.01.97
Test oil : ISO 4113
Combination No. : 0 400 366 203AD

Injection pump
Pump designation :
EP type number :

Governor
Governor design. :
Governor no. :

Cust. part No. : 3921144

Customer-spec. information
Customer : CDC
Motor : 6 CT/215Ps/2500

TEST BENCH REQUIREMENTS

Inlet line : 2.

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 047

Inlet press. bar : 1.5

Test nozzle holde
assembly : 1 688 901 017

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 014

Outside diameter : 6.0

x inside diameter : 2.0

F03

x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 28.0
Tolerance bar : ± 1.0

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.50
Check
tolerance *NW : ± 0.75

Start of delivery mark

*NW after s.o.d. : 11.00

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1250

Rack travel in mm : 12.00
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 122.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 3.5

Spread

Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 6.5

Rated speed rpm : 400

Rack travel in mm : 5.50
Tolerance mm : ± 0.10

Del. quantity
cm³/1000 strokes : 19.0
Tolerance
cm³/1000 strokes : ± 2.0

Check tolerance
cm³/1000S. : ± 4.5

Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 8.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : FREE
Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : ± 0.20

governor spring
pre-tension
click setting x : 4.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1250
Aneroid pressure
hPa : -

Del. quantity
cm³/1000 strokes : 122.0
Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 3.5

Spreed
Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 6.5

CONTROL LEVER

F04

control lever
position degree : 106.0
tolerance degree : ± 4.0

RATED SPEED

rack travel mm : 11.00
Rated speed rpm : 1295
Tolerance 1/min : ± 5

rack travel mm : 4.00
Rated speed rpm : 1370
Tolerance 1/min : ± 15

rack travel mm : 0.85
Tolerance mm : ± 0.55
Rated speed rpm : 1525

rack travel mm : 4.00
Rated speed rpm : 1375

LOW IDLE

control lever
position degree : 80.0
tolerance degree : ± 4.0

Setting point w/out bumper spring

Rated speed rpm : 400
rack travel mm : 5.00
Tolerance mm : ± 0.10

Testing:

Rated speed rpm : 400
rack travel mm : 5.50
Tolerance mm : ± 0.10

rack travel mm : 2.00
Rated speed rpm : 500
Tolerance 1/min : ± 30

TORQUE CONTROL

Rated speed rpm : 1250
rack travel mm : 12.00
Tolerance mm : ± 0.05

Rated speed rpm : 750
rack travel mm : 12.60
Tolerance mm : ± 0.10

Start interlock

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 750
Del. quantity
cm³/1000 strokes : 124.5
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 4.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.00
Tolerance mm : ± 1.00
Del. quantity
cm³/1000 strokes : 145.0
Tolerance
cm³/1000 strokes : ± 10.0
Check tolerance
cm³/1000S. : ± 13.0

LOW IDLE

Rated speed rpm : 400
Del. quantity
cm³/1000 strokes : 19.0
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 4.5
Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 8.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 24.01.97
Test oil : ISO 4113
Combination No. : 0 400 866 208AE

Injection pump
Pump designation :
EP type number :

Governor
Governor design. :
Governor no. :

Cust. part No. : 3921137

Customer-spec. information

Customer : CDC
Motor : 6 CT

TEST BENCH REQUIREMENTS

Inlet line : 2.

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 047

Inlet press. bar : 1.5

Test nozzle holde
assembly : 1 688 901 017

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 014

Outside diameter : 6.0

x inside diameter : 2.0

F06

x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 28.0
Tolerance bar : ± 1.0

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Start of delivery mark

°NW after s.o.d. : 10.00

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1100

Rack travel in mm : 11.35
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 106.5

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 3.5

Speed

Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 6.5

Rated speed rpm : 400

Rack travel in mm : 5.50
Tolerance mm : +- 0.10

Del. quantity
cm³/1000 strokes : 18.0
Tolerance
cm³/1000 strokes : +- 2.0

Check tolerance
cm³/1000S. : +- 4.5

Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 8.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : FREE
Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : +- 0.20

governor spring
pre-tension
click setting x : 2.75

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1100
Aneroid pressure
hPa : -

Del. quantity
cm³/1000 strokes : 106.5
Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 3.5

Spreed
Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 6.5

CONTROL LEVER

F07

control lever
position degree : 96.0
tolerance degree : +- 4.0

RATED SPEED
rack travel mm : 10.30
Rated speed rpm : 1145
Tolerance 1/min : +- 5

rack travel mm : 4.00
Rated speed rpm : 1205
Tolerance 1/min : +- 15

rack travel mm : 0.85
Tolerance mm : +- 0.55
Rated speed rpm : 1360

rack travel mm : 4.00
Rated speed rpm : 1210

LOW IDLE

control lever
position degree : 77.0
tolerance degree : +- 4.0

Setting point w/out bumper spring

Rated speed rpm : 400
rack travel mm : 5.00
Tolerance mm : +- 0.10

Testing:

Rated speed rpm : 400
rack travel mm : 5.50
Tolerance mm : +- 0.10

rack travel mm : 2.00
Rated speed rpm : 480
Tolerance 1/min : +- 30

TORQUE CONTROL

Rated speed rpm : 1100
rack travel mm : 11.35
Tolerance mm : +- 0.05

Start interlock

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.00
Tolerance mm : ± 1.00
Del. quantity
cm³/1000 strokes : 145.0
Tolerance
cm³/1000 strokes : ± 10.0
Check tolerance
cm³/1000s. : ± 13.0

LOW IDLE

Rated speed rpm : 400
Del. quantity
cm³/1000 strokes : 18.0
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000s. : ± 4.5
Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000s. : 8.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 24.01.97
Test oil : ISO 4113
Combination No. : 0 400 866 208AG

Injection pump
Pump designation :
EP type number :

Governor
Governor design. :
Governor no. :

Cust. part No. : 3915955

Customer-spec. information
Customer : CDC
Motor : 5 CT

TEST BENCH REQUIREMENTS

Inlet line : 2.

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 047

Inlet press. bar : 1.5

Test nozzle holder
assembly : 1 688 901 017

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 014

Outside diameter : 6.0

x inside diameter : 2.0

F09

x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 28.0
Tolerance bar : ± 1.0

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.50
Check
tolerance *NW : ± 0.75

Start of delivery mark

*NW after s.o.d. : 11.00

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1100

Rack travel in mm : 11.35
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 106.5

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 3.5

Speed

Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 6.5

Rated speed rpm : 400

Rack travel in mm : 5.90
Tolerance mm : ± 0.10

Del. quantity
cm³/1000 strokes : 18.0
Tolerance
cm³/1000 strokes : ± 2.0

Check tolerance
cm³/1000S. : ± 4.5

Spread
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 8.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : FREE
Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : ± 0.20

governor spring
pre-tension
click setting x : 2.75

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1100
Aneroid pressure
hPa : -

Del. quantity
cm³/1000 strokes : 106.5
Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 3.5

Spread
Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 6.5

CONTROL LEVER

F10

control lever
position degree : 96.0
tolerance degree : ± 4.0

RATED SPEED

rack travel mm : 10.30
Rated speed rpm : 1145
Tolerance 1/min : ± 5

rack travel mm : 4.00
Rated speed rpm : 1205
Tolerance 1/min : ± 15

rack travel mm : 0.85
Tolerance mm : ± 0.55
Rated speed rpm : 1360

rack travel mm : 4.00
Rated speed rpm : 1210

LOW IDLE

control lever
position degree : 77.0
tolerance degree : ± 4.0

Setting point w/out bumper spring

Rated speed rpm : 400
rack travel mm : 5.40
Tolerance mm : ± 0.10

Testing:

Rated speed rpm : 400
rack travel mm : 5.90
Tolerance mm : ± 0.10

rack travel mm : 2.00
Rated speed rpm : 480
Tolerance 1/min : ± 30

TORQUE CONTROL

Rated speed rpm : 1100
rack travel mm : 11.35
Tolerance mm : ± 0.05

Start interlock

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.00
Tolerance mm : \pm 1.00
Del. quantity
cm³/1000 strokes : 145.0
Tolerance
cm³/1000 strokes : \pm 10.0
Check tolerance
cm³/1000S. : \pm 13.0

LOW IDLE

Rated speed rpm : 400
Del. quantity
cm³/1000 strokes : 18.0
Tolerance
cm³/1000 strokes : \pm 2.0
Check tolerance
cm³/1000S. : \pm 4.5
Speed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 8.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 24.01.97
Test oil : ISO 4113
Combination No. : 0 400 866 208AH

Injection pump
Pump designation :
EP type number :

Governor
Governor design. :
Governor no. :

Cust. part No. : 3915965

Customer-spec. information
Customer : CDC
Motor : 6 CT

TEST BENCH REQUIREMENTS

Inlet line : 2.

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 047

Inlet press. bar : 1.5

Test nozzle holder
assembly : 1 688 901 100

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 014

Outside diameter : 6.0

x inside diameter : 2.0

x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 28.0
Tolerance bar : ± 1.0
Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.50
Check
tolerance *NW : ± 0.75

Start of delivery mark

*NW after s.o.d. : 11.00

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1100

Rack travel in mm : 12.05
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 113.5

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 3.5

Spread

Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 6.5

Rated speed rpm : 400

Rack travel in mm : 6.20
Tolerance mm : ± 0.10

Del. quantity
cm³/1000 strokes : 17.0
Tolerance
cm³/1000 strokes : ± 2.0

Check tolerance
cm³/1000S. : ± 4.5

Speed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 8.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : FREE
Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : ± 0.20

governor spring
pre-tension
click setting x : 2.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1100
Aneroid pressure
hPa : -

Del. quantity
cm³/1000 strokes : 113.5
Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 3.5

Speed
Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 6.5

CONTROL LEVER

F13

control lever
position degree : 96.0
tolerance degree : ± 4.0

RATED SPEED

rack travel mm : 11.00
Rated speed rpm : 1145
Tolerance 1/min : ± 5

rack travel mm : 4.00
Rated speed rpm : 1200
Tolerance 1/min : ± 15

rack travel mm : 0.85
Tolerance mm : ± 0.55
Rated speed rpm : 1350

rack travel mm : 4.00
Rated speed rpm : 1205

LOW IDLE

control lever
position degree : 75.0
tolerance degree : ± 4.0

Setting point w/out bumper spring

Rated speed rpm : 400
rack travel mm : 5.70
Tolerance mm : ± 0.10

Testing:

Rated speed rpm : 400
rack travel mm : 6.20
Tolerance mm : ± 0.10

TORQUE CONTROL

Rated speed rpm : 1100
rack travel mm : 12.05
Tolerance mm : ± 0.05

Rated speed rpm : 750
rack travel mm : 13.50
Tolerance mm : ± 0.10

Start interlock

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 750
Del. quantity
cm³/1000 strokes : 135.5
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 4.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.00
Tolerance mm : ± 1.00
Del. quantity
cm³/1000 strokes : 145.0
Tolerance
cm³/1000 strokes : ± 10.0
Check tolerance
cm³/1000S. : ± 13.0

LOW IDLE

Rated speed rpm : 400
Del. quantity
cm³/1000 strokes : 17.0
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 4.5
Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 8.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 22.01.97
Test oil : ISO 4113
Combination No. : 0 400 874 248
Injection pump
Pump designation : PES4A90D410RS2728
EP type number : 0 410 894 030
Governor
Governor design. : RSV350...750A0C2240
: 3L
Governor no. : 0 420 232 559
Cust. part No. :

Customer-spec. information
Customer : MB-NFZ
Motor : OM364
Power KW : 39.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2
Test oil inlet temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 1 419 992 198
Inlet press. bar : 1.5
Test nozzle holder assembly : 0 681 343 009
Opening pressure bar : 173.5
Tolerance bar : ± 1.5
Test lines : 1 680 750 015
Outside diameter : 6.0

F15

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0
Prestroke mm : 2.30
Tolerance mm : ± 0.05
Check tolerance mm : ± 0.10
Rack travel in mm : 10.50
Tolerance mm : ± 1.50
Firing order : 1- 3- 4- 2
Phasing : 0-90-180-270
Tolerance : ± 0.50
Check tolerance °NW : ± 0.75

BASIC SETTING

Rated speed rpm : 700
Rack travel in mm : 12.00
Tolerance mm : ± 0.05
Del. quantity cm³/1000 strokes : 58.0
Tolerance cm³/1000 strokes : ± 1.0
Check tolerance cm³/1000S. : ± 3.0
Speed

Tolerance
cm³/1000 strokes : 3.0

Check tolerance
cm³/1000S. : 4.5

Rated speed rpm : 350

Rack travel in mm : 8.60
Tolerance mm : + 0.10

Del. quantity
cm³/1000 strokes : 12.0
Tolerance
cm³/1000 strokes : + 2.0
Check tolerance
cm³/1000S. : + 4.0

Speed
Tolerance
cm³/1000 strokes : 2.5
Check tolerance
cm³/1000S. : 4.5

(3) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : - 3
Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : + 0.20

governor spring
pre-tension
click setting x : 2.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 700
Aneroid pressure
hPa : -

Del. quantity
cm³/1000 strokes : 58.0
Tolerance
cm³/1000 strokes : + 1.0
Check tolerance
cm³/1000S. : + 3.0

Speed
Tolerance
cm³/1000 strokes : 3.0

Check tolerance
cm³/1000S. : 4.5

CONTROL LEVER

control lever
position degree : 80.0
tolerance degree : + 4.0

ASSEMBLY GOVERNOR SETTING

Rated speed rpm : 750
rack travel mm : 11.00

Rated speed rpm : 784
Tolerance 1/min : + 4
rack travel mm : 4.00

rack travel mm : 0.85
Tolerance mm : + 0.55
Rated speed rpm : 850

Rated speed rpm : 751
rack travel mm : 11.00

Rated speed rpm : 785
Tolerance 1/min : + 4
rack travel mm : 4.00

rack travel mm : 0.85
Tolerance mm : + 0.55
Rated speed rpm : 850

Rated speed rpm : 752
rack travel mm : 11.00

Rated speed rpm : 786
Tolerance 1/min : + 4
rack travel mm : 4.00

rack travel mm : 0.85
Tolerance mm : + 0.55
Rated speed rpm : 850

Rated speed rpm : 753
rack travel mm : 11.00

Rated speed rpm : 787
Tolerance 1/min : + 4
rack travel mm : 4.00

rack travel mm : 0.85
Tolerance mm : + 0.55
Rated speed rpm : 850

Rated speed rpm : 754
rack travel mm : 11.00

Rated speed rpm : 788
Tolerance 1/min : \pm 4
rack travel mm : 4.00

rack travel mm : 0.85
Tolerance mm : \pm 0.55
Rated speed rpm : 850

Rated speed rpm : 755
rack travel mm : 11.00

Rated speed rpm : 789
Tolerance 1/min : \pm 4
rack travel mm : 4.00

rack travel mm : 0.85
Tolerance mm : \pm 0.55
Rated speed rpm : 850

LOW IDLE

control lever
position degree : 66.0
tolerance degree : \pm 4.0

Testing:

Rated speed rpm : 350
rack travel mm : 8.60
Tolerance mm : \pm 0.10

rack travel mm : 2.00
Rated speed rpm : 400
Tolerance 1/min : \pm 15

Rated speed rpm : 100

CRT mm min. : $>$ 19.50

SET IDLE AUXILIARY SPRING

Rated speed rpm : 100

TORQUE CONTROL

Rated speed rpm : 700
rack travel mm : 12.00
Tolerance mm : \pm 0.05

Start interlock

F17

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 16.70
Tolerance mm : \pm 0.20
Del. quantity
cm³/1000 strokes : 83.0
Tolerance
cm³/1000 strokes : \pm 5.0
Check tolerance
cm³/1000S. : \pm 8.0

LOW IDLE

Rated speed rpm : 350
Del. quantity
cm³/1000 strokes : 12.0
Tolerance
cm³/1000 strokes : \pm 2.0
Check tolerance
cm³/1000S. : \pm 4.0
Speed
Tolerance
cm³/1000 strokes : 2.5
Check tolerance
cm³/1000S. : 4.5

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 22.01.97
Test oil : ISO 4113

Combination No. : 0 402 036 762

Injection pump
Pump designation : PES6P110A12URS3353
EP type number : 0 412 016 752

Governor
Governor design. : RQV450...1100PA1233
: 1K
Governor no. : 0 421 815 479

Cust. part No. : 3926776

Customer-spec. information
Customer : CDC
Motor : 6CTA
Power kW : 194.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 093

Inlet press. bar : 2.0
Tolerance bar : ± 0.1

Test nozzle holder
assembly : 1 688 901 103

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 015

F18

Outside diameter : 6.0
x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Start of delivery blocking

*NW after s.o.d. : 8.00
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Barrel no. : 1

Beginning of delivery difference

and maximum rack
travel : 13.00
Difference °CS : 1.20

BASIC SETTING

Rated speed rpm : 1000

Rack travel in mm : 13.15
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 206.5

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 4.0

Spread

Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

Rated speed rpm : 500

Rack travel in mm : 6.00

Tolerance mm : ± 0.20

Del. quantity

cm³/1000 strokes : 22.5

Tolerance

cm³/1000 strokes : ± 3.0

Check tolerance

cm³/1000S. : ± 5.0

Spread

Tolerance

cm³/1000 strokes : 4.0

Check tolerance

cm³/1000S. : 3.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 1214

guide sleeve

travel mm : 8.09

Tolerance mm : ± 0.15

Rated speed rpm : 500

guide sleeve

travel mm : 1.82

Tolerance mm : ± 0.25

Rated speed rpm : 890

guide sleeve

travel mm : 4.75

Tolerance mm : ± 0.25

Rated speed rpm : 1570

guide sleeve

travel mm : 13.50

Tolerance mm : ± 0.50

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1000

Aneroid pressure

hPa : 1200

Del. quantity

cm³/1000 strokes : 206.5

Tolerance

cm³/1000 strokes : ± 1.0

Check tolerance

cm³/1000S. : ± 4.0

Spread

Tolerance

cm³/1000 strokes : 8.0

Check tolerance

cm³/1000S. : 12.0

CONTROL LEVER

control lever

position degree : 117.0

tolerance degree : ± 6.0

RATED SPEED

rack travel mm : 11.45

Rated speed rpm : 1170

Tolerance 1/min : ± 15

rack travel mm : 7.95

Rated speed rpm : 1230

Tolerance 1/min : ± 5

rack travel mm : 0.50

Tolerance mm : ± 0.50

Rated speed rpm : 1350

LOW IDLE

control lever

position degree : 79.0

tolerance degree : ± 6.0

Control lever difference

Grad : 38.0

tolerance degree : ± 6.0

Testing:

Rated speed rpm : 500

rack travel mm : 6.00

Tolerance mm : ± 0.20

Rated speed rpm : 400
CRT mm min. : > 7.50
Rated speed rpm : 500

TORQUE CONTROL

Rated speed rpm : 1000
rack travel mm : 13.15
Tolerance mm : ± 0.05

Rated speed rpm : 750
rack travel mm : 12.55
Tolerance mm : ± 0.20

Rated speed rpm : 1100
rack travel mm : 12.60
Tolerance mm : ± 0.10

ANEROID/ALTITUDE COMPENSATOR TEST

SETTING

Rated speed rpm : 1000
Pressure hPa : 1200

Pressure hPa : -
Rated speed rpm : 1000
rack travel mm : 10.15
Tolerance mm : ± 0.20

MEASUREMENT

Rated speed rpm : 1000

Pressure hPa : 720
rack travel mm : 12.20
Tolerance mm : ± 0.30

Pressure hPa : 580
rack travel mm : 11.20
Tolerance mm : ± 0.20

Start interlock

Rated speed rpm : > 100
Rated speed rpm : < 380

Check
speed 1/min : > 80
Check
speed 1/min : < 390

FUEL DELIVERY CHARACTERISTICS

F20

Aneroid pressure
hPa : 1200
Rated speed rpm : 750
Del. quantity
cm³/1000 strokes : 197.5
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

Aneroid pressure
hPa : 1200
Rated speed rpm : 1100
Del. quantity
cm³/1000 strokes : 190.5
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 5.0

Aneroid pressure
hPa : -
Rated speed rpm : 1000
Del. quantity
cm³/1000 strokes : 124.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 21.00
Tolerance mm : ± 0.50
Del. quantity
cm³/1000 strokes : 161.0
Tolerance
cm³/1000 strokes : ± 20.0
Check tolerance
cm³/1000S. : ± 25.0

LOW IDLE

Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 22.5
Tolerance
cm³/1000 strokes : ± 3.0

Check tolerance
cm³/1000S. : ← 5.0
Speed
Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 8.0

End of test specification sheet



BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 29.01.97
Test oil : ISO 4113

Combination No. : 0 402 736 869

Injection pump
Pump designation : PES6P120A12ORS7352
EP type number : 0 412 726 923

Governor
Governor design. : RQV350...1000PA1174K
Governor no. : 0 421 815 440

Cust. part No. : 3928155

Customer-spec. information

Customer : CDC
Motor : 6CTA-A
Power KW : 205.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 093

Inlet press. bar : 2.0
Tolerance bar : ± 0.1

Test nozzle holder
assembly : 1 688 901 103

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 015

Outside diameter : 6.0

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0

Prestroke mm : 4.00
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.75

Start of delivery blocking

*NW after s.o.d. : 5.50
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1000

Rack travel in mm : 15.15
Tolerance mm : ± 0.05

Del. quantity
 cm³/1000 strokes : 235.0

Tolerance
 cm³/1000 strokes : ± 1.0

Check tolerance
 cm³/1000S. : ± 4.0

Spreed

Tolerance
 cm³/1000 strokes : 5.0

Check tolerance
 cm³/1000S. : 9.0

Rated speed rpm : 375
 Del. quantity
 cm³/1000 strokes : 27.0
 Tolerance
 cm³/1000 strokes : ± 3.0
 Check tolerance
 cm³/1000S. : ± 5.0
 Spreed
 Tolerance
 cm³/1000 strokes : 8.0
 Check tolerance
 cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
 WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 1000
 guide sleeve
 travel mm : 8.20
 Tolerance mm : ± 0.10

Rated speed rpm : 350
 guide sleeve
 travel mm : 1.90
 Tolerance mm : ± 0.10

Rated speed rpm : 600
 guide sleeve
 travel mm : 5.30
 Tolerance mm : ± 0.20

Rated speed rpm : 450
 guide sleeve
 travel mm : 3.30
 Tolerance mm : ± 0.20

Rated speed rpm : 1200

guide sleeve
 travel mm : 9.80
 Tolerance mm : ± 0.20

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1000
 Aneroid pressure
 hPa : 1200
 Del. quantity
 cm³/1000 strokes : 235.0
 Tolerance
 cm³/1000 strokes : ± 1.0
 Check tolerance
 cm³/1000S. : ± 4.0
 Spreed
 Tolerance
 cm³/1000 strokes : 5.0
 Check tolerance
 cm³/1000S. : 9.0

CONTROL LEVER

control lever
 position degree : 118.0
 tolerance degree : ± 6.0

RATED SPEED

rack travel mm : 13.50
 Rated speed rpm : 1155
 Tolerance 1/min : ± 15

rack travel mm : 4.00
 Rated speed rpm : 1300
 Tolerance 1/min : ± 5

rack travel mm : 0.50
 Tolerance mm : ± 0.50
 Rated speed rpm : 1400

LOW IDLE

control lever
 position degree : 70.0
 tolerance degree : ± 6.0

Control lever difference
 Grad : 49.0
 tolerance degree : ± 6.0

Testing:

Rated speed rpm : 275

CRT mm miri. : > 8.20

Rated speed rpm : 425

TORQUE CONTROL

Rated speed rpm : 1000
rack travel mm : 15.15
Tolerance mm : ± 0.05

Rated speed rpm : 650
rack travel mm : 13.70
Tolerance mm : ± 0.20

Rated speed rpm : 1100
rack travel mm : 14.60
Tolerance mm : ± 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 1000
Pressure hPa : 1200

Pressure hPa : -
Rated speed rpm : 1000
rack travel mm : 9.70
Tolerance mm : ± 0.20

MEASUREMENT

Rated speed rpm : 1000

Pressure hPa : 825
rack travel mm : 13.80
Tolerance mm : ± 0.20

Pressure hPa : 370
rack travel mm : 11.15
Tolerance mm : ± 0.05

Start interlock

Rated speed rpm : > 100
Rated speed rpm : < 290

Check speed 1/min : > 80

Check speed 1/min : < 300

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1200
Rated speed rpm : 650
Del. quantity
cm³/1000 strokes : 210.5

Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

Aneroid pressure
hPa : -
Rated speed rpm : 1000
Del. quantity
cm³/1000 strokes : 99.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 3.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 11.50
Tolerance mm : ± 0.50
Del. quantity
cm³/1000 strokes : 180.0
Tolerance
cm³/1000 strokes : ± 20.0
Check tolerance
cm³/1000S. : ± 25.0

LOW IDLE

Rated speed rpm : 375
Del. quantity
cm³/1000 strokes : 27.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 5.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 24.01.97
Test oil : ISO 4113

Combination No. : 0 403 466 161

Injection pump
Pump designation : PES6MW100/120RS1240
EP type number : 0 413 406 239

Governor
Governor design. : RSV500...1100MW2A379
Governor no. : 0 420 085 262

Cust. part No. : 3926882

Customer-spec. information
Customer : CDC
Motor : 6 CT
Power KW : 161.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 093

Inlet press. bar : 2.0
Tolerance bar : ± 0.1

Test nozzle holde
assembly : 1 688 901 101

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 014

Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0

Prestroke mm : 3.55
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Start of delivery blocking

°NW after s.o.d. : 8.50
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Barrel no. : 1

Beginning of delivery differende

and maximum rack
travel : 15.00
Difference °CS : 1.50

BASIC SETTING

Rated speed rpm : 1100

Rack travel in mm : 11.80
Tolerance mm : + 0.05

Del. quantity
cm³/1000 strokes : 142.0

Tolerance
cm³/1000 strokes : + 1.0

Check tolerance
cm³/1000S. : + 4.0

Spread

Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 7.5

Rated speed rpm : 500

Rack travel in mm : 5.20
Tolerance mm : + 0.10
Del. quantity
cm³/1000 strokes : 21.5
Tolerance
cm³/1000 strokes : + 2.0
Check tolerance
cm³/1000S. : + 4.5
Spread
Tolerance
cm³/1000 strokes : 3.5
Check tolerance
cm³/1000S. : 5.5

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : - 3
Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : + 0.20

governor spring
pre-tension
click setting x : 4.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1100
Aneroid pressure
nPa : 1200
Del. quantity
cm³/1000 strokes : 142.0
Tolerance
cm³/1000 strokes : + 1.0
Check tolerance
cm³/1000S. : + 4.0
Spread
Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 7.5

CONTROL LEVER

control lever
position degree : 103.0
tolerance degree : + 4.0

RATED SPEED

rack travel mm : 10.90
Rated speed rpm : 1160
Tolerance 1/min : + 5

rack travel mm : 5.80
Rated speed rpm : 1230
Tolerance 1/min : + 5

rack travel mm : 1.00
Tolerance mm : + 0.70
Rated speed rpm : 1375

rack travel mm : 5.80
Rated speed rpm : 1235

LOW IDLE

control lever
position degree : 83.0
tolerance degree : + 4.0

Control lever difference
Grad : 20.0
tolerance degree : + 6.0

Setting point w/out bumper spring

Rated speed rpm : 500

rack travel mm : 4.70
Tolerance mm : ± 0.10

Testing:

Rated speed rpm : 500
rack travel mm : 5.20
Tolerance mm : ± 0.10

Rated speed rpm : 100

CRT mm min. : > 19.00

TORQUE CONTROL

Rated speed rpm : 1100
rack travel mm : 11.80
Tolerance mm : ± 0.05

Rated speed rpm : 750
rack travel mm : 12.60
Tolerance mm : ± 0.10

Rated speed rpm : 1000
rack travel mm : 12.50
Tolerance mm : ± 0.20

Rated speed rpm : 950
rack travel mm : 12.60
Tolerance mm : ± 0.20

ANEROID/ALTITUDE COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1200

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : 10.70
Tolerance mm : ± 0.20

MEASUREMENT

Rated speed rpm : 500

Pressure hPa : 790
rack travel mm : 12.10
Tolerance mm : ± 0.20

Pressure hPa : 620
rack travel mm : 11.50
Tolerance mm : ± 0.20

Start interlock

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1200
Rated speed rpm : 950
Del. quantity
cm³/1000 strokes : 153.0
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 5.0
Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 9.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 119.5
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 3.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : ± 1.00
Del. quantity
cm³/1000 strokes : 145.5
Tolerance
cm³/1000 strokes : ± 10.0
Check tolerance
cm³/1000S. : ± 13.0

LOW IDLE

Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 21.5
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 4.5
Spreed
Tolerance
cm³/1000 strokes : 3.5

Check tolerance
cm³/1000S. : 5.5

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 24.01.97
Test oil : ISO 4113

Combination No. : 0 403 466 169

Injection pump
Pump designation : PES6MW100/120RS1242
EP type number : 0 413 406 241

Governor
Governor design. : RSV500...1100MW5A385
Governor no. : 0 420 085 270

Cust. part No. : 3926885

Customer-spec. information
Customer : CDC
Motor : 6 CTA
Power KW : 179.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 093

Inlet press. bar : 2.0
Tolerance bar : ± 0.1

Test nozzle holder
assembly : 1 688 901 101

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 014

Outside diameter : 6.0

G02

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0

Prestroke mm : 3.20
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Start of delivery blocking

*NW after s.o.d. : 8.50
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Barrel no. : 1

Beginning of delivery difference

and maximum rack
travel : 15.00
Difference °CS : 1.50

BASIC SETTING

Rated speed rpm : 1100

Rack travel in mm : 12.80
Tolerance mm : + 0.05

Del. quantity
cm³/1000 strokes : 159.0

Tolerance
cm³/1000 strokes : + 1.0

Check tolerance
cm³/1000S. : + 4.0

Spread

Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 7.5

Rated speed rpm : 500

Rack travel in mm : 5.10
Tolerance mm : + 0.10

Del. quantity
cm³/1000 strokes : 21.0

Tolerance
cm³/1000 strokes : + 2.0

Check tolerance
cm³/1000S. : + 4.5

Spread

Tolerance
cm³/1000 strokes : 3.5

Check tolerance
cm³/1000S. : 5.5

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : - 3
Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : + 0.20

governor spring
pre-tension
click setting x : 3.50

G03

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1100
Aneroid pressure
hPa : 1200

Del. quantity
cm³/1000 strokes : 159.0

Tolerance
cm³/1000 strokes : + 1.0

Check tolerance
cm³/1000S. : + 4.0

Spread

Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 7.5

CONTROL LEVER

control lever
position degree : 109.0
tolerance degree : + 4.0

RATED SPEED

rack travel mm : 11.80
Rated speed rpm : 1170
Tolerance 1/min : + 5

rack travel mm : 7.00
Rated speed rpm : 1230
Tolerance 1/min : + 5

rack travel mm : 1.00
Tolerance mm : + 0.70
Rated speed rpm : 1300

rack travel mm : 7.00
Rated speed rpm : 1230

LOW IDLE

control lever
position degree : 85.0
tolerance degree : + 4.0

Control lever difference
Grad : 24.0
tolerance degree : + 6.0

Setting point w/out bumper spring

Rated speed rpm : 500

rack travel mm : 4.60
Tolerance mm : ± 0.10

Testing:

Rated speed rpm : 500
rack travel mm : 5.10
Tolerance mm : ± 0.10

Rated speed rpm : 100

CRT mm min. : > 19.00

TORQUE CONTROL

Rated speed rpm : 1100
rack travel mm : 12.80
Tolerance mm : ± 0.05

Rated speed rpm : 750
rack travel mm : 13.40
Tolerance mm : ± 0.20

Rated speed rpm : 1000
rack travel mm : 13.30
Tolerance mm : ± 0.20

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1200

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : 10.80
Tolerance mm : ± 0.20

MEASUREMENT

Rated speed rpm : 500
Pressure hPa : 900
rack travel mm : 13.15
Tolerance mm : ± 0.20

Pressure hPa : 560
rack travel mm : 11.50
Tolerance mm : ± 0.20

Start interlock

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1200
Rated speed rpm : 1000
Del. quantity
cm³/1000 strokes : 169.0
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 5.0
Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 9.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 119.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 3.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : ± 1.00
Del. quantity
cm³/1000 strokes : 140.0
Tolerance
cm³/1000 strokes : ± 10.0
Check tolerance
cm³/1000S. : ± 13.0

LOW IDLE

Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 21.0
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 4.5
Spreed
Tolerance
cm³/1000 strokes : 3.5
Check tolerance
cm³/1000S. : 5.5

End of test specification sheet



BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 24.01.97
Test oil : ISO 4113

Combination No. : F 002 A0Z 040

Injection pump
Pump designation : PES4A95D320/3RS2880
EP type number : 9 410 037 214

Governor
Governor design. : RSV475...1100A0C920R
Governor no. : F 002 A20 240

Cust. part No. : 3930147

Customer-spec. information
Customer : CDC
Motor : 4BT590
Power KW : 60.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 047

Inlet press. bar : 2.0
Tolerance bar : ± 0.1

Test nozzle holder
assembly : 1 688 901 101

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 014

Outside diameter : 6.0

G06

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0

Prestroke mm : 2.45
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 3- 4- 2

Phasing : 0-90-180-270
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Start of delivery blocking

*NW after s.o.d. : 6.50
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1100

Rack travel in mm : 9.85
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 80.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 3.0

Spreed

Tolerance
cm³/1000 strokes : 3.5

Check tolerance
cm³/1000S. : 6.0

Rated speed rpm : 475

Rack travel in mm : 5.50
Tolerance mm : ± 0.10

Del. quantity
cm³/1000 strokes : 23.5
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 4.5

Spreed
Tolerance
cm³/1000 strokes : 3.5
Check tolerance
cm³/1000S. : 5.5

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : - 3
Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : ± 0.20

governor spring
pre-tension
click setting x : 4.25

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1100

G07

Aneroid pressure
hPa : -

Del. quantity
cm³/1000 strokes : 80.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 3.0

Spreed
Tolerance
cm³/1000 strokes : 3.5
Check tolerance
cm³/1000S. : 6.0

CONTROL LEVER

control lever
position degree : 99.5
tolerance degree : ± 4.0

RATED SPEED

rack travel mm : 8.80
Rated speed rpm : 1165
Tolerance 1/min : ± 5

rack travel mm : 5.20
Rated speed rpm : 1215
Tolerance 1/min : ± 5

rack travel mm : 0.85
Tolerance mm : ± 0.55
Rated speed rpm : 1350

rack travel mm : 5.20
Rated speed rpm : 1225

LOW IDLE

control lever
position degree : 81.0
tolerance degree : ± 4.0

Control lever difference
Grad : 18.5
tolerance degree : ± 6.0

Setting point w/out bumper spring

Rated speed rpm : 475
rack travel mm : 5.00
Tolerance mm : ± 0.10

Testing:

Rated speed rpm : 475
rack travel mm : 5.50
Tolerance mm : ± 0.10

Rated speed rpm : 100
CRT mm min. : > 19.00

TORQUE CONTROL

Rated speed rpm : 1100
rack travel mm : 9.85
Tolerance mm : ± 0.05

Rated speed rpm : 750

Start interlock

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : ± 0.50
Del. quantity
cm³/1000 strokes : 121.0
Tolerance
cm³/1000 strokes : ± 10.0
Check tolerance
cm³/1000S. : ± 15.0

LOW IDLE

Rated speed rpm : 475
Del. quantity
cm³/1000 strokes : 23.5
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 4.5
Speed
Tolerance
cm³/1000 strokes : 3.5
Check tolerance
cm³/1000S. : 5.5

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 27.01.97
Test oil : ISO 4413
Combination No. : 0 400 074 883
Injection pump
Pump designation : PFS/M60C320RS185
EP type number : 0 410 064 006
Governor
Governor design. : RSF375/1900M78
Governor no. : 0 420 021 274

Cust. part No. :

Customer-spec. information
Customer : MB-PKW
Motor : OM601 D23 LA
Power KW : 72.0

TEST BENCH REQUIREMENTS

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 1 469 990 351
Inlet press. bar : 1.0
Test nozzle holder
assembly : 1 688 901 111
Opening pressure
bar : 148.5
Tolerance bar : ± 1.5
Test lines : 1 680 750 014
Outside diameter : 6.0
x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0
Prestroke mm : 2.05
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10
Rack travel in mm : 21.00
Tolerance mm : ± 1.00
Firing order : 1- 3- 4- 2

Phasing : 0-90-130-270

Start of delivery blocking

*NW after s.o.d. : 17.00
Tolerance : ± 0.20
Check
tolerance *NW : ± 0.30
Barrel no. : 1

BASIC SETTING

Rated speed rpm : 900
Rack travel in mm : 13.80
Tolerance mm : ± 0.05
Del. quantity
cm³/1000 strokes : 59.5
Tolerance
cm³/1000 strokes : ± 0.7
Check tolerance
cm³/1000S. : ± 1.7
Spreed
Tolerance
cm³/1000 strokes : 3.0

Check tolerance
 cm³/1000S. : 3.5
 Rated speed rpm : 375
 Rack travel in mm : 5.90
 Tolerance mm : ± 0.10
 Del. quantity
 cm³/1000 strokes : 6.5
 Tolerance
 cm³/1000 strokes : ± 0.5
 Spreed
 Tolerance
 cm³/1000 strokes : 1.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

—————
IDLE STAGE

Rack travel in mm : 6.00
 Tolerance mm : ± 0.10

—————
FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 900
 Ref. pressure
 ALDA / ADA hPa : 1350
 Del. quantity
 cm³/1000 strokes : 59.5
 Tolerance
 cm³/1000 strokes : ± 0.7
 Check tolerance
 cm³/1000S. : ± 1.7
 Spreed
 Tolerance
 cm³/1000 strokes : 3.0
 Check tolerance
 cm³/1000S. : 3.5

—————
RATED SPEED

control lever
 position degree : 50.0
 Rated speed rpm : 2200
 rack travel mm : 8.30
 Tolerance mm : ± 0.20
 Rated speed rpm : 2600
 rack travel mm : 0.50
 Tolerance mm : ± 0.50

—————
SET IDLE CONTROL LEVER POSITION

Rated speed rpm : 900
 CRT mm max. : 1.95

—————
LOW IDLE

control lever
 position degree : 12.0
 tolerance degree : ± 2.0

Setting point w/out bumper spring

Rated speed rpm : 375
 rack travel mm : 5.90

—————
SET IDLE AUXILIARY SPRING

Rated speed rpm : 500
 rack travel mm : 4.20
 Tolerance mm : ± 0.10

Load pick-up

Rated speed rpm : 200
 rack travel mm : 13.00

Rated speed rpm : 900

CRT mm max. : 1.95

rack travel mm : 5.90
 Rated speed rpm : 375

—————
TORQUE CONTROL

Rated speed rpm : 900
 rack travel mm : 13.80
 Tolerance mm : ± 0.05

Rated speed rpm : 1500
 rack travel mm : 13.20
 Tolerance mm : ± 0.10

Rated speed rpm : 1900
 rack travel mm : 12.50
 Tolerance mm : ± 0.10

Rated speed rpm : 900
 rack travel mm : 11.15
 Tolerance mm : ± 0.10

—————
ADJUSTMENT TEST ADA/ALDA

SETTING

Rated speed rpm : 900
Ref. pressure
ALDA / ADA hPa : 1600
rack travel mm : -0.25
Tolerance mm : ± 0.20

MEASUREMENT

Rated speed rpm : 900
Ref. pressure
ALDA / ADA hPa : 1100
rack travel mm : -2.65
Tolerance mm : ± 0.10

Ref. pressure
ALDA / ADA hPa : 750
rack travel mm : -4.30
Tolerance mm : ± 0.20

FUEL DELIVERY CHARACTERISTICS

Ref. pressure
ALDA / ADA hPa : 1850
Rated speed rpm : 1500
Del. quantity
cm³/1000 strokes : 58.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 2.0
Spreed
Tolerance
cm³/1000 strokes : 3.0
Check tolerance
cm³/1000S. : 3.5

Ref. pressure
ALDA / ADA hPa : 1850
Rated speed rpm : 1900
Spreed
Del. quantity
cm³/1000 strokes : 55.5
Tolerance
cm³/1000 strokes : ± 1.2
Check tolerance
cm³/1000S. : ± 2.2
Spreed
Tolerance
cm³/1000 strokes : 3.0
Check tolerance
cm³/1000S. : 3.5

Ref. pressure
ALDA / ADA hPa : 1100
Rated speed rpm : 900

Del. quantity
cm³/1000 strokes : 43.0
Tolerance
cm³/1000 strokes : ± 0.7
Check tolerance
cm³/1000S. : ± 1.7
Spreed
Tolerance
cm³/1000 strokes : 3.0
Check tolerance
cm³/1000S. : 3.5

Ref. pressure
ALDA / ADA hPa : 1100
Rated speed rpm : 900
Del. quantity
cm³/1000 strokes : 43.0
Tolerance
cm³/1000 strokes : ± 0.7
Check tolerance
cm³/1000S. : ± 1.7
Spreed
Tolerance
cm³/1000 strokes : 3.0
Check tolerance
cm³/1000S. : 3.5

HIGH IDLE

Ref. pressure
ALDA / ADA hPa : 1850
Rated speed rpm : 2200
rack travel mm : 8.30
Tolerance mm : ± 0.20
Del. quantity
cm³/1000 strokes : 31.0
Tolerance
cm³/1000 strokes : ± 2.2
Check tolerance
cm³/1000S. : ± 3.2
Spreed
Tolerance
cm³/1000 strokes : 3.0
Check tolerance
cm³/1000S. : 3.5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : > 20.10
Del. quantity
cm³/1000 strokes : 54.3
Tolerance
cm³/1000 strokes : ± 4.0
Check tolerance
cm³/1000S. : ± 5.0
Spreed

Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 8.5

End of test specification sheet

LOW IDLE

Rated speed rpm : 375
Del. quantity
cm³/1000 strokes : 7.8
Check tolerance
cm³/1000S. : ± 2.3
Spread
Check tolerance
cm³/1000S. : 1.5

control lever
position degree : > 42.00

control lever
position degree : < 39.50

SETTING PNEUMATIC FAST IDLE (PLA)
(PLA) POSITION

control lever
position degree : 12.0
tolerance degree : ± 2.0

Rated speed rpm : 425

Rack travel in mm : 7.50
Tolerance mm : ± 0.80
Del. quantity
cm³/1000 strokes : 16.5
Tolerance
cm³/1000 strokes : ± 3.5
Check tolerance
cm³/1000S. : ± 4.5
Vacuum hPa : 450.0

TESTING PNEUMATIC SHUTOFF DEVICE

Rated speed rpm : 375
Vacuum hPa : -450.0

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 23.01.97
Test oil : ISO 4113

Combination No. : 0 402 646 625

Injection pump
Pump designation : FE6P12GA52ORS7300
EP type number : 0 412 626 886

Governor
Governor design. : RQV275...1000PA1077K
Governor no. : 0 421 815 358

Cust. part No. : 1280165

Customer-spec. information

Customer : DAF
Motor : WS 242 M
Power KW : 242.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 025

Inlet press. bar : 1.5
Tolerance bar : ± 0.1

Overflow quantity
min. l/h : 140
Tolerance l/h : ± 10.0

Test nozzle holde
assembly : 1 688 901 105

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 089

Outside diameter : 8.0

x inside diameter : 3.0

x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 5.35
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 15.00
Tolerance mm : ± 0.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50

Start of delivery mark

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 980

Rack travel in mm : 15.05
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 228.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Speed

Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 275

Rack travel in mm : 5.30
Tolerance mm : +- 0.10

Del. quantity
cm³/1000 strokes : 17.0

Tolerance
cm³/1000 strokes : +- 3.0

Check tolerance
cm³/1000S. : +- 6.0

Speed
Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 1045
guide sleeve
travel mm : 9.83
Tolerance mm : +- 0.15

Rated speed rpm : 275
guide sleeve
travel mm : 2.14
Tolerance mm : +- 0.20

Rated speed rpm : 689
guide sleeve
travel mm : 6.43
Tolerance mm : +- 0.25

Rated speed rpm : 284
guide sleeve
travel mm : 2.27
Tolerance mm : +- 0.25

Rated speed rpm : 334

guide sleeve
travel mm : 3.08
Tolerance mm : +- 0.25

Rated speed rpm : 400
guide sleeve
travel mm : 3.92
Tolerance mm : +- 0.25

Rated speed rpm : 1310
guide sleeve
travel mm : 13.50
Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

control lever
position degree : - 1
Rated speed rpm : 1140

Rack travel in mm : 14.00
Tolerance mm : +- 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 980
Aneroid pressure
hPa : -

Del. quantity
cm³/1000 strokes : 228.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Speed
Tolerance
cm³/1000 strokes : 5.0
Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 119.0
tolerance degree : +- 4.0

RATED SPEED
rack travel mm : 14.00
Rated speed rpm : 1037
Tolerance 1/min : +- 5
Check
speed 1/min : +- 10

rack travel mm : 4.00
Rated speed rpm : 1165

Tolerance 1/min : + 15
 Check
 speed 1/min : + 20
 rack travel mm : 0.70
 Tolerance mm : + 0.70
 Rated speed rpm : 1250

LOW IDLE

control lever
 position degree : 74.0
 tolerance degree : + 4.0

Testing:

Rated speed rpm : 275
 rack travel mm : 5.30
 Tolerance mm : + 0.10

rack travel mm : 2.00
 Rated speed rpm : 375
 Tolerance 1/min : + 20

Rated speed rpm : 175

CRT mm min. : > 8.50

TORQUE CONTROL

Rated speed rpm : 980
 rack travel mm : 15.05
 Tolerance mm : + 0.05

Rated speed rpm : 850
 rack travel mm : 14.95
 Tolerance mm : + 0.10

Rated speed rpm : 750
 rack travel mm : 14.95
 Tolerance mm : + 0.10

Rated speed rpm : 600
 rack travel mm : 14.60
 Tolerance mm : + 0.10

Rated speed rpm : 500
 rack travel mm : 14.40
 Tolerance mm : + 0.10

ANEROID/ALTITUDE
 COMPENSATOR TEST

SETTING

Rated speed rpm : 980
 Pressure hPa : 1500
 rack travel mm : 15.05
 Tolerance mm : + 0.05

Pressure hPa : -
 Rated speed rpm : 980
 rack travel mm : 12.30
 Tolerance mm : + 0.10

MEASUREMENT

Rated speed rpm : 980

Pressure hPa : 480
 rack travel mm : 14.35
 Tolerance mm : + 0.05

Pressure hPa : 270
 rack travel mm : 12.90
 Tolerance mm : + 0.10

Start interlock

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
 hPa : -
 Rated speed rpm : 750
 Del. quantity
 cm³/1000 strokes : 238.0
 Tolerance
 cm³/1000 strokes : + 2.0
 Check tolerance
 cm³/1000S. : + 5.0
 Spreed
 Tolerance
 cm³/1000 strokes : 8.0
 Check tolerance
 cm³/1000S. : 12.0

Aneroid pressure
 hPa : -
 Rated speed rpm : 600
 Del. quantity
 cm³/1000 strokes : 157.0
 Tolerance
 cm³/1000 strokes : + 1.0
 Check tolerance
 cm³/1000S. : + 4.0

LOW IDLE

Rated speed rpm : 275
Del. quantity
cm³/1000 strokes : 17.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 24.01.97
Test oil : ISO 4113

Combination No. : 0 402 646 653

Injection pump
Pump designation : PE6P120A32ORS7360
EP type number : 0 412 626 936

Governor
Governor design. : RQ275/1150PA1193
Governor no. : 0 421 801 752

Cust. part No. : 1294723/2

Customer-spec. information
Customer : DAF
Motor : GS 200 M
Power KW : 200.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 000

Inlet press. bar : 1.5
Tolerance bar : ± 0.1

Test nozzle holde
assembly : 1 688 901 105

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 089

Outside diameter : 8.0

G17

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 5.25
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 11.50
Tolerance mm : ± 5.00

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °iW : ± 0.50

Start of delivery mark

Tolerance : ± 0.10
Check
tolerance °NW : ± 0.70

BASIC SETTING

Rated speed rpm : 1000

Rack travel in mm : 11.70
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 178.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : + 4.0

Spread

Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 275

Rack travel in mm : 5.50
Tolerance mm : + 0.10

Del. quantity
cm³/1000 strokes : 38.0
Tolerance
cm³/1000 strokes : + 3.0

Check tolerance
cm³/1000S. : + 6.0

Spread
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 1205
guide sleeve
travel mm : 6.49
Tolerance mm : + 0.10

Rated speed rpm : 275
guide sleeve
travel mm : 1.94
Tolerance mm : + 0.10

Rated speed rpm : 1150
guide sleeve
travel mm : 6.00
Tolerance mm : + 0.10

Rated speed rpm : 353
guide sleeve
travel mm : 4.33
Tolerance mm : + 0.10

Rated speed rpm : 440
guide sleeve
travel mm : 6.00
Tolerance mm : + 0.10

Rated speed rpm : 1360
guide sleeve
travel mm : 11.50
Tolerance mm : + 0.50

GUIDE SLEEVE POSITION

control lever
position degree : - 1
Rated speed rpm : 550

Rack travel in mm : 15.80
Tolerance mm : + 0.60

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1000
Aneroid pressure
hPa : 1000

Del. quantity
cm³/1000 strokes : 178.0
Tolerance
cm³/1000 strokes : + 1.0

Check tolerance
cm³/1000S. : + 4.0

Spread
Tolerance
cm³/1000 strokes : 5.0
Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 100.0
tolerance degree : + 4.0

RATED SPEED

rack travel mm : 10.70
Rated speed rpm : 1202
Tolerance 1/min : + 8

rack travel mm : 4.00
Rated speed rpm : 1280
Tolerance 1/min : + 15

rack travel mm : 0.70
Tolerance mm : + 0.70
Rated speed rpm : 1450

LOW IDLE

control lever
position degree : 74.0
tolerance degree : ± 4.0

Testing:

Rated speed rpm : 275
rack travel mm : 5.50
Tolerance mm : ± 0.10

rack travel mm : 2.00
Rated speed rpm : 340
Tolerance 1/min : ± 20

Rated speed rpm : 175

CRT mm min. : > 7.00

TORQUE CONTROL

Rated speed rpm : 1000
rack travel mm : 11.70
Tolerance mm : ± 0.05

Rated speed rpm : 1150
rack travel mm : 11.70
Tolerance mm : ± 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 600
Pressure hPa : 1000
rack travel mm : 11.70
Tolerance mm : ± 0.05

Pressure hPa : -
Rated speed rpm : 600
rack travel mm : 8.40
Tolerance mm : ± 0.10

MEASUREMENT

Rated speed rpm : 600
Pressure hPa : 390
rack travel mm : 10.95
Tolerance mm : ± 0.05

Pressure hPa : 210
rack travel mm : 9.50
Tolerance mm : ± 0.10

Start interlock

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 600
Del. quantity
cm³/1000 strokes : 116.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0

LOW IDLE

Rated speed rpm : 275
Del. quantity
cm³/1000 strokes : 38.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0
Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 27.01.97
Test oil : ISO 4113

Combination No. : 0 402 648 783

Injection pump
Pump designation : PE8P120A320LS7906
EP type number : 0 412 628 921

Governor
Governor design. : RQ750PA1326
Governor no. : 0 421 801 815

Cust. part No. : 04222 3938 KY

Customer-spec. information

Customer : KHD
Motor : BF8M1015/C
Power KW : 318.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 033

Inlet press. bar : 2.5
Tolerance bar : ± 0.1

Overflow quantity min. l/h : 200
Tolerance l/h : ± 20.0

Test nozzle holder assembly : 1 688 901 105

Opening pressure bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 689 750 075

Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant. per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 3.65
Tolerance mm : ± 0.05
Check tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 8- 7- 2- 6- 5
 : - 3- 1

Phasing : 0-45-90-135-180
 : -270-315
Tolerance : ± 0.30
Check tolerance *NW : ± 0.50

Start of delivery blocking

*NW after s.o.d. : 315.00
Tolerance : ± 0.50
Check tolerance *NW : ± 0.75

Barrel no. : 8

BASIC SETTING

Rated speed rpm : 700

Rack travel in mm : 12.60
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 365.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 4.0

Speed

Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 300

Del. quantity
cm³/1000 strokes : 20.0

Tolerance
cm³/1000 strokes : ± 3.0

Check tolerance
cm³/1000S. : ± 6.0

Speed

Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 715
guide sleeve
travel mm : 4.23
Tolerance mm : ± 0.15

Rated speed rpm : 610
guide sleeve
travel mm : 0.72
Tolerance mm : ± 0.25

Rated speed rpm : 900
guide sleeve
travel mm : 14.89
Tolerance mm : ± 0.25

Rated speed rpm : 862

guide sleeve
travel mm : 12.00
Tolerance mm : ± 0.25

Rated speed rpm : 930
guide sleeve
travel mm : 13.50
Tolerance mm : ± 0.50

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 700
Aneroid pressure
hPa : -

Del. quantity
cm³/1000 strokes : 365.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 4.0

Speed

Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 114.0
tolerance degree : ± 4.0

ASSEMBLY GOVERNOR SETTING

Rated speed rpm : 750
rack travel mm : 11.60

Rated speed rpm : 780
Tolerance 1/min : ± 4
rack travel mm : 5.50

rack travel mm : 0.50
Tolerance mm : ± 0.50
Rated speed rpm : 900

Rated speed rpm : 751
rack travel mm : 11.60

Rated speed rpm : 781
Tolerance 1/min : ± 4
rack travel mm : 5.50

rack travel mm : 0.50
Tolerance mm : ± 0.50

Rated speed rpm : 752
rack travel mm : 11.60

Rated speed rpm : 782
Tolerance 1/min : + 4
rack travel mm : 5.50

rack travel mm : 0.50
Tolerance mm : + 0.50
Rated speed rpm : 900

Rated speed rpm : 753
rack travel mm : 11.60

Rated speed rpm : 783
Tolerance 1/min : + 4
rack travel mm : 5.50

rack travel mm : 0.50
Tolerance mm : + 0.50

Rated speed rpm : 754
rack travel mm : 11.60

Rated speed rpm : 784
Tolerance 1/min : + 4
rack travel mm : 5.50

rack travel mm : 0.50
Tolerance mm : + 0.50
Rated speed rpm : 900

Rated speed rpm : 755
rack travel mm : 11.60

Rated speed rpm : 785
Tolerance 1/min : + 4
rack travel mm : 5.50

rack travel mm : 0.50
Tolerance mm : + 0.50

TORQUE CONTROL

Rated speed rpm : 700
rack travel mm : 12.60
Tolerance mm : + 0.05

Start interlock

Rated speed rpm : > 100
Rated speed rpm : < 560

Check speed 1/min : > 80
Check speed 1/min : < 580

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.25
Tolerance mm : + 0.75
Del. quantity cm³/1000 strokes : 200.0
Tolerance cm³/1000 strokes : + 15.0
Check tolerance cm³/1000S. : + 19.0

LOW IDLE

Rated speed rpm : 300
Del. quantity cm³/1000 strokes : 20.0
Tolerance cm³/1000 strokes : + 3.0
Check tolerance cm³/1000S. : + 6.0
Speed Tolerance cm³/1000 strokes : 8.0
Check tolerance cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 29.01.97
Test oil : ISO 4113

Combination No. : 0 402 648 793

Injection pump
Pump designation : PE8P120A320LS7873
EP type number : 0 412 628 880

Governor
Governor design. : RQ300/1050PA1268
Governor no. : 0 421 801 802

Cust. part No. : 04223118KY0165-17

Customer-spec. information
Customer : KHD
Motor : BF8M1015/C
Power KW : 400.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 047

Inlet press. bar : 2.0
Tolerance bar : ± 0.1

Overflow quantity
mfn. l/h : 160
Tolerance l/h : ± 20.0

Test nozzle holde
assembly : 1 688 901 105

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 075

Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 4.05
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 8- 7- 2- 6
 : - 4- 3

Phasing : 0-45-90-135-180
 : -270-315
Tolerance : ± 0.30
Check
tolerance *NW : ± 0.50

Start of delivery mark

Tolerance : ± 0.50
Check
tolerance *NW : ± 0.75

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1050

Rack travel in mm : 14.60
Tolerance mm : ± 0.05

<hr/>	
Del. quantity	
cm ³ /1000 strokes :	340.0
<hr/>	
Tolerance	
cm ³ /1000 strokes :	+ 1.0
<hr/>	
Check tolerance	
cm ³ /1000S.	: + 4.0
<hr/>	
Spread	
<hr/>	
Tolerance	
cm ³ /1000 strokes :	5.0
<hr/>	
Check tolerance	
cm ³ /1000S.	: 9.0
<hr/>	

Rated speed rpm :	300
Rack travel in mm :	5.00
Tolerance mm :	+ 0.10
Del. quantity	
cm ³ /1000 strokes :	20.0
Tolerance	
cm ³ /1000 strokes :	+ 3.0
Check tolerance	
cm ³ /1000S.	: + 6.0
Spread	
Tolerance	
cm ³ /1000 strokes :	8.0
Check tolerance	
cm ³ /1000S.	: 12.0

(B) SETTING OF INJECTION PUMP WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm :	1106
guide sleeve	
travel mm :	6.53
Tolerance mm :	+ 0.15
<hr/>	
Rated speed rpm :	300
guide sleeve	
travel mm :	1.66
Tolerance mm :	+ 0.20
<hr/>	
Rated speed rpm :	1050
guide sleeve	
travel mm :	6.00
Tolerance mm :	+ 0.10
<hr/>	
Rated speed rpm :	458

guide sleeve	
travel mm :	4.21
Tolerance mm :	+ 0.10
<hr/>	
Rated speed rpm :	580
guide sleeve	
travel mm :	6.00
Tolerance mm :	+ 0.10
<hr/>	
Rated speed rpm :	1290
guide sleeve	
travel mm :	11.50
Tolerance mm :	+ 0.50

GUIDE SLEEVE POSITION

control lever	
position degree :	90
Rated speed rpm :	700
<hr/>	
Rack travel in mm :	10.20
Tolerance mm :	+ 0.80

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm :	1050
Aneroid pressure	
hPa :	1600
Del. quantity	
cm ³ /1000 strokes :	340.0
Tolerance	
cm ³ /1000 strokes :	+ 1.0
Check tolerance	
cm ³ /1000S.	: + 4.0
Spread	
Tolerance	
cm ³ /1000 strokes :	5.0
Check tolerance	
cm ³ /1000S.	: 9.0

CONTROL LEVER

control lever	
position degree :	99.0
tolerance degree :	+ 4.0

RATED SPEED

rack travel mm :	13.60
Rated speed rpm :	1100
Tolerance 1/min :	+ 5
<hr/>	
rack travel mm :	4.00
Rated speed rpm :	1210
Tolerance 1/min :	+ 15

rack travel mm : 0.50
Tolerance mm : ± 0.50
Rated speed rpm : 1300

LOW IDLE

control lever
position degree : 72.0
tolerance degree : ± 4.0

Testing:

Rated speed rpm : 300
rack travel mm : 5.00
Tolerance mm : ± 0.10

rack travel mm : 2.00
Rated speed rpm : 415
Tolerance 1/min : ± 20

Rated speed rpm : 200
CRT mm min. : > 6.20

TORQUE CONTROL

Rated speed rpm : 1050
rack travel mm : 14.60
Tolerance mm : ± 0.05

ANEROID/ALTITUDE COMPENSATOR TEST

SETTING

Rated speed rpm : 400
Pressure hPa : 1600
rack travel mm : 14.60
Tolerance mm : ± 0.05

Pressure hPa : -
Rated speed rpm : 400
rack travel mm : 9.40
Tolerance mm : ± 0.20

MEASUREMENT

Rated speed rpm : 400
Pressure hPa : 570
rack travel mm : 11.10
Tolerance mm : ± 0.20

Pressure hPa : 1100
rack travel mm : 13.60
Tolerance mm : ± 0.05

Start interlock

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 400
Del. quantity
cm³/1000 strokes : 250.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 9.40
Tolerance mm : ± 0.75
Del. quantity
cm³/1000 strokes : 145.0
Tolerance
cm³/1000 strokes : ± 20.0
Check tolerance
cm³/1000S. : ± 24.0

LOW IDLE

Rated speed rpm : 300
Del. quantity
cm³/1000 strokes : 20.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 24.01.97
Test oil : ISO 4113

Combination No. : 0 402 676 838

Injection pump
Pump designation : PE6P120A320LS7909
EP type number : 0 412 626 963

Governor
Governor design. : RSV550...800POA671
Governor no. : 0 421 833 589

Cust. part No. : 0270743402

Customer-spec. information

Customer : MB-NFZ
Motor : OM441 LA eoromot
Power KW : 218.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 047

Inlet press. bar : 1.5
Tolerance bar : ± 0.1

Overflow quantity
min. l/h : 105
Tolerance l/h : ± 15.0

Test nozzle holder
assembly : 1 688 901 105

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 075

Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 5.25
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 20.50
Tolerance mm : ± 0.50

Firing order : 6- 3- 5- 2- 4-
: 1

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50

Start of delivery mark

Tolerance : ± 0.10
Check
tolerance °NW : ± 0.75

Barrel no. : 6

BASIC SETTING

Rated speed rpm : 780

Rack travel in mm : 14.50

Tolerance mm : +- 0.05

Del. quantity
cm3/1000 strokes : 229.0

Tolerance
cm3/1000 strokes : +- 1.0

Check tolerance
cm3/1000S. : +- 4.0

Spreed:

Tolerance
cm3/1000 strokes : 6.0

Check tolerance
cm3/1000S. : 9.0

Rated speed rpm : 550

Rack travel in mm : 4.30
Tolerance mm : +- 0.10

Del. quantity
cm3/1000 strokes : 19.0

Tolerance
cm3/1000 strokes : +- 3.0

Check tolerance
cm3/1000S. : +- 6.0

Spreed

Tolerance
cm3/1000 strokes : 8.0

Check tolerance
cm3/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : - 3
Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : +- 0.20

governor spring
pre-tension
click setting x : 2.50

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 780

Aneroid pressure
hPa : 1200

Del. quantity
cm3/1000 strokes : 229.0

Tolerance
cm3/1000 strokes : +- 1.0

Check tolerance
cm3/1000S. : +- 4.0

Spreed

Tolerance
cm3/1000 strokes : 6.0

Check tolerance
cm3/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 84.0

ASSEMBLY GOVERNOR SETTING

Rated speed rpm : 830
rack travel mm : 13.50

Rated speed rpm : 890
Tolerance 1/min : +- 4
rack travel mm : 4.00

rack travel mm : 0.85
Tolerance mm : +- 0.55

Rated speed rpm : 1300

Rated speed rpm : 831
rack travel mm : 13.50

Rated speed rpm : 891
Tolerance 1/min : +- 4
rack travel mm : 4.00

rack travel mm : 0.85
Tolerance mm : +- 0.55
Rated speed rpm : 1300

Rated speed rpm : 832
rack travel mm : 13.50

Rated speed rpm : 892
Tolerance 1/min : +- 4
rack travel mm : 4.00

rack travel mm : 0.85
Tolerance mm : +- 0.55
Rated speed rpm : 1300

Rated speed rpm : 833
rack travel mm : 13.50

Rated speed rpm : 893
Tolerance 1/min : + 4
rack travel mm : 4.00

rack travel mm : 0.85
Tolerance mm : + 0.55
Rated speed rpm : 1300

Rated speed rpm : 834
rack travel mm : 13.50

Rated speed rpm : 894
Tolerance 1/min : + 4
rack travel mm : 4.00

rack travel mm : 0.85
Tolerance mm : + 0.55
Rated speed rpm : 1300

Rated speed rpm : 835
rack travel mm : 13.50

Rated speed rpm : 895
Tolerance 1/min : + 4
rack travel mm : 4.00

rack travel mm : 0.85
Tolerance mm : + 0.55
Rated speed rpm : 1300

LOW IDLE

control lever
position degree : 74.0

Testing:

Rated speed rpm : 550
rack travel mm : 4.30
Tolerance mm : + 0.10

rack travel mm : 2.00
Rated speed rpm : 575
Tolerance 1/min : + 30

Rated speed rpm : 100
CRT mm min. : > 19.50

SET IDLE AUXILIARY SPRING

rack travel mm : 2.00

TORQUE CONTROL

Rated speed rpm : 780
rack travel mm : 14.50
Tolerance mm : + 0.05

Rated speed rpm : 700
rack travel mm : 14.50
Tolerance mm : + 0.10

ANEROID/ALTITUDE COMPENSATOR TEST

SETTING

Pressure hPa : -
Rated speed rpm : 500

MEASUREMENT

Pressure hPa : 400
rack travel mm : 1.20
Tolerance mm : + 0.05

Pressure hPa : 700
rack travel mm : 3.60
Tolerance mm : + 0.20

Start interlock

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1200
Rated speed rpm : 700

Del. quantity
cm³/1000 strokes : 234.0
Tolerance

cm³/1000 strokes : + 3.0
Check tolerance
cm³/1000S. : + 6.0

Spread
Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

Aneroid pressure
hPa : -
Rated speed rpm : 500

Del. quantity
cm³/1000 strokes : 138.0
Tolerance

cm³/1000 strokes : + 1.0

Check tolerance
cm³/1000s. : ± 4.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000s. : 12.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 250.0
Tolerance
cm³/1000 strokes : ± 15.0
Check tolerance
cm³/1000s. : ± 19.0

LOW IDLE

Rated speed rpm : 550
Del. quantity
cm³/1000 strokes : 19.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000s. : ± 6.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000s. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 04.10.96
Test oil : ISO 4113

Combination No. : 0 402 696 033

Injection pump
Pump designation : PE6H120/320LS4-2
EP type number : 0 412 626 003

Governor
Governor design. : RE36
Governor no. : 0 421 890 359

Cust. part No. : 0250745502

Customer-spec. information
Customer : MB-NFZ
Motor : OM 441 LA

TEST BENCH REQUIREMENTS

Inlet line : 3.2 ELAB

Test oil inlet temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 082

Inlet press. bar : 3.0
Tolerance bar : ± 0.1

Test nozzle holder assembly : 1 688 901 105

Opening pressure bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 089

Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 600

REMARKS

Pump-specific values in Section (B) must be observed!

(A) INJECTION PUMP SETTINGS
No basic setting.
Setting of constant delivery under Section C.

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 7.00
Tolerance mm : ± 0.05
Check tolerance mm : ± 0.10

Rack travel in. mm : 10.50
Tolerance mm : ± 0.50

Firing order : 6- 3- 5- 2- 4-
: 1

Phasing : 0-60-120-180-240
Tolerance : ± 0.50
Check tolerance °NW : ± 0.75

Start of delivery mark
Tolerance : ± 0.50
Check tolerance °NW : ± 0.75

Barrel no. : 6

(B) POSITIONER TESTING
Warm-up time: 3 minutes at
n=600 min⁻¹, Uact = 2.5 V

TESTING & SETTING RACK TRAVEL SENSOR POSITION

Engine speed min-1: 0

Setting point
(P, R and H pump)

Uact V : 3.100
 CRT mm : 13.00
 Tolerance mm : +/- 0.05
 Check tolerance mm : +/- 0.10

Check value
(F, R and H pump)

Uact V : 1.700
 CRT mm : 6.15
 Tolerance mm : +/- 0.25
 Check tolerance mm : +/- 0.30

Setting point
(M pump)

Uact V : 3.100
 CRT mm : 12.50
 Tolerance mm : +/- 0.05
 Check tolerance mm : +/- 0.10

Check value
(M pump)

Uact V : 1.700
 CRT mm : 5.50
 Tolerance mm : +/- 0.25
 Check tolerance mm : +/- 0.30

Stop position

Uact V : Value with
 deenergised adjusting magnet
 and control rod in
 stop position.

CRT mm : 0.75
 Tolerance mm : +/- 0.25
 Check tolerance mm : +/- 0.35

ENGINE-SPEED SENSOR
(ALL P and R pumps not
 H and M pumps)

Test with control rod
 in stop position

Engine speed min-1: 60
 Amplitude V : 1.4
 Tolerance V : +/- 0.6
 Check tolerance V : +/- 1.20

Engine speed min-1: 600
 Difference
 Amplitude to
 Amplitude V : max.1.4

(C) INJECTION PUMP WITH POSITIONER

TEST POINT V1

Rated speed rpm : 750
 Uact V : 3.000
 Prestroke solenoid
 Stroke mm : 7.00
 Del. quantity
 cm³/1000 strokes : 375.0
 Tolerance
 cm³/1000 strokes : +/- 1.0
 Check tolerance
 cm³/1000S. : +/- 4.0
 Spreed
 Tolerance
 cm³/1000 strokes : 5.0
 Check tolerance
 cm³/1000S. : 9.0

FUEL DELIVERY CHARACTERISTICS

Rated speed rpm : 1050
 Uact V : 3.000
 Prestroke solenoid
 Stroke mm : 7.00
 Del. quantity
 cm³/1000 strokes : 339.0
 Tolerance
 cm³/1000 strokes : +/- 3.0
 Check tolerance
 cm³/1000S. : +/- 6.0

Rated speed rpm : 550
 Uact V : 2.800
 Prestroke solenoid
 Stroke mm : 8.70
 Del. quantity
 cm³/1000 strokes : 367.0
 Tolerance
 cm³/1000 strokes : +/- 3.0
 Check tolerance
 cm³/1000S. : +/- 6.0

TEST POINT L1

Rated speed rpm : 300
Uact V : 1.500
Tolerance Volt : \pm 0.050
Check tolerance
Volt : \pm 0.060
Prestroke solenoid
Stroke mm : 8.00
Del. quantity
cm³/1000 strokes : 25.0
Tolerance
cm³/1000 strokes : \pm 3.0
Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 9.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
Uact V : 1.900
Prestroke solenoid
Stroke mm : 10.00
Del. quantity
cm³/1000 strokes : 106.0
Tolerance
cm³/1000 strokes : \pm 10.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 29.01.97
Test oil : ISO 4113
Combination No. : 0 402 736 889AA
Injection pump
Pump designation : PES6P120A12ORS7390
EP type number :
Governor
Governor design. : RQV350...1100PA1244K
Governor no. :

Cust. part No. : 3282739

Customer-spec. information
Customer : CUMMINS
Motor : 6CTAA
Power KW : 179.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2
Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 2 417 413 093
Inlet press. bar : 1.5
Overflow quantity
mfn. l/h : 90
Tolerance l/h : ± 10.0
Test nozzle holde
assembly : 1 688 901 101
Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

H05

Test lines : 1 680 750 008
Outside diameter : 6.0
x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0
Prestroke mm : 3.30
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10
Rack travel in mm : 20.50
Tolerance mm : ± 0.50
Firing order : 1- 5- 3- 6- 2-
: 4
Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50
Start of delivery blocking
°NW after s.o.d. : 7.70
Tolerance : ± 0.10
Check
tolerance °NW : ± 0.75
Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1100
Rack travel in mm : 13.70

Tolerance mm : + 0.05

Del. quantity
cm³/1000 strokes : 173.0

Tolerance
cm³/1000 strokes : + 1.0

Check tolerance
cm³/1000S. : + 4.0

Spread

Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 350

Rack travel in mm : 4.60
Tolerance mm : + 0.10

Del. quantity
cm³/1000 strokes : 18.0

Tolerance
cm³/1000 strokes : + 3.0

Check tolerance
cm³/1000S. : + 5.0

Spread

Tolerance
cm³/1000 strokes : 7.0

Check tolerance
cm³/1000S. : 11.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : - 1

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1100

Aneroid pressure
hPa : 1500

Del. quantity
cm³/1000 strokes : 173.0

Tolerance
cm³/1000 strokes : + 1.0

H06

Check tolerance
cm³/1000S. : + 4.0

Spread

Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

RATED SPEED

rack travel mm : 12.70

Rated speed rpm : 1145

Tolerance 1/min : + 5

Check
speed 1/min : + 20

rack travel mm : 0.50

Tolerance mm : + 0.50

Rated speed rpm : 1350

LOW IDLE

Testing:

Rated speed rpm : 350

rack travel mm : 4.60

Tolerance mm : + 0.10

Rated speed rpm : 350

TORQUE CONTROL

Rated speed rpm : 1100

rack travel mm : 13.70

Tolerance mm : + 0.05

Rated speed rpm : 700

rack travel mm : 13.85

Tolerance mm : + 0.10

Rated speed rpm : 500

rack travel mm : 12.95

Tolerance mm : + 0.15

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 700

Pressure hPa : 1500

rack travel mm : 13.20

Tolerance mm : + 0.10

Pressure hPa : -
Rated speed rpm : 700
rack travel mm : 10.10
Tolerance mm : ± 0.20

MEASUREMENT

Rated speed rpm : 700
Pressure hPa : 400
rack travel mm : 11.10
Tolerance mm : ± 0.20

Pressure hPa : 600
rack travel mm : 12.60
Tolerance mm : ± 0.05

Start interlock

Rated speed rpm : > 100
Rated speed rpm : < 290

Check speed 1/min : > 80
Check speed 1/min : < 300

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure hPa : 1500
Rated speed rpm : 700
Del. quantity cm³/1000 strokes : 171.0
Tolerance cm³/1000 strokes : ± 3.0
Check tolerance cm³/1000S. : ± 6.0
Speed Tolerance cm³/1000 strokes : 8.0
Check tolerance cm³/1000S. : 12.0

Aneroid pressure hPa : -
Rated speed rpm : 500
Del. quantity cm³/1000 strokes : 104.5
Tolerance cm³/1000 strokes : ± 2.0
Check tolerance cm³/1000S. : ± 4.0

STARTING FUEL DELIVERY

H07

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : ± 0.50
Del. quantity cm³/1000 strokes : 190.0
Tolerance cm³/1000 strokes : ± 20.0
Check tolerance cm³/1000S. : ± 24.0

LOW IDLE

Rated speed rpm : 350
Del. quantity cm³/1000 strokes : 18.0
Tolerance cm³/1000 strokes : ± 3.0
Check tolerance cm³/1000S. : ± 5.0
Speed Tolerance cm³/1000 strokes : 7.0
Check tolerance cm³/1000S. : 11.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 29.01.97
Test oil : ISO 4113

Combination No. : 0 402 746 908

Injection pump
Pump designation: : PES6P120A320R37232
EP type number : 0 412 726 846

Governor
Governor design. : RQV275...1000PA1001
Governor no. : 0 421 813 931

Cust. part No. : CCEP 5111A

Customer-spec. information:
Customer : RENAULT V.I.
Motor : MIDR 062045 E/3
Power KW : 249.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 071

Inlet press. bar : 2.5

Test nozzle holder
assembly : 1 688 901 105

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 089

Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 4.70
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 19.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50

Start of delivery mark

Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Barrel no. : 1

CRT ZERO POSITION

Rack travel in mm : 13.75
Tolerance mm : ± 0.05

BASIC SETTING

Rated speed rpm : 600

Del. quantity
cm³/1000 strokes : 265.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 4.0

SpreadTolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 275Rack travel in mm : -8.20
Tolerance mm : ± 0.10Del. quantity
cm³/1000 strokes : 31.0Tolerance
cm³/1000 strokes : ± 2.0Check tolerance
cm³/1000S. : ± 5.0**Spread**Tolerance
cm³/1000 strokes : 8.0Check tolerance
cm³/1000S. : 12.0

**(B) SETTING OF INJECTION PUMP
WITH GOVERNOR**

GUIDE SLEEVE TRAVELRated speed rpm : 1070
guide sleeve
travel mm : 8.30
Tolerance mm : ± 0.10Rated speed rpm : 275
guide sleeve
travel mm : 1.30
Tolerance mm : ± 0.20

Rated speed rpm : 850

guide sleeve
travel mm : 6.60
Tolerance mm : ± 0.20Rated speed rpm : 500
guide sleeve
travel mm : 3.90
Tolerance mm : ± 0.30Rated speed rpm : 1400
guide sleeve
travel mm : 11.50
Tolerance mm : ± 0.50

GUIDE SLEEVE POSITIONcontrol lever
position degree : - 1
Rated speed rpm : 1165Rack travel in mm : 13.60
Tolerance mm : ± 1.30

FULL LOAD DELIVERY AT FULL LOAD STOPRated speed rpm : 600
Aneroid pressure
hPa : 1000Del. quantity
cm³/1000 strokes : 265.0Tolerance
cm³/1000 strokes : ± 1.0Check tolerance
cm³/1000S. : ± 4.0**Spread**Tolerance
cm³/1000 strokes : 5.0Check tolerance
cm³/1000S. : 9.0

CONTROL LEVERcontrol lever
position degree : 302.0
tolerance degree : ± 4.0**RATED SPEED**
rack travel mm : -1.00
Rated speed rpm : 1080
Tolerance 1/min : ± 5rack travel mm : -9.70
Rated speed rpm : 1225
Tolerance 1/min : ± 15

rack travel mm : -13.25
Tolerance mm : + 0.55
Rated speed rpm : 1300

LOW IDLE

control lever
position degree : 247.0
tolerance degree : + 4.0

Testing:

Rated speed rpm : 275
rack travel mm : -8.20
Tolerance mm : + 0.10

Rated speed rpm : 200

CRT mm max. : < -6.70

Rated speed rpm : 370

TORQUE CONTROL

Rated speed rpm : 600

Rated speed rpm : 1000
Tolerance mm : + 0.10

Rated speed rpm : 500
rack travel mm : -5.50

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1000

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : -4.20
Tolerance mm : + 0.30

MEASUREMENT

Rated speed rpm : 500

Pressure hPa : 200
rack travel mm : -3.50
Tolerance mm : + 0.15

Pressure hPa : 520
rack travel mm : -0.85
Tolerance mm : + 0.05

Start interlock

Rated speed rpm : > 100
Rated speed rpm : < 225

Check
speed 1/min : > 80
Check
speed 1/min : < 245

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1000
Rated speed rpm : 1000
Del. quantity
cm³/1000 strokes : 244.0
Tolerance
cm³/1000 strokes : + 3.0
Check tolerance
cm³/1000S. : + 6.0

Aneroid pressure
hPa : 1000
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 91.0
Tolerance
cm³/1000 strokes : + 5.0
Check tolerance
cm³/1000S. : + 8.0
Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 122.0
Tolerance
cm³/1000 strokes : + 1.0
Check tolerance
cm³/1000S. : + 4.0

STARTING FUEL DELIVERY

Del. quantity
cm³/1000 strokes : 156.0
Tolerance
cm³/1000 strokes : + 15.0

Check tolerance
cm³/1000S. : ± 19.0

LOW IDLE

Rated speed rpm : 275
Del. quantity
cm³/1000 strokes : 31.0
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 5.0
Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 27.01.97
Test oil : ISO 4113

Combination No. : 0 402 748 812

Injection pump
Pump designation : PES8P120A720LS7425
EP type number : 0 412 728 814

Governor
Governor design. : RGV350...1200PA1310K
Governor no. : 0 421 815 541

Cust. part No. : CCEP 5164 66-136

Customer spec. information
Customer : RENAULT V.I.
Motor : MACK E9-750
Power KW : 552.0

TEST BENCH REQUIREMENTS

Inlet line : 4.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 077

Inlet press. bar : 2.0
Tolerance bar : ± 0.1

Overflow quantity
min. l/h : 190
Tolerance l/h : ± 20.0

Test nozzle holder
assembly : 1 688 901 105

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 089

Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 3.75
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.00
Tolerance mm : ± 0.50

Firing order : 1- 2- 7- 8- 4
 : - 6- 3

Phasing : 0-45-90-135-180
 : -270-315
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50

Start of delivery mark

°NW after s.o.d. : -0.15
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Barrel no. : 1

Beginning of delivery difference

betw. rack trav.
mm : 21.00
and maximum rack
travel : 10.00
Difference °CS : 4.25

CRT ZERO POSITION

Rack travel in mm : 13.30
Tolerance mm : +- 0.05

BASIC SETTING

Rated speed rpm : 1200

Del. quantity
cm³/1000 strokes : 305.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Speed

Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 8.0

Rated speed rpm : 325

Rack travel in mm : -6.40
Tolerance mm : +- 0.10

Del. quantity
cm³/1000 strokes : 53.0

Tolerance
cm³/1000 strokes : +- 2.0

Check tolerance
cm³/1000S. : +- 6.0

Speed

Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 1255

guide sleeve
travel mm : 9.50

Tolerance mm : +- 0.15

H13

Rated speed rpm : 350
guide sleeve
travel mm : 1.90
Tolerance mm : +- 0.20

Rated speed rpm : 833
guide sleeve
travel mm : 5.90
Tolerance mm : +- 0.25

Rated speed rpm : 480
guide sleeve
travel mm : 3.27
Tolerance mm : +- 0.25

Rated speed rpm : 1570
guide sleeve
travel mm : 13.50
Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

control lever
position degree : - 1
Rated speed rpm : 1390

Rack travel in mm : 12.30
Tolerance mm : +- 2.70

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1200
Aneroid pressure
hPa : 1200

Del. quantity
cm³/1000 strokes : 305.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Speed

Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 8.0

CONTROL LEVER

control lever
position degree : 117.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : -1.00

Rated speed rpm : 1250
Tolerance 1/min : + 5

rack travel mm : -9.30
Rated speed rpm : 1375
Tolerance 1/min : + 15

rack travel mm : -12.75
Tolerance mm : + 0.55
Rated speed rpm : 1450

LOW IDLE

control lever
position degree : 74.0
tolerance degree : + 4.0

Testing:

Rated speed rpm : 325
rack travel mm : -6.40
Tolerance mm : + 0.10

Rated speed rpm : 225

CRT mm max. : < -4.40

Rated speed rpm : 350

TORQUE CONTROL

Rated speed rpm : 1200

Rated speed rpm : 900
rack travel mm : -0.65
Tolerance mm : + 0.10

Rated speed rpm : 600
rack travel mm : -1.60
Tolerance mm : + 0.15

ANEROID/ALTITUDE COMPENSATOR TEST

SETTING

Rated speed rpm : 1200
Pressure hPa : 1200
Tolerance mm : + 0.10

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : -3.30

Tolerance mm : + 0.20

MEASUREMENT

Rated speed rpm : 1200

Pressure hPa : 640
rack travel mm : -2.70
Tolerance mm : + 0.20

Pressure hPa : 950
rack travel mm : -0.75
Tolerance mm : + 0.05

Start interlock

Rated speed rpm : > 250
Rated speed rpm : < 275

Check
speed 1/min : > 240
Check
speed 1/min : < 285

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1200
Rated speed rpm : 900
Del. quantity
cm³/1000 strokes : 293.0
Tolerance
cm³/1000 strokes : + 3.0
Check tolerance
cm³/1000S. : + 6.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 188.5
Tolerance
cm³/1000 strokes : + 1.0
Check tolerance
cm³/1000S. : + 4.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : + 0.50
Del. quantity
cm³/1000 strokes : 365.0
Tolerance
cm³/1000 strokes : + 15.0
Check tolerance
cm³/1000S. : + 19.0

LOW IDLE

Rated speed rpm : 325
Del. quantity
cm³/1000 strokes : 53.0
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 6.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 04.10.96
Test oil : ISO 4113
Combination No. : 0 402 796 033

Injection pump
Pump designation : PES6H120/720LS7
EP type number : 0 412 726 004

Governor
Governor design. : RE36
Governor no. : 0 421 890 360

Cust. part No. : G250745702

Customer-spec. information
Customer : MB-NFZ
Motor : OM 447 LA

TEST BENCH REQUIREMENTS

Inlet line : 3.2 EHAB

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 082

Inlet press. bar : 3.0
Tolerance bar : ± 0.1

Test nozzle holder
assembly : 1 688 901 105

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 089

Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 600

REMARKS

Pump-specific values
in Section (B)
must be observed!

(A) INJECTION PUMP SETTINGS
No basic setting.
Setting of constant delivery
under Section C.

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 7.00
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 0.50

Firing order : 6- 2- 4- 1- 5-
: 3

Phasing : 0-60-120-180-240
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Start of delivery mark
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Barrel no. : 6

(B) POSITIONER TESTING
Warm-up time: 3 minutes at
n=600 min⁻¹, Uact = 2.5 V

TESTING & SETTING RACK TRAVEL SENSOR POSITION

Engine speed min-1: 0

Setting point
(F, R and H pumps)

Uact V : 3.100
 CRT mm : 13.00
 Tolerance mm : +/- 0.05
 Check tolerance mm : +/- 0.10

Check value
(P, R and H pump)

Uact V : 1.700
 CRT mm : 6.15
 Tolerance mm : +/- 0.25
 Check tolerance mm : +/- 0.30

Setting point
(M pump)

Uact V : 3.100
 CRT mm : 12.50
 Tolerance mm : +/- 0.05
 Check tolerance mm : +/- 0.10

Check value
(M pump)

Uact V : 1.700
 CRT mm : 5.50
 Tolerance mm : +/- 0.25
 Check tolerance mm : +/- 0.30

Stop position

Uact V : Value with
 deenergised adjusting magnet
 and control rod in
 stop position.

CRT mm : 0.75
 Tolerance mm : +/- 0.25
 Check tolerance mm : +/- 0.35

ENGINE-SPEED SENSOR
(All P and R pumps not
 H and M pumps)

Test with control rod
 in stop position

Engine speed min-1: 60
 Amplitude V : 1.4
 Tolerance V : +/- 0.6
 Check tolerance V : +/- 1.20

Engine speed min-1: 600
 Difference Amplitude to
 Amplitude V : max.1.4

(C) INJECTION PUMP WITH POSITIONER

TEST POINT V1

Rated speed rpm : 800
 Uact V : 2.650
 Prestroke solenoid
 Stroke mm : 9.00
 Del. quantity
 cm³/1000 strokes : 302.0
 Tolerance
 cm³/1000 strokes : +/- 1.0
 Check tolerance
 cm³/1000S. : +/- 4.0
 Spreed
 Tolerance
 cm³/1000 strokes : 5.0
 Check tolerance
 cm³/1000S. : 9.0

FUEL DELIVERY CHARACTERISTICS

Rated speed rpm : 1100
 Uact V : 2.750
 Prestroke solenoid
 Stroke mm : 6.00
 Del. quantity
 cm³/1000 strokes : 302.0
 Tolerance
 cm³/1000 strokes : +/- 5.0
 Check tolerance
 cm³/1000S. : +/- 8.0

Rated speed rpm : 550
 Uact V : 2.350
 Prestroke solenoid
 Stroke mm : 9.00
 Del. quantity
 cm³/1000 strokes : 272.0
 Tolerance
 cm³/1000 strokes : +/- 8.0
 Check tolerance
 cm³/1000S. : +/- 11.0

TEST POINT L1

Rated speed rpm : 300
Uact V : 1.440
Tolerance Volt : ± 0.060
Check tolerance
Volt : ± 0.060
Prestroke solenoid
Stroke mm : 9.00
Del. quantity
cm³/1000 strokes : 25.0
Tolerance
cm³/1000 strokes : ± 3.0
Spread
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 9.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
Uact V : 1.900
Prestroke solenoid
Stroke mm : 9.00
Del. quantity
cm³/1000 strokes : 104.0
Tolerance
cm³/1000 strokes : ± 10.0

End of test specification sheet

TESTING & SETTING RACK TRAVEL SENSOR POSITION

Engine speed min-1: 0

Setting point
(P, R and H pump)

Uact V : 3.100
 CRT mm : 13.00
 Tolerance mm : +/- 0.05
 Check tolerance mm : +/- 0.10

Check value
(P, R and H pump)

Uact V : 1.700
 CRT mm : 6.15
 Tolerance mm : +/- 0.25
 Check tolerance mm : +/- 0.30

Setting point
(M pump)

Uact V : 3.100
 CRT mm : 12.50
 Tolerance mm : +/- 0.05
 Check tolerance mm : +/- 0.10

Check value
(M pump)

Uact V : 1.700
 CRT mm : 5.50
 Tolerance mm : +/- 0.25
 Check tolerance mm : +/- 0.30

Stop position

Uact V : Value with
 deenergised adjusting magnet
 and control rod in
 stop position.

CRT mm : 0.75
 Tolerance mm : +/- 0.25
 Check tolerance mm : +/- 0.35

ENGINE-SPEED SENSOR
(ALL P and R pumps not
 H and M pumps)

Test with control rod
 in stop position

Engine speed min-1: 60
 Amplitude V : 1.4
 Tolerance V : +/- 0.6
 Check tolerance V : +/- 1.20

Engine speed min-1: 600
 Difference Amplitude to
 Amplitude V : max.1.4

(C) INJECTION PUMP WITH POSITIONER

TEST POINT V1

Rated speed rpm : 750
 Uact V : 3.350
 Prestroke solenoid Stroke mm : 10.00
 Del. quantity cm³/1000 strokes : 328.0
 Tolerance cm³/1000 strokes : +/- 1.0
 Check tolerance cm³/1000S. : +/- 4.0
 Speed Tolerance cm³/1000 strokes : 5.0
 Check tolerance cm³/1000S. : 9.0

FUEL DELIVERY CHARACTERISTICS

Rated speed rpm : 750
 Uact V : 1.450
 Prestroke solenoid Stroke mm : 10.00
 Del. quantity cm³/1000 strokes : 72.0
 Tolerance cm³/1000 strokes : +/- 4.0
 Check tolerance cm³/1000S. : +/- 8.0
 Speed Tolerance cm³/1000 strokes : 4.0
 Check tolerance cm³/1000S. : 8.0

Rated speed rpm : 1000
 Uact V : 3.290
 Prestroke solenoid Stroke mm : 8.00
 Del. quantity cm³/1000 strokes : 310.0

Tolerance
cm³/1000 strokes : ± 4.0
Check tolerance
cm³/1000S. : ± 8.0

Rated speed rpm : 500
Uact V : 2.900
Prestroke solenoid
Stroke mm : 9.20
Del. quantity
cm³/1000 strokes : 303.0
Tolerance
cm³/1000 strokes : ± 5.0
Check tolerance
cm³/1000S. : ± 9.0

Rated speed rpm : 500
Uact V : 2.100
Prestroke solenoid
Stroke mm : 6.20
Del. quantity
cm³/1000 strokes : 174.0
Tolerance
cm³/1000 strokes : ± 4.0
Check tolerance
cm³/1000S. : ± 8.0

TEST POINT L1

Rated speed rpm : 300
Uact V : 1.500
Tolerance Volt : ± 0.060
Check tolerance
Volt : ± 0.080
Prestroke solenoid
Stroke mm : 7.20
Del. quantity
cm³/1000 strokes : 36.0
Tolerance
cm³/1000 strokes : ± 3.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
Uact V : 2.450
Prestroke solenoid
Stroke mm : 7.00
Del. quantity
cm³/1000 strokes : 183.0
Tolerance
cm³/1000 strokes : ± 10.0

Check tolerance
cm³/1000S. : ± 14.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 24.01.97
Test oil : ISO 4113
Combination No. : 0 402 796 814

Injection pump
Pump designation : PES6P120A720RS7367
EP type number : 0 412 726 932

Governor
Governor design. : RE30
Governor no. : 0 421 890 026

Cust. part No. :

Customer-spec. information
Customer : IVECO-FRANCE
Motor : 846U.41.600U

TEST BENCH REQUIREMENTS

Inlet line : 4.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 076

Inlet press. bar : 2.5
Tolerance bar : ± 0.1

Test nozzle holder
assembly : 1 688 901 105

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 089

Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 600

REMARKS

Pump-specific values
in Section (B)
must be observed!

(A) INJECTION PUMP SETTINGS
No basic setting.
Setting of constant delivery
under Section C.

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 2.85
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 20.50
Tolerance mm : ± 0.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Start of delivery blocking

Check
tolerance °NW : ± 0.40

Barrel no. : 1

(B) POSITIONER TESTING
Warm-up time: 3 minutes at
n=600 min⁻¹, Uact = 2.5 V

TESTING & SETTING RACK TRAVEL SENSOR POSITION

Engine speed min-1: 0

Setting point
(P, R and H pump)

Uact V : 3.100
 CRT mm : 13.00
 Tolerance mm : +/- 0.05
 Check tolerance mm : +/- 0.10

Check value
(P, R and H pump)

Uact V : 1.700
 CRT mm : 6.15
 Tolerance mm : +/- 0.25
 Check tolerance mm : +/- 0.30

Setting point
(M pump)

Uact V : 3.100
 CRT mm : 12.50
 Tolerance mm : +/- 0.05
 Check tolerance mm : +/- 0.10

Check value
(M pump)

Uact V : 1.700
 CRT mm : 5.50
 Tolerance mm : +/- 0.25
 Check tolerance mm : +/- 0.30

Stop position

Uact V : Value with
 deenergised adjusting magnet
 and control rod in
 stop position.

CRT mm : 0.75
 Tolerance mm : +/- 0.25
 Check tolerance mm : +/- 0.35

ENGINE-SPEED SENSOR
(All P and R pumps not
 H and M pumps)

Test with control rod
 in stop position

Engine speed min-1: 60
 Amplitude V : 1.4
 Tolerance V : +/- 0.6
 Check tolerance V : +/- 1.20

Engine speed min-1: 600
 Difference
 Amplitude to
 Amplitude V : max.1.4

(C) INJECTION PUMP WITH POSITIONER

TEST POINT V1

Rated speed rpm : 1050
 Uact V : 2.900
 Del. quantity
 cm³/1000 strokes : 296.0
 Tolerance
 cm³/1000 strokes : +/- 1.0
 Check tolerance
 cm³/1000S. : +/- 4.0
 Spread
 Tolerance
 cm³/1000 strokes : 5.0
 Check tolerance
 cm³/1000S. : 9.0

FUEL DELIVERY CHARACTERISTICS

Rated speed rpm : 500
 Uact V : 2.690
 Del. quantity
 cm³/1000 strokes : 238.0
 Tolerance
 cm³/1000 strokes : +/- 3.0
 Check tolerance
 cm³/1000S. : +/- 6.0

TEST POINT L1

Rated speed rpm : 275
 Uact V : 1.600
 Tolerance Volt : +/- 0.060
 Check tolerance
 Volt : +/- 0.080
 Del. quantity
 cm³/1000 strokes : 24.0
 Tolerance
 cm³/1000 strokes : +/- 3.0
 Spread
 Tolerance
 cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

End of test specification sheet



BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 23.01.97
Test oil : ISO 4113

Combination No. : 0 402 798 201

Injection pump
Pump designation : PES8H120/720LS1009
EP type number : 0 412 728 202

Governor
Governor design. : RE33
Governor no. : 0 421 890 362

Cust. part No. : 1364711

Customer-spec. information

Customer : SCANIA
Motor : DSC 1413/15
Power KW : 390.0

TEST BENCH REQUIREMENTS

Inlet line : 4(EHAB)

Test oil inlet
temp. °C : 40
Tolerance °C : + 2.0

Overflow valve : 2 417 413 082

Inlet press. bar : 3.0
Tolerance bar : + 0.1

Test nozzle holder
assembly : 1 688 901 105

Opening pressure
bar : 208.5
Tolerance bar : + 1.5

Test lines : 1 680 750 089

Outside diameter : 8.0

H25

x inside diameter : 3.0
x length mm : 600

REMARKS

Pump-specific values
in Section (B)
must be observed!

(A) INJECTION PUMP SETTINGS
No basic setting.
Setting of constant delivery
under Section C.

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : + 1.0

Prestroke mm : 8.00
Tolerance mm : + 0.05
Check
tolerance mm : + 0.10

Rack travel in mm : 10.50
Tolerance mm : + 0.50

Firing order : 1- 2- 7- 3- 4
 : - 6- 8

Phasing : 0-45-90-135-180
 : -270-315
Tolerance : + 0.50
Check
tolerance °NW : + 0.75

Start of delivery blocking
Tolerance : + 0.10
Check
tolerance °NW : + 0.75

Barrel no. : 1

(B) POSITIONER TESTING
Warm-up time: 3 minutes at
n=600 min⁻¹, Uact = 2.5 V

TESTING & SETTING RACK TRAVEL SENSOR POSITION

Engine speed min-1: 0

Setting point
(P, R and H pump)

Uact V : 3.100
 CRT mm : 13.00
 Tolerance mm : +/- 0.05
 Check tolerance mm : +/- 0.10

Check value
(P, R and H pump)

Uact V : 1.700
 CRT mm : 6.15
 Tolerance mm : +/- 0.25
 Check tolerance mm : +/- 0.30

Setting point
(M pump)

Uact V : 3.100
 CRT mm : 12.50
 Tolerance mm : +/- 0.05
 Check tolerance mm : +/- 0.10

Check value
(M pump)

Uact V : 1.700
 CRT mm : 5.50
 Tolerance mm : +/- 0.25
 Check tolerance mm : +/- 0.30

Stop position

Uact V : Value with
 deenergised adjusting magnet
 and control rod in
 stop position.

CRT mm : 0.75
 Tolerance mm : +/- 0.25
 Check tolerance mm : +/- 0.35

ENGINE-SPEED SENSOR
(All P and R pumps not
 H and M pumps)

Test with control rod
 in stop position

Engine speed min-1: 60
 Amplitude V : 1.4
 Tolerance V : +/- 0.6
 Check tolerance V : +/- 1.20

Engine speed min-1: 600
 Difference Amplitude to
 Amplitude V : max.1.4

(C) INJECTION PUMP WITH POSITIONER

TEST POINT V1

Rated speed rpm : 700
 Uact V : 3.150
 Prestroke solenoid Stroke mm : 7.60
 Del. quantity cm³/1000 strokes : 344.5
 Tolerance cm³/1000 strokes : +/- 1.0
 Check tolerance cm³/1000s. : +/- 6.0
 Spread Tolerance cm³/1000 strokes : 8.0
 Check tolerance cm³/1000s. : 12.0

FUEL DELIVERY CHARACTERISTICS

Rated speed rpm : 950
 Uact V : 3.450
 Prestroke solenoid Stroke mm : 8.20
 Del. quantity cm³/1000 strokes : 365.0
 Tolerance cm³/1000 strokes : +/- 4.0
 Check tolerance cm³/1000s. : +/- 7.0

TEST POINT L1

Rated speed rpm : 250
 Uact V : 1.400
 Tolerance Volt : +/- 0.060
 Check tolerance Volt : +/- 0.060
 Prestroke solenoid Stroke mm : 9.50
 Del. quantity cm³/1000 strokes : 31.0

Tolerance
cm³/1000 strokes : +- 3.0
Speed
Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 8.0

End of test specification sheet



BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 22.01.97
Test oil : ISO 4113
Combination No. : 0 403 244 056
Injection pump
Pump designation : PES4MW100/72GRS1525
EP type number : 0 413 204 022
Governor
Governor design. : RQ300/1300MW160
Governor no. : 0 420 082 077

Cust. part No. : 0270749502

Customer-spec. information
Customer : MB-NFZ
Motor : OM364LA
Power KW : 103.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1
Test oil inlet temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 1 419 992 198
Inlet press. bar : 1.5
Test nozzle holder assembly : 1 688 901 101
Opening pressure bar : 208.5
Tolerance bar : ± 1.5
Test lines : 1 680 750 089
Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 31.0
Tolerance bar : ± 1.0
Prestroke mm : 4.55
Tolerance mm : ± 0.05
Check tolerance mm : ± 0.10
Rack travel in mm : 20.00
Tolerance mm : ± 1.00
Firing order : 1- 3- 4- 2
Phasing : 0-90-180-270
Tolerance : ± 0.50
Check tolerance °NW : ± 0.75

BASIC SETTING

Rated speed rpm : 1300
Rack travel in mm : 13.30
Tolerance mm : ± 0.05
Del. quantity cm³/1000 strokes : 119.0
Tolerance cm³/1000 strokes : ± 1.0
Check tolerance cm³/1000S. : ± 3.0
Speed

Tolerance
 cm³/1000 strokes : 3.5

Check tolerance
 cm³/1000S. : 6.0

Rated speed rpm : 300

Rack travel in mm : 3.90
 Tolerance mm : + 0.10

Del. quantity
 cm³/1000 strokes : 12.0
 Tolerance
 cm³/1000 strokes : + 2.0
 Check tolerance
 cm³/1000S. : + 4.5

Spread
 Tolerance
 cm³/1000 strokes : 3.5
 Check tolerance
 cm³/1000S. : 5.5

(B) SETTING OF INJECTION PUMP
 WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 1353
 guide sleeve
 travel mm : 6.52
 Tolerance mm : + 0.15

Rated speed rpm : 300
 guide sleeve
 travel mm : 1.12
 Tolerance mm : + 0.20

Rated speed rpm : 1300
 guide sleeve
 travel mm : 6.00
 Tolerance mm : + 0.10

Rated speed rpm : 458
 guide sleeve
 travel mm : 2.45
 Tolerance mm : + 0.10

Rated speed rpm : 750
 guide sleeve
 travel mm : 6.00
 Tolerance mm : + 0.10

Rated speed rpm : 1570
 guide sleeve
 travel mm : 11.50
 Tolerance mm : + 0.50

GUIDE SLEEVE POSITION

control lever
 position degree : VL

control lever
 position degree : 109
 Rated speed rpm : 800

Rack travel in mm : 20.00
 Tolerance mm : + 0.80

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1300
 Aneroid pressure
 hPa : 1200

Del. quantity
 cm³/1000 strokes : 119.0
 Tolerance
 cm³/1000 strokes : + 1.0
 Check tolerance
 cm³/1000S. : + 3.0

Spread
 Tolerance
 cm³/1000 strokes : 3.5
 Check tolerance
 cm³/1000S. : 6.0

CONTROL LEVER

control lever
 position degree : 95.0
 tolerance degree : + 4.0

RATED SPEED

rack travel mm : 12.30
 Rated speed rpm : 1345
 Tolerance 1/min : + 5

rack travel mm : 4.00
 Rated speed rpm : 1465
 Tolerance 1/min : + 15

rack travel mm : 0.50
 Tolerance mm : + 0.50
 Rated speed rpm : 1575

LOW IDLE

control lever
position degree : 69.0
tolerance degree : ± 4.0

Testing:

Rated speed rpm : 300
rack travel mm : 3.90
Tolerance mm : ± 0.10

Rated speed rpm : 200
CRT mm min. : > 4.30

TORQUE CONTROL

Rated speed rpm : 1300
rack travel mm : 13.30
Tolerance mm : ± 0.05

Rated speed rpm : 750
rack travel mm : 13.30
Tolerance mm : ± 0.20

ANEROID/ALTITUDE COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1200
rack travel mm : 13.30
Tolerance mm : ± 0.05

Pressure hPa : -
Rated speed rpm : 500
Tolerance mm : ± 0.10

MEASUREMENT

Rated speed rpm : 500
Pressure hPa : 400
rack travel mm : 2.00
Tolerance mm : ± 0.10

Pressure hPa : 200
rack travel mm : 0.50
Tolerance mm : ± 0.10

Start interlock

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1200
Rated speed rpm : 750
Del. quantity
cm³/1000 strokes : 116.0
Tolerance
cm³/1000 strokes : ± 1.5
Check tolerance
cm³/1000S. : ± 4.0
Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 9.0

Aneroid pressure
hPa : 1200
Rated speed rpm : 1300
Del. quantity
cm³/1000 strokes : 105.0
Tolerance
cm³/1000 strokes : ± 1.5
Check tolerance
cm³/1000S. : ± 3.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 73.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 3.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 150.0
Tolerance
cm³/1000 strokes : ± 5.0
Check tolerance
cm³/1000S. : ± 8.0

LOW IDLE

Rated speed rpm : 300
Del. quantity
cm³/1000 strokes : 12.0
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 4.5
Spreed

Tolerance
cm3/1000 strokes : 3.5
Check tolerance
cm3/1000S. : 5.5

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 23.01.97
Test oil : ISO 4113
Combination No. : 0 403 474 008I
Injection pump
Pump designation : PES4MW100/720RS1181
EP type number : 0 413 404 107
Governor
Governor design. : RSV400...1000MW1A333
Governor no. : 0 420 085 118

Cust. part No. : 9881020

Customer-spec. information
Customer : LIEBHERR
Motor : D924T-E A2
Power KW : 75.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1
Test oil inlet temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 1 417 413 049
Inlet press. bar : 1.5
Test nozzle holder assembly : 0 681 343 009
Opening pressure bar : 173.5
Tolerance bar : ± 1.5
Test Lines : 1 680 750 008
Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 31.0
Tolerance bar : ± 1.0

Prestroke mm : 3.05
Tolerance mm : ± 0.05
Check tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 3- 4- 2

Phasing : 0-90-180-270
Tolerance : ± 0.50
Check tolerance °NW : ± 0.75

BASIC SETTING

Rated speed rpm : 740

Rack travel in mm : 11.45
Tolerance mm : ± 0.05

Del. quantity cm³/1000 strokes : 141.5

Tolerance cm³/1000 strokes : ± 1.0

Check tolerance cm³/1000S. : ± 4.0

Speed
Tolerance cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 7.5

Rated speed rpm : 400

Rack travel in mm : 5.00
Tolerance mm : + 0.10

Del. quantity
cm³/1000 strokes : 9.0

Tolerance
cm³/1000 strokes : + 2.0

Check tolerance
cm³/1000S. : + 4.5

Speed
Tolerance
cm³/1000 strokes : 3.5

Check tolerance
cm³/1000S. : 5.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : - 3
Rated speed rpm : 800

Rack travel in mm : 0.65
Tolerance mm : + 0.35

governor spring
pre-tension
click setting x : 1.50

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 740

Aneroid pressure
hPa : -

Del. quantity
cm³/1000 strokes : 141.5

Tolerance
cm³/1000 strokes : + 1.0

Check tolerance
cm³/1000S. : + 4.0

Speed
Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 7.5

CONTROL LEVER

control lever
position degree : 81.5
tolerance degree : + 4.0

RATED SPEED

rack travel mm : 10.45
Rated speed rpm : 760
Tolerance 1/min : + 5

rack travel mm : 4.00
Rated speed rpm : 775

Tolerance 1/min : + 5

rack travel mm : 1.00
Tolerance mm : + 0.70

Rated speed rpm : 950

rack travel mm : 4.00
Rated speed rpm : 790

LOW IDLE

control lever
position degree : 66.5
tolerance degree : + 4.0

Setting point w/out bumper spring

Rated speed rpm : 400
rack travel mm : 3.75
Tolerance mm : + 0.10

Testing:

Rated speed rpm : 400
rack travel mm : 5.00
Tolerance mm : + 0.10

rack travel mm : 2.00
Rated speed rpm : 500
Tolerance 1/min : + 30

Rated speed rpm : 100

CRT mm min. : > 19.00

TORQUE CONTROL

Rated speed rpm : 740
rack travel mm : 11.45
Tolerance mm : + 0.05

Rated speed rpm : 500
rack travel mm : 11.45
Tolerance mm : \pm 0.05

Rated speed rpm : 750
rack travel mm : 10.80
Tolerance mm : \pm 0.05

Start interlock

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 132.0
Tolerance
cm³/1000 strokes : \pm 2.0
Check tolerance
cm³/1000S. : \pm 5.0
Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 9.0

Aneroid pressure
hPa : --
Rated speed rpm : 750
Del. quantity
cm³/1000 strokes : 131.0
Tolerance
cm³/1000 strokes : \pm 1.0
Check tolerance
cm³/1000S. : \pm 4.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.25
Tolerance mm : \pm 0.75
Del. quantity
cm³/1000 strokes : 135.0
Tolerance
cm³/1000 strokes : \pm 5.0
Check tolerance
cm³/1000S. : \pm 8.0

LOW IDLE

Rated speed rpm : 400
Del. quantity
cm³/1000 strokes : 9.0
Tolerance
cm³/1000 strokes : \pm 2.0
Check tolerance
cm³/1000S. : \pm 4.5
Spreed
Tolerance
cm³/1000 strokes : 3.5
Check tolerance
cm³/1000S. : 5.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 29.01.97
Test oil : ISO 4113
Combination No. : 0 403 476 147
Injection pump
Pump designation : PES6MM100/720RS1131
: 1
EP type number : 0 413 406 165
Governor
Governor design. : RSV750...1200MWOA329
: -17
Governor no. : 0 420 085 291
Cust. part No. : 0270747902

Customer-spec. information
Customer : MB-NFZ
Motor : OM366LA
Power KW : 163.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1
Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 1 419 992 198
Inlet press. bar : 1.5
Test nozzle holder
assembly : 1 688 901 101
Opening pressure
bar : 208.5
Tolerance bar : ± 1.5
Test lines : 1 680 750 089

J07

Outside diameter : 8.0
x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 31.0
Tolerance bar : ± 1.0
Prestroke mm : 3.65
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10
Rack travel in mm : 10.50
Tolerance mm : ± 1.50
Firing order : 1- 5- 3- 6- 2-
: 4
Phasing : 0-60-120-180-240
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

BASIC SETTING

Rated speed rpm : 1180
Rack travel in mm : 13.15
Tolerance mm : ± 0.05
Del. quantity
cm³/1000 strokes : 104.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 3.0
Speed

Tolerance
 cm³/1000 strokes : 3.5

Check tolerance
 cm³/1000S. : 6.0

Rated speed rpm : 750

Rack travel in mm : 4.70
 Tolerance mm : + 0.25

Del. quantity
 cm³/1000 strokes : 12.0
 Tolerance
 cm³/1000 strokes : + 2.0
 Check tolerance
 cm³/1000S. : + 4.5

Spreed
 Tolerance
 cm³/1000 strokes : 3.5
 Check tolerance
 cm³/1000S. : 5.5

(B) SETTING OF INJECTION PUMP
 WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
 position degree : - 3
 Rated speed rpm : 800

Rack travel in mm : 0.65
 Tolerance mm : + 0.35

governor spring
 pre-tension
 click setting x : 4.75

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1180
 Aneroid pressure
 hPa : 1000

Del. quantity
 cm³/1000 strokes : 104.0
 Tolerance
 cm³/1000 strokes : + 1.0
 Check tolerance
 cm³/1000S. : + 3.0

Spreed
 Tolerance
 cm³/1000 strokes : 3.5

Check tolerance
 cm³/1000S. : 6.0

CONTROL LEVER

control lever
 position degree : 103.0
 tolerance degree : + 4.0

RATED SPEED

rack travel mm : 1.00
 Tolerance mm : + 0.70
 Rated speed rpm : 1400

ASSEMBLY GOVERNOR SETTING

Rated speed rpm : 1230
 rack travel mm : 12.10

Rated speed rpm : 1300
 Tolerance 1/min : + 4
 rack travel mm : 4.00

Rated speed rpm : 1231
 rack travel mm : 12.10

Rated speed rpm : 1301
 Tolerance 1/min : + 4
 rack travel mm : 4.00

Rated speed rpm : 1232
 rack travel mm : 12.10

Rated speed rpm : 1302
 Tolerance 1/min : + 4
 rack travel mm : 4.00

Rated speed rpm : 1233
 rack travel mm : 12.10

Rated speed rpm : 1303
 Tolerance 1/min : + 4
 rack travel mm : 4.00

Rated speed rpm : 1238
 rack travel mm : 12.10

Rated speed rpm : 1308
 Tolerance 1/min : + 4
 rack travel mm : 4.00

Rated speed rpm : 1239

rack travel mm : 12.10
Rated speed rpm : 1309
Tolerance 1/min : + 4
rack travel mm : 4.00

LOW IDLE

control lever
position degree : 36.0
tolerance degree : + 4.0

Testing:

Rated speed rpm : 750
rack travel mm : 4.70
Tolerance mm : + 0.25

rack travel mm : 2.00
Rated speed rpm : 785
Tolerance 1/min : + 25

Rated speed rpm : 100

CRT mm min. : > 19.00

TORQUE CONTROL

Rated speed rpm : 1180
rack travel mm : 13.15
Tolerance mm : + 0.05

Rated speed rpm : 600
rack travel mm : 13.15
Tolerance mm : + 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1000
rack travel mm : 13.15
Tolerance mm : + 0.05

Pressure hPa : -
Rated speed rpm : 500
Tolerance mm : + 0.10

MEASUREMENT

Rated speed rpm : 500

Pressure hPa : 500

J09

rack travel mm : 2.25
Tolerance mm : + 0.15
Pressure hPa : 350
rack travel mm : 1.10
Tolerance mm : + 0.05

Start interlock

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1000
Rated speed rpm : 600
Del. quantity
cm³/1000 strokes : 97.0

Tolerance
cm³/1000 strokes : + 1.5
Check tolerance
cm³/1000S. : + 4.0

Spread
Tolerance
cm³/1000 strokes : 5.0
Check tolerance
cm³/1000S. : 7.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 43.0
Tolerance
cm³/1000 strokes : + 1.0
Check tolerance
cm³/1000S. : + 3.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 105.0
Tolerance
cm³/1000 strokes : + 5.0
Check tolerance
cm³/1000S. : + 8.0

LOW IDLE

Rated speed rpm : 750
Del. quantity
cm³/1000 strokes : 12.0
Tolerance
cm³/1000 strokes : + 2.0

Check tolerance
cm³/1000S. : ± 4.5
Spread
Tolerance
cm³/1000 strokes : 3.5
Check tolerance
cm³/1000S. : 5.5

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 22.01.97
Test oil : ISO 4113

Combination No. : 9 400 087 497

Injection pump
Pump designation : PES6P120A120RS3344
EP type number : 9 400 087 090

Governor
Governor design. : RQV350...1100PA1207
Governor no. : 9 420 080 379

Cust. part No. : 3355976

Customer-spec. information
Customer : CUMMINS
Motor : 6 CTA - 290
Power KW : 214.6

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 076

Inlet press. bar : 3.0

Test nozzle holder
assembly : 1 688 901 019

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 008

Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 4.15
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 15.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240

Start of delivery blocking

*NW after s.o.d. : 7.50
Tolerance : ± 0.10
Check
tolerance *NW : ± 0.23

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1100

Rack travel in mm : 15.55
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 207.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spread

Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 325

Rack travel in mm : 6.80

Tolerance mm : +- 0.10

Del. quantity
cm³/1000 strokes : 44.0

Tolerance
cm³/1000 strokes : +- 3.0

Check tolerance
cm³/1000S. : +- 6.0

Spread

Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 650
guide sleeve

travel mm : 5.55
Tolerance mm : +- 0.25

Rated speed rpm : 1150
guide sleeve

travel mm : 8.40
Tolerance mm : +- 0.10

Rated speed rpm : 350
guide sleeve

travel mm : 1.55
Tolerance mm : +- 0.25

Rated speed rpm : 500
guide sleeve

travel mm : 4.05
Tolerance mm : +- 0.25

Rated speed rpm : 1400
guide sleeve

travel mm : 10.55

Tolerance mm : +- 0.25

GUIDE SLEEVE POSITION

control lever
position degree : - 1
Rated speed rpm : 1150

Rack travel in mm : 16.50

Tolerance mm : +- 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1100

Aneroid pressure
hPa : 1300

Del. quantity
cm³/1000 strokes : 207.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spread

Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 63.0
tolerance degree : +- 4.0

control lever
position degree : 118.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 14.50
Rated speed rpm : 1150

Tolerance 1/min : +- 5

rack travel mm : 4.00
Rated speed rpm : 1360

Tolerance 1/min : +- 15

rack travel mm : 0.50
Tolerance mm : +- 0.50

Rated speed rpm : 1500

LOW IDLE

control lever
position degree : 69.0
tolerance degree : ± 4.0

control lever
position degree : 14.0
tolerance degree : ± 4.0

Testing:

Rated speed rpm : 325
rack travel mm : 6.80
Tolerance mm : ± 0.10

Rated speed rpm : 100

CRT mm min. : > 9.50

Rated speed rpm : 375

TORQUE CONTROL

Rated speed rpm : 1100
rack travel mm : 15.55
Tolerance mm : ± 0.05

Rated speed rpm : 700
rack travel mm : 15.95
Tolerance mm : ± 0.05

Rated speed rpm : 720
rack travel mm : 15.95
Tolerance mm : ± 0.05

Rated speed rpm : 960
rack travel mm : 15.55
Tolerance mm : ± 0.05

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1300
rack travel mm : 15.95
Tolerance mm : ± 0.05

Pressure hPa : -
Rated speed rpm : 500

MEASUREMENT

Rated speed rpm : 500

Pressure hPa : 800
rack travel mm : 2.65
Tolerance mm : ± 0.15

Pressure hPa : 400
rack travel mm : 1.00
Tolerance mm : ± 0.10

Start interlock

Rated speed rpm : > 100
Rated speed rpm : < 270

Check
speed 1/min : > 80
Check
speed 1/min : < 290

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1300
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 217.0
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 5.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 125.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.00
Tolerance mm : ± 1.00
Del. quantity
cm³/1000 strokes : 190.0
Tolerance
cm³/1000 strokes : ± 10.0
Check tolerance
cm³/1000S. : ± 14.0

LOW IDLE

Rated speed rpm : 325
Del. quantity
cm³/1000 strokes : 44.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 29.01.97
Test oil : ISO 4113
Combination No. : ~~3~~ 400 087 471
Injection pump
Pump designation : PE6P120A32ORS3178
EP type number : 0 411 826 752
Governor
Governor design. : RQV25U...950PA921-3
Governor no. : 0 421 813 786
Cust. part No. : 8125313-P02

Customer-spec. information
Customer : VOLVO-TRUCK
Motor : TD 122 F
Power kW : 261.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1
Test oil inlet temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 1 417 413 025
Inlet press. bar : 1.5
Test nozzle holder assembly : 1 688 901 019
Opening pressure bar : 208.5
Tolerance bar : ± 1.5
Test lines : 1 680 750 067
Outside diameter : 6.0

x inside diameter : 3.0
x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0
Prestroke mm : 3.65
Tolerance mm : ± 0.05
Check tolerance mm : ± 0.10
Rack travel in mm : 10.50
Tolerance mm : ± 1.50
Firing order : 1- 5- 3- 6- 2-
: 4
Phasing : 0-60-120-180-240
Tolerance : ± 0.50
Check tolerance °NW : ± 0.75

BASIC SETTING

Rated speed rpm : 700
Rack travel in mm : 13.05
Tolerance mm : ± 0.05
Del. quantity cm³/1000 strokes : 230.0
Tolerance cm³/1000 strokes : ± 1.0
Check tolerance cm³/1000S. : ± 4.0
Speed

Tolerance
 cm³/1000 strokes : 5.0

Check tolerance
 cm³/1000S. : 9.0

Rated speed rpm : 250

Rack travel in mm : 4.70
 Tolerance mm : + 0.10

Del. quantity
 cm³/1000 strokes : 20.0
 Tolerance
 cm³/1000 strokes : + 3.0
 Check tolerance
 cm³/1000S. : + 6.0

Speed
 Tolerance
 cm³/1000 strokes : 8.0
 Check tolerance
 cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
 WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 985
 guide sleeve
 travel mm : 8.20
 Tolerance mm : + 0.10

Rated speed rpm : 250
 guide sleeve
 travel mm : 1.20
 Tolerance mm : + 0.20

Rated speed rpm : 450
 guide sleeve
 travel mm : 3.90
 Tolerance mm : + 0.30

Rated speed rpm : 700
 guide sleeve
 travel mm : 6.50
 Tolerance mm : + 0.20

Rated speed rpm : 1060
 guide sleeve
 travel mm : 9.60
 Tolerance mm : + 0.20

GUIDE SLEEVE POSITION

control lever
 position degree : - 1
 Rated speed rpm : 1030

Rack travel in mm : 16.50
 Tolerance mm : + 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 700
 Aneroid pressure
 hPa : 900
 Del. quantity
 cm³/1000 strokes : 230.0
 Tolerance
 cm³/1000 strokes : + 1.0
 Check tolerance
 cm³/1000S. : + 4.0

Speed
 Tolerance
 cm³/1000 strokes : 5.0
 Check tolerance
 cm³/1000S. : 9.0

CONTROL LEVER

control lever
 position degree : 64.0
 tolerance degree : + 4.0

control lever
 position degree : 120.0
 tolerance degree : + 4.0

RATED SPEED
 rack travel mm : 12.00
 Rated speed rpm : 985
 Tolerance 1/min : + 5

rack travel mm : 4.00
 Rated speed rpm : 1075
 Tolerance 1/min : + 15

rack travel mm : 0.50
 Tolerance mm : + 0.50
 Rated speed rpm : 1200

LOW IDLE

control lever
 position degree : 64.0
 tolerance degree : + 4.0

control lever
position degree : 9.0
tolerance degree : ± 4.0

Testing:

Rated speed rpm : 250
rack travel mm : 4.70
Tolerance mm : ± 0.10

Rated speed rpm : 100
CKT mm min. : > 6.20

Rated speed rpm : 315

TORQUE CONTROL

Rated speed rpm : 700
rack travel mm : 13.05
Tolerance mm : ± 0.05

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 900
rack travel mm : 13.05
Tolerance mm : ± 0.05

Pressure hPa : -
Rated speed rpm : 500

MEASUREMENT

Rated speed rpm : 500
Pressure hPa : 600
rack travel mm : 2.50
Tolerance mm : ± 0.10

Pressure hPa : 120
rack travel mm : 0.35
Tolerance mm : ± 0.05

Start interlock

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 700

Del. quantity
cm³/1000 strokes : 164.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000s. : ± 4.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : ± 0.50
Del. quantity
cm³/1000 strokes : 290.0
Tolerance
cm³/1000 strokes : ± 10.0
Check tolerance
cm³/1000s. : ± 14.0

LOW IDLE

Rated speed rpm : 250
Del. quantity
cm³/1000 strokes : 20.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000s. : ± 6.0
Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000s. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 29.01.97
Test oil : ISO 4113

Combination No. : 9 400 087 499

Injection pump
Pump designation : PE6P110A720RS3289-1
EP type number : 0 411 816 795

Governor
Governor design. : RSV350...900P1A600
Governor no. : 9 420 082 331

Cust. part No. : 1371920

Customer-spec. information
Customer : SCANIA
Motor : DS1193A
Power KW : 211.0

TEST BENCH REQUIREMENTS

Inlet line : 4.2

Vibration damper
(RoBo diaphragm) : 3.1

Test oil inlet temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 025

Inlet press. bar : 1.5
Tolerance bar : ± 0.1

Test nozzle holder assembly : 1 688 901 104

Opening pressure bar : 251.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 008

Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 3.35
Tolerance mm : ± 0.05
Check tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check tolerance °NW : ± 0.75

BASIC SETTING

Rated speed rpm : 850

Rack travel in mm : 12.35
Tolerance mm : ± 0.05

Del. quantity cm³/1000 strokes : 168.0

Tolerance cm³/1000 strokes : ± 1.0

Check tolerance cm³/1000S. : ± 4.0

<hr/>	
Speed	
Tolerance	
cm ³ /1000 strokes :	4.0
<hr/>	
Check tolerance	
cm ³ /1000S. :	7.5
<hr/>	
Rated speed rpm :	350
Rack travel in mm :	6.00
Tolerance mm :	+ 0.10
Del. quantity	
cm ³ /1000 strokes :	15.5
Tolerance	
cm ³ /1000 strokes :	+ 2.5
Check tolerance	
cm ³ /1000S. :	+ 5.0
Speed	
Tolerance	
cm ³ /1000 strokes :	4.5
Check tolerance	
cm ³ /1000S. :	7.5

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever	
position degree :	- 3
Rated speed rpm :	800
Rack travel in mm :	0.50
Tolerance mm :	+ 0.20
governor spring	
pre-tension	
click setting x :	2.75

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm :	850
Aneroid pressure	
hPa :	1200
Del. quantity	
cm ³ /1000 strokes :	168.0
Tolerance	
cm ³ /1000 strokes :	+ 1.0
Check tolerance	
cm ³ /1000S. :	+ 4.0
Speed	

Tolerance	
cm ³ /1000 strokes :	4.0
Check tolerance	
cm ³ /1000S. :	7.5

CONTROL LEVER

control lever	
position degree :	41.0
tolerance degree :	+ 4.0
control lever	
position degree :	91.0
tolerance degree :	+ 4.0

ASSEMBLY GOVERNOR SETTING

Rated speed rpm :	900
rack travel mm :	11.30
Rated speed rpm :	929
Tolerance 1/min :	+ 4
rack travel mm :	4.00
rack travel mm :	0.50
Tolerance mm :	+ 0.50
Rated speed rpm :	1000

Rated speed rpm :	901
rack travel mm :	11.30
Rated speed rpm :	930
Tolerance 1/min :	+ 4
rack travel mm :	4.00

rack travel mm :	0.50
Tolerance mm :	+ 0.50
Rated speed rpm :	1000

Rated speed rpm :	902
rack travel mm :	11.30

Rated speed rpm :	931
Tolerance 1/min :	+ 4
rack travel mm :	4.00

rack travel mm :	0.50
Tolerance mm :	+ 0.50
Rated speed rpm :	1000

Rated speed rpm :	903
rack travel mm :	11.30

Rated speed rpm :	932
-------------------	-----

Tolerance 1/min : \pm 4
 rack travel mm : 4.00

 rack travel mm : 0.50
 Tolerance mm : \pm 0.50
 Rated speed rpm : 1000

 Rated speed rpm : 904
 rack travel mm : 11.30

 Rated speed rpm : 933
 Tolerance 1/min : \pm 4
 rack travel mm : 4.00

 rack travel mm : 0.50
 Tolerance mm : \pm 0.50
 Rated speed rpm : 1000

 Rated speed rpm : 905
 rack travel mm : 11.30

 Rated speed rpm : 934
 Tolerance 1/min : \pm 4
 rack travel mm : 4.00

 rack travel mm : 0.50
 Tolerance mm : \pm 0.50
 Rated speed rpm : 1000

LOW IDLE

control lever
 position degree : 68.0
 tolerance degree : \pm 4.0

control lever
 position degree : 18.0
 tolerance degree : \pm 4.0

Setting point w/out bumper spring

Rated speed rpm : 350
 rack travel mm : 5.50
 Tolerance mm : \pm 0.10

Testing:

Rated speed rpm : 350
 rack travel mm : 6.00
 Tolerance mm : \pm 0.10

rack travel mm : 2.00
 Rated speed rpm : 395
 Tolerance 1/min : \pm 30

Rated speed rpm : 100

CRT mm min. : $>$ 19.00

TORQUE CONTROL

Rated speed rpm : 850
 rack travel mm : 12.35
 Tolerance mm : \pm 0.05

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
 Pressure hPa : 1200
 rack travel mm : 12.35
 Tolerance mm : \pm 0.05

Pressure hPa : -
 Rated speed rpm : 500
 rack travel mm : 9.95
 Tolerance mm : \pm 0.15

MEASUREMENT

Rated speed rpm : 500

 Pressure hPa : 200
 rack travel mm : 11.60
 Tolerance mm : \pm 0.10

Pressure hPa : 140
 rack travel mm : 10.75
 Tolerance mm : \pm 0.05

Start interlock

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
 hPa : -
 Rated speed rpm : 500
 Del. quantity
 cm³/1000 strokes : 113.0
 Tolerance
 cm³/1000 strokes : \pm 1.0
 Check tolerance
 cm³/1000S. : \pm 4.0

STARTING FUEL DELIVERY

Rated speed rpm : 100

rack travel mm : 20.00
Tolerance mm : ± 1.00
Del. quantity
cm³/1000 strokes : 240.0
Tolerance
cm³/1000 strokes : ± 10.0
Check tolerance
cm³/1000S. : ± 14.0

LOW IDLE

Rated speed rpm : 350
Del. quantity
cm³/1000 strokes : 15.5
Tolerance
cm³/1000 strokes : ± 2.5
Check tolerance
cm³/1000S. : ± 5.0
Speed
Tolerance
cm³/1000 strokes : 4.5
Check tolerance
cm³/1000S. : 7.5

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 29.01.97
Test oil : ISO 4113

Combination No. : F 000 409 000

Injection pump
Pump designation : PES5P120A720LS7420
EP type number : F 000 406 200

Governor
Governor design. : RQV300...1100PA1293
Governor no. : F 000 420 100

Cust. part No. : 0270747702

Customer-spec. information
Customer : MBB
Motor : OM449h LA
Power KW : 220.0

TEST BENCH REQUIREMENTS

Inlet line : 4.1

Test oil inlet
temp. °C : 40
Tolerance °C : + 2.0

Overflow valve : 1 417 413 047

Inlet press. bar : 2.0
Tolerance bar : + 0.1

Test nozzle holder
assembly : 1 688 901 105

Opening pressure
bar : 208.5
Tolerance bar : + 1.5

Test lines : 1 680 750 075

Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : + 1.0

Prestroke mm : 4.70
Tolerance mm : + 0.05
Check
tolerance mm : + 0.10

Rack travel in mm : 21.00

Firing order : 1- 3- 5- 4- 2

Phasing : 0-72-144-216-288
Tolerance : + 0.50
Check
tolerance *NW : + 0.75

BASIC SETTING

Rated speed rpm : 650

Rack travel in mm : 13.65
Tolerance mm : + 0.05

Del. quantity
cm³/1000 strokes : 252.5

Tolerance
cm³/1000 strokes : + 1.0

Check tolerance
cm³/1000S. : + 4.0

Spread

Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 300

Rack travel in mm : 5.40

Tolerance mm : ± 0.10

Del. quantity
cm³/1000 strokes : 17.0

Tolerance
cm³/1000 strokes : ± 3.0

Check tolerance
cm³/1000S. : ± 6.0

Spread
Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 1100

guide sleeve
travel mm : 6.80

Tolerance mm : ± 0.10

Rated speed rpm : 300

guide sleeve
travel mm : 1.15

Tolerance mm : ± 0.25

Rated speed rpm : 700

guide sleeve
travel mm : 3.65

Tolerance mm : ± 0.25

Rated speed rpm : 500

guide sleeve
travel mm : 2.75

Tolerance mm : ± 0.25

Rated speed rpm : 1300

guide sleeve
travel mm : 9.25

Tolerance mm : ± 0.25

GUIDE SLEEVE POSITION

control lever
position degree : - 1

Rated speed rpm : 1250

Rack travel in mm : 16.50

Tolerance mm : ± 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 650

Aneroid pressure
hPa : 1000

Del. quantity
cm³/1000 strokes : 252.5

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 4.0

Spread
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 52.0

tolerance degree : ± 4.0

control lever
position degree : 117.0

tolerance degree : ± 4.0

RATED SPEED

rack travel mm : 12.60

Rated speed rpm : 1145

Tolerance 1/min : ± 5

rack travel mm : 4.00

Rated speed rpm : 1265

Tolerance 1/min : ± 15

rack travel mm : 0.50

Tolerance mm : ± 0.50

Rated speed rpm : 1360

LOW IDLE

control lever
position degree : 83.0

tolerance degree : ± 4.0

control lever
position degree : 17.0

tolerance degree : ± 4.0

Testing:

Rated speed rpm : 300
 rack travel mm : 5.40
 Tolerance mm : + 0.10

Rated speed rpm : 100

CRT mm min. : > 8.00

Rated speed rpm : 350

TORQUE CONTROL

Rated speed rpm : 650
 rack travel mm : 13.65
 Tolerance mm : + 0.05

Rated speed rpm : 1100
 rack travel mm : 13.65
 Tolerance mm : + 0.05

ANEROID/ALTITUDE COMPENSATOR TEST

SETTING

Rated speed rpm : 500
 Pressure hPa : 1000
 rack travel mm : 13.65
 Tolerance mm : + 0.05

Pressure hPa : -
 Rated speed rpm : 500

MEASUREMENT

Rated speed rpm : 500

Pressure hPa : 600
 rack travel mm : 2.00
 Tolerance mm : + 0.10

Pressure hPa : 400
 rack travel mm : 0.75
 Tolerance mm : + 0.05

Start interlock

Rated speed rpm : > 100
 Rated speed rpm : < 220

Check speed 1/min : > 80
 Check speed 1/min : < 240

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure hPa : 1030
 Rated speed rpm : 1100
 Del. quantity cm3/1000 strokes : 246.0
 Tolerance cm3/1000 strokes : + 2.0
 Check tolerance cm3/1000S. : + 5.0

Aneroid pressure hPa : -
 Rated speed rpm : 500
 Del. quantity cm3/1000 strokes : 143.0
 Tolerance cm3/1000 strokes : + 1.0
 Check tolerance cm3/1000S. : + 4.0
 Spreed Tolerance cm3/1000 strokes : 5.0
 Check tolerance cm3/1000S. : 9.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
 Del. quantity cm3/1000 strokes : 235.0
 Tolerance cm3/1000 strokes : + 10.0
 Check tolerance cm3/1000S. : + 14.0

LOW IDLE

Rated speed rpm : 300
 Del. quantity cm3/1000 strokes : 17.0
 Tolerance cm3/1000 strokes : + 3.0
 Check tolerance cm3/1000S. : + 6.0
 Spreed Tolerance cm3/1000 strokes : 8.0
 Check tolerance cm3/1000S. : 12.0

End of test specification sheet



BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 29.01.97
Test oil : ISO 4113

Combination No. : F 000 409 001

Injection pump
Pump designation : PESSP120A720LS7420
EP type number : F 000 400 200

Governor
Governor design. : RQV300...1100PA1294
Governor no. : F 000 420 101

Cust. part No. : 0270747602

Customer-spec. information
Customer : MBB
Motor : OM449h LA
Power KW : 185.0

TEST BENCH REQUIREMENTS

Inlet line : 4.1

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 047

Inlet press. bar : 2.0
Tolerance bar : ± 0.1

Test nozzle holde
assembly : 1 688 901 105

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 075

Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 4.70
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 21.00

Firing order : 1- 3- 5- 4- 2

Phasing : 0-72-144-216-288
Tolerance : ± 0.50
Check
tolerance *NW : ± 0.75

BASIC SETTING

Rated speed rpm : 650

Rack travel in mm : 12.85
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 225.5

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 4.0

Speed

Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 300
Rack travel in mm : 5.30
Tolerance mm : ± 0.10
Del. quantity
cm³/1000 strokes : 17.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0
Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 1100
guide sleeve
travel mm : 8.20
Tolerance mm : ± 0.10

Rated speed rpm : 300
guide sleeve
travel mm : 2.05
Tolerance mm : ± 0.25

Rated speed rpm : 700
guide sleeve
travel mm : 5.35
Tolerance mm : ± 0.25

Rated speed rpm : 500
guide sleeve
travel mm : 4.50
Tolerance mm : ± 0.25

Rated speed rpm : 1300
guide sleeve
travel mm : 10.25
Tolerance mm : ± 0.25

GUIDE SLEEVE POSITION

control lever
position degree : - 1
Rated speed rpm : 1250

Rack travel in mm : 16.50
Tolerance mm : ± 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 650
Aneroid pressure
hPa : 1000
Del. quantity
cm³/1000 strokes : 225.5
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0
Speed
Tolerance
cm³/1000 strokes : 5.0
Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 52.0
tolerance degree : ± 4.0

control lever
position degree : 117.0
tolerance degree : ± 4.0

RATED SPEED
rack travel mm : 11.10
Rated speed rpm : 1160
Tolerance 1/min : ± 5

rack travel mm : 4.00
Rated speed rpm : 1260
Tolerance 1/min : ± 15

rack travel mm : 0.50
Tolerance mm : ± 0.50
Rated speed rpm : 1360

LOW IDLE

control lever
position degree : 83.0
tolerance degree : ± 4.0

control lever
position degree : 18.0
tolerance degree : ± 4.0

Testing:

Rated speed rpm : 300
 rack travel mm : 5.30
 Tolerance mm : ± 0.10

Rated speed rpm : 100

CRT mm min. : > 10.00

Rated speed rpm : 330

TORQUE CONTROL

Rated speed rpm : 650
 rack travel mm : 12.85
 Tolerance mm : ± 0.05

Rated speed rpm : 1100
 rack travel mm : 12.15
 Tolerance mm : ± 0.05

Rated speed rpm : 900
 rack travel mm : 12.85
 Tolerance mm : ± 0.05

Rated speed rpm : 1050
 rack travel mm : 12.15
 Tolerance mm : ± 0.05

ANEROID/ALTITUDE COMPENSATOR TEST

SETTING

Rated speed rpm : 500
 Pressure hPa : 1000
 rack travel mm : 12.85
 Tolerance mm : ± 0.05

Pressure hPa : -
 Rated speed rpm : 500

MEASUREMENT

Rated speed rpm : 500

Pressure hPa : 570
 rack travel mm : 1.30
 Tolerance mm : ± 0.10

Pressure hPa : 430
 rack travel mm : 0.45
 Tolerance mm : ± 0.05

Start interlock

Rated speed rpm : > 100
 Rated speed rpm : < 220

Check speed 1/min : > 80
 Check speed 1/min : < 240

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure hPa : 1000
 Rated speed rpm : 1100
 Del. quantity cm3/1000 strokes : 202.0
 Tolerance cm3/1000 strokes : ± 2.0
 Check tolerance cm3/1000S. : ± 5.0

Aneroid pressure hPa : -
 Rated speed rpm : 500
 Del. quantity cm3/1000 strokes : 150.0
 Tolerance cm3/1000 strokes : ± 1.0
 Check tolerance cm3/1000S. : ± 4.0

Spread Tolerance cm3/1000 strokes : 5.0
 Check tolerance cm3/1000S. : 9.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
 Del. quantity cm3/1000 strokes : 235.0
 Tolerance cm3/1000 strokes : ± 10.0
 Check tolerance cm3/1000S. : ± 14.0

LOW IDLE

Rated speed rpm : 300
 Del. quantity cm3/1000 strokes : 17.0
 Tolerance cm3/1000 strokes : ± 3.0

Check tolerance
cm³/1000S. : ± 6.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 29.01.97
Test oil : ISO 4113

Combination No. : F 000 409 100

Injection pump
Pump designation : PES5P120A720LS7420
EP type number : F 000 400 200

Governor
Governor design. : RQV300...1100PA1302
Governor no. : F 000 420 104

Cust. part No. : 0270748902

Customer-spec. information
Customer : MEB
Motor : OM449h LA
Power KW : 220.0

TEST BENCH REQUIREMENTS

Inlet line : 4.1

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 047

Inlet press. bar : 2.0
Tolerance bar : ± 0.1

Test nozzle holder
assembly : 1 688 901 105

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 075

Outside diameter : 8.0

K02

x inside diameter : 3.0
x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 4.70
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 21.00

Firing order : 1- 3- 5- 4- 2

Phasing : 0-72-144-216-288
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

BASIC SETTING

Rated speed rpm : 650

Rack travel in mm : 13.65
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 252.5

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 4.0

Spread

Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 300
Rack travel in mm : 5.40
Tolerance mm : ± 0.10
Del. quantity
cm³/1000 strokes : 17.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0
Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 1100
guide sleeve
travel mm : 8.20
Tolerance mm : ± 0.10

Rated speed rpm : 300
guide sleeve
travel mm : 2.05
Tolerance mm : ± 0.25

Rated speed rpm : 700
guide sleeve
travel mm : 5.35
Tolerance mm : ± 0.25

Rated speed rpm : 500
guide sleeve
travel mm : 4.50
Tolerance mm : ± 0.25

Rated speed rpm : 1300
guide sleeve
travel mm : 10.25
Tolerance mm : ± 0.25

GUIDE SLEEVE POSITION

control lever
position degree : - 1
Rated speed rpm : 1250

Rack travel in mm : 16.50
Tolerance mm : ± 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 650
Aneroid pressure
hPa : 1000
Del. quantity
cm³/1000 strokes : 252.5
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0
Speed
Tolerance
cm³/1000 strokes : 5.0
Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 52.0
tolerance degree : ± 4.0

control lever
position degree : 117.0
tolerance degree : ± 4.0

RATED SPEED

rack travel mm : 12.60
Rated speed rpm : 1145
Tolerance 1/min : ± 5

rack travel mm : 4.00
Rated speed rpm : 1270
Tolerance 1/min : ± 15

rack travel mm : 0.50
Tolerance mm : ± 0.50
Rated speed rpm : 1360

LOW IDLE

control lever
position degree : 83.0
tolerance degree : ± 4.0

control lever
position degree : 17.0
tolerance degree : ± 4.0

Testing:

Rated speed rpm : 300
rack travel mm : 5.40
Tolerance mm : ± 0.10

Rated speed rpm : 100

CRT mm min. : > 10.00

Rated speed rpm : 350

TORQUE CONTROL

Rated speed rpm : 650
rack travel mm : 13.65
Tolerance mm : ± 0.05

Rated speed rpm : 1100
rack travel mm : 13.65
Tolerance mm : ± 0.05

ANEROID/ALTITUDE COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1000
rack travel mm : 13.65
Tolerance mm : ± 0.05

Pressure hPa : -
Rated speed rpm : 500

MEASUREMENT

Rated speed rpm : 500

Pressure hPa : 600
rack travel mm : 2.00
Tolerance mm : ± 0.10

Pressure hPa : 400
rack travel mm : 0.75
Tolerance mm : ± 0.05

Start interlock

Rated speed rpm : > 100
Rated speed rpm : < 220

Check speed 1/min : > 80

Check speed 1/min : < 240

K04

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1000
Rated speed rpm : 1100
Del. quantity
cm³/1000 strokes : 246.0
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 5.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 143.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0
Spread
Tolerance
cm³/1000 strokes : 5.0
Check tolerance
cm³/1000S. : 9.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 235.0
Tolerance
cm³/1000 strokes : ± 10.0
Check tolerance
cm³/1000S. : ± 14.0

LOW IDLE

Rated speed rpm : 300
Del. quantity
cm³/1000 strokes : 17.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0
Spread
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet



BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 29.01.97
Test oil : ISO 4113
Combination No. : F 000 409 101
Injection pump
Pump designation : PES5P120A720LS7420
EP type number : F 000 400 200
Governor
Governor design. : RGV50C...1100PA1303
Governor no. : F 000 420 105
Cust. part No. : 0270748802

Customer-spec. information

Customer : MBB
Motor : OM449h LA
Power kW : 185.0

TEST BENCH REQUIREMENTS

Inlet line : 4.1
Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 1 417 413 047
Inlet press. bar : 2.0
Tolerance bar : ± 0.1
Test nozzle holder
assembly : 1 688 901 105
Opening pressure
bar : 208.5
Tolerance bar : ± 1.5
Test lines : 1 680 750 075
Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0
Prestroke mm : 4.70
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10
Rack travel in mm : 21.00
Firing order : 1- 3- 5- 4- 2
Phasing : 0-72-144-216-288
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

BASIC SETTING

Rated speed rpm : 650
Rack travel in mm : 12.85
Tolerance mm : ± 0.05
Del. quantity
cm³/1000 strokes : 225.5
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0
Speed
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 300

Rack travel in mm : 5.30
Tolerance mm : +- 0.10
Del. quantity
cm³/1000 strokes : 17.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 1100
guide sleeve
travel mm : 6.80
Tolerance mm : +- 0.10

Rated speed rpm : 300
guide sleeve
travel mm : 1.15
Tolerance mm : +- 0.25

Rated speed rpm : 700
guide sleeve
travel mm : 3.65
Tolerance mm : +- 0.25

Rated speed rpm : 500
guide sleeve
travel mm : 2.75
Tolerance mm : +- 0.25

Rated speed rpm : 1300
guide sleeve
travel mm : 9.25
Tolerance mm : +- 0.25

GUIDE SLEEVE POSITION

control lever
position degree : - 1
Rated speed rpm : 1250

K07

Rack travel in mm : 16.50
Tolerance mm : +- 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 650
Aneroid pressure
hPa : 1000
Del. quantity
cm³/1000 strokes : 225.5
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0
Spreed
Tolerance
cm³/1000 strokes : 5.0
Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 52.0
tolerance degree : +- 4.0

control lever
position degree : 117.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 11.10
Rated speed rpm : 1160
Tolerance 1/min : +- 5

rack travel mm : 4.00
Rated speed rpm : 1260
Tolerance 1/min : +- 15

rack travel mm : 0.50
Tolerance mm : +- 0.50
Rated speed rpm : 1360

LOW IDLE

control lever
position degree : 83.0
tolerance degree : +- 4.0

control lever
position degree : 18.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 300
 rack travel mm : 5.30
 Tolerance mm : ± 0.10

Rated speed rpm : 100

CRT mm min. : > 8.00

Rated speed rpm : 380

TORQUE CONTROL

Rated speed rpm : 650
 rack travel mm : 12.85
 Tolerance mm : ± 0.05

Rated speed rpm : 1100
 rack travel mm : 12.15
 Tolerance mm : ± 0.05

Rated speed rpm : 900
 rack travel mm : 12.85
 Tolerance mm : ± 0.05

Rated speed rpm : 1050
 rack travel mm : 12.15
 Tolerance mm : ± 0.05

ANEROID/ALTITUDE COMPENSATOR TEST

SETTING

Rated speed rpm : 500
 Pressure hPa : 1000
 rack travel mm : 12.85
 Tolerance mm : ± 0.05

Pressure hPa : -
 Rated speed rpm : 500

MEASUREMENT

Rated speed rpm : 500

Pressure hPa : 570
 rack travel mm : 1.30
 Tolerance mm : ± 0.10

Pressure hPa : 430
 rack travel mm : 0.45
 Tolerance mm : ± 0.05

Start interlock

K08

Rated speed rpm : > 100
 Rated speed rpm : < 220

Check speed 1/min : > 80
 Check speed 1/min : < 240

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure hPa : 1000
 Rated speed rpm : 1100
 Del. quantity cm3/1000 strokes : 202.0
 Tolerance cm3/1000 strokes : ± 2.0
 Check tolerance cm3/1000s. : ± 5.0

Aneroid pressure hPa : -
 Rated speed rpm : 500
 Del. quantity cm3/1000 strokes : 150.0
 Tolerance cm3/1000 strokes : ± 1.0
 Check tolerance cm3/1000s. : ± 4.0
 Speed
 Tolerance cm3/1000 strokes : 5.0
 Check tolerance cm3/1000s. : 9.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
 Del. quantity cm3/1000 strokes : 235.0
 Tolerance cm3/1000 strokes : ± 10.0
 Check tolerance cm3/1000s. : ± 14.0

LOW IDLE

Rated speed rpm : 300
 Del. quantity cm3/1000 strokes : 17.0
 Tolerance cm3/1000 strokes : ± 3.0

Check tolerance
cm³/1000S. : ± 6.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 13.02.97
Test oil : ISO 4113

Combination No. : 0 400 864 109

Injection pump
Pump designation : PES4A95D410/3RS2789
EP type number : 0 410 894 995

Governor
Governor design. : RSV325...1250A5C917L
Governor no. : 0 420 232 639

Cust. part No. : 0423 2332 KY

Customer-spec. information
Customer : KHD-DMI
Motor : F4L912/913
Power KW : 59.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 419 992 198

Inlet press. bar : 1.5

Test nozzle holder
assembly : 0 681 343 009

Opening pressure
bar : 173.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 014

Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 3.00
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 3- 4- 2

Phasing : 0-90-180-270
Tolerance : ± 0.50
Check
tolerance °MW : ± 0.75

BASIC SETTING

Rated speed rpm : 1250

Rack travel in mm : 11.35
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 76.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 3.0

Speed

Tolerance
cm³/1000 strokes : 3.5

Check tolerance
cm³/1000S. : 8.0

Rated speed rpm : 325

Rack travel in mm : 8.50
Tolerance mm : ± 0.10

Del. quantity
cm³/1000 strokes : 11.5

Tolerance
cm³/1000 strokes : ± 2.0

Check tolerance
cm³/1000S. : ± 4.5

Speed
Tolerance
cm³/1000 strokes : 5.5

Check tolerance
cm³/1000S. : 9.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : FREE
Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : ± 0.20

governor spring
pre-tension
click setting x : 3.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1250
Aneroid pressure
hPa : -

Del. quantity
cm³/1000 strokes : 76.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 3.0

Speed
Tolerance
cm³/1000 strokes : 3.5

Check tolerance
cm³/1000S. : 8.0

CONTROL LEVER

control lever
position degree : 102.0
tolerance degree : ± 4.0

RATED SPEED
rack travel mm : 10.35
Rated speed rpm : 1295
Tolerance 1/min : ± 5

rack travel mm : 4.00
Rated speed rpm : 1340
Tolerance 1/min : ± 15

rack travel mm : 0.85
Tolerance mm : ± 0.55
Rated speed rpm : 1510

rack travel mm : 4.00
Rated speed rpm : 1360

LOW IDLE

control lever
position degree : 69.0
tolerance degree : ± 4.0

Setting point w/out bumper spring

Rated speed rpm : 325
rack travel mm : 8.00
Tolerance mm : ± 0.10

Testing:

Rated speed rpm : 325
rack travel mm : 8.50
Tolerance mm : ± 0.10

rack travel mm : 2.00
Rated speed rpm : 475
Tolerance 1/min : ± 30

Rated speed rpm : 100

CRT mm min. : > 19.50

TORQUE CONTROL

Rated speed rpm : 1250
rack travel mm : 11.35
Tolerance mm : ± 0.05

Start interlock

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 17.00
Tolerance mm : \pm 0.75
Del. quantity
cm³/1000 strokes : 90.0
Tolerance
cm³/1000 strokes : \pm 7.5
Check tolerance
cm³/1000S. : \pm 10.0

LOW IDLE

Rated speed rpm : 325
Del. quantity
cm³/1000 strokes : 11.5
Tolerance
cm³/1000 strokes : \pm 2.0
Check tolerance
cm³/1000S. : \pm 4.5
Spreed
Tolerance
cm³/1000 strokes : 5.5
Check tolerance
cm³/1000S. : 9.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 31.01.97
Test oil : ISO 4113
Combination No. : 0 400 846 449

Injection pump
Pump designation : PES6A95D420LS2595
EP type number : 0 410 896 930

Governor
Governor design. : RQ200/1050AB1094
Governor no. : 0 420 201 623

Cust. part No. :

Customer-spec. information
Customer : RABA
Motor : D2156 HM6U
Power kW : 141.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 419 992 198

Inlet press. bar : 1.5

Test nozzle holde assembly : 0 681 343 009

Opening pressure bar : 173.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 014

Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 2.05
Tolerance mm : ± 0.05
Check tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.50
Check tolerance °NW : ± 0.75

BASIC SETTING

Rated speed rpm : 1050

Rack travel in mm : 10.65
Tolerance mm : ± 0.05

Del. quantity cm3/1000 strokes : 103.0

Tolerance cm3/1000 strokes : ± 1.0

Check tolerance cm3/1000S. : ± 3.0

Speed

Tolerance
 cm³/1000 strokes : 3.5

 Check tolerance
 cm³/1000S. : 6.0

 Rated speed rpm : 200
 Rack travel in mm : 6.00
 Tolerance mm : ± 0.10
 Del. quantity
 cm³/1000 strokes : 13.0
 Tolerance
 cm³/1000 strokes : ± 2.0
 Check tolerance
 cm³/1000S. : ± 4.5
 Spreed
 Tolerance
 cm³/1000 strokes : 3.5
 Check tolerance
 cm³/1000S. : 5.5

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
 position degree : 109
 Rated speed rpm : 300
 Rack travel in mm : 20.00
 Tolerance mm : ± 0.80

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1050
 Aneroid pressure
 hPa : -
 Del. quantity
 cm³/1000 strokes : 103.0
 Tolerance
 cm³/1000 strokes : ± 1.0
 Check tolerance
 cm³/1000S. : ± 3.0
 Spreed
 Tolerance
 cm³/1000 strokes : 3.5
 Check tolerance
 cm³/1000S. : 6.0

RATED SPEED

rack travel mm : 9.60
 Rated speed rpm : 1103
 Tolerance 1/min : ± 8
 rack travel mm : 4.00
 Rated speed rpm : 1140
 Tolerance 1/min : ± 15
 rack travel mm : 0.50
 Tolerance mm : ± 0.50
 Rated speed rpm : 1225

LOW IDLE

Testing:

Rated speed rpm : 200
 rack travel mm : 6.00
 Tolerance mm : ± 0.10
 rack travel mm : 2.00
 Rated speed rpm : 290
 Tolerance 1/min : ± 20
 Rated speed rpm : 100
 CRT mm min. : > 7.50
 Rated speed rpm : 350
 CRT mm max. : < 1.00

TORQUE CONTROL

Rated speed rpm : 1050
 rack travel mm : 10.65
 Tolerance mm : ± 0.05
 Rated speed rpm : 500
 rack travel mm : 11.20
 Tolerance mm : ± 0.10
 Rated speed rpm : 740
 rack travel mm : 11.20
 Tolerance mm : ± 0.10
 Rated speed rpm : 800
 rack travel mm : 11.00
 Tolerance mm : ± 0.10

Start interlock

Rated speed rpm : > 100
 Rated speed rpm : < 140

Check
speed 1/min : > 80
Check
speed 1/min : < 160

End of test specification sheet

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 91.5

Aneroid pressure
hPa : -
Rated speed rpm : 800
Del. quantity
cm³/1000 strokes : 103.0
Tolerance
cm³/1000 strokes : ± 1.5
Check tolerance
cm³/1000s. : ± 3.5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 17.80
Tolerance mm : ± 0.30
Del. quantity
cm³/1000 strokes : 150.0
Tolerance
cm³/1000 strokes : ± 5.0
Check tolerance
cm³/1000s. : ± 8.0

LOW IDLE

Rated speed rpm : 200
Del. quantity
cm³/1000 strokes : 13.0
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000s. : ± 4.5
Speed
Tolerance
cm³/1000 strokes : 3.5
Check tolerance
cm³/1000s. : 5.5

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 24.01.97
Test oil : ISO 4113

Combination No. : 0 402 746 614

Injection pump
Pump designation : PES6P120A320RS7419
EP type number : 0 412 726 961

Governor
Governor design. : RQV300...1300PA1288K
Governor no. : 0 421 815 519

Cust. part No. : 386 6799

Customer-spec. information
Customer : CDC
Motor : 6CTA
Power KW : 320.4

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 093

Inlet press. bar : 2.0
Tolerance bar : ± 0.1

Test nozzle holde
assembly : 1 688 901 103

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 015

Outside diameter : 6.0

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0

Prestroke mm : 3.65
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 9.50
Tolerance mm : ± 1.00

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °/NW : ± 0.75

Start of delivery blocking

*NW after s.o.d. : 12.25
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1300

Rated speed rpm : 300

Rack travel in mm : 6.20
 Del. quantity
 cm³/1000 strokes : 26.0
 Tolerance
 cm³/1000 strokes : ± 3.0
 Check tolerance
 cm³/1000S. : ± 5.0
 Spreed
 Tolerance
 cm³/1000 strokes : 5.0
 Check tolerance
 cm³/1000S. : 8.0

(B) SETTING OF INJECTION PUMP
 WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 1372
 guide sleeve
 travel mm : 9.96
 Tolerance mm : ± 0.15

Rated speed rpm : 300
 guide sleeve
 travel mm : 1.29
 Tolerance mm : ± 0.20

Rated speed rpm : 917
 guide sleeve
 travel mm : 6.76
 Tolerance mm : ± 0.25

Rated speed rpm : 590
 guide sleeve
 travel mm : 4.95
 Tolerance mm : ± 0.25

Rated speed rpm : 1710
 guide sleeve
 travel mm : 13.50
 Tolerance mm : ± 0.50

CONTROL LEVER

control lever
 position degree : 120.0
 tolerance degree : ± 4.0

RATED SPEED

rack travel mm : 13.00
 Rated speed rpm : 1365
 Tolerance 1/min : ± 5
 rack travel mm : 4.00

Rated speed rpm : 1520
 Tolerance 1/min : ± 15
 rack travel mm : 0.50
 Tolerance mm : ± 0.50
 Rated speed rpm : 1600

LOW IDLE

control lever
 position degree : 71.0
 tolerance degree : ± 4.0

Control lever difference

Grad : 49.0
 tolerance degree : ± 6.0

Testing:

Rated speed rpm : 300
 rack travel mm : 6.20

Rated speed rpm : 250

CRT mm min. : > 7.00

Rated speed rpm : 450

TORQUE CONTROL

Rated speed rpm : 1300

Rated speed rpm : 900
 rack travel mm : 13.60
 Tolerance mm : ± 0.10

Rated speed rpm : 600
 rack travel mm : 13.05
 Tolerance mm : ± 0.20

ANEROID/ALTITUDE
 COMPENSATOR TEST

SETTING

Rated speed rpm : 1300
 Pressure hPa : 1500

Pressure hPa : -
 Rated speed rpm : 1000
 rack travel mm : 9.85
 Tolerance mm : ± 0.20

MEASUREMENT

Rated speed rpm : 1300
Pressure hPa : 890
rack travel mm : 12.80
Tolerance mm : +- 0.20
Pressure hPa : 400
rack travel mm : 10.80
Tolerance mm : +- 0.20
Start interlock

Rated speed rpm : 300
Del. quantity
cm3/1000 strokes : 26.0
Tolerance
cm3/1000 strokes : +- 3.0
Check tolerance
cm3/1000S. : +- 5.0
Spreed
Tolerance
cm3/1000 strokes : 5.0
Check tolerance
cm3/1000S. : 8.0

FIJEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1500
Rated speed rpm : 900
Del. quantity
cm3/1000 strokes : 24.0
Tolerance
cm3/1000 strokes : +- 6.0
Check tolerance
cm3/1000S. : +- 8.0
Spreed
Tolerance
cm3/1000 strokes : 8.0
Check tolerance
cm3/1000S. : 12.0

Aneroid pressure
hPa : -
Rated speed rpm : 1000
Del. quantity
cm3/1000 strokes : 123.0
Tolerance
cm3/1000 strokes : +- 1.0
Check tolerance
cm3/1000S. : +- 3.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 9.10
Del. quantity
cm3/1000 strokes : 123.0
Tolerance
cm3/1000 strokes : +- 20.0
Check tolerance
cm3/1000S. : +- 25.0

LOW IDLE

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 04.02.97
Test oil : ISO 4113
Combination No. : 0 402 776 834
Injection pump
Pump designation : PES6P120A72ORS7382
EP type number : 0 412 726 943
Governor
Governor design. : RSV400...750P4A610
Governor no. : 0 421 833 520

Cust. part No. : RE66451

Customer-spec. information

Customer : DEERE
Motor : 6081 HFO01
Power KW : 175.0

TEST BENCH REQUIREMENTS

Inlet line : 4.2
Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 2 417 413 079
Inlet press. bar : 2.0
Test nozzle holde
assembly : 1 688 901 101
Opening pressure
bar : 208.5
Tolerance bar : ± 1.5
Test lines : 1 680 750 015
Outside diameter : 6.0

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0
Prestroke mm : 3.60
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10
Rack travel in mm : 10.50
Tolerance mm : ± 1.50
Firing order : 1- 5- 3- 6- 2-
: 4
Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.75
Start of delivery blocking
°NW after s.o.d. : 9.00
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75
Barrel no. : 1
Beginning of delivery differende
and maximum rack
travel : 14.00
Difference ° CS : 2.50

BASIC SETTING

Rated speed rpm : 700

Rack travel in mm : 13.60
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 251.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 4.0

Spread

Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 400

Rack travel in mm : 5.50
Tolerance mm : ± 0.10

Del. quantity
cm³/1000 strokes : 22.0

Tolerance
cm³/1000 strokes : ± 3.0

Check tolerance
cm³/1000S. : ± 5.0

Spread

Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : - 3
Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : ± 0.20

governor spring
pre-tension
click setting x : 2.50

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 700

Aneroid pressure
hPa : -

Del. quantity
cm³/1000 strokes : 251.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 4.0

Spread

Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 91.0
tolerance degree : ± 4.0

RATED SPEED

rack travel mm : 12.00

Rated speed rpm : 755

Tolerance 1/min : ± 5

rack travel mm : 4.00

Rated speed rpm : 790

Tolerance 1/min : ± 5

rack travel mm : 0.85

Tolerance mm : ± 0.55

Rated speed rpm : 950

rack travel mm : 4.00

Rated speed rpm : 820

LOW IDLE

control lever
position degree : 74.0
tolerance degree : ± 4.0

Setting point w/out bumper spring

Rated speed rpm : 400

rack travel mm : 5.00

Tolerance mm : ± 0.10

Testing:

Rated speed rpm : 400
rack travel mm : 5.50
Tolerance mm : ± 0.10

Rated speed rpm : 100
CRT mm min. : > 19.00

TORQUE CONTROL

Rated speed rpm : 700
rack travel mm : 13.60
Tolerance mm : ± 0.05

Start interlock

Rated speed rpm : > 100

Check
speed 1/min : > 80

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : ± 0.50
Del. quantity
cm³/1000 strokes : 105.0
Tolerance
cm³/1000 strokes : ± 20.0
Check tolerance
cm³/1000S. : ± 25.0

LOW IDLE

Rated speed rpm : 400
Del. quantity
cm³/1000 strokes : 22.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 5.0
Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 04.02.97
Test oil : ISO 4113

Combination No. : 0 402 776 835

Injection pump
Pump designation : PES6P120A720RS7382
EP type number : 0 412 726 943

Governor
Governor design. : RSV400...750P4A607
Governor no. : 0 421 833 521

Cust. part No. : RE66458

Customer-spec. information

Customer : DEERE
Motor : 6081 HF001
Power KW : 175.0

TEST BENCH REQUIREMENTS

Inlet line : 4.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 079

Inlet press. bar : 2.0

Test nozzle holder
assembly : 1 688 901 101

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 015

Outside diameter : 6.0

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0

Prestroke mm : 3.60
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.75

Start of delivery blocking

*NW after s.o.d. : 9.00
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Barrel no. : 1

Beginning of delivery difference

and maximum rack
travel : 14.00
Difference °CS : 2.50

BASIC SETTING

Rated speed rpm : 700

Rack travel in mm : 13.60
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 251.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 4.0

Spread

Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 400

Rack travel in mm : 5.50
Tolerance mm : ± 0.10

Del. quantity
cm³/1000 strokes : 22.0

Tolerance
cm³/1000 strokes : ± 3.0

Check tolerance
cm³/1000S. : ± 5.0

Spread

Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : - 3
Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : ± 0.20

governor spring
pre-tension
click setting x : 2.50

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 700

Aneroid pressure
hPa : -

Del. quantity
cm³/1000 strokes : 251.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 4.0

Spread

Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 91.0
tolerance degree : ± 4.0

RATED SPEED

rack travel mm : 12.00
Rated speed rpm : 755
Tolerance 1/min : ± 5

rack travel mm : 4.00
Rated speed rpm : 790
Tolerance 1/min : ± 5

rack travel mm : 0.85
Tolerance mm : ± 0.55
Rated speed rpm : 950

rack travel mm : 4.00
Rated speed rpm : 820

LOW IDLE

control lever
position degree : 74.0
tolerance degree : ± 4.0

Setting point w/out bumper spring

Rated speed rpm : 400
rack travel mm : 5.00
Tolerance mm : ± 0.10

Testing:

Rated speed rpm : 400
rack travel mm : 5.50
Tolerance mm : \pm 0.10

Rated speed rpm : 100
CRT mm min. : $>$ 19.00

TORQUE CONTROL

Rated speed rpm : 700
rack travel mm : 13.60
Tolerance mm : \pm 0.05

Start interlock

Rated speed rpm : $>$ 100

Check
speed 1/min : $>$ 80

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : \pm 0.50
Del. quantity
cm³/1000 strokes : 105.0
Tolerance
cm³/1000 strokes : \pm 20.0
Check tolerance
cm³/1000S. : \pm 25.0

LOW IDLE

Rated speed rpm : 400
Del. quantity
cm³/1000 strokes : 22.0
Tolerance
cm³/1000 strokes : \pm 3.0
Check tolerance
cm³/1000S. : \pm 5.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 03.02.97
Test oil : ISO 4113

Combination No. : F 002 A0Z 013

Injection pump
Pump designation : PES6A95D320/3RS2881
EP type number : 9 410 037 215

Governor
Governor design. : RSV475...1000A0C890R
Governor no. : F 002 A20 213

Cust. part No. : 3930163

Customer-spec. information
Customer : CDC
Motor : 6BTA
Power KW : 123.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 047

Inlet press. bar : 2.0
Tolerance bar : ± 0.1

Test nozzle holder assembly : 1 688 901 101

Opening pressure bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 014

Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0

Prestroke mm : 2.85
Tolerance mm : ± 0.05
Check tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240

Start of delivery blocking

*NW after s.o.d. : 7.50
Tolerance : ± 0.10
Check tolerance *NW : ± 0.29

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1000

Rack travel in mm : 13.70
Tolerance mm : ± 0.05

Del. quantity cm³/1000 strokes : 116.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 3.0

Spread

Tolerance
cm³/1000 strokes : 3.5

Check tolerance
cm³/1000S. : 6.0

Rated speed rpm : 475

Rack travel in mm : 5.95
Tolerance mm : ± 0.10

Del. quantity
cm³/1000 strokes : 20.6

Tolerance
cm³/1000 strokes : ± 2.0

Check tolerance
cm³/1000S. : ± 4.5

Spread

Tolerance
cm³/1000 strokes : 3.5

Check tolerance
cm³/1000S. : 5.5

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : FREE

Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : ± 0.20

governor spring
pre-tension
click setting x : 2.50

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1000

Aneroid pressure
hPa : 1200

Del. quantity
cm³/1000 strokes : 116.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 3.0

Spread

Tolerance
cm³/1000 strokes : 3.5

Check tolerance
cm³/1000S. : 6.0

CONTROL LEVER

control lever
position degree : 95.0

tolerance degree : ± 4.0

RATED SPEED

rack travel mm : 12.70

Rated speed rpm : 1045

Tolerance 1/min : ± 5

rack travel mm : 6.70

Rated speed rpm : 1120

Tolerance 1/min : ± 5

rack travel mm : 0.85

Tolerance mm : ± 0.55

Rated speed rpm : 1200

rack travel mm : 6.70

Rated speed rpm : 1120

LOW IDLE

control lever
position degree : 75.0

tolerance degree : ± 4.0

Control lever difference

Grad : 20.0

tolerance degree : ± 6.0

Setting point w/out bumper spring

Rated speed rpm : 475

rack travel mm : 5.45

Tolerance mm : ± 0.10

Testing:

Rated speed rpm : 475

rack travel mm : 5.95

Tolerance mm : \pm 0.10
Rated speed rpm : 100
CRT mm min. : $>$ 19.00

TORQUE CONTROL

Rated speed rpm : 1000
rack travel mm : 13.70
Tolerance mm : \pm 0.05

Rated speed rpm : 750

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1200

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : 11.00
Tolerance mm : \pm 0.10

MEASUREMENT

Rated speed rpm : 500

Pressure hPa : 600
rack travel mm : 13.20
Tolerance mm : \pm 0.20

Pressure hPa : 370
rack travel mm : 11.70
Tolerance mm : \pm 0.20

Start interlock

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 87.5
Tolerance
cm³/1000 strokes : \pm 1.0
Check tolerance
cm³/1000S. : \pm 3.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : \pm 0.50
Del. quantity
cm³/1000 strokes : 121.5
Tolerance
cm³/1000 strokes : \pm 10.0
Check tolerance
cm³/1000S. : \pm 15.0

LOW IDLE

Rated speed rpm : 475
Del. quantity
cm³/1000 strokes : 20.6
Tolerance
cm³/1000 strokes : \pm 2.0
Check tolerance
cm³/1000S. : \pm 4.5
Spreed
Tolerance
cm³/1000 strokes : 3.5
Check tolerance
cm³/1000S. : 5.5

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 11.02.97
Test oil : ISO 4113
Combination No. : 0 402 076 770A
Injection pump
Pump designation : PES6P110A320LS3318
EP type number : 0 412 016 749
Governor
Governor design. : RSV350...750P4A561
Governor no. :

Cust. part No. : 1823837C91A

Customer-spec. information
Customer : NAVISTAR
Motor : DT-531
Power KW : 243.0

TEST BENCH REQUIREMENTS

Inlet line : 4.2
Test oil inlet temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 1 417 413 076
Inlet press. bar : 2.8
Tolerance bar : ± 0.1
Test nozzle holder assembly : 1 688 901 101
Opening pressure bar : 208.5
Tolerance bar : ± 1.5
Test lines : 1 680 750 015
Outside diameter : 6.0

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0
Prestroke mm : 3.00
Tolerance mm : ± 0.05
Check tolerance mm : ± 0.10
Rack travel in mm : 10.50
Tolerance mm : ± 1.50
Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check tolerance °NW : ± 0.75

Start of delivery blocking

Tolerance : ± 0.50
Check tolerance °NW : ± 0.75
Barrel no. : 1

BASIC SETTING

Rated speed rpm : 900
Rack travel in mm : 12.55
Tolerance mm : ± 0.05
Del. quantity cm³/1000 strokes : 216.5

Tolerance
 cm³/1000 strokes : + 1.0

Check tolerance
 cm³/1000S. : + 3.0

Spreed

Tolerance
 cm³/1000 strokes : 4.0

Check tolerance
 cm³/1000S. : 6.5

Rated speed rpm : 350

Rack travel in mm : 4.90
 Tolerance mm : + 0.10
 Del. quantity
 cm³/1000 strokes : 14.5
 Tolerance
 cm³/1000 strokes : + 2.0
 Check tolerance
 cm³/1000S. : + 4.5
 Spreed
 Tolerance
 cm³/1000 strokes : 8.0
 Check tolerance
 cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
 WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
 position degree : ~ 3
 Rated speed rpm : 800

Rack travel in mm : 0.50
 Tolerance mm : + 0.20

governor spring
 pre-tension
 click setting x : 4.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 900
 Aneroid pressure
 hPa : -
 Del. quantity
 cm³/1000 strokes : 216.5

L01

Tolerance
 cm³/1000 strokes : + 1.0
 Check tolerance
 cm³/1000S. : + 3.0
 Spreed
 Tolerance
 cm³/1000 strokes : 4.0
 Check tolerance
 cm³/1000S. : 6.5

CONTROL LEVER

control lever
 position degree : 47.0
 tolerance degree : + 4.0

RATED SPEED

rack travel mm : 11.50
 Rated speed rpm : 910
 Tolerance 1/min : + 5

rack travel mm : 4.00
 Rated speed rpm : 950
 Tolerance 1/min : + 5

rack travel mm : 0.85
 Tolerance mm : + 0.55
 Rated speed rpm : 1025

rack travel mm : 4.00
 Rated speed rpm : 955

LOW IDLE

control lever
 position degree : 26.0
 tolerance degree : + 4.0

Testing:

Rated speed rpm : 350
 rack travel mm : 4.90
 Tolerance mm : + 0.10

Rated speed rpm : 100

CRT mm min. : > 19.00

TORQUE CONTROL

Rated speed rpm : 900
 rack travel mm : 12.55
 Tolerance mm : + 0.05

Start interlock

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : \pm 0.50
Del. quantity
cm³/1000 strokes : 145.0
Tolerance
cm³/1000 strokes : \pm 20.0
Check tolerance
cm³/1000S. : \pm 25.0

LOW IDLE

Rated speed rpm : 350
Del. quantity
cm³/1000 strokes : 14.5
Tolerance
cm³/1000 strokes : \pm 2.0
Check tolerance
cm³/1000S. : \pm 4.5
Spread
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 11.02.97
Test oil : ISO 4113

Combination No. : 0 402 076 770B

Injection pump
Pump designation : PES6P110A320LS3318
EP type number :

Governor
Governor design. : RSV350...750P4A561
Governor no. :

Cust. part No. : 1823837C91B

Customer-spec. information
Customer : NAVISTAR
Motor : DT-531
Power KW : 205.0

TEST BENCH REQUIREMENTS

Inlet line : 4.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 076

Inlet press. bar : 2.8
Tolerance bar : ± 0.1

Test nozzle holde
assembly : 1 688 901 101

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 015

Outside diameter : 6.0

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0

Prestroke mm : 3.00
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.75

Start of delivery blocking

Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 650

Rack travel in mm : 11.65
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 200.0

Tolerance
cm³/1000 strokes : + 1.0

Check tolerance
cm³/1000S. : + 3.0

Spreed

Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 6.5

Rated speed rpm : 340

Rack travel in mm : 5.20
Tolerance mm : + 0.10

Del. quantity
cm³/1000 strokes : 35.0

Tolerance
cm³/1000 strokes : + 2.0

Check tolerance
cm³/1000S. : + 4.5

Spreed

Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : - 3
Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : + 0.20

governor spring
pre-tension
click setting x : 4.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 650
Aneroid pressure
hPa : -
Del. quantity
cm³/1000 strokes : 200.0

L04

Tolerance
cm³/1000 strokes : + 1.0

Check tolerance
cm³/1000S. : + 3.0

Spreed

Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 6.5

CONTROL LEVER

control lever
position degree : 97.0
tolerance degree : + 4.0

RATED SPEED

rack travel mm : 10.20
Rated speed rpm : 750
Tolerance 1/min : + 5

rack travel mm : 4.00
Rated speed rpm : 800
Tolerance 1/min : + 5

rack travel mm : 0.85
Tolerance mm : + 0.55
Rated speed rpm : 900

rack travel mm : 4.00
Rated speed rpm : 805

LOW IDLE

control lever
position degree : 76.0
tolerance degree : + 4.0

Testing:

Rated speed rpm : 340
rack travel mm : 5.20
Tolerance mm : + 0.10

Rated speed rpm : 100

CRT mm min. : > 19.00

TORQUE CONTROL

Rated speed rpm : 650
rack travel mm : 11.65
Tolerance mm : + 0.05

Start interlock

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : \pm 0.50
Del. quantity
cm³/1000 strokes : 145.0
Tolerance
cm³/1000 strokes : \pm 20.0
Check tolerance
cm³/1000s. : \pm 25.0

LOW IDLE

Rated speed rpm : 340
Del. quantity
cm³/1000 strokes : 35.0
Tolerance
cm³/1000 strokes : \pm 2.0
Check tolerance
cm³/1000s. : \pm 4.5
Spread
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000s. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 11.02.97
Test oil : ISO 4113
Combination No. : 0 402 076 770C

Injection pump
Pump designation : PES6P110A320LS3318
EP type number :

Governor
Governor design. : RSV350...750P4A561
Governor no. :

Cust. part No. : 1823837C91C

Customer-spec. information
Customer : NAVISTAR
Motor : DT-531
Power KW : 227.5

TEST BENCH REQUIREMENTS

Inlet line : 4.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 076

Inlet press. bar : 2.8
Tolerance bar : ± 0.1

Test nozzle holde
assembly : 1 688 901 101

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 015

Outside diameter : 6.0

L06

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0

Prestroke mm : 3.00
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.75

Start of delivery blocking
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 900

Rack travel in mm : 12.45
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 213.5

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 3.0

Spread

Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 6.5

Rated speed rpm : 340

Rack travel in mm : 5.20
Tolerance mm : ± 0.10

Del. quantity
cm³/1000 strokes : 35.0

Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 4.5

Spread

Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : - 3
Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : ± 0.20

governor spring
pre-tension
click setting x : 4.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 900
Aneroid pressure
hPa : -
Del. quantity
cm³/1000 strokes : 213.5

L07

Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 3.0

Spread

Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 6.5

CONTROL LEVER

control lever
position degree : 97.0
tolerance degree : ± 4.0

RATED SPEED

rack travel mm : 11.40
Rated speed rpm : 910
Tolerance 1/min : ± 5

rack travel mm : 4.00
Rated speed rpm : 950

rack travel mm : 0.85
Tolerance mm : ± 0.55
Rated speed rpm : 1025

rack travel mm : 4.00
Rated speed rpm : 955

LOW IDLE

control lever
position degree : 76.0
tolerance degree : ± 4.0

Testing:

Rated speed rpm : 340
rack travel mm : 5.20
Tolerance mm : ± 0.10

Rated speed rpm : 100

CRT mm min. : > 19.00

TORQUE CONTROL

Rated speed rpm : 900
rack travel mm : 12.45
Tolerance mm : ± 0.05

Start interlock

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : \pm 0.50
Del. quantity
cm³/1000 strokes : 145.0
Tolerance
cm³/1000 strokes : \pm 20.0
Check tolerance
cm³/1000S. : \pm 25.0

LOW IDLE

Rated speed rpm : 340
Del. quantity
cm³/1000 strokes : 35.0
Tolerance
cm³/1000 strokes : \pm 2.0
Check tolerance
cm³/1000S. : \pm 4.5
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 11.02.97
Test oil : ISO 4113
Combination No. : 0 402 076 770D

Injection pump
Pump designation : PES6P110A320LS3318
EP type number :

Governor
Governor design. : RSV350...750P4A56?
Governor no. :

Cust. part No. : 1823837C91D

Customer spec. information
Customer : NAVISTAR
Motor : DT-531
Power KW : 160.5

TEST BENCH REQUIREMENTS

Inlet line : 4.2

Test oil inlet temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 076

Inlet press. bar : 2.8
Tolerance bar : ± 0.1

Test nozzle holder assembly : 1 688 901 101

Opening pressure bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 015

Outside diameter : 6.0

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0

Prestroke mm : 3.00
Tolerance mm : ± 0.05
Check tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check tolerance *NW : ± 0.75

Start of delivery blocking
Tolerance : ± 0.50
Check tolerance *NW : ± 0.75

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 650

Rack travel in mm : 11.15
Tolerance mm : ± 0.05

Del. quantity cm³/1000 strokes : 187.0

Tolerance
 cm³/1000 strokes : ± 1.0

Check tolerance
 cm³/1000S. : ± 3.0

Spread

Tolerance
 cm³/1000 strokes : 4.0

Check tolerance
 cm³/1000S. : 8.0

Rated speed rpm : 340

Rack travel in mm : 5.20
 Tolerance mm : ± 0.10

Del. quantity
 cm³/1000 strokes : 35.0

Tolerance
 cm³/1000 strokes : ± 2.0

Check tolerance
 cm³/1000S. : ± 4.5

Spread

Tolerance
 cm³/1000 strokes : 8.0

Check tolerance
 cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
 WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
 position degree : - 3
 Rated speed rpm : 800

Rack travel in mm : 0.50
 Tolerance mm : ± 0.20

governor spring
 pre-tension
 click setting x : 4.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 650
 Aneroid pressure
 hPa : -
 Del. quantity
 cm³/1000 strokes : 187.0

L10

Tolerance
 cm³/1000 strokes : ± 1.0

Check tolerance
 cm³/1000S. : ± 3.0

Spread

Tolerance
 cm³/1000 strokes : 4.0

Check tolerance
 cm³/1000S. : 8.0

CONTROL LEVER

control lever
 position degree : 97.0
 tolerance degree : ± 4.0

RATED SPEED

rack travel mm : 10.20
 Rated speed rpm : 750
 Tolerance 1/min : ± 5

rack travel mm : 4.00
 Rated speed rpm : 800
 Tolerance 1/min : ± 5

rack travel mm : 0.85
 Tolerance mm : ± 0.55
 Rated speed rpm : 900

rack travel mm : 4.00
 Rated speed rpm : 805

LOW IDLE

control lever
 position degree : 76.0
 tolerance degree : ± 4.0

Testing:

Rated speed rpm : 340
 rack travel mm : 5.20
 Tolerance mm : ± 0.10

Rated speed rpm : 100

CRT mm min. : > 19.00

TORQUE CONTROL

Rated speed rpm : 650
 rack travel mm : 11.15
 Tolerance mm : ± 0.05

Start interlock

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : \pm 0.50
Del. quantity
cm³/1000 strokes : 145.0
Tolerance
cm³/1000 strokes : \pm 20.0
Check tolerance
cm³/1000S. : \pm 25.0

LOW IDLE

Rated speed rpm : 340
Del. quantity
cm³/1000 strokes : 35.0
Tolerance
cm³/1000 strokes : \pm 2.0
Check tolerance
cm³/1000S. : \pm 4.5
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 25.09.96
Test oil : ISO 4113
Combination No. : 0 402 076 770E
Injection pump
Pump designation : PES6P110A32OLS3318
EP type number :
Governor
Governor design. : RS/350...75GP4A561
Governor no. :
Cust. part No. : 1823837C91E

Customer-spec. information
Customer : NAVISTAR
Motor : DT-531
Power kW : 149.0

TEST BENCH REQUIREMENTS

Inlet line : 4.2
Test oil inlet temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 1 417 413 076
Inlet press. bar : 2.8
Tolerance bar : ± 0.1
Test nozzle holder assembly : 1 688 901 101
Opening pressure bar : 208.5
Tolerance bar : ± 1.5
Test lines : 1 680 750 015
Outside diameter : 6.0

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0
Prestroke mm : 3.00
Tolerance mm : ± 0.05
Check tolerance mm : ± 0.10
Rack travel in mm : 10.50
Tolerance mm : ± 1.50
Firing order : 1- 5- 3- 6- 2-
: 4
Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check tolerance °NW : ± 0.75
Start of delivery blocking
Tolerance : ± 0.50
Check tolerance °NW : ± 0.75
Barrel no. : 1

BASIC SETTING

Rated speed rpm : 650
Rack travel in mm : 10.75
Tolerance mm : ± 0.05
Del. quantity cm³/1000 strokes : 176.5

Tolerance
 cm³/1000 strokes : + 1.0

Check tolerance
 cm³/1000S. : + 3.0

Spreed

Tolerance
 cm³/1000 strokes : 4.0

Check tolerance
 cm³/1000S. : 6.5

Rated speed rpm : 340

Rack travel in mm : 5.20
 Tolerance mm : + 0.10
 Del. quantity
 cm³/1000 strokes : 35.0
 Tolerance
 cm³/1000 strokes : + 2.0
 Check tolerance
 cm³/1000S. : + 4.5
 Spreed
 Tolerance
 cm³/1000 strokes : 8.0
 Check tolerance
 cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
 WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
 position degree : - 3
 Rated speed rpm : 800

Rack travel in mm : 0.50
 Tolerance mm : + 0.20

governor spring
 pre-tension
 click setting x : 4.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 650
 Aneroid pressure
 hPa : -
 Del. quantity
 cm³/1000 strokes : 176.5

Tolerance
 cm³/1000 strokes : + 1.0
 Check tolerance
 cm³/1000S. : + 3.0
 Spreed
 Tolerance
 cm³/1000 strokes : 4.0
 Check tolerance
 cm³/1000S. : 6.5

CONTROL LEVER

control lever
 position degree : 97.0
 tolerance degree : + 4.0

RATED SPEED

rack travel mm : 10.20
 Rated speed rpm : 750
 Tolerance 1/min : + 5

rack travel mm : 4.00
 Rated speed rpm : 800
 Tolerance 1/min : + 5

rack travel mm : 0.85
 Tolerance mm : + 0.55
 Rated speed rpm : 900

rack travel mm : 4.00
 Rated speed rpm : 805

LOW IDLE

control lever
 position degree : 76.0
 tolerance degree : + 4.0

Testing:

Rated speed rpm : 340
 rack travel mm : 5.20
 Tolerance mm : + 0.10

Rated speed rpm : 100

CRT mm min. : > 19.00

TORQUE CONTROL

Rated speed rpm : 650
 rack travel mm : 10.75
 Tolerance mm : + 0.05

Start interlock

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : \pm 0.50
Del. quantity
cm³/1000 strokes : 145.0
Tolerance
cm³/1000 strokes : \pm 20.0
Check tolerance
cm³/1000S. : \pm 25.0

LOW IDLE

Rated speed rpm : 340
Del. quantity
cm³/1000 strokes : 35.0
Tolerance
cm³/1000 strokes : \pm 2.0
Check tolerance
cm³/1000S. : \pm 4.5
Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 11.02.97
Test oil : ISO 4113
Combination No. : 0 402 076 770F

Injection pump
Pump designation : PES6P110A320LS3318
EP type number :

Governor
Governor design. : RSV350...750P4A561
Governor no. :

Cust. part No. : 1823837C91F

Customer-spec. information
Customer : NAVISTAR
Motor : DT-531
Power KW : 171.5

TEST BENCH REQUIREMENTS

Inlet line : 4.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 076

Inlet press. bar : 2.8
Tolerance bar : ± 0.1

Test nozzle holde
assembly : 1 688 901 101

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 015

Outside diameter : 6.0

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0

Prestroke mm : 3.00
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.75

Start of delivery blocking
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 900

Rack travel in mm : 12.45
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 222.5

Tolerance
 cm³/1000 strokes : + 1.0

Check tolerance
 cm³/1000S. : + 3.0

Spread

Tolerance
 cm³/1000 strokes : 4.0

Check tolerance
 cm³/1000S. : 6.5

Rated speed rpm : 340

Rack travel in mm : 5.20
 Tolerance mm : + 0.10

Del. quantity
 cm³/1000 strokes : 35.0

Tolerance
 cm³/1000 strokes : + 2.0

Check tolerance
 cm³/1000S. : + 4.5

Spread

Tolerance
 cm³/1000 strokes : 8.0

Check tolerance
 cm³/1000S. : 12.0

(3) SETTING OF INJECTION PUMP
 WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
 position degree : - 3

Rated speed rpm : 800

Rack travel in mm : 0.50
 Tolerance mm : + 0.20

governor spring
 pre-tension
 click setting x : 4.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 900

Aneroid pressure
 hPa : -

Del. quantity
 cm³/1000 strokes : 222.5

Tolerance
 cm³/1000 strokes : + 1.0

Check tolerance
 cm³/1000S. : + 3.0

Spread

Tolerance
 cm³/1000 strokes : 4.0

Check tolerance
 cm³/1000S. : 6.5

CONTROL LEVER

control lever
 position degree : 97.0

tolerance degree : + 4.0

RATED SPEED

rack travel mm : 11.40

Rated speed rpm : 910

Tolerance 1/min : + 5

rack travel mm : 4.00

Rated speed rpm : 950

Tolerance 1/min : + 5

rack travel mm : 0.85

Tolerance mm : + 0.55

Rated speed rpm : 1025

rack travel mm : 4.00

Rated speed rpm : 955

LOW IDLE

control lever
 position degree : 76.0

tolerance degree : + 4.0

Testing:

Rated speed rpm : 340

rack travel mm : 5.20

Tolerance mm : + 0.10

Rated speed rpm : 100

CRT mm min. : > 19.00

TORQUE CONTROL

Rated speed rpm : 900

rack travel mm : 12.45

Tolerance mm : + 0.05

Start interlock

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : \pm 0.50
Del. quantity
cm³/1000 strokes : 145.0
Tolerance
cm³/1000 strokes : \pm 20.0
Check tolerance
cm³/1000s. : \pm 25.0

LOW IDLE

Rated speed rpm : 340
Del. quantity
cm³/1000 strokes : 35.0
Tolerance
cm³/1000 strokes : \pm 2.0
Check tolerance
cm³/1000s. : \pm 4.5
Spread
tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000s. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 11.02.97
Test oil : ISO 4113
Combination No. : 0 402 076 7706
Injection pump
Pump designation : PES6P110A320LS3318
EP type number :
Governor
Governor design. : RSV350...750P4A561
Governor no. :
Cust. part No. : 1823837C91G

Customer-spec. information
Customer : NAVISIAAR
Motor : DT-531
Power KW : 130.5

TEST BENCH REQUIREMENTS

Inlet line : 4.2
Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 1 417 413 076
Inlet press. bar : 2.8
Tolerance bar : ± 0.1
Test nozzle holde
assembly : 1 688 901 101
Opening pressure
bar : 208.5
Tolerance bar : ± 1.5
Test lines : 1 680 750 015
Outside diameter : 6.0

L18

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0
Prestroke mm : 3.00
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10
Rack travel in mm : 10.50
Tolerance mm : ± 1.50
Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.75

Start of delivery blocking
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75
Barrel no. : 1

BASIC SETTING

Rated speed rpm : 650
Rack travel in mm : 9.95
Tolerance mm : ± 0.05
Del. quantity
cm³/1000 strokes : 158.0

Tolerance
cm³/1000 strokes : + 1.0

Check tolerance
cm³/1000S. : + 3.0

Spread

Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 8.0

Rated speed rpm : 340

Rack travel in mm : 5.20
Tolerance mm : + 0.10

Del. quantity
cm³/1000 strokes : 35.0

Tolerance
cm³/1000 strokes : + 2.0

Check tolerance
cm³/1000S. : + 4.5

Spread
Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : - 3
Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : + 0.20

governor spring
pre-tension
click setting x : 4.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 650
Aneroid pressure
hPa : -
Del. quantity
cm³/1000 strokes : 158.0

L19

Tolerance
cm³/1000 strokes : + 1.0

Check tolerance
cm³/1000S. : + 3.0

Spread
Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 8.0

CONTROL LEVER

control lever
position degree : 97.0

RATED SPEED
rack travel mm : 10.20

Rated speed rpm : 750
Tolerance 1/min : + 5

rack travel mm : 4.00
Rated speed rpm : 800

Tolerance 1/min : + 5

rack travel mm : 0.85
Tolerance mm : + 0.55

Rated speed rpm : 900

rack travel mm : 4.00
Rated speed rpm : 805

LOW IDLE

control lever
position degree : 76.0

Testing:

Rated speed rpm : 340
rack travel mm : 5.20

Tolerance mm : + 0.10

Rated speed rpm : 100

CRT mm min. : > 19.00

TORQUE CONTROL

Rated speed rpm : 650
rack travel mm : 9.95

Tolerance mm : + 0.05

Start interlock

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : \pm 0.50
Del. quantity
cm³/1000 strokes : 145.0
Tolerance
cm³/1000 strokes : \pm 20.0
Check tolerance
cm³/1000s. : \pm 25.0

LOW IDLE

Rated speed rpm : 340
Del. quantity
cm³/1000 strokes : 35.0
Tolerance
cm³/1000 strokes : \pm 2.0
Check tolerance
cm³/1000s. : \pm 4.5
Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000s. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 11.02.97
Test oil : ISO 4113
Combination No. : 0 402 076 770H

Injection pump
Pump designation : PES6P110A320LS3318
EP type number :

Governor
Governor design. : RSV350...750P4A561
Governor no. :

Cust. part No. : 1823837C91H

Customer-spec. information
Customer : NAVISTAR
Motor : DT-531
Power KW : 149.0

TEST BENCH REQUIREMENTS

Inlet line : 4.2

Test oil inlet temp. °C : 40
Tolerance °C : + 2.0

Overflow valve : 1 417 413 076

Inlet press. bar : 2.8
Tolerance bar : + 0.1

Test nozzle holder assembly : 1 688 901 101

Opening pressure bar : 208.5
Tolerance bar : + 1.5

Test lines : 1 680 750 015

Outside diameter : 6.0

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : + 1.0

Prestroke mm : 3.00
Tolerance mm : + 0.05
Check tolerance mm : + 0.10

Rack travel in mm : 10.50
Tolerance mm : + 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : + 0.30
Check tolerance °NW : + 0.75

Start of delivery blocking
Tolerance : + 0.50
Check tolerance °NW : + 0.75

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 900

Rack travel in mm : 9.95
Tolerance mm : + 0.05

Del. quantity cm³/1000 strokes : 138.5

Tolerance
cm³/1000 strokes : + 1.0

Check tolerance
cm³/1000S. : + 3.0

Speed

Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 6.5

Rated speed rpm : 340

Rack travel in mm : 5.20
Tolerance mm : + 0.10

Del. quantity
cm³/1000 strokes : 35.0

Tolerance
cm³/1000 strokes : + 2.0

Check tolerance
cm³/1000S. : + 4.5

Speed
Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : - 3
Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : + 0.20

governor spring
pre-tension
click setting x : 4.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 900
Aneroid pressure
hPa : -
Del. quantity
cm³/1000 strokes : 138.5

Tolerance
cm³/1000 strokes : + 1.0

Check tolerance
cm³/1000S. : + 3.0

Speed
Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 6.5

CONTROL LEVER

control lever
position degree : 97.0
tolerance degree : + 4.0

RATED SPEED

rack travel mm : 8.90
Rated speed rpm : 920
Tolerance 1/min : + 5

rack travel mm : 4.00
Rated speed rpm : 950

rack travel mm : 0.85
Tolerance mm : + 0.55
Rated speed rpm : 1025

rack travel mm : 4.00
Rated speed rpm : 955

LOW IDLE

control lever
position degree : 76.0
tolerance degree : + 4.0

Testing:

Rated speed rpm : 340
rack travel mm : 5.20
Tolerance mm : + 0.10

Rated speed rpm : 100

CRT mm min. : > 19.00

TORQUE CONTROL

Rated speed rpm : 900
rack travel mm : 9.95
Tolerance mm : + 0.05

Start interlock

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : \pm 0.50
Del. quantity
cm³/1000 strokes : 145.0
Tolerance
cm³/1000 strokes : \pm 20.0
Check tolerance
cm³/1000S. : \pm 25.0

LOW IDLE

Rated speed rpm : 340
Del. quantity
cm³/1000 strokes : 35.0
Tolerance
cm³/1000 strokes : \pm 2.0
Check tolerance
cm³/1000S. : \pm 4.5
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 11.02.97
Test oil : ISO 4113
Combination No. : 0 402 076 770J
Injection pump
Pump designation : PES6P110A320LS3318
EP type number :
Governor
Governor design. : RSV350...750P4A561
Governor no. :
Cust. part No. : 1823837C91J

Customer-spec. information:
Customer : NAVISTAR
Motor : DT-531
Power KW : 231.0

TEST BENCH REQUIREMENTS

Inlet line : 4.2
Test oil inlet temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 1 417 413 076
Inlet press. bar : 2.8
Tolerance bar : ± 0.1
Test nozzle holder assembly : 1 688 901 101
Opening pressure bar : 208.5
Tolerance bar : ± 1.5
Test lines : 1 680 750 015
Outside diameter : 6.0

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0
Prestroke mm : 3.0J
Tolerance mm : ± 0.05
Check tolerance mm : ± 0.10
Rack travel in mm : 10.5J
Tolerance mm : ± 1.50
Firing order : 1- 5- 3- 6- 2-
: 4
Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check tolerance °NW : ± 0.75
Start of delivery blocking
Tolerance : ± 0.50
Check tolerance °NW : ± 0.75
Barrel no. : 1

BASIC SETTING

Rated speed rpm : 650
Rack travel in mm : 12.65
Tolerance mm : ± 0.05
Del. quantity cm³/1000 strokes : 228.5

Tolerance
 cm³/1000 strokes : + 1.0

Check tolerance
 cm³/1000S. : + 3.0

Spread

Tolerance
 cm³/1000 strokes : 4.0

Check tolerance
 cm³/1000S. : 6.5

Rated speed rpm : 340

Rack travel in mm : 5.20
 Tolerance mm : + 0.10

Del. quantity
 cm³/1000 strokes : 35.0

Tolerance
 cm³/1000 strokes : + 2.0

Check tolerance
 cm³/1000S. : + 4.5

Spread

Tolerance
 cm³/1000 strokes : 8.0

Check tolerance
 cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
 WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
 position degree : - 3

Rated speed rpm : 800

Rack travel in mm : 0.50
 Tolerance mm : + 0.20

governor spring
 pre-tension
 click setting x : 4.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 650

Aneroid pressure
 hPa : -

Del. quantity
 cm³/1000 strokes : 228.5

L25

Tolerance
 cm³/1000 strokes : + 1.0

Check tolerance
 cm³/1000S. : + 3.0

Spread

Tolerance
 cm³/1000 strokes : 4.0

Check tolerance
 cm³/1000S. : 6.5

CONTROL LEVER

control lever
 position degree : 97.0

tolerance degree : + 4.0

RATED SPEED

rack travel mm : 10.20

Rated speed rpm : 750

Tolerance 1/min : + 5

rack travel mm : 4.00

Rated speed rpm : 800

Tolerance 1/min : + 5

rack travel mm : 0.85

Tolerance mm : + 0.55

Rated speed rpm : 900

rack travel mm : 4.00

Rated speed rpm : 805

LOW IDLE

control lever
 position degree : 76.0

tolerance degree : + 4.0

Testing:

Rated speed rpm : 340

rack travel mm : 5.20

Tolerance mm : + 0.10

Rated speed rpm : 100

CRT mm min. : > 19.00

TORQUE CONTROL

Rated speed rpm : 650

rack travel mm : 12.65

Tolerance mm : + 0.05

Start interlock

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : + 0.50
Del. quantity
cm³/1000 strokes : 145.0
Tolerance
cm³/1000 strokes : + 20.0
Check tolerance
cm³/1000S. : + 25.0

LOW IDLE

Rated speed rpm : 340
Del. quantity
cm³/1000 strokes : 35.0
Tolerance
cm³/1000 strokes : + 2.0
Check tolerance
cm³/1000S. : + 4.5
Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 06.02.97
Test oil : ISO 4113

Combination No. : 0 402 076 815

Injection pump
Pump designation : PES6P120A320LS3387
EP type number : 0 412 026 804

Governor
Governor design. : RSV350...750P4A561
Governor no. : 0 421 833 593

Cust. part No. : 1829851C91

Customer-spec. information
Customer : NAVISTAR
Motor : DTA-531
Power KW : 224.0

TEST BENCH REQUIREMENTS

Inlet line : 2.4

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 076

Inlet press. bar : 2.8
Tolerance bar : ± 0.1

Test nozzle holder
assembly : 1 688 901 101

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 015

Outside diameter : 6.0

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0

Prestroke mm : 3.00
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.75

Start of delivery blocking
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 700

Rack travel in mm : 13.50
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 249.0

Tolerance
 cm³/1000 strokes : +- 1.0

Check tolerance
 cm³/1000S. : +- 3.0

Spread

Tolerance
 cm³/1000 strokes : 4.0

Check tolerance
 cm³/1000S. : 6.5

Rated speed rpm : 350

Rack travel in mm : 5.50
 Tolerance mm : +- 0.10
 Del. quantity
 cm³/1000 strokes : 38.5
 Tolerance
 cm³/1000 strokes : +- 2.0
 Check tolerance
 cm³/1000S. : +- 4.5
 Spread
 Tolerance
 cm³/1000 strokes : 8.0
 Check tolerance
 cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
 WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
 position degree : - 3
 Rated speed rpm : 800

Rack travel in mm : 0.50
 Tolerance mm : +- 0.20

governor spring
 pre-tension
 click setting x : 3.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 700
 Aneroid pressure
 hPa : -
 Del. quantity
 cm³/1000 strokes : 249.0

Tolerance
 cm³/1000 strokes : +- 1.0
 Check tolerance
 cm³/1000S. : +- 3.0
 Spread
 Tolerance
 cm³/1000 strokes : 4.0
 Check tolerance
 cm³/1000S. : 6.5

CONTROL LEVER

control lever
 position degree : 91.0
 tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 13.50
 Rated speed rpm : 760
 Tolerance 1/min : +- 5

rack travel mm : 4.00
 Rated speed rpm : 810
 Tolerance 1/min : +- 5

rack travel mm : 0.85
 Tolerance mm : +- 0.55
 Rated speed rpm : 900

rack travel mm : 4.00
 Rated speed rpm : 810

LOW IDLE

control lever
 position degree : 73.0
 tolerance degree : +- 4.0

Testing:

Rated speed rpm : 350
 rack travel mm : 5.50
 Tolerance mm : +- 0.10

Rated speed rpm : 100

CRT mm min. : > 19.00

TORQUE CONTROL

Rated speed rpm : 700
 rack travel mm : 13.50
 Tolerance mm : +- 0.05

Start interlock

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : \pm 0.50
Del. quantity
cm³/1000 strokes : 103.0
Tolerance
cm³/1000 strokes : \pm 20.0
Check tolerance
cm³/1000S. : \pm 25.0

LOW IDLE

Rated speed rpm : 350
Del. quantity
cm³/1000 strokes : 38.5
Tolerance
cm³/1000 strokes : \pm 2.0
Check tolerance
cm³/1000S. : \pm 4.5
Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 05.06.96
Test oil : ISO 4113

Combination No. : 0 402 736 843

Injection pump
Pump designation : PES6P12GA12CIRS7281
EP type number : 0 412 726 890

Governor
Governor design. : RQV400...1250PA1060K
Governor no. : 0 421 815 343

Cust. part No. : 3925086

Customer-spec. information
Customer : CDC
Motor : 68TA-A
Power KW : 130.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 093

Inlet press. bar : 2.0
Tolerance bar : ± 0.1

Test nozzle holder assembly : 1 688 901 103

Opening pressure bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 015

Outside diameter : 6.0

M02

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0

Prestroke mm : 3.60
Tolerance mm : ± 0.05
Check tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check tolerance *NW : ± 0.75

Start of delivery blocking

*NW after s.o.d. : 6.25
Tolerance : ± 0.50
Check tolerance *NW : ± 0.75

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1250

Rack travel in mm : 13.65
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 160.5

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 4.0

Sp. read

Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

Rated speed rpm : 420

Rack travel in mm : 6.00
Tolerance mm : ± 0.20

Del. quantity
cm³/1000 strokes : 15.0

Tolerance
cm³/1000 strokes : ± 3.0

Check tolerance
cm³/1000S. : ± 5.0

Spreed
Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 8.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 1328
guide sleeve
travel mm : 7.62
Tolerance mm : ± 0.15

Rated speed rpm : 400
guide sleeve
travel mm : 1.44
Tolerance mm : ± 0.20

Rated speed rpm : 685
guide sleeve
travel mm : 3.50
Tolerance mm : ± 0.25

Rated speed rpm : 490
guide sleeve
travel mm : 2.50

Tolerance mm : ± 0.25

Rated speed rpm : 1710
guide sleeve
travel mm : 11.50
Tolerance mm : ± 0.50

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1250
Aneroid pressure
hPa : 1200

Del. quantity
cm³/1000 strokes : 160.5

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 4.0

Spreed
Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

CONTROL LEVER

control lever
position degree : 117.0
tolerance degree : ± 6.0

RATED SPEED

rack travel mm : 12.60
Rated speed rpm : 1325
Tolerance 1/min : ± 15

rack travel mm : 4.00
Rated speed rpm : 1480
Tolerance 1/min : ± 5

rack travel mm : 0.50
Tolerance mm : ± 0.50
Rated speed rpm : 1550

LOW IDLE

control lever
position degree : 72.0
tolerance degree : ± 6.0

Control Lever difference

Grad : 45.0
tolerance degree : ± 6.0

Testing:

Rated speed rpm : 420
rack travel mm : 6.00
Tolerance mm : ± 0.20

Rated speed rpm : 300
CRT mm min. : > 7.70

Rated speed rpm : 425

TORQUE CONTROL

Rated speed rpm : 1250
rack travel mm : 13.65
Tolerance mm : ± 0.05

Rated speed rpm : 800
rack travel mm : 11.90
Tolerance mm : ± 0.10

Rated speed rpm : 500
rack travel mm : 11.60
Tolerance mm : ± 0.20

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 1250
Pressure hPa : 1200

Pressure hPa : -
Rated speed rpm : 1250
rack travel mm : 10.40
Tolerance mm : ± 0.20

MEASUREMENT

Rated speed rpm : 1250

Pressure hPa : 375
rack travel mm : 12.80
Tolerance mm : ± 0.30

Pressure hPa : 260
rack travel mm : 11.70
Tolerance mm : ± 0.20

Start interlock

Rated speed rpm : > 100
Rated speed rpm : < 280

Check speed 1/min : > 80
Check speed 1/min : < 290

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure hPa : 1200
Rated speed rpm : 800
Del. quantity cm³/1000 strokes : 131.5
Tolerance cm³/1000 strokes : ± 3.0
Check tolerance cm³/1000S. : ± 6.0
Spread Tolerance cm³/1000 strokes : 8.0
Check tolerance cm³/1000S. : 12.0

Aneroid pressure hPa : -
Rated speed rpm : 1250
Del. quantity cm³/1000 strokes : 107.5
Tolerance cm³/1000 strokes : ± 1.0
Check tolerance cm³/1000S. : ± 4.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 13.50
Tolerance mm : ± 0.50
Del. quantity cm³/1000 strokes : 155.0
Tolerance cm³/1000 strokes : ± 20.0
Check tolerance cm³/1000S. : ± 25.0

LOW IDLE

Rated speed rpm : 420
Del. quantity cm³/1000 strokes : 15.0
Tolerance cm³/1000 strokes : ± 3.0
Check tolerance cm³/1000S. : ± 5.0
Spread

Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 8.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 24.05.96
Test oil : ISO 4113

Combination No. : 0 402 736 844

Injection pump
Pump designation : PES6P120A12URS7287
EP type number : 0 412 726 896

Governor
Governor design. : RQV400...1250PA964
: 1K
Governor no. : 0 421 815 354

Cust. part No. : 3921925

Customer-spec. information
Customer : CDC
Motor : 6BTA-A
Power kW : 171.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 093

Inlet press. bar : 2.0
Tolerance bar : ± 0.1

Test nozzle holder
assembly : 1 688 901 103

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 015

Outside diameter : 6.0
x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0

Prestroke mm : 3.60
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 12.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.75

Start of delivery blocking

*NW after s.o.d. : 6.25
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1150

Rack travel in mm : 14.85
Tolerance mm : ± 0.05

<hr/>	
Del. quantity	
cm ³ /1000 strokes :	194.5
<hr/>	
Tolerance	
cm ³ /1000 strokes :	+ 1.0
<hr/>	
Check tolerance	
cm ³ /1000S. :	+ 4.0
<hr/>	
Spreed	
<hr/>	
Tolerance	
cm ³ /1000 strokes :	8.0
<hr/>	
Check tolerance	
cm ³ /1000S. :	12.0
<hr/>	

Rated speed rpm :	420
Rack travel in mm :	5.90
Tolerance mm :	+ 0.20
Del. quantity	
cm ³ /1000 strokes :	16.5
Tolerance	
cm ³ /1000 strokes :	+ 3.0
Check tolerance	
cm ³ /1000S. :	+ 5.0
Spreed	
Tolerance	
cm ³ /1000 strokes :	4.0
Check tolerance	
cm ³ /1000S. :	8.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever	
position degree :	MAX
Rated speed rpm :	1475
Rack travel in mm :	10.50
Tolerance mm :	+ 1.50

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm :	1150
Anerofid pressure	
hPa :	1200
Del. quantity	
cm ³ /1000 strokes :	194.5

M07

Tolerance	
cm ³ /1000 strokes :	+ 1.0
Check tolerance	
cm ³ /1000S. :	+ 4.0
Spreed	
Tolerance	
cm ³ /1000 strokes :	8.0
Check tolerance	
cm ³ /1000S. :	12.0

CONTROL LEVER

control lever	
position degree :	120.0
tolerance degree :	+ 6.0

RATED SPEED

rack travel mm :	13.40
Rated speed rpm :	1315
Tolerance 1/min :	+ 15

rack travel mm :	4.00
Rated speed rpm :	1485
Tolerance 1/min :	+ 5

rack travel mm :	0.50
Tolerance mm :	+ 0.50
Rated speed rpm :	1550

LOW IDLE

control lever	
position degree :	73.0
tolerance degree :	+ 6.0

Control lever difference

Grad :	47.0
tolerance degree :	+ 4.0

Testing:

Rated speed rpm :	420
rack travel mm :	5.90
Tolerance mm :	+ 0.20

Rated speed rpm :	300
-------------------	-----

CRT mm min. :	> 9.00
---------------	--------

Rated speed rpm :	425
-------------------	-----

TORQUE CONTROL

Rated speed rpm : 1150
rack travel mm : 14.85
Tolerance mm : ± 0.05

Rated speed rpm : 800
rack travel mm : 14.00
Tolerance mm : ± 0.20

Rated speed rpm : 1250
rack travel mm : 14.50
Tolerance mm : ± 0.10

Rated speed rpm : 900
rack travel mm : 14.20
Tolerance mm : ± 0.20

Rated speed rpm : 600
rack travel mm : 13.40
Tolerance mm : ± 0.20

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 1150
Pressure hPa : 1200

Pressure hPa : -
Rated speed rpm : 1150
rack travel mm : 10.00
Tolerance mm : ± 0.20

MEASUREMENT

Rated speed rpm : 1150

Pressure hPa : 645
rack travel mm : 12.80
Tolerance mm : ± 0.30

Pressure hPa : 355
rack travel mm : 10.80
Tolerance mm : ± 0.20

Start interlock

Rated speed rpm : > 100
Rated speed rpm : < 315

Check
speed 1/min : > 80
Check
speed 1/min : < 325

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1200
Rated speed rpm : 900
Del. quantity
cm³/1000 strokes : 182.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0
Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

Aneroid pressure
hPa : -
Rated speed rpm : 1150
Del. quantity
cm³/1000 strokes : 92.0
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 4.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 12.50
Tolerance mm : ± 0.50
Del. quantity
cm³/1000 strokes : 155.0
Tolerance
cm³/1000 strokes : ± 20.0
Check tolerance
cm³/1000S. : ± 25.0

LOW IDLE

Rated speed rpm : 420
Del. quantity
cm³/1000 strokes : 16.5
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 5.0
Speed
Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 8.0

End of test specification sheet



BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 15.05.96
Test oil : ISO 4113

Combination No. : 0 402 736 870

Injection pump
Pump designation : PES6P120A120RS7352
EP type number : 0 412 726 923

Governor
Governor design. : RQV350...900PA1175K
Governor no. : 0 421 815 441

Cust. part No. : 3928156

Customer-spec. information
Customer : CDC
Motor : 5CTA-A
Power KW : 205.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 093

Inlet press. bar : 2.0
Tolerance bar : ± 0.1

Test nozzle holde
assembly : 1 688 901 103

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 015

Outside diameter : 6.0

M10

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0

Prestroke mm : 4.00
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.75

Start of delivery blocking

*NW after s.o.d. : 5.50
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 900

Rack travel in mm : 15.25
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 236.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spread

Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 350

Rack travel in mm : 7.00
Tolerance mm : +- 0.10

Del. quantity
cm³/1000 strokes : 27.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 5.0

Spread
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : VH
Rated speed rpm : 1150

Rack travel in mm : 13.90

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 900
Aneroid pressure
hPa : 1200
Del. quantity
cm³/1000 strokes : 236.0
Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spread
Tolerance
cm³/1000 strokes : 5.0
Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 119.0
tolerance degree : +- 6.0

RATED SPEED

rack travel mm : 13.90
Rated speed rpm : 1075
Tolerance 1/min : +- 15

rack travel mm : 4.00
Rated speed rpm : 1230
Tolerance 1/min : +- 5

rack travel mm : 0.50
Tolerance mm : +- 0.50
Rated speed rpm : 1400

LOW IDLE

control lever
position degree : 69.0
tolerance degree : +- 6.0

Control lever difference

Grad : 50.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 350
rack travel mm : 7.00
Tolerance mm : +- 0.10

Rated speed rpm : 275

CRT mm min. : > 8.10

Rated speed rpm : 425

TORQUE CONTROL

Rated speed rpm : 900
rack travel mm : 15.25

Tolerance mm : \pm 0.05
Rated speed rpm : 650
rack travel mm : 14.25
Tolerance mm : \pm 0.20

Rated speed rpm : 1000
rack travel mm : 15.00
Tolerance mm : \pm 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 900
Pressure hPa : 1200

Pressure hPa : -
Rated speed rpm : 900
rack travel mm : 9.70
Tolerance mm : \pm 0.20

MEASUREMENT

Rated speed rpm : 900

Pressure hPa : 825
rack travel mm : 13.80
Tolerance mm : \pm 0.20

Pressure hPa : 370
rack travel mm : 11.15
Tolerance mm : \pm 0.05

Start interlock

Rated speed rpm : $>$ 100
Rated speed rpm : $<$ 290

Check speed 1/min : $>$ 80
Check speed 1/min : $<$ 300

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure hPa : 1200
Rated speed rpm : 650
Del. quantity cm³/1000 strokes : 226.5
Tolerance cm³/1000 strokes : \pm 3.0
Check tolerance cm³/1000S. : \pm 6.0
Spreed

M12

Tolerance cm³/1000 strokes : 8.0
Check tolerance cm³/1000S. : 12.0

Aneroid pressure hPa : -
Rated speed rpm : 1000
Del. quantity cm³/1000 strokes : 99.0
Tolerance cm³/1000 strokes : \pm 1.0
Check tolerance cm³/1000S. : \pm 3.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 11.40
Tolerance mm : \pm 0.50
Del. quantity cm³/1000 strokes : 185.0
Tolerance cm³/1000 strokes : \pm 20.0
Check tolerance cm³/1000S. : \pm 25.0

LOW IDLE

Rated speed rpm : 350
Del. quantity cm³/1000 strokes : 27.0
Tolerance cm³/1000 strokes : \pm 3.0
Check tolerance cm³/1000S. : \pm 5.0
Spreed
Tolerance cm³/1000 strokes : 8.0
Check tolerance cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 28.05.96
Test oil : ISO 4113

Combination No. : 0 402 736 373

Injection pump
Pump designation : PES6P120A120RS7353
EP type number : 0 412 726 924

Governor
Governor design. : RQV350...1150PA1188K
Governor no. : 0 421 815 449

Cust. part No. : 392867i

Customer-spec. information

Customer : CDC
Motor : 6CTA-A
Power KW : 157.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet temp. °C : 40
Tolerance °C : +- 2.0

Overflow valve : 2 417 413 093

Inlet press. bar : 2.0
Tolerance bar : +- 0.1

Test nozzle holder assembly : 1 688 901 103

Opening pressure bar : 208.5
Tolerance bar : +- 1.5

Test lines : 1 680 750 015

Outside diameter : 6.0

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : +- 1.0

Prestroke mm : 4.00
Tolerance mm : +- 0.05
Check tolerance mm : +- 0.10

Rack travel in mm : 10.50
Tolerance mm : +- 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : +- 0.30
Check tolerance °NW : +- 0.75

Start of delivery blocking

*NW after s.o.d. : 5.25
Tolerance : +- 0.50
Check tolerance °NW : +- 0.75

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1100

Rack travel in mm : 12.85
Tolerance mm : +- 0.05

Del. quantity
cm³/1000 strokes : 137.5

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 4.0

Speed

Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 350

Rack travel in mm : 6.00
Tolerance mm : ± 0.20

Del. quantity
cm³/1000 strokes : 23.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 5.0

Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1100
Aneroid pressure
hPa : 1200
Del. quantity
cm³/1000 strokes : 187.5
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0
Speed
Tolerance
cm³/1000 strokes : 5.0
Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 114.0
tolerance degree : ± 6.0

RATED SPEED

rack travel mm : 11.80
Rated speed rpm : 1210
Tolerance 1/min : ± 15

rack travel mm : 4.00
Rated speed rpm : 1350
Tolerance 1/min : ± 5

rack travel mm : 0.50
Tolerance mm : ± 0.50
Rated speed rpm : 1425

LOW IDLE

control lever
position degree : 69.0
tolerance degree : ± 6.0

Control lever difference

Grad : 45.0
tolerance degree : ± 6.0

Testing:

Rated speed rpm : 350
rack travel mm : 6.00
Tolerance mm : ± 0.20

Rated speed rpm : 275

CRT mm min. : > 7.90

Rated speed rpm : 425

TORQUE CONTROL

Rated speed rpm : 1100
rack travel mm : 12.85
Tolerance mm : ± 0.05

Rated speed rpm : 650
rack travel mm : 11.80
Tolerance mm : ± 0.20

Rated speed rpm : 1150
rack travel mm : 12.80

Tolerance mm : ± 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 1100
Pressure hPa : 1200

Pressure hPa : -
Rated speed rpm : 1100
rack travel mm : 8.90
Tolerance mm : ± 0.20

MEASUREMENT

Rated speed rpm : 1100

Pressure hPa : 520
rack travel mm : 11.60
Tolerance mm : ± 0.20

Pressure hPa : 255
rack travel mm : 9.75
Tolerance mm : ± 0.05

Start interlock

Rated speed rpm : > 100
Rated speed rpm : < 290

Check
speed 1/min : > 80
Check
speed 1/min : < 300

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1200
Rated speed rpm : 650
Del. quantity
cm³/1000 strokes : 169.5
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

Aneroid pressure
hPa : -
Rated speed rpm : 1100

Del. quantity
cm³/1000 strokes : 91.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 3.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 11.50
Tolerance mm : ± 0.50
Del. quantity
cm³/1000 strokes : 185.0
Tolerance
cm³/1000 strokes : ± 20.0
Check tolerance
cm³/1000S. : ± 25.0

LOW IDLE

Rated speed rpm : 350
Del. quantity
cm³/1000 strokes : 23.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 5.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 10.02.97
Test oil : ISO 4113
Combination No. : 0 402 746 615
Injection pump
Pump designation : PES6P120A32ORS7419
EP type number : 0 412 726 961
Governor
Governor design. : RQV300...1250PA1289K
Governor no. : 0 421 815 520

Cust. part No. : 386 6800

Customer-spec. information
Customer : CDC
Motor : 6CTA
Power KW : 249.5

TEST BENCH REQUIREMENTS

Inlet line : 3.2
Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 2 417 413 093
Inlet press. bar : 2.0
Tolerance bar : ± 0.1
Test nozzle holder
assembly : 1 688 901 103
Opening pressure
bar : 208.5
Tolerance bar : ± 1.5
Test lines : 1 680 750 015
Outside diameter : 6.0

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0
Prestroke mm : 3.60
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10
Rack travel in mm : 10.50
Tolerance mm : ± 1.50
Firing order : 1- 5- 3- 6- 2-
: 4
Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.75
Start of delivery blocking
°NW after s.o.d. : 12.25
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75
Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1250
Rack travel in mm : 12.15
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 190.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 4.0

Speed

Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

Rated speed rpm : 300

Rack travel in mm : 6.20
Tolerance mm : ± 0.20

Del. quantity
cm³/1000 strokes : 26.0

Tolerance
cm³/1000 strokes : ± 3.0

Check tolerance
cm³/1000S. : ± 5.0

Speed
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 8.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 1372
guide sleeve
travel mm : 9.86
Tolerance mm : ± 0.15

Rated speed rpm : 300
guide sleeve
travel mm : 1.29
Tolerance mm : ± 0.20

Rated speed rpm : 917
guide sleeve
travel mm : 6.76
Tolerance mm : ± 0.25

Rated speed rpm : 590
guide sleeve
travel mm : 4.95

Tolerance mm : ± 0.25

Rated speed rpm : 1710
guide sleeve
travel mm : 13.50
Tolerance mm : ± 0.50

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1250
Aneroid pressure
nPa : 1200

Del. quantity
cm³/1000 strokes : 190.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 4.0

Speed
Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

CONTROL LEVER

control lever
position degree : 117.0
tolerance degree : ± 4.0

RATED SPEED
rack travel mm : 11.10
Rated speed rpm : 1320
Tolerance 1/min : ± 5

rack travel mm : 4.00
Rated speed rpm : 1460
Tolerance 1/min : ± 15

rack travel mm : 0.50
Tolerance mm : ± 0.50
Rated speed rpm : 1575

LOW IDLE

control lever
position degree : 75.0
tolerance degree : ± 4.0

Control lever difference
Grad : 42.0
tolerance degree : ± 6.0

Testing:

Rated speed rpm : 300
rack travel mm : 6.20
Tolerance mm : ± 0.20

Rated speed rpm : 250

CRT mm min. : > 7.00

Rated speed rpm : 450

TORQUE CONTROL

Rated speed rpm : 1250
rack travel mm : 12.15
Tolerance mm : ± 0.05

Rated speed rpm : 800
rack travel mm : 11.90
Tolerance mm : ± 0.10

Rated speed rpm : 1100
rack travel mm : 12.10
Tolerance mm : ± 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 1250
Pressure hPa : 1200

Pressure hPa : -
Rated speed rpm : 1000
rack travel mm : 9.70
Tolerance mm : ± 0.20

MEASUREMENT

Rated speed rpm : 1250
Pressure hPa : 560
rack travel mm : 11.50
Tolerance mm : ± 0.20

Pressure hPa : 400
rack travel mm : 10.70
Tolerance mm : ± 0.20

Start interlock

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1200
Rated speed rpm : 800
Del. quantity
cm³/1000 strokes : 195.5
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0
Spread
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

Aneroid pressure
hPa : -
Rated speed rpm : 1000
Del. quantity
cm³/1000 strokes : 123.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 3.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 9.90
Tolerance mm : ± 0.20
Del. quantity
cm³/1000 strokes : 176.5
Tolerance
cm³/1000 strokes : ± 20.0
Check tolerance
cm³/1000S. : ± 25.0

LOW IDLE

Rated speed rpm : 300
Del. quantity
cm³/1000 strokes : 26.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 5.0
Spread
Tolerance
cm³/1000 strokes : 5.0
Check tolerance
cm³/1000S. : 8.0

End of test specification sheet



BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 23.07.96
Test oil : ISO 4113

Combination No. : 0 402 746 642

Injection pump
Pump designation : PES6P120A720RS7321
EP type number : 0 412 726 906

Governor
Governor design. : RQV325...900PA944
 : K
Governor no. : 0 421 815 455

Cust. part No. : 3136C5212-P16

Customer spec. information
Customer : MACK
Motor : E7-350
Power KW : 261.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 084

Inlet press. bar : 2.8
Tolerance bar : ± 0.1

Test nozzle holder
assembly : 1 688 901 103

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 008

M20

Outside diameter : 6.0
x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0

Prestroke mm : 2.80
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 12.00
Tolerance mm : ± 1.00

Firing order : 1- 5- 3- 6- 2-
 : 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance *NW : ± 0.75

Start of delivery blocking
Tolerance : ± 0.50
Check
tolerance *NW : ± 0.75

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 900

Rack travel in mm : 14.15
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 319.5

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 4.0

Speed

Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 340

Rack travel in mm : 4.80
Tolerance mm : ± 0.10

Del. quantity
cm³/1000 strokes : 31.5

Tolerance
cm³/1000 strokes : ± 3.0

Check tolerance
cm³/1000S. : ± 5.0

Speed
Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 900

Aneroid pressure
hPa : 1200

Del. quantity
cm³/1000 strokes : 319.5

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 4.0

Speed
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 117.0
tolerance degree : ± 6.0

RATED SPEED
rack travel mm : 13.10
Rated speed rpm : 945
Tolerance 1/min : ± 5

Check
speed 1/min : ± 10

rack travel mm : 4.00
Rated speed rpm : 1100
Tolerance 1/min : ± 15

Check
speed 1/min : ± 20

rack travel mm : 0.50
Tolerance mm : ± 0.50
Rated speed rpm : 1200

LOW IDLE

control lever
position degree : 66.0
tolerance degree : ± 6.0

Testing:

Rated speed rpm : 340
rack travel mm : 4.80
Tolerance mm : ± 0.10

Rated speed rpm : 275

CRT mm min. : > 6.10

Rated speed rpm : 425

TORQUE CONTROL

Rated speed rpm : 900
rack travel mm : 14.15
Tolerance mm : ± 0.05

Rated speed rpm : 625
rack travel mm : 13.55
Tolerance mm : ± 0.10

Rated speed rpm : 500
rack travel mm : 12.80
Tolerance mm : ± 0.40

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 900
Pressure hPa : 1200

Pressure hPa : -
Rated speed rpm : 900
rack travel mm : 8.60
Tolerance mm : +- 0.20

MEASUREMENT

Rated speed rpm : 900

Pressure hPa : 310
rack travel mm : 13.00
Tolerance mm : +- 0.20

Pressure hPa : 420
rack travel mm : 10.15
Tolerance mm : +- 0.05

Start interlock

Rated speed rpm : > 100
Rated speed rpm : < 250

Check
speed 1/min : > 80
Check
speed 1/min : < 255

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1200
Rated speed rpm : 625
Del. quantity
cm³/1000 strokes : 339.5
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

Aneroid pressure
hPa : -
Rated speed rpm : 400

Del. quantity
cm³/1000 strokes : 171.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 4.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : +- 1.00
Del. quantity
cm³/1000 strokes : 190.0
Tolerance
cm³/1000 strokes : +- 20.0
Check tolerance
cm³/1000S. : +- 30.0

LOW IDLE

Rated speed rpm : 340
Del. quantity
cm³/1000 strokes : 31.5
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 5.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 23.07.96
Test oil : ISO 4113

Combination No. : 0 402 746 976

Injection pump
Pump designation : PES6P120A72ORS7323
EP type number : 0 412 726 907

Governor
Governor design. : RQV325...875P1909
Governor no. : 0 421 815 398

Cust. part No. : 313GC5213-P6

Customer-spec. information

Customer : MACK
Motor : EMN7300
Power KW : 223.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 084

Inlet press. bar : 2.8
Tolerance bar : ± 0.1

Test nozzle holde
assembly : 1 688 901 101

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 008

Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0

Prestroke mm : 2.80
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.00

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.75

Start of delivery blocking

Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 875

Rack travel in mm : 12.85
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 213.0

Tolerance
 cm³/1000 strokes : + 1.0

 Check tolerance
 cm³/1000S. : + 4.0

 Speed

 Tolerance
 cm³/1000 strokes : 5.0

 Check tolerance
 cm³/1000S. : 9.0

 Rated speed rpm : 325

 Rack travel in mm : 5.20
 Tolerance mm : + 0.10
 Del. quantity
 cm³/1000 strokes : 44.0
 Tolerance
 cm³/1000 strokes : + 3.0
 Check tolerance
 cm³/1000S. : + 5.0
 Speed
 Tolerance
 cm³/1000 strokes : 8.0
 Check tolerance
 cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 875
 Aneroid pressure
 hPa : 1200
 Del. quantity
 cm³/1000 strokes : 213.0
 Tolerance
 cm³/1000 strokes : + 1.0
 Check tolerance
 cm³/1000S. : + 4.0
 Speed
 Tolerance
 cm³/1000 strokes : 5.0
 Check tolerance
 cm³/1000S. : 9.0

CONTROL LEVER

control lever
 position degree : 113.0
 tolerance degree : + 6.0

RATED SPEED
 rack travel mm : 11.85
 Rated speed rpm : 920
 Tolerance 1/min : + 5
 Check
 speed 1/min : + 10

 rack travel mm : 4.00
 Rated speed rpm : 1090
 Tolerance 1/min : + 15
 Check
 speed 1/min : + 20

rack travel mm : 0.50
 Tolerance mm : + 0.50
 Rated speed rpm : 1200

LOW IDLE

control lever
 position degree : 65.0
 tolerance degree : + 6.0

Testing:

Rated speed rpm : 325
 rack travel mm : 5.20
 Tolerance mm : + 0.10

 Rated speed rpm : 275

 CRT mm min. : > 6.50

 Rated speed rpm : 425

TORQUE CONTROL

Rated speed rpm : 875
 rack travel mm : 12.85
 Tolerance mm : + 0.05

 Rated speed rpm : 510
 rack travel mm : 14.15
 Tolerance mm : + 0.10

 Rated speed rpm : 400
 rack travel mm : 13.50
 Tolerance mm : + 0.20

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 510
Pressure hPa : 1200

Pressure hPa : -
Rated speed rpm : 510
rack travel mm : 8.50
Tolerance mm : +- 0.20

MEASUREMENT

Rated speed rpm : 510

Pressure hPa : 785
rack travel mm : 13.10
Tolerance mm : +- 0.20

Pressure hPa : 370
rack travel mm : 9.90
Tolerance mm : +- 0.05

Start interlock

Rated speed rpm : > 100
Rated speed rpm : < 275

Check
speed 1/min : > 80
Check
speed 1/min : < 285

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1200
Rated speed rpm : 510
Del. quantity
cm³/1000 strokes : 295.5
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0
Spread
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

Aneroid pressure
hPa : -
Rated speed rpm : 400

Del. quantity
cm³/1000 strokes : 159.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 4.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 11.30
Tolerance mm : +- 1.00
Del. quantity
cm³/1000 strokes : 215.0
Tolerance
cm³/1000 strokes : +- 20.0
Check tolerance
cm³/1000S. : +- 25.0

LOW IDLE

Rated speed rpm : 325
Del. quantity
cm³/1000 strokes : 44.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 5.0
Spread
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 23.07.96
Test oil : ISO 4113

Combination No. : 0 402 746 980

Injection pump
Pump designation : PES6P120A320LS7328
EP type number : 0 412 726 908

Governor
Governor design. : RQV350...1250PA1136K
Governor no. : 0 421 815 402

Cust. part No. : 1823108C91

Customer-spec. information
Customer : NAVISTAR
Motor : DTA-408
Power KW : 171.5

TEST BENCH REQUIREMENTS

Inlet line : 4.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 076

Inlet press. bar : 2.8
Tolerance bar : ± 0.1

Test nozzle holder
assembly : 1 688 901 101

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 008

Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0

Prestroke mm : 2.90
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 11.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.75

Start of delivery blocking
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1150

Rack travel in mm : 13.25
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 175.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 4.0

Spread

Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

Rated speed rpm : 325

Rack travel in mm : 6.70
Tolerance mm : ± 0.10

Del. quantity
cm³/1000 strokes : 27.0

Tolerance
cm³/1000 strokes : ± 3.0

Check tolerance
cm³/1000S. : ± 5.0

Spread

Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 1440

Rack travel in mm : 12.30
Tolerance mm : ± 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1150

Aneroid pressure
hPa : 1500

Del. quantity
cm³/1000 strokes : 175.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 4.0

Spread

Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

CONTROL LEVER

control lever
position degree : 63.0
tolerance degree : ± 4.0

control lever
position degree : 119.0
tolerance degree : ± 6.0

RATED SPEED

rack travel mm : 12.30
Rated speed rpm : 1285
Tolerance 1/min : ± 15

rack travel mm : 4.00
Rated speed rpm : 1460
Tolerance 1/min : ± 5

rack travel mm : 0.50
Tolerance mm : ± 0.50
Rated speed rpm : 1550

LOW IDLE

control lever
position degree : 75.0
tolerance degree : ± 6.0

control lever
position degree : 16.5
tolerance degree : ± 4.0

Testing:

Rated speed rpm : 325
rack travel mm : 6.70
Tolerance mm : ± 0.10

Rated speed rpm : 275

CRT mm min. : > 7.50

Rated speed rpm : 425

TORQUE CONTROL

Rated speed rpm : 1150

rack travel mm : 13.25
 Tolerance mm : + 0.05

 Rated speed rpm : 850
 rack travel mm : 12.50
 Tolerance mm : + 0.10

 Rated speed rpm : 1250
 rack travel mm : 13.35
 Tolerance mm : + 0.10

 Rated speed rpm : 650
 rack travel mm : 11.90
 Tolerance mm : + 0.20

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 1250
 Pressure hPa : 1500

 Pressure hPa : -
 Rated speed rpm : 1250
 rack travel mm : 9.80
 Tolerance mm : + 0.20

MEASUREMENT

Rated speed rpm : 1250

 Pressure hPa : 970
 rack travel mm : 12.50
 Tolerance mm : + 0.20

 Pressure hPa : 435
 rack travel mm : 11.00
 Tolerance mm : + 0.05

Start interlock

Rated speed rpm : > 100
 Rated speed rpm : < 280

 Check speed 1/min : > 80
 Check speed 1/min : < 290

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure hPa : 1500
 Rated speed rpm : 850
 Del. quantity cm³/1000 strokes : 167.5

Tolerance cm³/1000 strokes : + 3.0
 Check tolerance cm³/1000S. : + 6.0
 Spreed
 Tolerance cm³/1000 strokes : 8.0
 Check tolerance cm³/1000S. : 12.0

 Aneroid pressure hPa : -
 Rated speed rpm : 1250
 Del. quantity cm³/1000 strokes : 93.0
 Tolerance cm³/1000 strokes : + 2.0
 Check tolerance cm³/1000S. : + 4.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
 rack travel mm : 20.50
 Tolerance mm : + 1.00
 Del. quantity cm³/1000 strokes : 130.0
 Tolerance cm³/1000 strokes : + 20.0
 Check tolerance cm³/1000S. : + 30.0

LOW IDLE

Rated speed rpm : 325
 Del. quantity cm³/1000 strokes : 27.0
 Tolerance cm³/1000 strokes : + 3.0
 Check tolerance cm³/1000S. : + 5.0
 Spreed
 Tolerance cm³/1000 strokes : 5.0
 Check tolerance cm³/1000S. : 9.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 23.07.96
Test oil : ISO 4113

Combination No. : 0 402 746 982

Injection pump
Pump designation : PES6P120A320LS7322
EP type number : 0 412 726 904

Governor
Governor design. : RQV350...1000PA1135K
Governor no. : 0 421 815 404

Cust. part No. : 1823153C91

Customer-spec. information
Customer : NAVISTAR
Motor : DTA-531
Power KW : 205.0

TEST BENCH REQUIREMENTS

Inlet line : 2.4

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 076

Inlet press. bar : 2.8
Tolerance bar : ± 0.1

Test nozzle holde
assembly : 1 688 901 101

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 008

Outside diameter : 6.0

N01

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0

Prestroke mm : 2.90
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 11.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.75

Start of delivery blocking

Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1000

Rack travel in mm : 14.45
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 220.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 4.0

Spreed

Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

Rated speed rpm : 325

Rack travel in mm : 6.00
Tolerance mm : ± 0.20

Del. quantity
cm³/1000 strokes : 21.5

Tolerance
cm³/1000 strokes : ± 3.0

Check tolerance
cm³/1000S. : ± 5.0

Spreed

Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1000

Aneroid pressure
hPa : 1200

Del. quantity
cm³/1000 strokes : 220.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 4.0

Spreed

Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

CONTROL LEVER

control lever
position degree : 120.0
tolerance degree : ± 6.0

RATED SPEED
rack travel mm : 13.40
Rated speed rpm : 1055
Tolerance 1/min : ± 15

rack travel mm : 4.00
Rated speed rpm : 1170
Tolerance 1/min : ± 5

rack travel mm : 0.50
Tolerance mm : ± 0.50
Rated speed rpm : 1250

LOW IDLE

control lever
position degree : 73.0
tolerance degree : ± 6.0

Testing:

Rated speed rpm : 325
rack travel mm : 6.00
Tolerance mm : ± 0.20

Rated speed rpm : 275

CRT mm min. : > 7.00

Rated speed rpm : 425

TORQUE CONTROL

Rated speed rpm : 1000
rack travel mm : 14.45
Tolerance mm : ± 0.05

Rated speed rpm : 650
rack travel mm : 14.10
Tolerance mm : ± 0.10

Rated speed rpm : 500
rack travel mm : 13.50
Tolerance mm : ± 0.20

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 1000
Pressure hPa : 1200

Pressure hPa : -
Rated speed rpm : 1000
rack travel mm : 10.40
Tolerance mm : ± 0.20

MEASUREMENT

Rated speed rpm : 1000

Pressure hPa : 650
rack travel mm : 13.30
Tolerance mm : ± 0.20

Pressure hPa : 290
rack travel mm : 11.55
Tolerance mm : ± 0.05

Start interlock

Rated speed rpm : > 100
Rated speed rpm : < 280

Check
speed 1/min : > 80
Check
speed 1/min : < 290

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1200
Rated speed rpm : 650
Del. quantity
cm³/1000 strokes : 241.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0
Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

Aneroid pressure
hPa : -
Rated speed rpm : 1000
Del. quantity
cm³/1000 strokes : 125.5
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 4.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : ± 1.00
Del. quantity
cm³/1000 strokes : 130.0
Tolerance
cm³/1000 strokes : ± 20.0
Check tolerance
cm³/1000S. : ± 30.0

LOW IDLE

Rated speed rpm : 325
Del. quantity
cm³/1000 strokes : 21.5
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 5.0
Speed
Tolerance
cm³/1000 strokes : 5.0
Check tolerance
cm³/1000S. : 9.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 23.07.96
Test oil : ISO 4113

Combination No. : 0 402 746 983

Injection pump
Pump designation : PES6P120A320LS7328
EP type number : 0 412 726 908

Governor
Governor design. : RQV350...1250PA1137K
Governor no. : 0 421 815 405

Cust. part No. : 1823107C91

Customer-spec. information
Customer : NAVISTAR
Motor : DTA-408
Power KW : 157.0

TEST BENCH REQUIREMENTS

Inlet line : 4.2

Test oil inlet temp. °C : 40
Tolerance °C : +- 2.0

Overflow valve : 2 417 413 076

Inlet press. bar : 2.8
Tolerance bar : +- 0.1

Test nozzle holder assembly : 1 688 901 101

Opening pressure bar : 208.5
Tolerance bar : +- 1.5

Test lines : 1 680 750 008

Outside diameter : 6.0

NO4

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : +- 1.0

Prestroke mm : 2.90
Tolerance mm : +- 0.05
Check tolerance mm : +- 0.10

Rack travel in mm : 11.50
Tolerance mm : +- 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : +- 0.30
Check tolerance °NW : +- 0.75

Start of delivery blocking
Tolerance : +- 0.50
Check tolerance °NW : +- 0.75

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1150

Rack travel in mm : 12.55
Tolerance mm : +- 0.05

Del. quantity cm³/1000 strokes : 158.5

Tolerance
 cm³/1000 strokes : + 1.0

Check tolerance
 cm³/1000S. : + 4.0

Speed

Tolerance
 cm³/1000 strokes : 8.0

Check tolerance
 cm³/1000S. : 12.0

Rated speed rpm : 335

Rack travel in mm : 6.60
 Tolerance mm : + 0.10

Del. quantity
 cm³/1000 strokes : 24.0

Tolerance
 cm³/1000 strokes : + 3.0

Check tolerance
 cm³/1000S. : + 5.0

Speed

Tolerance
 cm³/1000 strokes : 5.0

Check tolerance
 cm³/1000S. : 9.0

(B) SETTING OF INJECTION PUMP
 WITH GOVERNOR

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1150

Aneroid pressure
 hPa : 1500

Del. quantity
 cm³/1000 strokes : 158.5

Tolerance
 cm³/1000 strokes : + 1.0

Check tolerance
 cm³/1000S. : + 4.0

Speed

Tolerance
 cm³/1000 strokes : 8.0

Check tolerance
 cm³/1000S. : 12.0

CONTROL LEVER

control lever
 position degree : 119.0
 tolerance degree : + 6.0

RATED SPEED

rack travel mm : 11.60
 Rated speed rpm : 1290
 Tolerance 1/min : + 15

rack travel mm : 4.00
 Rated speed rpm : 1435
 Tolerance 1/min : + 5

rack travel mm : 0.50
 Tolerance mm : + 0.50
 Rated speed rpm : 1525

LOW IDLE

control lever
 position degree : 77.0
 tolerance degree : + 6.0

Testing:

Rated speed rpm : 335
 rack travel mm : 6.60
 Tolerance mm : + 0.10

Rated speed rpm : 275

CRT mm min. : > 7.50

Rated speed rpm : 425

TORQUE CONTROL

Rated speed rpm : 1150
 rack travel mm : 12.55
 Tolerance mm : + 0.05

Rated speed rpm : 850
 rack travel mm : 11.75
 Tolerance mm : + 0.10

Rated speed rpm : 650
 rack travel mm : 11.10
 Tolerance mm : + 0.20

Rated speed rpm : 1225
 rack travel mm : 12.70
 Tolerance mm : + 0.10

ANEROID/ALTIITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 1225
Pressure hPa : 1500

Pressure hPa : -
Rated speed rpm : 1150
rack travel mm : 10.20
Tolerance mm : + 0.20

MEASUREMENT

Rated speed rpm : 1225

Pressure hPa : 850
rack travel mm : 12.00
Tolerance mm : + 0.20

Pressure hPa : 420
rack travel mm : 10.45
Tolerance mm : + 0.05

Start interlock

Rated speed rpm : > 100
Rated speed rpm : < 280

Check
speed 1/min : > 80
Check
speed 1/min : < 290

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1500
Rated speed rpm : 850
Del. quantity
cm³/1000 strokes : 141.0
Tolerance
cm³/1000 strokes : + 3.0
Check tolerance
cm³/1000S. : + 6.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

Aneroid pressure
hPa : -
Rated speed rpm : 1150

Del. quantity
cm³/1000 strokes : 95.0
Tolerance
cm³/1000 strokes : + 2.0
Check tolerance
cm³/1000S. : + 4.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 21.00
Tolerance mm : + 1.00
Del. quantity
cm³/1000 strokes : 130.0
Tolerance
cm³/1000 strokes : + 20.0
Check tolerance
cm³/1000S. : + 30.0

LOW IDLE

Rated speed rpm : 335
Del. quantity
cm³/1000 strokes : 24.0
Tolerance
cm³/1000 strokes : + 3.0
Check tolerance
cm³/1000S. : + 5.0
Spreed
Tolerance
cm³/1000 strokes : 5.0
Check tolerance
cm³/1000S. : 9.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 23.07.96
Test oil : ISO 4113
Combination No. : 0 402 748 809
Injection pump
Pump designation : PES8P12CA920/4LS7320
EP type number : 0 412 728 809
Governor
Governor design. : RQV325...950PA848
: K
Governor no. : 0 421 815 388
Cust. part No. : 313GC5214F2

Customer-spec. information
Customer : MACK
Motor : E9-500
Power KW : 373.0

TEST BENCH REQUIREMENTS

Inlet line : 4.2
Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 2 417 413 086
Inlet press. bar : 2.8
Tolerance bar : ± 0.1
Test nozzle holder
assembly : 1 688 901 101
Opening pressure
bar : 208.5
Tolerance bar : ± 1.5
Test lines : 1 680 750 008

N07

Outside diameter : 6.0
x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0
Prestroke mm : 3.60
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10
Rack travel in mm : 10.50
Tolerance mm : ± 1.50
Firing order : 1- 2- 7- 8- 4
: - 6- 3
Phasing : 0-45-90-135-180
: -270-315
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.75
Start of delivery blocking
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75
Barrel no. : 1

BASIC SETTING

Rated speed rpm : 950
Rack travel in mm : 15.15
Tolerance mm : ± 0.05
Del. quantity
cm³/1000 strokes : 243.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 4.0

Spread

Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rack travel in mm : 5.30
Tolerance mm : ± 0.20

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 1150

Rack travel in mm : 10.00
Tolerance mm : ± 2.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 950
Aneroid pressure
hPa : 1200
Del. quantity
cm³/1000 strokes : 243.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0
Spread
Tolerance
cm³/1000 strokes : 5.0
Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 119.0
tolerance degree : ± 6.0

RATED SPEED
rack travel mm : 14.10
Rated speed rpm : 995
Tolerance 1/min : ± 5

rack travel mm : 4.00
Rated speed rpm : 1150
Tolerance 1/min : ± 15

rack travel mm : 0.50
Tolerance mm : ± 0.50
Rated speed rpm : 1500

LOW IDLE

control lever
position degree : 73.0
tolerance degree : ± 6.0

Testing:

Rated speed rpm : 325
rack travel mm : 5.30
Tolerance mm : ± 0.20

Rated speed rpm : 275

CRT mm min. : > 6.80

Rated speed rpm : 400

TORQUE CONTROL

Rated speed rpm : 950
rack travel mm : 15.15
Tolerance mm : ± 0.05

Rated speed rpm : 650
rack travel mm : 14.40
Tolerance mm : ± 0.10

Rated speed rpm : 500
rack travel mm : 13.70
Tolerance mm : ± 0.20

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 950
Pressure hPa : 1200

rack travel mm : 15.15
Tolerance mm : ± 0.10

Pressure hPa : -
Rated speed rpm : 950
rack travel mm : 8.75
Tolerance mm : ± 0.20

MEASUREMENT

Rated speed rpm : 950
Pressure hPa : 535
rack travel mm : 12.85
Tolerance mm : ± 0.20

Pressure hPa : 230
rack travel mm : 10.35
Tolerance mm : ± 0.65

Start interlock

Rated speed rpm : > 100
Rated speed rpm : < 260

Check speed 1/min : > 80
Check speed 1/min : < 270

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure hPa : 1200
Rated speed rpm : 650
Del. quantity cm³/1000 strokes : 259.0
Tolerance cm³/1000 strokes : ± 3.0
Check tolerance cm³/1000S. : ± 6.0
Speed Tolerance cm³/1000 strokes : 10.0
Check tolerance cm³/1000S. : 14.0

Aneroid pressure hPa : -
Rated speed rpm : 400
Del. quantity cm³/1000 strokes : 146.0
Tolerance cm³/1000 strokes : ± 2.0
Check tolerance cm³/1000S. : ± 4.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 11.20
Tolerance mm : ± 0.50
Del. quantity cm³/1000 strokes : 185.0
Tolerance cm³/1000 strokes : ± 20.0
Check tolerance cm³/1000S. : ± 25.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 11.02.97
Test oil : ISO 4113

Combination No. : 0 402 798 803

Injection pump
Pump designation : PES8P120A920/4LS7336
EP type number : 0 412 728 813

Governor
Governor design. : RE30
Governor no. : 0 421 890 034

Cust. part No. : 313 GC 5209

Customer-spec. information
Customer : MACK
Motor : E9-550
Power KW : 410.0

TEST BENCH REQUIREMENTS

Inlet line : 4.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 086

Inlet press. bar : 2.0
Tolerance bar : ± 0.1

Test nozzle holder
assembly : 1 688 901 103

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 008

Outside diameter : 6.0

N10

x inside diameter : 2.0
x length mm : 600

REMARKS

Pump-specific values
in Section (B)
must be observed!

(A) INJECTION PUMP SETTINGS
No basic setting.
Setting of constant delivery
under Section C.

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0

Prestroke mm : 3.30
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 0.20

Firing order : 1- 2- 7- 8- 4
 : - 6- 3

Phasing : 0-45-90-135-180
 : -270-315
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.75

Start of delivery blocking
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Barrel no. : 1

(B) POSITIONER TESTING
Warm-up time: 3 minutes at
n=600 min⁻¹, Uact = 2.5 V

TESTING & SETTING RACK TRAVEL SENSOR POSITION

Engine speed min-1: 0

Setting point
(P, R and H pump)

Uact V : 3.100
 CRT mm : 13.00
 Tolerance mm : +/- 0.05
 Check tolerance mm : +/- 0.10

Check value
(P, R and H pump)

Uact V : 1.700
 CRT mm : 6.15
 Tolerance mm : +/- 0.25
 Check tolerance mm : +/- 0.30

Setting point
(M pump)

Uact V : 3.100
 CRT mm : 12.50
 Tolerance mm : +/- 0.05
 Check tolerance mm : +/- 0.10

Check value
(M pump)

Uact V : 1.700
 CRT mm : 5.50
 Tolerance mm : +/- 0.25
 Check tolerance mm : +/- 0.30

Stop position

Uact V : Value with
 deenergised adjusting magnet
 and control rod in
 stop position.

CRT mm : 0.75
 Tolerance mm : +/- 0.25
 Check tolerance mm : +/- 0.35

ENGINE-SPEED SENSOR
(All P and R pumps not
 H and M pumps)

Test with control rod
 in stop position

Engine speed min-1: 60
 Amplitude V : 1.4
 Tolerance V : +/- 0.6
 Check tolerance V : +/- 1.20

Engine speed min-1: 600
 Difference
 Amplitude to
 Amplitude V : max. 1.4

(C) INJECTION PUMP WITH POSITIONER

TEST POINT V1

Rated speed rpm : 900
 Uact V : 2.950
 Del. quantity
 cm³/1000 strokes : 303.0
 Tolerance
 cm³/1000 strokes : +/- 1.0
 Check tolerance
 cm³/1000S. : +/- 4.0
 Speed
 Tolerance
 cm³/1000 strokes : 7.0
 Check tolerance
 cm³/1000S. : 11.0

FUEL DELIVERY CHARACTERISTICS

Rated speed rpm : 625
 Uact V : 2.880
 Del. quantity
 cm³/1000 strokes : 339.5
 Tolerance
 cm³/1000 strokes : +/- 5.0
 Check tolerance
 cm³/1000S. : +/- 8.0
 Speed
 Tolerance
 cm³/1000 strokes : 12.0
 Check tolerance
 cm³/1000S. : 16.0

TEST POINT L1

Rated speed rpm : 325
 Uact V : 1.340
 Tolerance Volt : +/- 0.060
 Check tolerance
 Volt : +/- 0.070
 Del. quantity
 cm³/1000 strokes : 27.0

Tolerance
cm³/1000 strokes : ± 3.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
Uact V : 4.700
Del. quantity
cm³/1000 strokes : 185.0
Tolerance
cm³/1000 strokes : ± 15.0
Check tolerance
cm³/1000S. : ± 20.0
Spreed
Tolerance
cm³/1000 strokes : 40.0
Check tolerance
cm³/1000S. : 45.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 08.10.96
Test oil : ISO 4113

Combination No. : 0 402 996 311

Injection pump
Pump designation : PES6P120A72ORS8512
EP type number : 0 412 926 214

Governor
Governor design. : RE30
Governor no. : 0 421 890 024

Cust. part No. : 313 GC 5225 P2

Customer-spec. information

Customer : MACK
Motor : E7

TEST BENCH REQUIREMENTS

Inlet line : 1/2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 3 413 359 008

Inlet press. bar : 3.0
Tolerance bar : ± 0.1

Test nozzle holder
assembly : 1 688 901 103

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 008

Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

Pump-specific values
in Section (B)
must be observed!

(A) INJECTION PUMP SETTINGS
No basic setting.
Setting of constant delivery
under Section C.

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0

Prestroke mm : 4.20
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 12.00
Tolerance mm : ± 0.20

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240

Start of delivery blocking

Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Barrel no. : 1

(B) POSITIONER TESTING

Warm-up time: 3 minutes at
n=600 min⁻¹, Uact = 2.5 V

TESTING & SETTING RACK TRAVEL SENSOR
POSITION

Engine speed min-1: 0

Setting point
(P, R and H pump)

Uact V : 3.100
CRT mm : 13.00
Tolerance mm : +/- 0.15
Check tolerance mm : +/- 0.10

Check value
(P, R and H pump)

Uact V : 1.700
CRT mm : 6.15
Tolerance mm : +/- 0.25
Check tolerance mm : +/- 0.30

Setting point
(M pump)

Uact V : 3.100
CRT mm : 12.50
Tolerance mm : +/- 0.05
Check tolerance mm : +/- 0.10

Check value
(M pump)

Uact V : 1.700
CRT mm : 5.50
Tolerance mm : +/- 0.25
Check tolerance mm : +/- 0.30

Stop position

Uact V : Value with
deenergised adjusting magnet
and control rod in
stop position.

CRT mm : 0.75
Tolerance mm : +/- 0.25
Check tolerance mm : +/- 0.35

ENGINE-SPEED SENSOR
(All P and R pumps not
H and M pumps)

Test with control rod
in stop position

Engine speed min-1: 60

Amplitude V : 1.4
Tolerance V : +/- 0.6
Check tolerance V : +/- 1.20

Engine speed min-1: 600
Difference
Amplitude to
Amplitude V : max.1.4

(C) INJECTION PUMP WITH POSITIONER

TEST POINT V1

Rated speed rpm : 900
Uact V : 3.050
Del. quantity
cm³/1000 strokes : 310.0
Tolerance
cm³/1000 strokes : +/- 1.0
Check tolerance
cm³/1000S. : +/- 5.0
Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 14.0

FUEL DELIVERY CHARACTERISTICS

Rated speed rpm : 625
Uact V : 3.260
Del. quantity
cm³/1000 strokes : 392.0
Tolerance
cm³/1000 strokes : +/- 10.0
Check tolerance
cm³/1000S. : +/- 12.0
Speed
Tolerance
cm³/1000 strokes : 16.0
Check tolerance
cm³/1000S. : 18.0

TEST POINT L1

Rated speed rpm : 325
Rated speed rpm : 325
Uact V : 1.310
Uact V : 1.310
Tolerance Volt : +/- 0.060
Check tolerance
Volt : +/- 0.070
Del. quantity
cm³/1000 strokes : 33.0
Del. quantity
cm³/1000 strokes : 33.0

Tolerance
cm³/1000 strokes : ± 3.0
Tolerance
cm³/1000 strokes : ± 3.0
Spreed
Tolerance
cm³/1000 strokes : 6.0
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 14.0
Check tolerance
cm³/1000S. : 14.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
Uact V : 4.700
Del. quantity
cm³/1000 strokes : 195.0
Tolerance
cm³/1000 strokes : ± 19.0
Check tolerance
cm³/1000S. : ± 22.0
Spreed
Tolerance
cm³/1000 strokes : 40.0
Check tolerance
cm³/1000S. : 50.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 11.02.97
Test oil : ISO 4113

Combination No. : 0 403 466 152

Injection pump
Pump designation : PES6MW100/120RS1238
EP type number : 0 413 406 237

Governor
Governor design. : RSV500...1100MWOA368
Governor no. : 0 420 085 251

Cust. part No. : 3926378

Customer-spec. information
Customer : CDC
Motor : 6 CT
Power KW : 143.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 093

Inlet press. bar : 2.0
Tolerance bar : ± 0.1

Test nozzle holde
assembly : 1 688 901 101

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 014

Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0

Prestroke mm : 2.80
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Start of delivery blocking

*NW after s.o.d. : 8.00
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Barrel no. : 1

Beginning of delivery differende

and maximum rack
travel : 15.00
Difference °CS : 2.00

BASIC SETTING

Rated speed rpm : 1100

Rack travel in mm : 11.00
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 132.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 4.0

Spread

Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 7.5

Rated speed rpm : 500

Rack travel in mm : 5.15
Tolerance mm : ± 0.10
Del. quantity
cm³/1000 strokes : 22.5
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 4.5
Spread
Tolerance
cm³/1000 strokes : 3.5
Check tolerance
cm³/1000S. : 5.5

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever
position degree : - 3
Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : ± 0.20

governor spring
pre-tension
click setting x : 3.25

N17

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1100
Aneroid pressure
hPa : 900
Del. quantity
cm³/1000 strokes : 132.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0
Spread
Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 7.5

CONTROL LEVER

control lever
position degree : 94.0
tolerance degree : ± 4.0

RATED SPEED

rack travel mm : 10.00
Rated speed rpm : 1160
Tolerance 1/min : ± 5

rack travel mm : 6.00
Rated speed rpm : 1230

rack travel mm : 1.00
Rated speed rpm : 1400

rack travel mm : 6.00
Rated speed rpm : 1230

LOW IDLE

control lever
position degree : 80.0
tolerance degree : ± 4.0

Control lever difference
Grad : 14.0
tolerance degree : ± 4.0

Setting point w/out bumper spring

Rated speed rpm : 500
rack travel mm : 4.65
Tolerance mm : ± 0.10

Testing:

Rated speed rpm : 500
rack travel mm : 5.15
Tolerance mm : ± 0.10

Rated speed rpm : 100

CRT mm min. : > 19.00

TORQUE CONTROL

Rated speed rpm : 1100
rack travel mm : 11.00
Tolerance mm : ± 0.05

Rated speed rpm : 750
rack travel mm : 11.70
Tolerance mm : ± 0.10

Rated speed rpm : 1000
rack travel mm : 11.45
Tolerance mm : ± 0.20

Rated speed rpm : 950
rack travel mm : 11.50
Tolerance mm : ± 0.20

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 900

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : 10.30
Tolerance mm : ± 0.20

MEASUREMENT

Rated speed rpm : 500

Pressure hPa : 590
rack travel mm : 10.80
Tolerance mm : ± 0.20

Pressure hPa : 545
rack travel mm : 10.60
Tolerance mm : ± 0.20

Start interlock

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 900

Rated speed rpm : 950

Del. quantity
cm³/1000 strokes : 141.5

Tolerance
cm³/1000 strokes : ± 2.0

Check tolerance
cm³/1000S. : ± 5.0

Speed
Tolerance
cm³/1000 strokes : 6.0

Check tolerance
cm³/1000S. : 9.0

Aneroid pressure
hPa : -

Rated speed rpm : 500

Del. quantity
cm³/1000 strokes : 117.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 3.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : ± 1.00

Del. quantity
cm³/1000 strokes : 177.0

Tolerance
cm³/1000 strokes : ± 10.0

Check tolerance
cm³/1000S. : ± 13.0

LOW IDLE

Rated speed rpm : 500

Del. quantity
cm³/1000 strokes : 22.5

Tolerance
cm³/1000 strokes : ± 2.0

Check tolerance
cm³/1000S. : ± 4.5

Speed
Tolerance
cm³/1000 strokes : 3.5

Check tolerance
cm³/1000S. : 5.5

End of test specification sheet



BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 04.02.97
Test oil : ISO 4113

Combination No. : 0 402 076 809

Injection pump
Pump designation : PES6P100B320RS3384
EP type number : 0 412 006 713

Governor
Governor design. : RSV400...1125POA644
Governor no. : 0 421 833 557

Cust. part No. : 51.11103-7564

Customer-spec. information
Customer : MAN
Motor : D0826 LE531
Power KW : 191.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 047

Inlet press. bar : 2.0
Tolerance bar : ± 0.1

Overflow quantity min. L/h : 150
Tolerance L/h : ± 10.0

Test nozzle holder assembly : 1 688 901 103

Opening pressure bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 008

Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant. per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 3.30
Tolerance mm : ± 0.05
Check tolerance mm : ± 0.10

Rack travel in mm : 13.50
Tolerance mm : ± 0.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check tolerance °NW : ± 0.50

Start of delivery blocking

Tolerance : ± 0.10
Check tolerance °NW : ± 0.75

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 925

Rack travel in mm : 14.10
Tolerance mm : ± 0.05

<hr/>	
Del. quantity	
cm ³ /1000 strokes :	198.0
<hr/>	
Tolerance	
cm ³ /1000 strokes :	+ 1.0
<hr/>	
Check tolerance	
cm ³ /1000S. :	+ 4.0
<hr/>	
Spread	
<hr/>	
Tolerance	
cm ³ /1000 strokes :	4.0
<hr/>	
Check tolerance	
cm ³ /1000S. :	6.0
<hr/>	

Rated speed rpm :	400
<hr/>	
Rack travel in mm :	4.90
Tolerance mm :	+ 0.10
Del. quantity	
cm ³ /1000 strokes :	25.0
Tolerance	
cm ³ /1000 strokes :	+ 3.0
Check tolerance	
cm ³ /1000S. :	+ 6.0
Spread	
Tolerance	
cm ³ /1000 strokes :	3.5
Check tolerance	
cm ³ /1000S. :	5.5

(B) SETTING OF INJECTION PUMP WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever	
position degree :	- 3
Rated speed rpm :	800
<hr/>	
Rack travel in mm :	0.50
Tolerance mm :	+ 0.20
<hr/>	
governor spring	
pre-tension	
click setting x :	5.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm :	925
-------------------	-----

Aneroid pressure	
hPa :	1500
Del. quantity	
cm ³ /1000 strokes :	198.0
Tolerance	
cm ³ /1000 strokes :	+ 1.0
Check tolerance	
cm ³ /1000S. :	+ 4.0
Spread	
Tolerance	
cm ³ /1000 strokes :	4.0
Check tolerance	
cm ³ /1000S. :	6.0

CONTROL LEVER

control lever	
position degree :	101.0
tolerance degree :	+ 4.0

RATED SPEED

rack travel mm :	12.50
Rated speed rpm :	1155
Tolerance 1/min :	+ 5

rack travel mm :	4.00
Rated speed rpm :	1245
Tolerance 1/min :	+ 15

rack travel mm :	0.85
Tolerance mm :	+ 0.55
Rated speed rpm :	1400

rack travel mm :	4.00
Rated speed rpm :	1250

LOW IDLE

control lever	
position degree :	77.0
tolerance degree :	+ 4.0

Setting point w/out bumper spring

Rated speed rpm :	400
rack travel mm :	4.40
Tolerance mm :	+ 0.10

Testing:

Rated speed rpm :	400
rack travel mm :	4.90
Tolerance mm :	+ 0.10

rack travel mm : 2.00
Rated speed rpm : 500
Tolerance 1/min : ± 30

TORQUE CONTROL

Rated speed rpm : 925
rack travel mm : 14.10
Tolerance mm : ± 0.05

Rated speed rpm : 1125
rack travel mm : 13.60
Tolerance mm : ± 0.05

Rated speed rpm : 700
rack travel mm : 14.15
Tolerance mm : ± 0.10

Rated speed rpm : 1025
rack travel mm : 13.95
Tolerance mm : ± 0.10

ANEROID/ALTITUDE COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1500
rack travel mm : 14.10
Tolerance mm : ± 0.15

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : 9.60
Tolerance mm : ± 0.10

MEASUREMENT

Rated speed rpm : 500

Pressure hPa : 150
rack travel mm : 9.85
Tolerance mm : ± 0.05

Pressure hPa : 800
rack travel mm : 12.50
Tolerance mm : ± 0.15

Start interlock

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1500

N22

Rated speed rpm : 1125
Del. quantity
cm³/1000 strokes : 187.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0

Aneroid pressure
hPa : 1500
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 194.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 88.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 9.60
Tolerance mm : ± 0.20
Del. quantity
cm³/1000 strokes : 110.0
Tolerance
cm³/1000 strokes : ± 10.0
Check tolerance
cm³/1000S. : ± 14.0

LOW IDLE

Rated speed rpm : 400
Del. quantity
cm³/1000 strokes : 25.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0
Speed
Tolerance
cm³/1000 strokes : 3.5
Check tolerance
cm³/1000S. : 5.5

End of test specification sheet



BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 31.01.97
Test oil : ISO 4113

Combination No. : 0 402 086 702

Injection pump
Pump designation : PES6P100B321RS3388
EP type number : 0 412 006 714

Governor
Governor design. : RSV40C...1125POA674
Governor no. : 0 421 833 592

Cust. part No. : 51.11103-7564

Customer-spec. information
Customer : MAN
Motor : D0826 LE531
Power KW : 191.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 047

Inlet press. bar : 2.0
Tolerance bar : ± 0.1

Overflow quantity
min. l/h : 150
Tolerance l/h : ± 10.0

Test nozzle holder
assembly : 1 688 901 703

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 008

Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 3.30
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 13.50
Tolerance mm : ± 0.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50

Start of delivery blocking

Tolerance : ± 0.10
Check
tolerance °NW : ± 0.75

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 925

Rack travel in mm : 14.10
Tolerance mm : ± 0.05

<hr/>	
Del. quantity	
cm ³ /1000 strokes :	198.0
<hr/>	
Tolerance	
cm ³ /1000 strokes :	+ 1.0
<hr/>	
Check tolerance	
cm ³ /1000S. :	+ 4.0
<hr/>	
Speed	
<hr/>	
Tolerance	
cm ³ /1000 strokes :	4.0
<hr/>	
Check tolerance	
cm ³ /1000S. :	6.0
<hr/>	

Rated speed rpm :	400
<hr/>	
Rack travel in mm :	4.90
Tolerance mm :	+ 0.10
Del. quantity	
cm ³ /1000 strokes :	25.0
Tolerance	
cm ³ /1000 strokes :	+ 3.0
Check tolerance	
cm ³ /1000S. :	+ 6.0
<hr/>	
Speed	
Tolerance	
cm ³ /1000 strokes :	3.5
Check tolerance	
cm ³ /1000S. :	5.5

(B) SETTING OF INJECTION PUMP WITH GOVERNOR

GUIDE SLEEVE POSITION

control lever	
position degree :	- 3
<hr/>	
governor spring	
pre-tension	
click setting x :	5.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm :	925
Aneroid pressure	
hPa :	1500
Del. quantity	
cm ³ /1000 strokes :	198.0

Tolerance	
cm ³ /1000 strokes :	+ 1.0
Check tolerance	
cm ³ /1000S. :	+ 4.0
<hr/>	
Speed	
Tolerance	
cm ³ /1000 strokes :	4.0
Check tolerance	
cm ³ /1000S. :	6.0

CONTROL LEVER

control lever	
position degree :	100.0
tolerance degree :	+ 4.0

RATED SPEED

rack travel mm :	12.60
Rated speed rpm :	1175
Tolerance 1/min :	+ 5

rack travel mm :	4.00
Rated speed rpm :	1265
Tolerance 1/min :	+ 15

rack travel mm :	0.85
Tolerance mm :	+ 0.55
Rated speed rpm :	1400

rack travel mm :	4.00
Rated speed rpm :	1265

LOW IDLE

control lever	
position degree :	76.0
tolerance degree :	+ 4.0

Setting point w/out bumper spring

Rated speed rpm :	400
rack travel mm :	4.40
Tolerance mm :	+ 0.10

Testing:

Rated speed rpm :	400
rack travel mm :	4.90
Tolerance mm :	+ 0.10

rack travel mm :	2.00
Rated speed rpm :	490
Tolerance 1/min :	+ 30

TORQUE CONTROL

Rated speed rpm : 925
rack travel mm : 14.10
Tolerance mm : ± 0.05

Rated speed rpm : 1125
rack travel mm : 13.60
Tolerance mm : ± 0.05

Rated speed rpm : 700
rack travel mm : 14.15
Tolerance mm : ± 0.10

Rated speed rpm : 1025
rack travel mm : 13.95
Tolerance mm : ± 0.10

**ANEROID/ALTITUDE
COMPENSATOR TEST****SETTINGS**

Rated speed rpm : 500
Pressure hPa : 1500
rack travel mm : 14.10
Tolerance mm : ± 0.15

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : 9.60
Tolerance mm : ± 0.10

MEASUREMENT

Rated speed rpm : 500

Pressure hPa : 150
rack travel mm : 9.85
Tolerance mm : ± 0.05

Pressure hPa : 800
rack travel mm : 12.50
Tolerance mm : ± 0.15

Start interlock

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1500
Rated speed rpm : 1125
Del. quantity
cm³/1000 strokes : 187.0

Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0

Aneroid pressure
hPa : 1500
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 194.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 88.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 9.60
Tolerance mm : ± 0.20
Del. quantity
cm³/1000 strokes : 110.0
Tolerance
cm³/1000 strokes : ± 10.0
Check tolerance
cm³/1000S. : ± 14.0

LOW IDLE

Rated speed rpm : 400
Del. quantity
cm³/1000 strokes : 25.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0
Speed
Tolerance
cm³/1000 strokes : 3.5
Check tolerance
cm³/1000S. : 5.5

End of test specification sheet

